



N72-18493
NASA SP-7037 (13)

AERONAUTICAL ENGINEERING

CASE FILE
COPY

A SPECIAL BIBLIOGRAPHY

WITH INDEXES

Supplement 13

JANUARY 1972

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

PREVIOUS BIBLIOGRAPHIES IN THIS SERIES

<i>Document</i>	<i>Date</i>	<i>Coverage</i>
NASA SP-7037	September 1970	Jan.-Aug. 1970
NASA SP-7037 (01)	January 1971	Sept.-Dec. 1970
NASA SP-7037 (02)	February 1971	January 1971
NASA SP-7037 (03)	March 1971	February 1971
NASA SP-7037 (04)	April 1971	March 1971
NASA SP-7037 (05)	May 1971	April 1971
NASA SP-7037 (06)	June 1971	May 1971
NASA SP-7037 (07)	July 1971	June 1971
NASA SP-7037 (08)	August 1971	July 1971
NASA SP-7037 (09)	September 1971	August 1971
NASA SP-7037 (10)	October 1971	September 1971
NASA SP-7037 (11)	November 1971	October 1971
NASA SP-7037 (12)	December 1971	November 1971

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by Informatics Tisco, Inc.

Use of funds for printing this publication approved by the Director of the Office of Management and Budget June 23, 1971.

AERONAUTICAL ENGINEERING

A Special Bibliography

Supplement 13

A selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in December 1971 in

- *Scientific and Technical Aerospace Reports (STAR)*
- *International Aerospace Abstracts (IAA).*



Scientific and Technical Information Office
OFFICE OF INDUSTRY AFFAIRS AND TECHNOLOGY UTILIZATION 1971
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C.

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering.

This supplement to *Aeronautical Engineering—A Special Bibliography* (NASA SP-7037) lists 283 reports, journal articles, and other documents originally announced in December 1971 in *Scientific and Technical Aerospace Reports (STAR)* or in *International Aerospace Abstracts (IAA)*. For previous bibliographies in this series, see inside of front cover.

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied by an abstract. The listing of the entries is arranged in two major sections, *IAA Entries* and *STAR Entries* in that order. The citations and abstracts are reproduced exactly as they appeared originally in *IAA* or *STAR*, including the original accession numbers from the respective announcement journals. This procedure, which saves time and money, accounts for the slight variation in citation appearances.

Three indexes—subject, personal author, and contract number—are included. An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A71-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc., (AIAA), as follows: Paper copies are available at \$5.00 per document up to a maximum of 20 pages. The charge for each additional page is 25 cents. Microfiche⁽¹⁾ are available at the rate of \$1.00 per microfiche for documents identified by the # symbol following the accession number. A number of publications, because of their special characteristics, are available only for reference in the AIAA Technical Information Service Library. Minimum airmail postage to foreign countries is \$1.00. Please refer to the accession number, e.g., A71-10613, when requesting publications.

STAR ENTRIES (N71-10000 Series)

A source from which a publication abstracted in this Section is available to the public is ordinarily given on the last line of the citation, e.g., Avail: NTIS. The following are the most commonly indicated sources (full addresses of these organizations are listed at the end of this introduction):

Avail: NTIS. Sold by the National Technical Information Service at a standard price of \$3.00 for hard copy (printed, facsimile, or reproduced from microcopy) of 300 pages or less. Documents in the 301 to 600 page range are sold for \$6.00 in hard copy, and those in the 601 to 900 page range are sold at \$9.00. Documents exceeding 900 pages are priced by NTIS on an individual basis. These prices apply retroactively to all documents in the NTIS collection, but in addition, documents of 300 pages or less that are over two years old (from date of announcement in *Government Reports Announcements*, or *STAR* for those items announced only in *STAR*) will have a surcharge of \$3.00 added for a total price of \$6.00. No additional surcharge will be added for documents over 300 pages.

Microfiche is available from NTIS at a standard price of 95 cents (regardless of age) for those documents identified by the # sign following the accession number (e.g., N71-10411#) and having an NTIS availability shown in the citation.

Avail: SOD (or GPO). Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The price is given following the availability line. (An order received by NTIS for one of these documents will be filled at the SOD price if hard copy is requested. NTIS will also fill microfiche requests, at the standard 95 cent price, for those documents identified by a # symbol.)

Avail: NASA Scientific and Technical Information Office. Documents with this availability are usually news releases or informational brochures available without charge in paper copy.

Avail: AEC Depository Libraries. Organizations in U.S. cities and abroad that maintain collections of U.S. Atomic Energy Commission reports, usually in microfiche form, are listed in *Nuclear Science Abstracts*. Services available from the USAEC and its depositories are described in a booklet, *Science Information Available from the Atomic Energy Commission* (TID-4550), which may be obtained without charge from the USAEC Division of Technical Information.

Avail: Univ. Microfilms. Documents so indicated are dissertations selected from *Dissertation Abstracts*, and are sold by University Microfilms as xerographic copy (HC) at \$10.00 each and microfilm at \$4.00 each, regardless of the length of the manuscript. Handling and shipping charges are additional. All requests should cite the author and the Order Number as they appear in the citation.

(1) A microfiche is a transparent sheet of film, 105 x 148 mm in size, containing up to 72 pages of information reduced to micro images (not to exceed 20:1 reduction)

- Avail: HMSO. Publications of Her Majesty's Stationery Office are sold in the U.S. by British Information Services (BIS), New York City. The U.S. price (including a service charge) is given, or a conversion table may be obtained from BIS.
- Avail: National Lending Library, Boston Spa, England. Sold by this organization at the price shown. (If none is given, an inquiry should be addressed to NLL.)
- Avail: ZLDI. Sold by the Zentralstelle für Luftfahrtokumentation und -Information, Munich, Federal Republic of Germany, at the price shown in deutschmarks (DM).
- Avail: Issuing Activity, or Corporate Author, or no indication of availability: Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document.
- Avail: U.S. Patent Office. Sold by Commissioner of Patents, U.S. Patent Office, at the standard price of \$.50 each, postage free.
- Other availabilities: If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line.

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the *STAR Entries* and *IAA Entries* sections. It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA. A listing of public collections of NASA documents is included on the inside back cover.

SUBSCRIPTION AVAILABILITY

This publication is available on subscription from the National Technical Information Service (NTIS). The annual subscription rate for the monthly supplements, excluding the annual cumulative index, is \$18.00. All questions relating to subscriptions should be referred to the NTIS.

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics
and Astronautics
Technical Information Service
750 Third Ave.
New York, N.Y. 10017

British Information Service
845 Third Ave.
New York, N.Y. 10022

Commissioner of Patents
U.S. Patent Office
Washington, D.C. 20231

ESRO/ELDO Space Documentation Service
European Space Research Organization
114, av. de Neuilly
92-Neuilly-sur-Seine, France

Her Majesty's Stationery Office
P.O. Box 569, S.E. 1
London, England

NASA Scientific and Technical Information
Facility
P.O. Box 33
College Park, Maryland 20740

National Aeronautics and Space
Administration
Scientific and Technical Information
Office (KSI)
Washington, D.C. 20546

National Lending Library for Science
and Technology
Boston Spa, Yorkshire, England

National Technical Information Service
Springfield, Virginia 22151

Superintendent of Documents
U.S. Government Printing Office
Washington, D.C. 20402

University Microfilms, Inc.
A Xerox Company
300 North Zeeb Road
Ann Arbor, Michigan 48106

University Microfilms, Inc.
Tylers Green
London, England


U.S. Atomic Energy Commission
Division of Technical Information
P.O. Box 62
Oak Ridge, Tennessee 37830

Zentralstelle für Luftfahrt-doku-
mentation und-Information
8 München 86
Postfach 880
Federal Republic of Germany


TABLE OF CONTENTS


	Page
IAA Entries	691
STAR Entries	707
Subject Index	A-1
Personal Author Index	B-1
Contract Number Index	C-1

TYPICAL CITATION AND ABSTRACT FROM STAR



TYPICAL CITATION AND ABSTRACT FROM /AA





AERONAUTICAL ENGINEERING

A Special Bibliography (Suppl. 13)

JANUARY 1972

IAA ENTRIES

A71-42921 Fluidics. Robert O. McDonald (Honeywell, Inc., Commercial Div., Minneapolis, Minn.). (*Institute of Electrical and Electronics Engineers, Textile Industry Technical Conference, Charlotte, N.C., May 1, 2, 1969, Paper 70-TP-120-IGA.*) *IEEE Transactions on Industry and General Applications*, vol. IGA-7, May-June 1971, p. 367-373.

A rapid resumé of the basic theory of fluidic devices including wall attachment amplifiers, turbulence amplifiers, and vortex amplifiers is presented. The basic fluidic devices are then treated in their application as sensors of temperature and pressure, and there is a review of fluidic indicators and associated relays. Current application of these fluidic devices and fluidic systems for chemical industry inspection, and rejection, fluidic systems for the ammunition industry, and fluidic systems for jet aircraft controls are discussed. The discussion covers the operational benefits of the fluidic systems under actual operating field experience. (Author)

A71-42922 # FAA flight test research approach to the SST airworthiness standards. R. F. LeSuer, R. Abrams, and R. D. Forrest (FAA, Flight Standards Service, Washington, D.C.). (*Flight Test Symposium, Montreal, Canada, Feb. 8, 1971.*) *Canadian Aeronautics and Space Journal*, vol. 17, Sept. 1971, p. 271-274.

A test program in which several proposed takeoff requirements were evaluated using an F-102A. Particular attention was given to takeoff speeds, expected operational takeoff speed abuses and their effects on safe performance, and minimum speed determination methods. Handling qualities and performance trends were evaluated on a six-degree-of-freedom flight simulator. The aircraft simulated include a reference subsonic design, a generalized SST design, and a specific model of the Concorde prototype. V.P.

A71-42923 # On the variation of intensity of aircraft 'permanent' magnetic fields. P. Charlton (Canadian Armed Forces, Directorate of Aeronautical Engineering, Toronto, Canada). *Canadian Aeronautics and Space Journal*, vol. 17, Sept. 1971, p. 275-277.

The performance of Magnetic Anomaly Detection (MAD) equipment is dependent upon the signal-to-noise ratio achieved. The amount of noise, in turn, is a function of the strength of the aircraft's magnetic field and the degree to which it is affected by aircraft movements relative to the earth's field. Nulling out, or compensating, the aircraft's field reduces the effective aircraft field strength and hence the maneuver noise. However, after compensation the aircraft permanent field strength has been found to change,

apparently due to the earth's field inducing magnetism into components of the aircraft structure. These changes in the so-called permanent field degrade MAD equipment performance but tests have shown that they can be predicted, measured and, to some degree, alleviated by selective parking of the aircraft relative to the local earth's field direction. (Author)

A71-42926 # Mi-12 - A new dimension in helicopter design (Mi-12 - Eine neue Dimension im Hubschrauberbau). Karl-Heinz Eyermann. *Technisch-ökonomische Informationen der zivilen Luftfahrt*, vol. 7, no. 8, 1971, p. 345-354. In German.

The design concepts for the Mi-12 have been significantly influenced by the specific economic and geographic conditions of the northern and eastern territories of the USSR. The Mi-12 is well suited for the transportation of heavy equipment needed for the production of oil and for other industrial developments. One of the most difficult problems which had to be solved during the design of the aircraft was the connection between the two pairs of gas turbines by a rigid shaft of 30 m length. The potential of the helicopter for the transportation of heavy loads was demonstrated in a flight in which the Mi-12 reached an altitude of 2951 m with a payload weighing 31,030 kg. In another flight the aircraft rose with a payload of 40,204.50 kg to an altitude of 2255 m. G.R.

A71-42927 # The control system of the Tu-154 (Steuerungssystem der Tu-154). F. Woloschin. (*Grazhdanskaia Aviatsiia*, no. 5, 1971.) *Technisch-ökonomische Informationen der zivilen Luftfahrt*, vol. 7, no. 8, 1971, p. 355-374. 17 refs. In German.

The Tu-154 has a cruising speed of about 0.9 Mach at altitudes of 11,000 m. Compressibility effects of the air under those conditions affect the stability and control characteristics of the aircraft. A dependence on manual control is only justified at flight speeds up to 0.85 Mach. The Tu-154 employs, therefore, a nonreversible hydraulic control system, making use of four hydraulic pumps. Details of a suitable design of the control system are discussed, giving attention to the maintenance of aircraft control in case of an emergency due to failure of a component. G.R.

A71-43088 * Radar observations of the convective process in the clear air - A review. II. T. G. Konrad and J. S. Brennan (Johns Hopkins University, Silver Spring, Md.). *Aero-Revue*, Sept. 1971, p. 487-489. 12 refs. USAF-NASA-supported research.

Cells often have turreted tops. Contour tracings of the same cell taken from a PPI sequence are presented. The cell growth is shown by the time sequence at several altitudes covering roughly 20 min. At the lower altitudes the cell appears singular and its pattern becomes progressively more unrecognizable with time as the top of the cell grows to higher levels. At higher elevations the cell appears two-headed. Aspects of cell drift, growth, and distribution are discussed. G.R.

A71-43089 The application of high lift devices to competition gliders. Nicholas Goodhart. *Aero-Revue*, Sept. 1971, p. 489-491.

The theoretical benefits to be obtained from high lift devices are examined, giving particular attention to Sigma high performance gliders. It is generally accepted that competition gliders will normally operate by climbing in circling flight in thermals and making distance in straight gliding flight between thermals. The merit of various design possibilities for the conflicting climb/cruise requirements are investigated. G.R.

A71-43090 # Optimal autorotation landing parameters for a helicopter (Optymalne parametry autorotacyjnego lądowania śmigłowca). Kazimierz Szumański. *Instytut Lotnictwa, Prace*, no. 45, 1971, p. 3-18. 5 refs. In Polish.

Theoretical analysis of factors governing the autorotation-mode helicopter landing process. A method is described for delineating domains within which the landing parameters can be varied while ensuring touchdown in a given area at zero sinking speed. A limitation is imposed on the rotor speed due to flow separation on the blades. Numerical examples are given for the Mi-2 helicopter. T.M.

A71-43197 # Repair or throwaway - Graphic screening techniques help supply the answer. James K. Segar (Lockheed-California Co., Burbank, Calif.). *Logistics Spectrum*, vol. 5, Fall 1971, p. 18-25.

It has been estimated that an overall saving as great as 30% may be realized if each spare part assembly is subjected to an economic analysis of the desirability of repairing the assembly. A technique is presented for making repair-throwaway decisions which minimize costs over life cycle. The technique indicates those cases where a clear-cut decision cannot be made because of imprecise knowledge of costs and failure rates. It is pointed out that the repair-throwaway analysis should be considered for each part as early as possible in the development stage of an aircraft because potential economic savings are greatest then. G.R.

A71-43226 Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings. Seminar sponsored by the Flight Safety Foundation. Arlington, Va., Flight Safety Foundation, Inc., 1971. 117 p. \$6.00.

An approach to safety problems is discussed together with corporate accident statistics, the determination of the causes of aircraft skidding accidents, Lufthansa pilot training programs, aircraft wake turbulence, the airport certification program, and corporate flight operations in the Japan area. Other subjects considered include ditching and survival, aviation fuels and their safety aspects, the significance of circadian rhythm for pilots, in-flight monitoring and engine reliability, and aircraft modifications. G.R.

A71-43227 # 1970 corporate accident statistics. C. A. McKinnon (Flight Safety Foundation, Inc., Arlington, Va.). In: *Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings.* Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 9-15.

The data presented are based on preliminary data furnished through the courtesy of the National Transportation Safety Board and the Federal Aviation Administration. In an analysis of the data it is found that 70% of the Corporate/Executive fatal accidents occurred on ferry flights. There is a lack of discipline in some corporate flying that becomes acute on flights without passengers. It is pointed out that corporations should be able to improve their safety record with more careful selection, training, and supervision of pilots. This is particularly true of smaller organizations with single pilot operations. G.R.

A71-43228 * # Determining causation of aircraft skidding accidents or incidents. Walter B. Horne and Upshur T. Joyner

(NASA, Langley Research Center, Hampton, Va.). In: *Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings.* Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 16-29.

Accident investigators have been especially hampered by the lack of reliable means to establish the actual slipperiness of the runway for a given accident situation to aid in their determinations. Slipperiness measurements obtained with a NASA test vehicle are discussed. Computations of aircraft stopping distance using test vehicle stopping distance measurements are compared to FAR wet field length requirements. The investigations of the causes of two aircraft accidents/incidents have shown reasonable agreement between calculated airplane stopping distance on a specific wet runway and the observed aircraft stopping distance. G.R.

A71-43229 # Ditching and survival. Norman C. Seebach (Flight Safety Foundation, Inc., Arlington, Va.). In: *Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings.* Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 30-36.

The ditching of a DC-9 jet in the Caribbean in May 1970 is briefly reviewed. Twenty-three passengers lost their lives in the incident. The Coast Guard estimated the swells to be from 8 to 10 feet. Problems were experienced with the life vests both in the aircraft and in the water. The lessons to be learned from the accident are discussed. The importance of passenger-briefing is emphasized, and suggestions for such a briefing are made. It is recommended that each crewmember's jacket be equipped with a small battery-operated VHF transceiver to coordinate rescue operations with aircraft overhead. G.R.

A71-43231 # Aviation fuels and their safety aspects. Alexander R. Ogston. In: *Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings.* Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 45-54.

Hazards caused by the use of the highly volatile and flammable gasoline during the early days of aviation are reviewed. A special gasoline called 'Safety Fuel' was produced prior to World War II. Unfortunately there were certain problems which at the time defied practical solution. The advent of the jet engine, which can use low volatility fuel, represented a major contribution to flight safety. Various currently used fuels are discussed together with properties related to safety aspects of a fuel. In conclusion it is pointed out that there appears to be a well-justified case for prohibiting by regulatory action the use of JP-4 or Jet B type fuel in commercial passenger-carrying aircraft. G.R.

A71-43233 # In-flight monitoring and engine reliability. W. K. Russell (Dallas Airmotive, Inc., Dallas, Tex.). In: *Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings.* Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 65-70.

An original and unique system of turbine engine operational surveillance has been developed. The program is computer-oriented in order to achieve consistency plus rapid response time and particularly to store and correlate pertinent operational data from the time of the manufacturer's green test run-up to today's flight. The method permits performance-monitoring starting at any time of the engine's life. It is attempted to determine deterioration from the time of the profile, and not on the basis of a comparison of engine data with a 'theory engine.' To establish the preliminary profile, the operator has to accumulate 25 to 30 recordings of selected readings during established cruise conditions. G.R.

A71-43234 * # Aircraft wake turbulence progress and plans. William A. McGowan and Mason T. Charak (NASA, Washington, D.C.). In: *Annual Corporate Aircraft Safety Seminar, 16th,*

Washington, D.C., April 19, 20, 1971, Proceedings.
Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 71-87, 22 refs.

Analytical and flight test data are used to establish the inflight hazards associated with trailing vortex encounters. Techniques are suggested for avoiding the damaging manifestations of aircraft wake turbulence, taking into account various flight regimes. The comprehensive aircraft wake turbulence research program supported by NASA is outlined. Flight and model tests and instrument development for remote wind sensing are used to improve understanding of the aircraft wake turbulence generated by heavy transport aircraft. Other studies are conducted for uncovering ways to prevent the trailing vortices from forming or to induce early dissipation of dangerous winds. G.R.

A71-43235 # Don't call them air carrier airports. James C. Pope (FAA, Airport Certification Branch, Washington, D.C.). In: Annual Corporate Aircraft Safety Seminar, 16th, Washington, D.C., April 19, 20, 1971, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1971, p. 88-100.

In 1970 Congress enacted the Airport and Airway Development Act of 1970 which provides for mandatory minimum safety standards, airport certification, and improved air navigation facilities. The act includes provisions for issuance of airport operating certificates to airports serving air carriers certificated by the Civil Aeronautics Board. As a result of a comprehensive evaluation of all related factors, a two-phase certification program has been developed. The regulations regarding airport operating certificates are presented, and the tasks that lie ahead are analyzed. G.R.

A71-43312 # Lifting line theory of a wing in uniform shear flow. Kuninobu Morita. *JSME, Bulletin*, vol. 14, June 1971, p. 550-558; Discussion, p. 558-560; Author's Closure, p. 560-563. 9 refs.

Analysis of the characteristics of a finite large aspect ratio wing in a uniform shear flow with velocity variations along the wing span. A singularity approach different from the one used by Kármán and Tsien (1943) is applied to determine the characteristics of various wings of this type in discrete form. Also studied is the different behavior of large aspect wing characteristics in a uniform shear flow and in a uniform potential flow. Analytical expressions are given for a planar wing and for aerodynamic forces providing minimum drag. V.Z.

A71-43347 # Nitrous oxide - A natural source of stratospheric NO. Michael B. McElroy and John C. McConnell (Harvard University, Cambridge, Mass.). *Journal of the Atmospheric Sciences*, vol. 28, Sept. 1971, p. 1095-1098. 33 refs. NSF Grant No. GP-13982.

Investigation of an important natural source of NO, the reaction $O(\text{super } 1D) + N_2O$ yields $2NO$, and comparison of the natural source with estimates for the source due to a fleet of 500 planes cruising for an average of 7 hr a day. The natural and artificial inputs above 15 km are of comparable magnitude. The natural source corresponds to a net production of NO, averaged over the globe, of about 2×10 to the 7th molecules sq cm/sec , and offers a yardstick for judging the possible significance of any artificial input. Additional sources of stratospheric NO, due to downward diffusion from the ionosphere and upward transport from the earth's surface, are discussed but are not quantitatively estimated. (Author)

A71-43357 Comparative study of two-dimensional and three-dimensional wakes in supersonic and hypersonic rarefied-gas flows (Etude comparative des sillages bidimensionnels et tridimensionnels dans des écoulements supersoniques et hypersoniques de gaz raréfié). Jean Allègre, Christian Matrand, and Michel Raffin

(CNRS, Laboratoire d'Aérodynamique, Meudon, Hauts-de-Seine, France). *Académie des Sciences (Paris), Comptes Rendus, Série A - Sciences Mathématiques*, vol. 273, no. 11, Sept. 13, 1971, p. 467-469. In French. Direction des Recherches et Moyens d'Essais Contract No. 525-68.

Results of an experimental study of the wakes of two- and three-dimensional bodies in rarefied-gas wind tunnels at various Mach and Reynolds numbers. Some remarks are made concerning the wake configuration of a dihedral in a high-speed rarefied-gas flow. A comparison is made between the wakes of a cone and a dihedral placed at a 12-deg angle of attack in a Mach 4 flow, showing a larger opening in the case of the two-dimensional wake and a lower pressure recorded on the axis of the two-dimensional wake downstream from the base. A.B.K.

A71-43379 Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Seminar sponsored by the Flight Safety Foundation. Arlington, Va., Flight Safety Foundation, Inc., 1970. 140 p. \$5.00.

General aspects of aviation developments are discussed, and corporate aircraft accident statistics are examined. Factors related to the aircraft accidents and their prevention are considered including aircraft vortex wakes, accelerate-stop criteria, rescue operations in case of crash or fire, physical fitness and fatigue in aircrew members, and corporate pilot training programs. Questions of adequately functioning instrumentation as an important factor in avoiding accidents are covered by giving attention to altitude indicating devices and the advantages of Angle of Attack Instrumentation. G.R.

A71-43380 # Another look at accelerate-stop criteria. T. G. Foxworth and H. F. Marthinsen (Air Line Pilots Association, Washington, D.C.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 28 p. 74 refs.

Accelerate-stop criteria developed prior to the introduction of the jet transport are reviewed in light of operational experience. Reaction times presently used by the manufacturers in accelerate-stop calculations are examined from the human engineering standpoint. Results of a flight simulator study showing pilot reaction times for transition to the rejected take-off configuration are presented. Each pilot subject in the study was unexpectedly confronted with a simultaneous fire warning bell and light at some specified time increment prior to attaining $V_{\text{sub } 1}$ during a simulated take-off. The resulting times for transition to the full braking configuration and the associated overspeeds above the critical engine failure speed, $V_{\text{sub } 1}$, are compared to the certification performance and show a need for revision to the present criteria. (Author)

A71-43381 * # Aircraft vortex wakes. Robert W. Boswinkle, Jr. (NASA, Langley Research Center, Hampton, Va.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 8 p. 8 refs.

An aircraft which is producing lift leaves a rotating flow field behind each wing as it flies forward. There is usually one pair of oppositely rotating flow fields, or vortices, extending downstream from each wing tip and moving downward. Each vortex has a core region in which the rotational velocities build up from zero in the center to some maximum velocity at the edge of the core. If another aircraft crosses laterally through the core of each vortex, it will be subjected to an up-flow, a down-flow, and then another up-flow. Hazards connected with these air motions for a light aircraft are discussed. G.R.

A71-43382 # Operational considerations of angle of attack. W. Lange (Teledyne Avionics, Charlottesville, Va.). In: Annual

Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 9 p.

Technology has now provided a new addition to instrumentation used for the evaluation and control of a certain aspect of total aircraft performance. This addition is called Angle of Attack Instrumentation. Various parameters and relations which are involved in the lift performance of an aircraft are examined. The importance of the angle of attack in connection with lift performance is discussed, together with aspects regarding the occurrence of a phugoid oscillation. G.R.

A71-43383 # Altitude awareness. Fred Illston (American Airlines, Inc., New York, N.Y.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 16 p.

The development of the altitude instrumentation for the aircraft pilot is discussed. The first instruments, based on the variation of the air pressure with altitude, were improved to allow for barometric adjustments. Weaknesses of the three-pointer Altimeter led to the Servo-Altimeter, a drum-pointer configuration, and to direct readout of the altitude on a digital counter. Other approaches discussed include the radar Altimeter with the 'Altitude Alert' system, and automatic altitude reporting systems. G.R.

A71-43384 # Altitude... or pressure. John J. Carroll (National Transportation Safety Board, Bureau of Aviation Safety, Washington, D.C.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 6 p.

Several years ago, government agency studies concluded that regardless of barometric altimetry system inadequacies, there was nothing better to go to. After the rash of catastrophic air carrier approach and landing accidents during December 1968 and January 1969, the Safety Board released a series of recommendations to the FAA intended to prevent recurrences of such accidents. Among other things it was pointed out that 'the reassessment of altimetry systems with particular regard to their susceptibility to insidious interference by forms of precipitation needs to be the subject of attention by the highest level of aeronautical research facilities and personnel.' G.R.

A71-43385 # Pressure instruments - Their use and misuse. James W. Angus (Kollsman Instrument Corp., Syosset, N.Y.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 10 p.

The pressure altimeter, sensitive airspeed and vertical velocity instruments are a very important aid during the landing and takeoff phases of flight. There are six key points to be considered which will allow the pilot to obtain proper performance from his instruments. These points include the selection of the right instruments, careful instrument installation, the pilot's ability to recognize the normal from the abnormal conditions of operation, the identification of a problem for the repairman, the selection of a suitable repair shop, and familiarity with a number of altimeter characteristics. G.R.

A71-43386 # Trust your altimeter. James L. Hemingway (FAA, Washington, D.C.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 4 p.

In the case of a test program conducted in 1963 involving 152 general aviation aircraft it was found that not a single altimeter was

within the tolerance now specified in the rules. A subsequently adopted regulation requires all general aviation aircraft to have an altimeter and static system test before being flown in IFR. Possible problems with altimeters are discussed along with suggestions for remedial action. G.R.

A71-43387 # Pitot static systems. J. A. Severt (Swearingen Aircraft, San Antonio, Tex.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 3 p.

A number of aspects of pitot-static systems are discussed, giving attention to the various components involved. It is pointed out that a removable drain plug which is easily accessible for inspection shall be located at all low points where water may collect. Problems of line installation are considered, together with the location of the manifolds, and the design of the alternate static system. G.R.

A71-43388 # Corporate training. E. L. Hutcheson (Flight Safety Foundation, Inc., Arlington, Va.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 12 p.

It is pointed out that in aviation the group with the most stringent training requirements for pilots has percentage-wise the smallest number of accidents caused by pilots. Examples of accident causes involving pilot errors are considered. A training program for pilots is suggested, giving attention to a ground and a flight training phase. Flight Check Records are recommended to determine any area that needs specific stress during this training. G.R.

A71-43389 # The challenge of aircraft crash fire rescue. Earl W. Keegan (Flight Safety Foundation, Inc., Arlington, Va.). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 7 p. 9 refs.

This paper provides a review of the current airport fire-fighting equipment and requirements. Statistics are offered concerning the inadequacies of such equipment at many airports served by air carriers and suggestions are made for improving the situation. The latest available fire-fighting equipment and fire-fighting agents are detailed as well as that equipment programmed by manufacturers for future use. The author also offers ideas and concepts on fire-fighting tactics that could be employed today, and those to meet future airport needs. (Author)

A71-43391 # Corporate operations in Latin America. Harold Curtis (National Distillers). In: Annual Corporate Aircraft Safety Seminar, 15th, San Antonio, Tex., May 11-13, 1970, Proceedings. Arlington, Va., Flight Safety Foundation, Inc., 1970. 9 p.

It is assumed that multiengine pressurized turbine-powered aircraft are used. Standard vhf communication and navigation in duplicate is essential, and dual ADF is suggested. The use of hf is recommended as the only means to maintain communication in certain areas. Various details regarding flight operations in Latin America are discussed including the amount of fuel to be carried, the paper work, problems of navigation, food, vaccinations, and weather. G.R.

A71-43448 On combustion generated noise. Warren C. Strahle (Georgia Institute of Technology, Atlanta, Ga.). *Journal of Fluid Mechanics*, vol. 49, Sept. 29, 1971, p. 399-414. 21 refs.

Upon review of past experimental results and theoretical efforts it is apparent that the mechanism by which combustion noise is generated is not well understood. A theory of combustion noise is developed in this paper which follows rigorously from the principles

of fluid mechanics. Lighthill's approach, used in his studies of aerodynamic noise, is closely followed in the present work. The sound radiated from open, turbulent flames is found to depend strongly upon the structure of such flames; at present their structure is not well known. However, meaningful bounds and scaling rules for the sound power output and spectral content are derived based upon the present limited knowledge. A framework is developed which explains past experimental work and the origin of combustion noise. (Author)

A71-43487 # The integral equation of the supporting rectangular plane in symmetric flow (Zur Integralgleichung der tragenden Rechteckfläche bei symmetrischer Anströmung). H. Schubert and W. Wittig (Halle, Universität, Halle, East Germany). *Zeitschrift für angewandte Mathematik und Mechanik*, vol. 51, Aug. 1971, p. 345-352. 10 refs. In German.

A rectangular thin airfoil in a flow orthogonal to the leading edge is considered, taking into account the case of a small angle of attack. The flow around the airfoil is analyzed by making use of two components, the fundamental flow and the perturbation flow. Assumptions needed for obtaining a singular integral equation for calculating the circulation density are discussed. The singular integral equation is transformed into the form reported by Weissinger (1949). G.R.

A71-43554 # Experimental study of the operation of axial-flow compressors during rotation of the guide vanes (Eksperimental'noe issledovanie raboty osevykh kompressorov pri povorote napravliaiushchikh lopatok). V. I. Titenskii and V. G. Karpov. *Energomashinostroenie*, vol. 17, July 1971, p. 43-46. 5 refs. In Russian.

Study of the possibilities of a method of expanding the range of stable operation of axial-flow compressors by regulating the rotating guide vanes on two four-stage model compressors with degrees of reactivity of 0.5 and 1, respectively. It is shown that regulation of rotating guide vanes may be successfully used for compressors with both degrees of reactivity. It is further shown that Titenskii and Shirokov's (1967) method of calculating the characteristics of the stages and flow area of an axial-flow compressor during rotation of the guide vanes gives results which are in satisfactory agreement with experimental results. A.B.K.

A71-43586 Société Internationale de Photogrammétrie, Symposium on Photogrammetry of Moving Objects, Saint-Mandé, Val-de-Marne, France, September 21, 22, 1970, Proceedings. Part 2 (Société Internationale de Photogrammétrie, Symposium sur la Photogrammétrie des Objets en Mouvement, Saint-Mandé, Val-de-Marne, France, September 21, 22, 1970, Proceedings. Part 2). Société Française de Photogrammétrie, Bulletin, Jan. 1971. 63 p. In French, English, and German.

The papers deal with developments in the field of photogrammetry, including photo-optical calibration of radio-navigation aids, photogrammetry in traffic merging studies and photogrammetric analysis of an airfoil.

V.P.

A71-43587 Photo-optical calibration of aeronautics radio navigation aids. Gabor Remetey-Fülöpp (VIZITERV, Budapest, Hungary). (Société Internationale de Photogrammétrie, Symposium sur la Photogrammétrie des Objets en Mouvement, Saint-Mandé, Val-de-Marne, France, Sept. 21, 22, 1970.) Société Française de Photogrammétrie, Bulletin, Jan. 1971, p. 19-26. 5 refs.

The advantages of photogrammetric techniques for calibrating and checking airport ILS systems are outlined. In the photogrammetric method, the aircraft is made to circle or to perform radial flights, with lights flashing up at an appropriate pointer position of the cockpit voltmeter, or at a relative minimum or maximum field intensity measured by the board voltmeter. Colored lights may be used to distinguish between flashing signals referring to

relative minimum or maximum position. The ground equipment incorporates a phototheodolite or digitized theodolite fitted with a technical camera, and an electronic range meter for determining the Y-base distances. V.P.

A71-43588 Photogrammetric analysis of the aerodynamics of a rotating airfoil (Analyse photogrammétrique de l'aérodynamique d'une voilure tournante). A.-J. Brandenberger (Université Laval, Quebec, Canada). (Société Internationale de Photogrammétrie, Symposium sur la Photogrammétrie des Objets en Mouvement, Saint-Mandé, Val-de-Marne, France, Sept. 21, 22, 1970.) Société Française de Photogrammétrie, Bulletin, Jan. 1971, p. 27-31. In French.

A wind tunnel investigation is described in which the aerodynamics effects produced by a helicopter rotor were recorded photogrammetrically with the aid of smoke visualization techniques. The observed effects are plotted. The equipment and procedure employed are described, and the precision of the technique is assessed. V.P.

A71-43592 * # Compressible flow across shaft face seals. John Zuk, Lawrence P. Ludwig, and Robert L. Johnson (NASA, Lewis Research Center, Cleveland, Ohio). *British Hydromechanics Research Association, International Conference on Fluid Sealing, 5th, University of Warwick, Coventry, England, Mar. 30-Apr. 2, 1971, Paper. 44* p. 20 refs.

An analysis is presented for compressible fluid flow across shaft face seals and narrow slots. The analysis includes fluid inertia, viscous friction and entrance losses. Subsonic and choked flow conditions can be predicted and analyzed. The model is valid for both laminar and turbulent flows. Results agree with experiment and with solutions which are more limited in applicability. Results show that a parallel film can have a positive film stiffness under choked flow conditions. (Author)

A71-43599 * # Inlet-engine-nozzle wind tunnel test techniques. D. N. Bowditch (NASA, Lewis Research Center, Cleveland, Ohio). *NATO, AGARD, Meeting of the Propulsion and Energetics Panel, 38th, Sandefjord, Norway, Sept. 13-17, 1971, Paper. 29* p. 20 refs.

Experimental investigation of the inlet, engine, and exhaust nozzle of a supersonic propulsion system. Wind-tunnel and flight-test exhaust nozzle results are compared, and the accuracy of flight measurements is assessed. Comparisons are also presented for nozzle performance obtained with a cold jet, a powered turbojet simulator, and a solid jet boundary simulator. The effect of the local boundary layer on nozzle performance is discussed, and the need for good dynamic measurements during inlet-engine testing is illustrated for transients such as inlet unstart and engine stall. Also, the transient nature of inlet distortion and its effect on the engine are described for two different operating conditions. T.M.

A71-43600 * # Effect of operating variables on pollutant emissions from aircraft turbine engine combustors. Jack Grobman (NASA, Lewis Research Center, Cleveland, Ohio). *General Motors Corp., Symposium, Warren, Mich., Sept. 27, 28, 1971, Paper. 40* p. 29 refs.

The purpose of this paper is to review NASA-Lewis combustor research aimed at reducing exhaust emissions from jet aircraft engines. Experimental results of tests performed on both conventional and experimental combustors over a range of inlet total pressure, inlet total temperature, reference velocity, and fuel-air ratio are presented to demonstrate the effect of operating variables on pollutant emissions. Combustor design techniques to reduce emissions are discussed. Improving fuel atomization by using an air-assist fuel nozzle has been shown to significantly reduce hydrocarbon and carbon monoxide emissions during idle. A short-length

annular swirl-can combustor has demonstrated a significant reduction in nitric oxide emissions compared to a conventional combustor operating at similar conditions. The use of diffuser wall bleed to provide variable control of combustor airflow distribution may enable the achievement of reduced emissions without compromising combustor performance. (Author)

A71-43878 Low frequency air navigation in Southeast Asia. Bruce E. Gearhart (USAF, Washington, D.C.). *Signal*, vol. 26, Nov. 1971, p. 20-24.

The discussion is concerned primarily with the AN/MRN-13 set, while a brief comparison with the AN/GRN-6 set is conducted to show planning differences. Both sets were deployed to Khe Sanh and Kham Due for tactical air support. The AN/MRN-13 is a mobile, air conditioned beacon which utilizes the NA/URN-5 transmitter. The URN-5 operates from an unattended V-83 van, with power adjustable from 25 watts to 400 watts. The URN-5 can be preset to any frequency within 200 to 800 kHz. Experience with the equipment is discussed, giving attention also to certain operation and maintenance problems. G.R.

A71-43887 Test report: Acrostar Mk. II (Test: Acrostar Mk. II). Walter Wolfrum. *Flugrevue/Flugwelt International*, Oct. 1971, p. 30-33. In German.

The history and technical characteristics of an all-wood single-seat high-performance acrobatic light-weight aircraft. The aircraft is designed for stresses ranging from +8 g to -8 g and for long periods of inverted flight. The aircraft profile is almost symmetrical, which means that the aerodynamic characteristics hardly differ in normal and inverted flight. The Hartzell constant speed propeller is driven by 220 hp Franklin 6A-350-CI six-cylinder air-cooled engine. The landing gear is not retractable. Extensive tests performed with the aircraft are described in detail. V.R.

A71-43888 A step toward automatic air traffic control. (Der automatischen Flugsicherung einen Schritt näher). Wilfried E. Zuschlag (Internationale Büro-Maschinen Gesellschaft mbH, Sindelfingen, West Germany). *Flugrevue/Flugwelt International*, Oct. 1971, p. 35-38, 43, 44. In German.

The application of the IBM 9020 multiprocessing computer system to air traffic control is examined. The computer system and its operation are described, and the control sectors for inflight control at air route traffic control centers are discussed. An operational malfunction-analysis program is outlined, and the modes of operation of the polymorphic IBM 9020 computer system are examined. V.P.

A71-43889 Laser technique for determining the meteorological visibility range at airports (Lasertechnik zur Bestimmung der meteorologischen Sicht auf Flugplätzen). Roland Ziegler. *Flugrevue/Flugwelt International*, Oct. 1971, p. 45, 46. In German.

Methods and equipments currently used at airports to determine the runway visibility range (RVR), the slant visibility range (SVR), the lower cloud boundary, and the atmospheric damping coefficient are reviewed. The advantages of using lasers as light sources and using lidars for determining the relationship between reflected light and the state of the atmosphere are outlined. V.P.

A71-43897 Principles of automated checking of the operational capability of aircraft engines and the systems functionally connected to them. G. P. Shibanov. (Avtometriia, Sept.-Oct. 1970, p. 111-117.) *Automatic Monitoring and Measuring*, Sept.-Oct. 1970, p. 476-481. Translation.

Consideration of certain enumerated principles from the point of view of Boolean algebra and the algebra of events and states in an

attempt to formulate these principles relative to their realization with an automatic monitoring system (AMS) designed on the basis of digital technology. An algorithm is derived which establishes the connection between the separate states of the AMS and the operating regimes of the monitored object, and may be used for automatic association of the states of the AMS to the cyclogram for checking the operational capability of different types of aircraft engines and the systems functionally connected with them. F.R.L.

A71-44071 # Selecting the geometry of a two-dimensional variable-geometry nozzle for a supersonic wind tunnel (O vybere geometrii ploskogo reguliruemogo sopla sverkhzvukovoi aerodinamicheskoi truby). L. P. Kozhenkova. *Akademiia Nauk Latvinskoi SSR, Izvestiia, Seriya Fizicheskikh i Tekhnicheskikh Nauk*, no. 4, 1971, p. 45-48. In Russian.

Formulas are derived, using which the principal geometrical parameters of a two-dimensional supersonic variable-area nozzle can be calculated as a function of the Mach number. The advantages of varying the rigid portion of the nozzle with respect to the Mach number in the case of a wide range of Mach numbers are demonstrated. V.P.

A71-44077 Minimum order state reconstruction filters for constant plants. Lee Gregor Hofmann (Systems Technology, Inc., Princeton, N.J.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 22-30. 21 refs. Contract No. AF 33(615)-69-C-1359.

Optimal control laws and decoupling control laws usually require the complete plant state. However, only a limited number of measurements are usually available in practice. Procedures are developed for obtaining the equations for a minimum order filter which can reconstruct the state from the given measurements when the rank of the augmented control effectiveness matrix is equal to the number of measurements and when a certain matrix constructed from the plant matrices is nonsingular. If m is the number of measurements for an n -th order plant, this filter requires a total of $(n-m)$ integrations and differentiations for realization in general. For the case of practical interest where no differentiations are required, the filter requires $(n-m)$ integrations for realization. An application to a significant multiple control-point problem in aircraft flight control illustrates the use of the theory. T.M.

A71-44089 Identification of aircraft states and parameters. W. H. Kroy, Jr. (McDonnell Douglas Astronautics Co., Huntington Beach, Calif.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 302a, 302b. 6 refs.

The utilization is discussed of available flight test measurements for improved estimates of parameters characterizing new aircraft. The example cited involves estimating the aerodynamic parameters associated with the equations of motion of a large aircraft, such as the DC-10, in the lateral mode when nonperfect measurements of the state and nonperfect measurements of some of the derivatives of the state are available. The total number of states and parameters to be identified is 26. A modified version of the Kopp/Oxford form of the relinearized Kalman filter was developed and used to identify the augmented state vector. Good starting estimates reduced the level of biased errors appreciably. The ability of the filter to estimate the states was very good, with errors in the fraction of one percent. M.V.E.

A71-44093 A nonvarying-C* control scheme for aircraft. Edward R. Rang (Honeywell, Inc., Hopkins, Minn.; U.S. Naval

Postgraduate School, Monterey, Calif.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 369-374. 14 refs.

Evaluation of the concept that a sum of normal acceleration and pitch rate appears to be the best variable to use to control aircraft in the longitudinal axis. The C-Criterion specifies that the time response of this quantity must fall in a prescribed envelope for all speeds and altitudes. The control scheme is based on the observation that this is equivalent to controlling the system so that the coefficients of a certain equation which describes the aircraft's short-period motion are held fixed. This is done by using feedbacks with variable gains, the gain-changing mechanism being found by using gradient techniques. The system was shown to be practical by analog simulation. It was found to be tolerant of instrument noise, elevator hysteresis, and other complications not accounted for in the analytical derivations. F.R.L.

A71-44104 **An application of stochastic optimal control theory to the optimal rescheduling of airplanes.** R. S. Ellis and R. W. Rishel (Bell Telephone Laboratories, Inc., Whippany, N.J.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 527-535. 5 refs.

A model for the air traffic flow between two airports subject to random constraints on the take-off and landing capacities is set up. A dynamic programming algorithm for computation of optimal landing and take-off rules is established. For a simple case the algorithm is used to compute the optimal solutions explicitly. The methods used will generalize to problems of optimal control of linear systems subject to random constraints. The specific case discussed illustrates the problems that will be encountered in computing optimal feedback control laws for these types of systems. (Author)

A71-44105 **An approach to semiautomated optimal scheduling and holding strategies for air traffic control.** Michael Athans and Lynn W. Porter (MIT, Cambridge, Mass.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 536-545. 5 refs.

Consideration of the problem of coordinating the traffic flow and holding patterns of N aircraft which desire to land on a single runway. A distance separation is to be enforced over the outer marker. It is shown that this problem can be attacked as a variation of a linear-quadratic optimal control problem. The solution of this optimization problem can be used to indicate which aircraft can accomplish headway corrections by velocity control, and which ones must undergo path stretching or holding maneuvers. The gradual implementation of these strategies in current and evolutionary ATC systems is discussed. F.R.L.

A71-44106 **Active flutter control - Flight test system synthesis.** Robert P. Johannes (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 599-607.

Discussion of the synthesis of a flutter mode control system for flight test, with summary of a study to determine the feasibility of an actual flutter control demonstration as part of the Control Configured Vehicles (CCV) Advanced Development Program. The analytical study shows that it is quite practical to artificially destabilize a symmetrical wing flutter mode through adverse mass balancing, and then provide active flutter control of the mode and those modes directly associated with that unstable mode for flight demonstration on the Load Alleviation and Mode Stabilization (LAMS) test vehicle. F.R.L.

A71-44107 **Active flutter suppression - An emerging technology.** G. O. Thompson and G. J. Kass (Boeing Co., Wichita, Kan.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 608-616. 40 refs.

Consideration of the control of aircraft elastic modes as a result of studies made over the past decade. Flight demonstration of Stability Augmentation Systems on the B-52 and XB-70 aircraft have demonstrated the value of suppressing stable structural modes. These programs and others which provide the basis to proceed with confidence to active control of unstable modes are discussed. Attention is also given to the limited analytical studies accomplished on unstable or flutter modes, with suggestion of future areas of research which can bring this emerging technology to fruition. F.R.L.

A71-44108 **Potential performance gains by use of a flutter suppression system.** L. J. Topp (Boeing Co., Seattle, Wash.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 617-623.

Discussion of the potential gains which can be achieved by using an active flutter suppression system (FSS) in lieu of conventional means of flutter speed improvement. Analyses show that an FSS, using a dedicated control surface, may impose a smaller weight penalty on an aircraft than mass balancing, an increase in stiffness, or geometry changes. The amount of flutter speed improvement with the FSS is shown to be a function of the location of applied force, the type of sensor or sensors and their locations, and the control system transfer function. Results indicate that adequate margins in gain and phase, as well as the required modal damping, can be achieved. F.R.L.

A71-44109 **A feasibility study of active wing/store flutter control.** W. E. Triplett (McDonnell Aircraft Co., St. Louis, Mo.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 624-632. 12 refs.

Analytical investigations of active feedback flutter control for fighter type aircraft, specifically with respect to wing/store flutter control, show promise of significant benefits for both contemporary and future aircraft. The F-4 Phantom aircraft with an external store is idealized for a flutter critical configuration. Computer programs, based on both frequency and time domains, are used with conventional control system design techniques to generate feedback compensation for active control of flutter for this configuration. Results of linear analyses indicate the possibility of expanding the permissible flight envelope by 150 knots using the existing aileron control surfaces and establish preliminary requirements for control system hardware. (Author)

A71-44111 **Adaptive guaranteed cost control of systems with uncertain parameters.** S. S. L. Chang and T. K. C. Peng (New York, State University, Stony Brook, N.Y.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 686-694. 15 refs. NSF Grant No. GK-16017; Grant No. AF AFOSR 70-1890.

Discussion of guaranteed cost control, a method of synthesizing a closed-loop system in which the controlled plant has large parameter uncertainty. The basic theoretical development of guaranteed cost control is given, and it is shown how it can be incorporated into an adaptive system. The uncertainty in system parameters is reduced first by either on-line measurement and evaluation, or prior knowledge of the parametric dependence of a certain easily measured situation parameter. Guaranteed cost control is then used to take up the residual uncertainty. It is shown that the

uncertainty in system parameters introduces an additional term in the Riccati equation. A FORTRAN program for computing the guaranteed cost matrix and control law is developed and applied to an air frame control problem with large parameter variations. F.R.L.

A71-44113 *Parameter and model identification of nonlinear dynamical systems using a suboptimal fixed-point smoothing algorithm.* Robert T. N. Chen and Bernard J. Eulrich (Cornell Aeronautical Laboratory, Inc., Buffalo, N.Y.). In: Joint Automatic Control Conference, 12th, Washington University, St. Louis, Mo., August 11-13, 1971, Preprints of Technical Papers. New York, Institute of Electrical and Electronics Engineers, Inc., 1971, p. 731-740. 22 refs. Contract No. N 00019-69-0534.

This paper presents a suboptimal fixed-point nonlinear data smoothing algorithm for parameter and initial state estimation of nonlinear dynamic systems having a large number of parameters and unknown forcing inputs. Also presented in the paper is a method for estimating the unknown forcing inputs or modeling errors. A start-up procedure for the fixed-point smoothing algorithm and an improved computational algorithm for the variances of the fixed-point smoothed estimates are also proposed. Application of the proposed methods to the identification of V/STOL aircraft parameters is given. (Author)

A71-44189 *R & D in Soviet aviation.* Arthur J. Alexander (RAND Corp., Santa Monica, Calif.). *Instruments and Control Systems*, vol. 44, Oct. 1971, p. 37-40.

Research institutes, design bureaus, and manufacturing plants are administratively autonomous organizations coordinated under the Ministry of Aviation. A prominent feature of the Soviet aircraft industry is the absence of small contractors. Emphasis on the use of handbooks permits the research institutes to control aerodynamic structures and manufacturing techniques. A proposal for a new aircraft is submitted to several independent design bureaus. The building of the prototype is discussed together with the manufacture of the product, and approaches responsible for technological innovations. G.R.

A71-44271 # *Imai-Lamla's approximation method for the circular profile with a normal jet (Metoda de aproximare a lui Imai-Lamla pentru profilul circular cu jet normal).* A. Bárony-Nagy (Academia Română, Institutul de Matematică, Bucharest, Rumania). *Studii și Cercetări Matematice*, vol. 23, no. 9, 1971, p. 1339-1352. In Rumanian.

Brief discussion of the principle of Imai-Lamla's approximation method for subsonic flows in the presence of a steady current to infinity, parallel to the Ox axis, described by Bárony-Nagy (1969, 1971). An attempt is made to obtain the complex potential of the flow of the compressible fluid, in second approximation, under the same conditions. This problem is reduced to a Volterra problem with two given singularities, and by applying the Kutta-Joukowski theorem, the resultant of the aerodynamic forces is calculated, with an example. M.M.

A71-44273 *Solid-state airborne weather radar fully satisfying ARINC and TSO specifications.* Atsushi Kurokawa, Yoshitaka Sueishi, and Toshio Hakoda (Tokyo Shibaura Electric Co., Ltd., Tokyo, Japan). *Toshiba Review*, June 1971, p. 19-23. 8 refs.

Description of the technical status and future prospects of an airborne weather radar now being used in civilian aviation. A second-generation radar of solid-state design has been completed and is ready for commercial production. The solid-state design has made possible a weight reduction of about 30%, and a reduction in power requirement by half as compared with the vacuum tube design. F.R.L.

A71-44342 *Circling performance of sailplanes.* D. J. Marsden (Alberta, University, Edmonton, Alberta, Canada). *Aero-Revue*, Oct. 1971, p. 549-552. 10 refs.

Proposal of variable geometry in the form of high lift flaps as a means of increasing the overall cross-country speed of a sailplane by providing a better compromise between cruise and climb performance. The circling performance of a sailplane with high lift flaps is analyzed, keeping the main design parameters in the range dictated by operational considerations of straight glide performance and the characteristics of thermals encountered. The results show that a substantial increase in both climb performance and effective cross-country speed can be expected. F.R.L.

A71-44346 *A study of the stability of a plate-like load towed beneath a helicopter.* D. F. Sheldon (Royal Military College of Science, Swindon, Wilts., England). *Journal of Mechanical Engineering Science*, vol. 13, Oct. 1971, p. 330-343. 14 refs. Research supported by the Science Research Council.

Recent experience has shown that a plate-like load suspended beneath a helicopter moving in horizontal forward flight has unstable characteristics at both low and high forward speeds. These findings have prompted a theoretical analysis to determine the longitudinal and lateral dynamic stability of a suspended pallet. Only the longitudinal stability is considered here. Although it is strictly a nonlinear problem, the usual assumptions have been made to obtain linearized equations of motion. The aerodynamic derivative data required for these equations have been obtained, where possible, for the appropriate ranges of Reynolds and Strouhal number by means of static and dynamic wind tunnel testing. The resulting stability equations (with full aerodynamic derivative information) have been set up and solved, on a digital computer, to give direct indication of a stable or unstable system for a combination of physical parameters. These results have indicated a longitudinal unstable mode for all practical forward speeds. Simultaneously the important stability derivatives were found for this instability and modifications were made subsequently in the suspension system to eliminate the instabilities in the longitudinal sense. Throughout this paper, all metric dimensions are given approximately. (Author)

A71-44347 *Streamline curvature analysis of compressible and high Mach number cascade flows.* J. P. Bindon (Natal, University, Durban, Natal, Republic of South Africa) and A. D. Carmichael (MIT, Cambridge, Mass.). *Journal of Mechanical Engineering Science*, vol. 13, Oct. 1971, p. 344-357. 24 refs. Research supported by the South African Council for Scientific and Industrial Research.

A blade to blade design tool for analysing the subsonic, transonic and supersonic flows in axial turbine blades is presented using the streamline curvature method. The work includes a numerical convergence analysis which produced convergence of the digital computer programme for all cases attempted. Computed results are compared with experiment and other theory. Comparisons for turbine type cascades up to Mach 1.0 show a satisfactory agreement and techniques introduced give improved leading edge results and allow the Kutta-Joukowski condition to be applied at the trailing edge for the accurate determination of the velocity distribution and the cascade deviation. Predictions for convergent-divergent supersonic wind tunnel type nozzles agree closely with experiment and with other theories. Numerical difficulties are found to be more acute for subsonic/supersonic turbine cascades and experimental agreement, while acceptable, is inferior to that obtained for subsonic cascades. (Author)

A71-44352 *Supersonic transport aviation and air traffic control (L'aviation de transport supersonique et le controle du trafic aérien).* Jean Maigret. *Navigation* (Paris), vol. 19, Oct. 1971, p. 405-416. In French.

Results of studies conducted for more than five years by the work group formed by the German, British, and French Institutes of

Navigation concerning supersonic transport. Taxiing, takeoff, and landing maneuvers are discussed, as well as operations in terminal areas (climb and descent below Flight Level 250). Subsonic cruise and acceleration to supersonic cruise, the termination of cruise, and deceleration and descent to lower airspace are considered. Aspects of the role of ATC above ocean regions are outlined. F.R.L.

A71-44353 *Integrated system of control and operation of aircraft (Système intégré de contrôle et de commande des avions).* M. J. Jullien and J. C. Peigney (Thomson - CSF, Paris, France). *Navigation* (Paris), vol. 19, Oct. 1971, p. 417-431. In French.

Exposition of the major operational components and techniques of apparatus for visualization and manual control suitable for assembling, and for best presentation of, all useful information in each phase of a commercial or military flight. New concepts of the instrument panel to respond to old and new requirements, and new techniques and developments are described. Attention is given to the interconnections of the integrated system with the other on-board electronic equipment. F.R.L.

A71-44365 *Liquid hydrogen as a fuel for the future.* Lawrence W. Jones (Michigan, University, Ann Arbor, Mich.). *Science*, vol. 174, Oct. 22, 1971, p. 367-370. 13 refs.

The use of liquid hydrogen as a long-term replacement for hydrocarbon fuel for land and air transportation seems technically feasible. It is an ideal fuel from the standpoint of a completely cyclic system, serving as a 'working substance' in a closed chemical and thermodynamic cycle. The energy-per-unit-weight advantage over gasoline or any other hydrocarbon fuel makes liquid hydrogen particularly advantageous for aircraft and long-range land transport. As a pollution-free fuel, it must be seriously considered as the logical replacement for hydrocarbons in the 21st century. G.R.

A71-44393 # *An algorithm for search of compromise control in static hierarchical systems (Pro odin algoritmu poshuku kompromisnogo keruvannia u statichnikh ierarkhichnikh sistemakh).* V. L. Volkovich and M. F. Radom'skii. *Avtomatika*, vol. 16, July-Aug. 1971, p. 42-51. 12 refs. In Ukrainian.

It is shown that two compromise-control search problems arise for each subsystem of the inner level in a multilevel static hierarchical system. Several types of interactions between the subsystems are possible, depending on the relationships among periods of commands applied to the subsystems. In the case of simultaneous interaction among all the subsystems, the search for compromise control is reduced to a nonlinear programming problem. The results are illustrated by the example of automatic air traffic control of a number of aircraft over a given territory. T.M.

A71-44454 *Automatic flight - An introduction.* *Interavia*, vol. 26, Oct. 1971, p. 1141-1144.

Brief history of automatic flight control system development in the U.K. and the U.S., together with a description of various flight control systems and the current state of these programs. In the American approach, the pilot is retained in the control loop, while some Europeans consider that the pilot should evolve into a systems manager. Progress at the Blind Landing Experimental Unit (BLEU) is discussed. F.R.L.

A71-44455 *Automatic flight - The American view.* *Interavia*, vol. 26, Oct. 1971, p. 1145-1147.

Review of American developments in automatic flight and their application. The American philosophy on automatic landing has always included a requirement that the pilot must at all times be aware of what is going on and must supervise it. The requirements established by the FAA are outlined, and American interest in visibility enhancement as an aid to the pilot is discussed. F.R.L.

A71-44456 *Triplex and simplex - The Trident and the Caravelle.* *Interavia*, vol. 26, Oct. 1971, p. 1148-1150.

Review of two major European programs to develop automatic flight control systems that would eventually permit the aircraft to which they were fitted to carry out automatic landings in Category IIIA conditions. These were the Smiths Industries SEP5 triplex system for the de Havilland (Hawker Siddeley) Trident and the Lear Siegler-Sud Aviation AWLS simplex system for the Sud Aviation (Aérospatiale) Caravelle. The Trident made the first autoflare with fare paying passengers aboard, and the Caravelle made the first automatic landing in scheduled service in Category IIIA conditions. More experience has been gained with these aircraft than with any other type of civil aircraft. F.R.L.

A71-44558 *The effects of an oscillating flap and an acoustic resonance on vortex shedding.* J. M. R. Graham and D. J. Maull (Cambridge University, Cambridge, England). *Journal of Sound and Vibration*, vol. 18, Oct. 8, 1971, p. 371-380. 8 refs.

Vortex shedding from the blunt trailing edge of a flat plate spanning a wind tunnel under two kinds of periodic excitation is described. The conditions under which these two forms of excitation, an oscillating flap and an acoustic resonance, cause the vortex shedding to be in phase along the span are compared. Particular attention is paid to cases when the natural shedding frequency and either the flap frequency or the center frequency of the acoustic resonance, respectively, are not quite coincident. (Author)

A71-44559 *Interpolation of aerodynamic damping of lifting rotors in forward flight from measured response variance.* G. H. Gaonkar (Washington University, St. Louis, Mo.). *Journal of Sound and Vibration*, vol. 18, Oct. 8, 1971, p. 381-389. 12 refs.

Description of methods for the direct computation of the blade response variance matrix up to high rotor advance ratios for a series of inertia numbers. Numerical results refer to a rigid blade flapping model with an elastically restrained flapping hinge at the rotor center. Different combinations of the advance ratio, tip-loss factor, flapping restraint parameter and inertia number are included. The white noise excitation is treated without and with input modulation, the latter case including azimuthwise blade input variation. The mean square response study of the model shows that up to an advance ratio of the order of 0.3 and at conventional values of the inertia number the perturbation approach is satisfactory. The numerical scheme, in addition to solving directly the response variance equations which are similar in structure to the original blade dynamic equations, uses the fact that the variable part of system parameter functions are independent of the inertia number. M.M.

A71-44560 *A note on the acoustic output from round and interfering jets.* D. Middleton (Nottingham University, Nottingham, England). *Journal of Sound and Vibration*, vol. 18, Oct. 8, 1971, p. 417-421. 12 refs.

A model is presented for estimating the acoustic output per unit slice in the adjustment region of a round subsonic jet, and the deduced contributions of the annular, adjustment and fully-developed regions are found to be approximately in the proportions 25:24:1. The method is extended to the case when two similar adjacent parallel round jets interfere, the estimated reduction in total acoustic output being up to 2 dB. An approach to the calculation of the attenuation of suppressor nozzles is also given. (Author)

A71-44572 # *The shape of a supersonic aircraft (Kształt samolotu naddźwiękowego).* Kazimierz Gilewski. *Technika Lotnicza i Astronautyczna*, vol. 26, Sept. 1971, p. 7-10, 29. 5 refs. In Polish.

It is shown that the dissemination of shock waves from a supersonic body can be minimized by employing an aerodynamic shape corresponding to a channel with a converging inlet section and a diverging outlet section. Air compressed at the inlet moves through the channel to fill the outlet region evacuated by the forward motion

of the body. A specific aircraft design is proposed which employs a rectangular channel containing the propulsion system. The bottom wall of the channel is used to provide some of the required lift. T.M.

A71-44574 # Damage of aircraft parts by corrosion (Uszkodzenia części lotniczych przez korozję). Emil Gruszczyński and Edward Sychowicz. *Technika Lotnicza i Astronautyczna*, vol. 26, Sept. 1971, p. 16-20. 10 refs. In Polish.

Examples of actual corrosive damage of aircraft parts, occasioned by friction forces, intercrystalline attack, and hot gases. A worn universal joint is used to demonstrate the oxidation of a surface exposed to friction loading. Corrosive damage along grain boundaries is described in terms of effects resulting in service, and mechanisms responsible for blade damage in gas turbines are explained. T.M.

A71-44577 * # Aerodynamics of lift fan V/STOL aircraft. Jerry V. Kirk, Leo P. Hall, and Brent K. Hodder (NASA, Ames Research Center, Moffett Field, Calif.; U.S. Army, Air Mobility Research and Development Laboratory). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-981*. 9 p. 11 refs. Members, \$1.50; nonmembers, \$2.00.

Lift fans have been shown to be effective for providing direct lift for V/STOL aircraft. Recent efforts at Ames Research Center have been directed toward determining the aerodynamic characteristics of podded lift fans located fore and aft of the wing to allow higher wing loading and reduce constraints on wing design. Most existing design studies in which lift fans were used for direct lift show that a fan pressure ratio of about 1.3 is optimum while an augmentation ratio of 2.5 is maintained. For this reason an investigation was made of the aerodynamic characteristics of a 1.3 pressure ratio lift fan. Results show that podded lift-fan configurations can produce induced lift approaching the magnitude of the better fan-in-wing configurations while reducing significantly the variation of pitching moment with forward speed. The 1.3 pressure ratio lift fan performs well in crossflow and research is being conducted to reduce lift-fan noise. (Author)

A71-44578 # Canada's STOL program - A progress report. C. C. Halton (Ministry of Transport, Ottawa, Canada). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-982*. 14 p. Members, \$1.50; nonmembers, \$2.00.

Evaluation of the opportunity for STOL aircraft to supplement and complement conventional air transportation in Canada. In Canada air traffic accounts for 30% of passenger traffic in the Quebec-Windsor corridor, and 60% of the common carrier traffic. It is emphasized that a STOL system that will fulfill the various roles that can be seen for it must be capable of landings and takeoffs that are short, steep, and quiet. F.R.L.

A71-44579 # The trends of the STOL system. M. Avramito (Société Nationale Industrielle Aérospatiale, Paris, France). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-983*. 6 p. Members, \$1.50; nonmembers, \$2.00.

The STOL system is necessary to increase the productivity of air transport in short-haul traffic. It comprises ground installations with short runways, three-dimensional area navigational aids and well-adapted and quiet aircraft. It will deal with the traffic problems of under-developed countries, areas of difficult access, secondary cities and especially interurban travel. The type and capacity of the future aircraft depend on the date of their commercial entry into service. Aérospatiale is developing a new concept of STOL aircraft which will be ready by the end of the 70's. M.M.

A71-44582 # The design and analysis of a fully-flexible ram-air inflated parawing. Basil S. Papadale, Jr. (Virginia Polytechnic Institute and State University, Blacksburg, Va.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-986*. 10 p. 5 refs. Members, \$1.50; nonmembers, \$2.00.

Based on previous research, tests were conducted to determine an optimum method of inflating a keel or leading-edge section of a parawing in hopes of increasing stability. Several small parawings were constructed and tested at low velocities. Increased stability and reliability were noted. The final parawing design had a ram-air inflated keel and leading-edge. An approximation method for determining the inflated wing shape was derived. It was concluded, that the use of semirigid members in a parawing is beneficial to stability characteristics. (Author)

A71-44585 # Performance prediction and evaluation of propulsion-augmented high lift systems for STOL aircraft. R. L. Gielow (Lockheed-Georgia Co., Marietta, Ga.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-990*. 9 p. 6 refs. Members, \$1.50; nonmembers, \$2.00.

A technique has been developed for predicting the aerodynamic forces of powered-lift systems. Theoretically generated powered section data are distributed spanwise along a lifting line to produce three-dimensional characteristics which exhibit good correlation with experimental results. Employing this technique, baseline-configured aircraft are sized to perform a military STOL mission for field lengths of 1500 to 2500 feet. The lift system concepts include the internally and externally blown jet flaps, BLC, and pure thrust deflection. Direct lift engines are also considered. The sizing process recognizes differences in lift system weight and aerodynamic performance. A comparison of the optimally-sized aircraft produces some interesting conclusions concerning the tradeoff between sophisticated systems and their associated weight penalties. (Author)

A71-44586 # A comparison of outflows from a helicopter, tilt wing and jet lift hovering aircraft. Odd E. Michaelsen (Canadair, Ltd., Montreal, Canada). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-992*. 13 p. Members, \$1.50; nonmembers, \$2.00.

The objectives of the flight test measurements discussed were to assess the suitability of the CL-84 and the Harrier as hover rescue vehicles compared to helicopters. The data shows that, near the downwash impingement area, the vertical variation of the outflow velocity is appreciably different for the three vehicles. While the helicopter velocity-height profile is nearly uniform, the higher disk loading vehicles show higher velocities near the ground and lower velocities at head height. These differences reduce rapidly with radial distance. The measured results were in good agreement with analytically predicted velocity-height profiles. (Author)

A71-44588 # Prediction of flow angularity near a supersonic fuselage forebody with arbitrary cross-section. Jerome A. Forner (USAF, Aeronautical Systems Div., Wright-Patterson AFB, Ohio). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-996*. 11 p. 12 refs. Members, \$1.50; nonmembers, \$2.00.

A simple method was developed to predict flow angularity around the side of a typical uncambered fuselage forebody at supersonic speeds with zero sideslip. The method falls within the class of slender body solutions in small perturbation theory. The body cross-section at any axial location is analytically described by a truncated cosine series, whose coefficients vary with axial position as the body cross-section changes. A disturbance velocity potential is found, which is made up of axial and crossflow components due to an equivalent body of revolution, plus axial and crossflow com-

ponents which adjust for the body asymmetry. The potential is made to satisfy the approximate boundary conditions of flow tangency on the body. A computer solution provides plots which compare the theoretical crossflow around a fuselage forebody for which experimental data was available. Comparisons were made at Mach 2.5 with angles of attack of -7.5, 7.5, and 12.5 degrees and Mach 2.2 at 8.3 degrees. Agreement of flow angularity is generally good. Surface static pressures were also compared at Mach 2.2 and agreement was unsatisfactory. Recommendations for possible improvements to the method are made. (Author)

A71-44591 # Trends in the field of automatic control in the last two decades (Von Kármán Lecture). I. Flügge-Lotz (Stanford University, Stanford, Calif.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-1001.* 32 p. 22 refs. Members, \$1.50; nonmembers, \$2.00.

Discussion of the essential events which occurred in the controls field in the last two decades with the intent of giving the aeronautical engineer some aspects which have attracted great attention. Essential trends of the solution possibilities for optimal control problems are indicated. It is stressed that one aspect of optimal controls has really not gained enough attention. It has been pointed out what enormous role the chosen performance criterion plays. However, it is not always clear which of several performance criteria is the most important one for a specific design. M.M.

A71-44594 # The impact of future transportation technology. Robert L. Maxwell (U.S. Department of Transportation, Office of Systems Engineering, Washington, D.C.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-1010.* 10 p. 6 refs. Members, \$1.50; nonmembers, \$2.00.

Discussion of the necessity for new approaches to evaluation criteria of new system design for future transportation technology. An example of this is cited in the approach taken by the CARD (Civil Aviation Research and Development) Policy Study of the problem of aircraft noise. It is pointed out that mass transit systems such as personal rapid transit, dial-a-ride, dual mode and dynamic traffic control are expected to make a positive contribution. Transportation technology, guided by these new evaluation criteria, is expected to have a dominant effect on our future civilization while minimizing the negative impact to a much more satisfactory degree than has been achieved in the past. M.M.

A71-44596 # STOL, VTOL, and V/STOL - Where do they fit in. *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-1015.* 6 p. Members, \$1.50; nonmembers, \$2.00.

Synopsis of broad comments from AIAA members on various aspects of the merits and developments, present and future, of the STOL, VTOL, and V/STOL family of aircraft. The aspects covered include: the current situation, the background and current status of each of these aircraft varieties, the military role, the worth of pursuing the development of a V/STOL aircraft (i.e., a transport that has the combined capabilities of the STOL and VTOL aircraft and can operate in any mode, including the conventional), the implementation problem, and implementation suggestions. M.V.E.

A71-44597 # Technology and the environment - Friends or foes. Glenn Larson (U.S. Department of Transportation, Transportation Systems Center, Cambridge, Mass.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-1016.* 16 p. Members, \$1.50; nonmembers, \$2.00.

Background material taken from current literature is presented, giving the diverse views that concerned people have on the subject of environmental impact. Some equate environmental degradation directly to the misuse of technology. Others would admit of a less direct relationship but see our survival directly dependent upon the proper use of technology. A shift in values appears to be underway with a corresponding shift in emphasis between first-order effects and side effects. Views on how this shift in emphasis can be achieved in our society are explored, again by quoting from a number of statements in the current literature. (Author)

A71-44600 # Commercial air transportation - What's the prognosis. *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-1022.* 18 p. Members, \$1.50; nonmembers, \$2.00.

Current trends in the industry of commercial air transportation are reviewed, and the requirements of optimal planning for the future are examined. Key issues discussed include airline economic viability, industry regulation, public service, and environmental compatibility. Options and considerations are presented rather than 'pat' solutions, for optimum solutions to many of the problems are clearly not evident. Only joint industry/government dialogues are likely to start an effective search for sound principles and 'good' objectives. M.V.E.

A71-44602 * # The CARD Study - What is its impact. C. A. Syvertson (NASA, Ames Research Center, Moffett Field, Calif.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-1024.* 10 p. Members, \$1.50; nonmembers, \$2.00.

The nature and magnitude of the three major problems confronting civil aviation are discussed in the light of the Civil Aviation Research and Development (CARD) Policy Study, along with CARD Study's key recommendations for each problem. The highest priority belongs to the problem of aircraft noise abatement for it affects the solutions to other problems. The most urgent recommendation asks that time-phased research goals be established calling for noise reductions at the generating source of about 10 to 15 dB per decade. Congestion, the next on the priority list, is a complex problem whose solution involves an organized effort directed at the combination of air traffic control, runway capacity, and airport development. The third major problem of low-density, short-haul service is important to civil aviation's ability to contribute to the goals of the nation, particularly in regard to future regional development. A government-sponsored determination of market sensitivities to changes in service, fare, frequency, and equipment, as well as government-funding of studies for the design and analysis of appropriate vehicles, is recommended. M.V.E.

A71-44604 # Adiabatic laminar boundary-layer/shock-wave interactions on flared axisymmetric bodies. Harry P. Horton (Von Kármán Institute for Fluid Dynamics, Rhode-Saint-Genèse, Belgium). *AIAA Journal*, vol. 9, Nov. 1971, p. 2141-2148. 27 refs.

A method is described for calculating the over-all properties of flare-induced laminar boundary-layer/shock-wave interactions on axisymmetric bodies at zero incidence in supersonic flow, under adiabatic conditions. The method consists of an extension to axisymmetric flow of the two-dimensional integral method of Lees and Reeves, as recently improved by Klineberg. The relationship between the local slope and Mach number of the external inviscid stream is calculated by a suitable inversion of the second-order shock-expansion method of Syvertson and Dennis. Satisfactory agreement is demonstrated between the theory and measurements on hollow cylinder-flare models at Mach numbers of 2.2 and 4.0. (Author)

A71-44613 # Downwash-velocity potential method for lifting surfaces. John Kenneth Haviland (Virginia, University, Charlottesville, Va.). *AIAA Journal*, vol. 9, Nov. 1971, p. 2268, 2269. 6 refs.

It is demonstrated in the steady-state case that the method is capable of achieving 5% accuracy with moderate array sizes, involving 16 points or less, and with wake of less than 5 chord lengths. Further, it is shown that the accuracy improves as these numbers increase. Future work will investigate the applicability of an extended method to the oscillating case with arbitrary planforms.

G.R.

A71-44620 # Transonic flows by coordinate transformation. P. O. Baronti, S. Elzweig (Advanced Technology Laboratories, Inc., Jericho, N.Y.), and R. Vaglio-Laurin (New York University, New York, N.Y.). *AIAA Journal*, vol. 9, Nov. 1971, p. 2280. Contract No. N 00014-71-C-0197.

It is pointed out that a problem regarding the periodical recalculation of far field boundary conditions in the method used by Murman and Cole (1971) can be avoided by a new approach. This approach involves the transformation of the infinite domain around the airfoil into a finite domain by coordinate transformation. A typical numerical solution for a nonlifting circular arc airfoil at a freestream Mach number of 0.8 is presented.

G.R.

A71-44621 # Aerodynamic characteristics of slender wedge-wings in hypersonic strong interaction flows. C. M. Rodkiewicz and T. K. Chattopadhyay. *AIAA Journal*, vol. 9, Nov. 1971, p. 2280-2282.

The investigation discussed is based on the results obtained by Chattopadhyay and Rodkiewicz (1971). A formula for the shear stress on the wall is obtained, and expressions for the different forces acting on the wedge are presented. Effects of parameter changes on the lift/drag ratio of a 2 deg wedge and of a flat plate are determined.

G.R.

A71-44624 * # Approximate analytic solution for the position and strength of shock waves about cones in supersonic flow. Sanford S. Davis (NASA, Ames Research Center, Aerodynamics Branch, Moffett Field, Calif.). *AIAA Journal*, vol. 9, Nov. 1971, p. 2287-2289.

The equations derived are valid for higher Mach numbers and/or larger cone semiangles than the equations obtained previously by Lighthill (1948) and Whitham (1952). Both the Whitham procedure for calculating a uniformly valid first-order solution, and the simplification afforded by the conical symmetry of the flow are utilized in the derivation. Only the details of the second order characteristics are used in order to obtain a solution. The expressions found for the pressure rise across the shock wave and for the angle that the conical shock wave makes with the linearized Mach cone differ from the results of Lighthill and Whitham by the appearance of an additional factor in the denominators.

G.R.

A71-44692 # Use of a correlation system of equations for accuracy analysis in flight dynamics problems (Primenenie korrelatsionnoi sistemy uravnenii dlia analiza tochnosti v zadachakh dinamiki poleta). I. O. Mel'ts, T. A. Pykhova, and G. V. Uskov. In: Nonlinear and optimal systems. Moscow, Izdatel'stvo Nauka, 1971, p. 246-263; Discussion, p. 263. 10 refs. In Russian.

Development of methods of calculating the mathematical expectations of typical functions encountered in various flight dynamics problems. An effective method of calculating the right members of the correlation system (a system of equations for mathematical expectations and correlation moments of phase coordinates) for various problems of flight vehicle dynamics is developed, and the required tables are compiled. The development of methods which make it possible to take into account nonlinear

couplings and the discrete-continuous nature of the control in obtaining the correlation system is also considered.

A.B.K.

A71-44761 Some new results of flight dynamics. II (Quelques résultats nouveaux de la mécanique du vol. II). Werner Schulz (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Porz-Wahn, West Germany) and Peter Hamel (Messerschmitt-Bölkow-Blohm GmbH, Hamburg, West Germany). (*Association Française des Ingénieurs et Techniciens de l'Aéronautique et de l'Espace and Deutsche Gesellschaft für Luft- und Raumfahrt, Journée Otto Lilienthal, 11th, Paris, France, Dec. 16, 1970.*) *L'Aéronautique et l'Astronautique*, no. 30, 1971, p. 13-18. 34 refs. In French.

After appreciating the methodical change of theoretical considerations and experimental investigations, with which Lilienthal tried to approach the solution of the problem of the free flight of man, three topics are discussed, to the treatment of which flight dynamics can be useful: the problem of flight noise, the decrease of the influence of gusts on aircraft, and the problem of dynamics stability of parachute-load systems. A reduction of noise annoyance on the ground, particularly after the take-off of V/STOL aircraft, may be obtained by the determination of noise optimal flight profiles. For gust decrease, the method of 'tuned lift control,' the lift due to automatic control attacking in the neutral point of the aircraft, proves to be the most advantageous. The analytical treatment of the greatly nonlinear problem of dynamic stability of parachute-load systems succeeds well by employing the theory of describing function, as comparisons with results obtained by numerical integration show.

(Author)

A71-44763 Measurements of velocities in a subsonic wind tunnel (0.10 less than V less than 20 m/sec) (Mesures des vitesses en soufflerie subsonique 0.10 less than V less than 20 m/s). J. Moinard and C. Froger (Centre d'Etudes et Recherches des Charbonnages de France, Verneuil-en-Halatte, Oise, France). *L'Aéronautique et l'Astronautique*, no. 30, 1971, p. 31-37. In French.

Review of low speed wind tunnel studies carried out at the Centre d'Etudes et Recherches des Charbonnages de France (CERCHAR), which show that at very low speeds the sound waves due mainly to the noise of the fan which ensures air circulation in the wind tunnel are propagated in all directions. In this range of velocities the acoustic pressure variations in the testing section have about the same magnitude as the dynamic pressures to be measured. To overcome this difficulty the aerodynamic study was complemented by an acoustic one on a model, and corrections were applied to the full scale tunnel.

F.R.L.

A71-44765 Maintenance and reliability of civil transport aircraft (Maintenance et fiabilité des avions de transport civils). J. Emery (Société Nationale Industrielle Aérospatiale, Toulouse, France). *L'Aéronautique et l'Astronautique*, no. 30, 1971, p. 56-64. In French.

General discussion of aircraft and equipment maintenance and reliability problems. Modern methods of satisfactory solutions with best time, cost, and weight compromises are described. Aircraft availability involves systems reliability, redundancy, supervision and preventive maintenance, and flight under specific limitations. The cost of maintenance involves working hours and spare parts, tools, and standardization.

F.R.L.

A71-44766 The multi-purpose military aircraft Panavia 200 (MRCA Program) (L'avion militaire polyvalent Panavia 200 /Programme M.R.C.A./). Georges Bruner (Centre de Documentation de l'Armement, Paris, France). *L'Aéronautique et l'Astronautique*, no. 30, 1971, p. 65-70. In French.

Designed and built jointly by Western Germany, United Kingdom and Italy, the military aircraft Panavia 200 will be a

multipurpose aircraft capable of performing three main tasks: close air support, air superiority and interdiction/strike. The sometimes conflicting requirements resulting from the performance of these three missions could be conciliated owing to a variable geometry conception. The main characteristics of the plane are recalled and some details are given on the engines, the armament and the electronics of this aircraft, the first flight of which is planned for end 1973. (Author)

A71-44975 **Folding sidewall aircraft tires.** Paul M. Wagner (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio). *Shell Aviation News*, no. 399, 1971, p. 18-21.

Development of the folding sidewall tire and its flight demonstration. This tire can be folded in flight for compact storage and expanded again for normal usage upon gear extension. On a retrofit basis it would provide present aircraft with the capability to employ larger tires, thereby improving ground flotation. The tire offers improved performance at high deflection, and run-flat emergency operational capability. An inflation/deflation system, however, reduces the reliability of an aircraft. Results of tests on ten tires exhibited excellent tread wear qualities. F.R.L.

A71-44982 # **Planning a program for assessing the possibility that SST aircraft might modify climate.** Robert H. Cannon, Jr. (U.S. Department of Transportation, Washington, D.C.). (*American Meteorological Society, Annual Meeting, 51st, San Francisco, Calif., Jan. 12, 1971.*) *American Meteorological Society, Bulletin*, vol. 52, Sept. 1971, p. 836-842.

Description of the characteristics of projected SST fleet operations, followed by review of some pertinent aspects of the nature of the atmosphere, the ways that have been suggested that it might be affected by SST operations, and what is still to be learned. The preliminary planning of a program to gain the necessary additional knowledge, and the way it is proposed to carry out the program are discussed. The possible effects of carbon dioxide, water vapor, contrails, particulates, nitrogen oxides, and carbon monoxide are considered. The assessment program will involve study of engine emissions, atmospheric modeling, and photochemistry. F.R.L.

A71-44983 # **The effect of weather on the operations and economics of air transportation today.** W. Boynton Beckwith (United Air Lines, Inc., Chicago, Ill.). (*American Meteorological Society, Annual Meeting, 51st, San Francisco, Calif., Jan. 12, 1971.*) *American Meteorological Society, Bulletin*, vol. 52, Sept. 1971, p. 863-868.

Review of technical improvements in aircraft and navigational and aircraft aids which have eliminated most of the problems of adverse weather which the air transportation industry faced 30 years ago. In spite of this progress, nature is still capable of setting up hostile environments for aircraft operations. Such elements as thunderstorms, fog, turbulence, snowstorms, heavy rain, and high winds can close airports, divert flights, and cause disservice to passengers. Using typical cases, the full effects of weather interruptions are discussed and related to the present-day U.S. fleet of 2400 transport aircraft and to their control. Recent economic studies provide a basis for assessing the cost of several weather factors which interfere with scheduled air transportation. F.R.L.

A71-44986 **Airborne laser profiling of the Arctic pack ice.** Robert D. Ketchum, Jr. (U.S. Naval Oceanographic Office, Ocean Science Dept., Washington, D.C.). *Remote Sensing of Environment*, vol. 2, Oct. 1971, p. 41-52.

Description of the results of an analysis of laser terrain profile data obtained with coincident photography from an altitude of 1000 ft over the sea ice fields of the Beaufort Sea in April 1968. Analysis of the data reveals that sea ice surface roughness and the nature of the roughness as well as relative surface reflectivities, which are both manifested in the laser terrain profile, can be used to interpret the

categorical stages of ice development. The laser terrain profiler seemingly detected, with acceptable accuracy, all ice features traversed; however, ice pressure ridges, ice hummocks, or ice blocks could not be distinguished from each other on the record because the measurement is only two-dimensional. These features were always detectable even when occurring in rapid succession. Cracks are very discernible on the laser terrain profile record. M.M.

A71-45004 # **Retardation of condensate particle crystallization in a jet engine nozzle (O zaderzhke kristallizatsii chastits kondensata v soople reaktivnogo dvigatelia).** A. P. Tishin, V. A. Khudiakov, and V. N. Kostin. *Aviatsionnaia Tekhnika*, vol. 14, no. 2, 1971, p. 24-31. 5 refs. In Russian.

The influence of retardation of crystallization on the energy characteristics of a jet engine is analyzed. Approximate estimates of the influence of crystallization on the flow rate are obtained. The expansion process in the engine is shown to occur at a prescribed area ratio of the nozzle exit section, and it is shown that in the absence of crystallization in the nozzle, the pressure at the nozzle exit section can differ appreciably from the pressure calculated for equilibrium expansion. A more accurate approach, therefore, is to compare the processes with and without crystallization (rather than for a constant outlet pressure). The relative effectiveness of the expansion process in the absence of crystallization is assessed on the basis of special thermodynamic calculations for two compositions with 7 and 15% aluminum and for a BeH₂ + H₂O₂ fuel. Nonequilibrium flows of two-phase combustion products are calculated for studying the influence of the heat transfer rate between the particles and the gas during the crystallization process. V.P.

A71-45011 # **Profiling the temperature field along the radius in front of a turbine stage (O profilirovanii polia temperatur po radiusu pered turbinnoi stupen'iu).** A. M. Toptunov. *Aviatsionnaia Tekhnika*, vol. 14, no. 2, 1971, p. 76-83. 8 refs. In Russian.

A method is proposed for determining the optimal temperature field along the radius in front of a gas-turbine stage. The possibility of obtaining a radially nonuniform temperature field with a bypass turbine of special design is studied, and the applicability of this approach to regeneratively cooled turbine engines is demonstrated. V.P.

A71-45012 # **Applicability of statistical methods to the analysis of the characteristics of sheet joints in aircraft structures (K primeneniui statisticheskikh metodov dlia analiza kharakteristik listovykh soedinenii aviakonstruktsii).** V. P. Burmistrov. *Aviatsionnaia Tekhnika*, vol. 14, no. 2, 1971, p. 84-90. 9 refs. In Russian.

The possibility of using statistical methods for analyzing the observed spread of the principal characteristics of sheet joints is discussed. Problems involved in the determination of the distribution laws of breaking loads and numerical characteristics are examined. The influence of the spread of the parameters of a joint is evaluated, and the minimum strength of a spot-welded joint is determined. The interrelation between random parameters is studied on the basis of statistics characterizing the relationship between random quantities. All results are obtained for spot-welded and adhesive joints of high-strength aluminum alloy sheet. V.P.

A71-45016 # **Determination of transient functions and impulse transient functions for an aircraft in its unsteady motion by the method of Laplace-Carson integral transforms (K voprosu o nakhozhdenii perekhodnykh i impul'snykh perekhodnykh funktsii samoleta pri ego neustanovivshemsia dvizhenii metodom integral'nogo preobrazovaniia Laplasa-Karsona).** V. A. Sannikov. *Aviatsionnaia Tekhnika*, vol. 14, no. 2, 1971, p. 102-108. In Russian.

An approximate method is proposed for analyzing the intrinsic dynamic characteristics of an aircraft under unsteady flight conditions. The method consists of integrating approximately the linear

differential equation of perturbed motion of the aircraft over a finite interval of time. A solution over the entire interval under consideration is obtained by consecutively passing from one approximation interval to the next. V.P.

A71-45018 # Influence of fuselage strains on the work of a small-aspect-ratio wing (*O vliianii deformatsii fiuzeliazha na rabotu kryla malogo nadlineniia*). E. A. Ivanova and V. A. Komarov. *Aviatsionnaia Tekhnika*, vol. 14, no. 2, 1971, p. 112-114. In Russian.

Some aspects of the calculation of a small-aspect-ratio wing with allowance for the fuselage strains are examined. The strong influence of fuselage strains, particularly in the case of antisymmetric loading, on the work of the wing is demonstrated on the basis of extensive calculations performed for a delta wing. V.P.

A71-45022 # Substantiation of the constraints placed on the overall excess air ratio (*K obosnovaniu ogranichenii, nakladyvaemykh na summarnyi koeffitsient izbytkha vozdukha*). A. M. Akhmedzianov, B. N. Chizhov, and V. P. Alatorsev. *Aviatsionnaia Tekhnika*, vol. 14, no. 2, 1971, p. 132-136. In Russian.

The permissible deviations of the overall excess air ratio in test-bed engine studies are analyzed with a view toward obtaining excess air ratio values that correspond to technical specifications for various modes of engine operation. A diagram for calculating the constraints placed on the excess-air ratio is proposed. V.P.

A71-45160 # Integration of the kinematic equations of an astatic gyroscope (*Ob integrirovanii kinematicheskikh uravnenii astaticheskogo giroskopa*). L. A. Motyl'kov (Leningradskii Korablistroitel'nyi Institut, Leningrad, USSR). *Priboroostroenie*, vol. 14, no. 7, 1971, p. 94-98. 6 refs. In Russian.

Analysis of an astatic gyroscope mounted on an aircraft that moves in an arbitrary fashion near the earth's surface. The rotor axis is close to vertical at the initial moment. Integrals of the kinematic equations are obtained without imposing any restrictions on the rotation of the gimbals or on aircraft motion. Many special cases of gyroscope motion follow from these integrals. T.M.

A71-45180 # Expression for the ideal weight of shell fuselages (*Su una espressione del peso ideale delle fusoliere a guscio*). Giuseppe Gabrielli. *Torino, Accademia delle Scienze, Classe di Scienze Fisiche, Matematiche e Naturali, Atti*, vol. 105, Mar.-Apr. 1971, p. 227-231. In Italian.

Derivation of an expression for the ideal weight of fuselages with the shape of a body of revolution with a straight axis to which can be likened the shapes adopted in modern aircraft, particularly passenger transports. From this expression, which takes into account stressed loads and their distribution as well as cabin pressurization, is derived a general formula to which can be conveniently reduced, by the adoption of suitable coefficients, empirical formulas which give the real weight of fuselages on the basis of data measured statistically. M.M.

A71-45280 # The detection of hot corrosion-sulfidation in Navy aircraft turbine engines. James E. Newhart (U.S. Navy, Naval Air Propulsion Test Center, Trenton, N.J.). *American Society for Nondestructive Testing, National Fall Conference, 31st, Detroit, Mich., Oct. 18-21, 1971, Paper*. 9 p. 5 refs.

Study of the catastrophic deterioration of vanes and blades in the hot section of an aircraft powerplant, caused by operation in an environment containing varying amounts of sea salts. The condition is termed hot corrosion or, more commonly, sulfidation. Current procedures for the repair of nozzle guide vanes exhibiting hot corrosion attack call for the removal of the corrosion by grinding, blending of the surface, and then recoating the ground area. Several nondestructive methods for rapid detection are discussed. F.R.L.

A71-45295 * # The reduction of VTOL operational noise through flight trajectory management. F. H. Schmitz (U.S. Army, Air Mobility Research and Development Laboratory, Moffett Field, Calif.) and W. Z. Stepniewski (Boeing Co., Philadelphia, Pa.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-991*. 16 p. 14 refs. Members, \$1.50; nonmembers, \$2.00. NASA-Army-supported research.

The concept of altering the flight path of VTOL aircraft to reduce ground noise levels in communities adjacent to the landing site is explored. Two classes of VTOLs are considered: prop-rotor and lift-fan aircraft. Theoretical performance and acoustic models are developed and then mathematically flown to yield representative takeoff and landing flight profiles. Proposed noise abatement profiles are compared with minimum time and fuel trajectories to assess the possible annoyance reduction through flight path control. Significant annoyance reductions are feasible if a nearly vertical takeoff flight path is flown near the landing site. However, the time expended and fuel consumed increase. A procedure is also suggested which assesses the overall community annoyance to VTOL operations. Several noise abatement trajectories of both types of aircraft are evaluated to determine which flight paths are most acceptable to the VTOL port's neighboring community. (Author)

A71-45296 # The heavy lift helicopter program - An advanced technology solution to transportation problems. Ben Tencer and J. P. Cosgrove (Boeing Co., Philadelphia, Pa.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-994*. 9 p. 6 refs. Members, \$1.50; nonmembers, \$2.00.

Description of the advanced technology developments in rotor and drive, flight controls, and cargo handling systems areas of the Heavy Lift Helicopter System (HLHS). The system was conceived to expedite the loading and offloading of containerized cargo from ships. The shift to containerization, coupled with the projected availability of a vertical lift system, has provided the opportunity for significant improvement in the logistics support to both military and commercial customers. Commercial applications of the HLHS will also be feasible and profitable in areas such as power line construction, forestry, and bridge building. F.R.L.

A71-45297 # Factors in STOL flight control configuration. William P. A. Harris (Boeing Co., Seattle, Wash.). *American Institute of Aeronautics and Astronautics, Annual Meeting and Technical Display, 8th, Washington, D.C., Oct. 25-28, 1971, Paper 71-993*. 17 p. 8 refs. Members, \$1.50; nonmembers, \$2.00.

The STOL flight control problem is discussed in relationship to its unique operational requirements. A survey is made of the historic growth of control system techniques, and their implementation, in order to put into perspective the STOL position. The danger of regarding STOL control as a simple extension of CTOL technique is discussed, and in contrast, the concept of task orientation and configuration is developed as pertinent to the STOL problem. Reference is made to current control system technology and analytical tools, and thoughts are presented on future trends. The need for a composite approach to control implementation is emphasized. (Author)

A71-45325 # Additives to fuels for jet-propelled aircraft (Survey) (*Prisadki k toplivam dlia reaktivnoi aviatsii (Obzor)*). Ia. B. Chertkov. *Khimiia i Tekhnologiya Topliv i Masel*, vol. 16, no. 8, 1971, p. 59-61. 21 refs. In Russian.

A review is presented of typical additives that are being used or recommended for use in aircraft fuels. The following types of additives are considered: antioxidant; metal deactivating; anticorrosive; antiwear; preventing ice crystal formation; preventing accumulation of static electricity; coagulating; thickening; stabilizing; biocide; and antismoke. O.H.

A71-45380 # Possible modes of operation of a centripetal stage (O vozmozhnykh rezhimakh radial'no-osevoi stupeni). M. V. Adler and G. S. Solov'eva. *Energomashinostroenie*, vol. 17, Aug. 1971, p. 20-22. In Russian.

The universal characteristics of a centripetal stage are examined. The influence of the rate of airflow and the pressure ratio on the power is demonstrated, and the velocity triangles of a centripetal stage are examined for two types of compressor and two types of turbine. V.P.

A71-45381 # Analytical design of a transonic airfoil cascade (Analiticheskoe postroenie transzvukovoi reshetki profilei). E. E. Drozd and E. G. Lazarenko. *Energomashinostroenie*, vol. 17, Aug. 1971, p. 38, 39. In Russian.

A simple and time-saving method is proposed for designing a transonic airfoil cascade, and evaluating quantitatively its efficiency from the velocity distribution, without recourse to experimental tests. It is shown how an airfoil lattice with an infinite chord can be reduced to one with a finite chord. V.P.

A71-45383 The lubricating quality of aviation fuels. R. T. Aird (Lucas Group Research Centre, Birmingham, England) and S. L. Forgham (Lucas Gas Turbine Equipment, Ltd., Birmingham, England). (*Institute of Mechanical Engineers and Royal Institute of Chemistry, Joint Conference on Chemical Effects at Bearing Surfaces, Swansea, Wales, Jan. 6-8, 1971.*) *Wear*, vol. 18, Nov. 1971, p. 361-380. 17 refs. Research supported by the Ministry of Technology.

Aviation fuels from different sources have shown marked differences in their ability to lubricate load bearing surfaces in aircraft fuel pumps. Over the years there have been changes in the methods used in the refining of aviation fuels. An investigation was conducted to determine what differences existed in the lubricating ability of these fuels. Aviation fuels are produced to conform with comprehensive national specifications but there is no section which relates specifically to lubricating properties. Permitted variations in fuel specification tests, for example, distillation characteristics and viscosity, have failed to relate to service performance. A test has been developed based on the assumption that the resistance to breakdown of the boundary lubricating film depends upon the tenacity of certain fuel constituents adsorbed on the bearing surfaces. G.R.

STAR ENTRIES

N71-36398* Translation Consultants, Ltd., Arlington, Va.
RELATION BETWEEN STRATOSPHERE TURBULENCE CAUSING AIRCRAFT BUFFETING AND THE VERTICAL DISTRIBUTION OF METEOROLOGICAL PARAMETERS
 [SVYAZ TURBULENTNOSTI V STRATOSFERE, VYZYVAYUSHCHEY BOLTANKU SAMOLETOV, S VERTIKALNYM PASPREDELENIYEM METEOROLOGICHESKIKH PARAMETROV]

G. S. Buldovskiy Washington NASA Oct. 1971 18 p refs
 Transl. into ENGLISH from Gidrometeoizdat (USSR), no. 70
 1970 p 79-92

(Contract NASw-2038)

(NASA-TT-F-13981) Avail: NTIS CSCL 01A

The relation between aircraft buffeting of various intensities and the vertical distribution of meteorological parameters calculated from radiosonde data is determined. In this case the main problem reduces to finding the critical values of these parameters, which optimally characterize the successfulness of a diagnosis of the presence or absence of aircraft buffeting. It is found that the successfulness of such diagnosis is optimally characterized by the vertical wind vector shear, the Richardson number, and the change in thermal stability from the underlying to the overlying layer (a change which characterizes the boundaries of the baroclinic layers). On the basis of a graph of the dependence of aircraft buffeting on a combination of two of these factors, a buffeting parameter is obtained in terms of which a condition governing the presence or absence of buffeting is expressed. Author

N71-36399* Aeronautical Research Labs., Melbourne (Australia).

ON THE FICTION OF LEADING EDGE SUCTION

A. E. Billington Jan. 1971 7 p refs

(ARL/SM-Note-360) Avail: NTIS

It is shown that the so-called leading edge suction of thin aerofoil theory is a misnomer. It results from misinterpreting the meaning of the leading edge singularity. Author

N71-36400* Advisory Group for Aerospace Research and Development, Paris (France). Ad Hoc Committee.

ENGINE-AIRPLANE INTERFERENCE AND WALL CORRECTIONS IN TRANSONIC WIND TUNNEL TESTS

Aug. 1971 143 p refs

(AGARD-AR-36-71) Avail: NTIS

CONTENTS:

1. CONCLUSIONS AND RECOMMENDATIONS ON ENGINE AIRPLANE INTERFERENCE AND WALL CORRECTIONS IN TRANSONIC WIND TUNNEL TESTS A. Ferri 5 p

2. ENGINE-AIRPLANE INTERFERENCE IN TRANSONIC TESTS F. Jaarsma 117 p refs

3. WALL CORRECTIONS FOR AIRPLANES WITH LIFT IN TRANSONIC WIND TUNNEL TESTS R. Monti 15 p refs

N71-36401* Advisory Group for Aerospace Research and Development, Paris (France).

CONCLUSIONS AND RECOMMENDATIONS ON ENGINE

AIRPLANE INTERFERENCE AND WALL CORRECTIONS IN TRANSONIC WIND TUNNEL TESTS

Antonio Ferri (New York Univ., N. Y.) In its Eng.-Airplane Interference and Wall Corrections in Transonic Wind Tunnel Tests Aug. 1971 5 p
 Avail: NTIS

The conclusions and recommendations are presented concerning the correct representation in wind tunnel tests of the interaction between engine flow and airplane characteristics, and wall interference at high lift. A review of experimental methods in use for determining engine-airplane interference in transonic tests includes the following topics: (1) inlet airplane interference, (2) engine thrust with airplane drag and nozzle characteristics, (3) exhaust flow and airplane interference, and (4) determination of interference of the engine flow on the aerodynamic characteristics of the complete configuration. It is concluded that all of the approaches have important unknowns and shortcomings; action is required by research groups to develop new techniques, and improve existing ones. F.O.S.

N71-36402* Advisory Group for Aerospace Research and Development, Paris (France).

ENGINE-AIRPLANE INTERFERENCE IN TRANSONIC TESTS

F. Jaarsma (Natl. Aero- and Astronaut. Res. Inst.) In its Eng.-Airplane Interference and Wall Corrections in Transonic Wind Tunnel Tests Aug. 1971 117 p refs

Avail: NTIS

A compilation is presented of the response to a distributed questionnaire on engine-airframe interference in transonic tests among aeronautical laboratories operating transonic wind tunnels, aircraft manufacturers, engine companies, and airplane users in the AGARD countries. The experimental techniques, correction procedures, advantages and limitations of inlet, nozzle/afterbody, complete model testing, and engine thrust determination are discussed in a technical order. Author

N71-36403* Advisory Group for Aerospace Research and Development, Paris (France).

WALL CORRECTIONS FOR AIRPLANES WITH LIFT IN TRANSONIC WIND TUNNEL TESTS

R. Monti (Univ. Degli Studi, Naples, Italy) In its Eng.-Airplane Interference and Wall Corrections in Transonic Wind Tunnel Tests Aug. 1971 15 p refs

Avail: NTIS

The technical information supplied by the Ad Hoc Committee is summarized. After some preliminary remarks on wall interference corrections in transonic tests, the different answers to the AGARD questionnaire are presented together with the main points made by the committee members as representatives of the different countries. A number of general agreements among the committee members are stated which indicate the state-of-the-art of transonic wind tunnel corrections. The discussions and the conclusions of the committee are presented on the problems which appear to be most important for future research. Problems are briefly reviewed and research areas are indicated for which the committee agreed an international program will be most profitable. A list of references is provided which includes the works referenced by all the different groups participating in the committee. Author

N71-36404* United Aircraft Corp., East Hartford, Conn.
ANALYTICAL INVESTIGATION OF THE EFFECTS OF BLADE FLEXIBILITY, UNSTEADY AERODYNAMICS, AND VARIABLE INFLOW ON HELICOPTER ROTOR STALL CHARACTERISTICS

E. D. Bellinger Washington NASA Sep. 1971 114 p refs
 (Contract NAS1-8350)

(NASA-CR-1769) Avail: NTIS CSCL 01C

An analytical study was conducted to investigate systematically the relative importance of blade flexibility,

unsteady aerodynamics, and variable inflow (with and without wake distortions) in determining predicted helicopter rotor stall characteristics. The theoretical results of this study were compared with a corresponding full scale wind tunnel results for the H-34 rotor system. The classical theory (rigid blades, steady aerodynamics, and constant inflow) produced good correlation at nominally unstalled operating conditions. However, rotor lifts significantly lower than the test values were predicted at high blade angles of attack. The use of unsteady airfoil data provided the most significant improvement in correlation by allowing higher section lift coefficients to be reached due to the stall delay phenomenon associated with unsteady operating conditions. The primary effect of blade flexibility was due to blade torsional deflections, which, as with blade pitch changes, had a direct effect on performance. Variable inflow, although producing significant changes in the angle of attack distribution over the disc, did not appreciably affect rotor performance.

Author

N71-36405# National Physical Lab., Teddington (England). Div. of Numerical Analysis and Computing
ANALYTICAL AND NUMERICAL STUDIES OF DOWNWASH OVER RECTANGULAR PLANFORMS
 H. C. Garner (RAE) and G. F. Miller May 1971 28 p refs (NPL-MA-99) Avail: NTIS

The distribution of downwash at the surface of rectangular planforms with prescribed subsonic aerodynamic loading is considered. Three separate aspects of the problem are treated analytically, the results of each being tested against those derived from an accurate numerical procedure. Asymptotic expressions for large and small aspect ratio are formulated and shown to apply over a wide range of aspect ratio. Downwash routines from certain existing lifting-surface methods are studied, and their patterns of convergence are illustrated and compared. A logarithmic singularity near the leading tip corner is identified, but it is observed that this can exist without serious detriment to the lifting-surface methods.

Author (ESRO)

N71-36406# Rochester Applied Science Associates, Inc., N.Y.
AN EXPERIMENTAL STUDY OF TIP VORTEX MODIFICATION BY MASS FLOW INJECTION Final Technical Report, 1 Feb. 1969 - 31 Jan. 1971

Stephen A. Rinehart, John C. Balcerak, and Richard P. White, Jr. Jan. 1971 85 p refs (Contract N00014-69-C-1069) (AD-726736; RASA-71-01) Avail: NTIS CSCL 20/4

An experimental program was conducted to investigate the modifications of a tip vortex which could be obtained by injecting the core of a tip vortex with a stream of air. Wind tunnel tests of an airfoil model were conducted. The results obtained from flow-visualization studies, balance data, and vortex-meter measurements show how the strength of the tip vortex can be reduced significantly by the injection of a linear mass flow of air into the core of the tip vortex. The reduction in drag obtained with injection is important since it allows the recovery of power required to inject the tip vortex core with mass flow.

Author (GRA)

N71-36407# Technion - Israel Inst. of Tech., Haifa. Dept. of Aeronautical Engineering.

CALCULATION OF LIFT INTERFERENCE CORRECTIONS DUE TO WIND TUNNEL TEST SECTION BOUNDARIES BY THE VORTEX LATTICE METHOD Annual Report, 1 Apr. 1970 - 31 Mar. 1971

E. Wasserstrom, Y. Borovik, D. Hazanovsky, and J. Rom Apr. 1971 44 p refs (TAE-124; Rept-180-088) Avail: NTIS

The vortex lattice numerical method is used to calculate lift interference corrections due to wind tunnel test-section boundaries. Various test-section geometrical shapes are considered, such as square, rectangular and circular. The

calculations were carried out for closed, partially open and completely open (free-jet) test sections respectively. The model is represented mathematically by a simple horseshoe vortex. Spanwise as well as longitudinal variations of the normal induced velocity at the model are determined. The resulting interference parameters agree with available exact theoretical calculations.

Author

N71-36408# ARO, Inc., Arnold Air Force Station, Tenn.
TESTS CONDUCTED IN THE AEDC 16-ft TRANSONIC TUNNEL ON A 0.0226-SCALE MODEL OF THE C-5A AIRCRAFT FOR DATA CORRELATION BETWEEN THREE TRANSONIC WIND TUNNELS Final Report, 30 Dec. 1969 - 20 Jan. 1970

J. A. Black AEDC Jul. 1971 64 p refs (Contract F40600-72-C-0003) (AD-727006; AEDC-TR-71-105; ARO-PWT-TR-71-68) Avail: NTIS CSCL 14/2

Tests were conducted on two configurations of a 0.0226-scale model of the C-5A aircraft for the purpose of data correlation with other major transonic test facilities. The results reported herein were obtained at Mach numbers from 0.600 to 0.825 and Reynolds numbers from 2.1 million to 4.2 million and represent the AEDC contribution to the correlation study.

Author (GRA)

N71-36409# Texas Univ., Austin. Applied Mechanics Research Lab.

SUPERSONIC AIRFOILS OF MINIMUM TOTAL DRAG

Don James Hull Dec. 1970 35 p refs (Grant AF-AFOSR-1744-69) (AD-726767; TR-1020; AFOSR-71-1956-TR) Avail: NTIS CSCL 20/4

Minimum drag airfoil shapes in supersonic flow for a given chord length are considered. The shapes are assumed to be two-dimensional and symmetric. In order to relate the drag of the airfoil to its geometry, it is assumed that the airfoil is slender. The boundary layer is specified to be entirely turbulent. Two cases are solved: (a) minimum drag shape for a given chord and (b) minimum drag shape for a given chord and heat transfer rate. For each case, the minimal shape is obtained by employing the calculus of variations in one independent and dependent variable to the drag expression.

Author (GRA)

N71-36410# National Research Council of Canada, Ottawa (Ontario).

COMPARISON OF THIN PLATE AND THICK AEROFOIL BLADES IN A CENTRIFUGAL FAN

H. S. Fowler Aug. 1971 33 p refs (ME-238; NRC-12166) Avail: NTIS

The patterns and stability of the airflow in the rotor of a centrifugal fan have been studied, with thin plate blading and with thick aerofoil blades. Specifications of the blading are presented, and a detailed comparison is made of the visualized flow patterns in the channels, exit velocity profiles, flow characteristic curves, and operating range. It is concluded that the aerofoil blading has a wider operating range, and some explanations of this are derived from study of the flow patterns.

Author

N71-36411*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

A METHOD FOR CALCULATING THE AERODYNAMIC LOADING ON WING-BODY COMBINATIONS AT SMALL ANGLES OF ATTACK IN SUPERSONIC FLOW

Charlie M. Jackson, Jr. and Wallace C. Sawyer Oct. 1971 32 p refs (NASA-TN-D-6441; L-7822) Avail: NTIS CSCL 20D

This report describes a theoretical method for estimating the aerodynamic loading on a wing-body configuration. In order to provide a basis for evaluation of the method, experimental

measurements of surface pressures, forces, and moments were made on a series of basic wing-body configurations over a Mach number range from 2.5 to 4.5. Comparison of the theoretical estimates with these experimental data generally indicated good agreement for the entire range of configurations and test conditions. Author

N71-36412* National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.
PERFORMANCE OF CLOSELY SPACED TWIN-JET AFTERBODIES WITH DIFFERENT INBOARD-OUTBOARD FAIRING AND NOZZLE SHAPES
 Edwin E. Lee, Jr. and Jack F. Runckel Washington Sep. 1971 151 p refs
 (NASA-TM-X-2329; L-7759) Avail: NTIS CSCL 01A

Thrust-minus-drag forces and pressure distributions were obtained on the afterbody and nozzle sections of various fuselage closures at Mach numbers from 0.60 to 2.01. Four interfairing contours were investigated: a circular-arc; an elliptical; and a blunt configuration, all ending at the nozzle attachment station; and one blunt-based type extending between the nozzles. Also, limited data were obtained with tail booms of circular or oval cross section extending from the sides of the afterbody past the nozzles. Propulsive nozzle shapes represented variable geometry iris and convergent-divergent types with circular arc and conical boattailing, respectively. Each was configured for minimum and maximum throat area (dry and augmented power) and operated with compressed air at pressure ratios up to 20, depending on Mach number. Author

N71-36413* National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.
AN IMPROVED METHOD FOR CALCULATING SUPERSONIC PRESSURE FIELDS ABOUT BODIES OF REVOLUTION
 Robert J. Mack Washington Oct. 1971 34 p refs
 (NASA-TN-D-6508; L-7873) Avail: NTIS CSCL 01A

An improved near-field method for determining supersonic-flow-field properties about a body of revolution is presented and discussed. Comparisons between the improved method, Whitham's theory, and wind-tunnel results are shown for four bodies of revolution - three closed-nose bodies and one ducted body. At Mach numbers of 2.96, 3.83, and 4.63 and ratios of radial distance to body length of 1.0, 2.0 and 5.0, results show that the improved method does reasonably well in predicting flow-field pressure signatures and represents a definite improvement over existing near-field theory. It is also shown that the simple area balancing shock prediction technique works reasonably well for bodies with pointed nose sections provided the improved method is used to locate the body flow-field disturbances more exactly. Author

N71-36414* National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.
EXPERIMENTAL INVESTIGATION OF A LOW REYNOLDS NUMBER PARTIAL ADMISSION SINGLE STAGE SUPERSONIC TURBINE
 Louis J. Goldman Washington Oct. 1971 22 p refs
 (NASA-TM-X-2382; E-6380) Avail: NTIS CSCL 01A

Turbine performance characteristics were obtained for a single stage partial-admission supersonic turbine operating at low Reynolds numbers. The turbine was tested over a range of pressure ratios from 20 to 150 and equivalent speeds from 20 to 100 percent of design. Author

N71-36415* National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.
LONGITUDINAL AERODYNAMIC CHARACTERISTICS AT MACH 1.50 TO 4.63 OF A MISSILE MODEL EMPLOYING VARIOUS CANARDS AND A TRAILING EDGE FLAP CONTROL

Charles D. Trescot, Jr. Washington Oct. 1971 113 p refs
 (NASA-TM-X-2367; L-6163) Avail: NTIS CSCL 01A

An investigation was made in a unitary plan wind tunnel to determine the static longitudinal stability and control characteristics of a missile configuration with cruciform delta wings and various horizontal canards. The controls consisted of three different trapezoidal canards and a wing trailing-edge flap located on the horizontal wings only. The tests were made at Mach numbers from 1.50 to 4.63, through an angle-of-attack range from about -4 to 30 deg, at an angle of sideslip of 0 deg, and at a Reynolds number of 8,200,000 per meter. The results are summarized in the form of various pertinent aerodynamic parameters as a function of Mach number. Although no detailed analysis of the results was made, the summary of results is useful in demonstrating the importance of certain parameters and should be useful in providing a source of systematic experimental data for correlation with analytical techniques. Author

N71-36416* National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.
CALCULATED PRESSURE DISTRIBUTIONS AND COMPONENTS OF TOTAL-DRAG COEFFICIENTS FOR 18 CONSTANT-VOLUME, SLENDER BODIES OF REVOLUTION AT ZERO INCIDENCE FOR MACH NUMBERS FROM 2.0 TO 12.0, WITH EXPERIMENTAL AERODYNAMIC CHARACTERISTICS FOR THREE OF THE BODIES

Louis S. Stivers, Jr. Washington Oct. 1971 99 p refs
 (NASA-TN-D-6536; A-4005) Avail: NTIS CSCL 20D

The pressure distributions and drag coefficients of 18 constant length and volume, slender bodies of revolution at zero incidence were calculated for Mach numbers 2.0 to 12.0. Four bodies were selected from each of four families of profiles: the Sears-Haack, the parabolic arc, the Von Karman, and one of Miele's. A 3/4-power body and a cone body were included to complete the group. Experimental aerodynamic characteristics for two Sears-Haack bodies and the 3/4-power body were obtained from tests in the Ames 3.5-foot hypersonic wind tunnel at Mach numbers of 5.4, 7.4, and 10.5. The calculations showed that the Sears-Haack bodies generally provided the least drag throughout the range of Mach numbers from 2.0 to 12.0. The experimental aerodynamic characteristics of the three bodies showed that the overall lift and drag characteristics did not differ markedly, but that the minimum-drag coefficients were the least for the Sears-Haack bodies. The centers of pressure for the three bodies were roughly approximated by the centers of projected plan area of the bodies. Author

N71-36418* National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.
PREDICTION OF CENTERLINE SHOCK-LAYER THICKNESS AND PRESSURE DISTRIBUTION ON DELTA WING-BODY CONFIGURATIONS
 George E. Kaatari Washington Oct. 1971 22 p refs
 (NASA-TN-D-6550; A-4013) Avail: NTIS CSCL 20D

Methods are presented to calculate both the shock inclination angle and the surface pressure coefficient in the vertical plane of symmetry of bodies at angle of attack. The methods are applicable over an angle-of-attack range from 0 deg to a maximum angle that depends on the body slenderness ratio; for very slender bodies, this maximum angle of attack approaches 90 deg. The methods apply to configurations of elliptical cross section and of rectangular cross section with rounded corners. Author

N71-36419* Air Force Academy, Colo. Frank J. Seiler Research Lab.
THE RAM-WING SURFACE EFFECT VEHICLE COMPARISON OF ONE DIMENSIONAL THEORY WITH WIND TUNNEL AND FREE FLIGHT RESULTS
 Roger W. Gallington, Mark K. Miller, and Woodrow D. Smith 29 Oct. 1971 38 p refs

(AD-727774; SRL-TR-71-0012) Avail: NTIS CSCL 01/3

The one-dimensional channel flow theory with leakage is described. Using this theory lift and drag laws for low aspect ratio ram-wings with side plates are derived. The one-dimensional channel flow theory is corroborated by wind tunnel tests of two ram-wings of significantly different geometry. Lift/drag ratios far superior to existing surface effect vehicles were measured. A series of successful free flight model tests show that complete vehicles designed from the one-dimensional channel flow theory can be statically and dynamically stable over a ground clearance range from zero to infinity. Author (GRA)

N71-36421*# Aeronautical Research Associates of Princeton, Inc., N.J.

SINGLE-DEGREE-OF-FREEDOM ROLL RESPONSE DUE TO TWO-DIMENSIONAL VERTICAL GUSTS

John C. Houbolt and Asim Sen Jul. 1971 17 p refs

(Contract NAS1-9200)

(NASA-CR-111966; ARAP-160) Avail: NTIS CSCL 01A

The single-degree-of-freedom of roll response due to encountering vertical gusts which are random in the spanwise direction as well as the flight direction is studied. Cross spectral functions associated with the von Karman spectral function are used to evaluate the roll response. Results analogous to the results that apply in the case of vertical motion response only are found. It is shown that the wing tip acceleration due to roll for the two-dimensional turbulence case can be greater than the vertical acceleration that is found for the vertical motion reference case. An interesting possible means for evaluation of gust severity sigma sub w and turbulence scale L from vertical and rolling accelerations only is developed. Author

N71-36422*# Bolt, Beranek, and Newman, Inc., Canoga Park, Calif.

AERODYNAMIC SOUND RADIATION FROM LIFTING SURFACES WITH AND WITHOUT LEADING-EDGE SERRATIONS

Alan S. Hersh and Richard E. Hayden [1971] 101 p refs

(Contract NAS2-5974)

(NASA-CR-114370) Avail: NTIS CSCL 01A

A series of fundamental studies were conducted to understand how lifting surfaces radiate sound in both smooth and turbulent flow. The application of leading edge serrations as a device for reducing the sound radiated from these surfaces was studied for the case of smooth inflow. The directivity pattern radiated by a small airfoil in flow was compared with that predicted by Curle's point dipole sound theory, and was found to be sufficient to present a partial check on that aspect of his theory. A theoretical model predicting the sound radiated from a small airfoil in turbulent flow shows good agreement with experiment over a wide speed range. The good agreement between theory and experiment suggests that for small airfoils in turbulent flow, most of the radiated sound is generated by the time derivative of the fluctuating lift induced by the turbulent flow. Author

N71-36424*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

PRELIMINARY TESTS OF THE MIXER NOZZLE CONCEPT FOR REDUCING BLOWN FLAP NOISE

Jack H. Goodykoontz, William A. Olsen, and Robert G. Dorsch [1971] 11 p

(NASA-TM-X-67938; E-6617) Avail: NTIS CSCL 01A

Noise measurements were made with a small scale external blown flap model using the mixing nozzle concept to reduce the velocity impingement at the flaps. To simplify the apparatus the mixer nozzle was simulated by a multi-lobed orifice plate. A comparison was made of the data obtained with a single orifice and an eight lobe orifice, both having the same total area of discharge. Results show that noise was reduced about 6 db below the wing when the flaps were blown with the multi-element orifice. Author

N71-36425# Cranfield Inst. of Technology (England). Coll. of Aeronautics.

THE FEASIBILITY OF THE LARGE FREIGHT AIRSHIP

D. Howe Mar. 1971 49 p refs

(Rept-5) Avail: NTIS

The reasons for the current interest in airships are analyzed and certain proposals critically examined. Some indication of the performance requirements for a large freight airship are given and the optimum speed for maximum work capacity is established. A discussion of the likely design features of the craft is concluded by selection of a particular example for numerical comparison. This is a 1000 ton gross displacement airship which in one version employs a novel method for overall control of displacement. Author

N71-36426*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

SUBSONIC CHARACTERISTICS OF A TWIN-JET SWEEP-WING FIGHTER MODEL WITH LEADING EDGE KRUEGER FLAPS

Edward J. Ray and Julian G. Carmichael, Jr. (McDonnell Douglas Corp., St. Louis, Mo.) Washington Oct. 1971 69 p refs

(NASA-TM-X-2325; L-7804) Avail: NTIS CSCL 01C

An investigation has been conducted at Mach numbers of 0.60 and 0.90 to determine the effects of various combinations of leading-edge Krueger flaps, inboard plain flaps, and out-board slats on the static aerodynamic characteristics of a twin-jet, swept-wing fighter-airplane model. The angle-of-attack range was varied from -2 deg to 24 deg and the angle-of-sideslip range was varied from about 4 deg to -15 deg. The results of the investigation indicated that the addition of Krueger flaps caused significant improvements in maximum lift coefficient and in drag coefficient at high lift coefficients. Author

N71-36427# Sandia Labs., Albuquerque, N.Mex.

ANALOG SIMULATION OF A GUIDED PARACHUTE-PAYLOAD SYSTEM

R. Vaughn, G. E. Reis, and J. A. Stark May 1971 38 p refs

(SC-DR-710097) Avail: NTIS

A description is given of a device to complement field trials in training pilots in the maneuvering of a remotely controlled steerable parachute-payload system and to study the behavior of such a system when under the control of a pilot. The device consists of roll and glide controls operated by the pilot which are coupled to an analog computer that synthesizes the flight behavior of the parachute-payload system. A stylized picture of a ground target as seen by a camera on board the payload and generated in the computer is presented on an oscilloscope. This picture is viewed by the pilot who manipulates the controls and attempts to impact the parachute and payload on the target. Author

N71-36429# Army Foreign Science and Technology Center, Charlottesville, Va.

HELICOPTER AERODYNAMICS

D. I. Bazov 14 May 1971 224 p refs Transl. into ENGLISH of the mono. "Aerodinamika Vertoletov" Moscow, Transport Publ. House, 1969 p 1-196

(AD-726841; FSTC-HT-23-549-71; ACSJ-J-9360) Avail: NTIS CSCL 01/1

The book contains the principles of helicopter flight, special characteristics of the main rotor and its function in autorotation axial and oblique flow, regimes of vertical and horizontal flight, climb and descent, takeoff and landing, balance, stability and control of the helicopter and their acting aerodynamic forces. Author (GRA)

N71-36430# Naval Air Development Center, Johnsville, Pa. Aero Mechanics Dept.

DEVELOPMENT AND EVALUATION OF AIRCRAFT CLOCKS INSENSITIVE TO HIGH INTENSITY MAGNETIC FIELDS Final Report

Lloyd G. Blades 8 Jul. 1971 15 p
(AD-726700; NADC-AM-7123) Avail: NTIS CSCL 01/3

Aircraft mechanical clocks and battery-operated clocks designed to be resistant to high intensity magnetic fields were developed.
Author (GRA)

N71-36431*# National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.
EVALUATION OF BREAKING PERFORMANCE OF A LIGHT, TWIN-ENGINE AIRPLANE ON GROOVED AND UNGROOVED PAVEMENTS

Thomas J. Yager, W. Pelham Phillips, and Perry L. Deal
Washington Oct. 1971 35 p refs
(NASA-TN-D-8444; L-7643) Avail: NTIS CSCL 01A

The braking performance of a nine-place, light, twin-engine airplane was evaluated on comparative grooved and ungrooved surfaces of a landing research runway. The test airplane was equipped with manual braking on the main wheels of the tricycle landing gear, and its weight varied from (7500 to 8000 lb). The test results indicate that pavement grooving significantly improves aircraft braking and directional control on wet runways. Measurements and observations of airplane tire treads made during this test program showed no indication of unusual wear and/or damage attributable to grooved surfaces. Comparative braking data obtained with a jet fighter and a civil and a military jet transport are also presented.
Author

N71-36432# Nortronics, Palos Verdes Peninsula, Calif. Electronics Div.

CONCEPT FORMULATION STUDY FOR AUTOMATIC INSPECTION, DIAGNOSTIC AND PROGNOSTIC SYSTEMS (AIDAPS) Interim Report
Apr. 1971 349 p refs

(Contract DAAJ01-71-C-0503)
(AD-726951; NORT-71-209-1; USAAVSCOM-TR-72-1; IR-1)
Avail: NTIS CSCL 01/3

The report represents the first formally documented submittal prepared as part of the concept formulation study for Automatic Inspection, Diagnostic and Prognostic Systems (AIDAPS) for Army aircraft. The principal objective of this phase A effort is to establish that only basic engineering, rather than experimental effort, is required to proceed with engineering development of AIDAP systems. Confirmation of this fact is presented by in-depth discussions of the availability of applicable AIDAPS technology thereby demonstrating categorically the feasibility of proceeding with development and deployment of AIDAP systems without further research effort. In the process of accomplishing this objective, several subsidiary tasks were performed that provide a base of information from which phases B and C can proceed.
Author (GRA)

N71-36433# National Transportation Safety Board, Washington, D.C. Bureau of Aviation Safety.

AIRCRAFT ACCIDENT REPORTS: BRIEF FORMAT, SUPPLEMENTAL ISSUE, 1969 ACCIDENTS
Jul. 1971 63 p

(NTSB-BA-71-2) Avail: NTIS

Reports of 108 aircraft accidents are presented as a supplement for 1969. The accident reports included were delayed pending supplemental data, additional study, or because of difficult areas in the investigation. Twenty-seven of the reports cover foreign registered aircraft accidents that occurred in the United States or its possessions.
Author

N71-36434# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT PRELIMINARY REPORT: ALASKA AIRLINES, INCORPORATED, BOEING 727, N2969G, JUNEAU, ALASKA, 4 SEPTEMBER 1971

12 Oct. 1971 10 p
(SB-71-87) Avail: NTIS

The facts, circumstances, and conditions surrounding the fatal crash of the Alaska Airline, Inc., Flight 1866 on September 4, 1971 are presented. No concrete causes were established for the accident.
E.H.W.

N71-36435*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

STABILITY AND CONTROL CHARACTERISTICS OF A LARGE SCALE DEFLECTED SLIPSTREAM STOL MODEL WITH A WING OF 5.7 ASPECT RATIO

V. Robert Page and Thomas N. Aiken Washington Oct. 1971 66 p refs

(NASA-TN-D-6393; A-3342) Avail: NTIS CSCL 01B

A wind tunnel investigation was conducted to determine the stability and control characteristics of a large scale model representative of a propeller-driven STOL transport. Longitudinal and lateral directional characteristics were obtained for a four-engine configuration having a wing of 5.7 aspect ratio fully immersed in the propeller slipstream. Configuration variables included an aileron, a spoiler, a slot-lip aileron, a spanwise variation of propeller thrust, and two vertical heights of the horizontal tail.
Author

N71-36436*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

LARGE-SCALE WIND-TUNNEL TESTS OF A PROPELLER-DRIVEN DEFLECTED SLIPSTREAM STOL MODEL IN GROUND EFFECT

V. Robert Page and Thomas N. Aiken Washington Oct. 1971 42 p refs

(NASA-TM-X-2313; A-3927) Avail: NTIS CSCL 01A

A wind-tunnel investigation was conducted to determine the longitude and lateral-directional characteristics of a large-scale STOL transport model in ground effect. Test configurations included three wing spans (aspect ratios, 5.71, 6.52, and 8.06), with and without full-span triple-slotted trailing-edge flaps, horizontal tail on and off, spanwise variation of propeller thrust (to vary the span loading and descent capability), differential propeller pitch for yaw control, and spoiler and slot-lip aileron for roll control.
Author

N71-36437# National Transportation Safety Board, Washington, D.C.

ANNUAL REVIEW OF AIRCRAFT ACCIDENT DATA: US AIR CARRIER OPERATIONS, CALENDAR YEAR 1969

18 Aug. 1971 119 p
(NTSB-ARC-71-1) Avail: NTIS

Statistical, cause/factor and injury tables, accident rates, and the briefs of accidents involving U.S. air carriers are reported for 1969. An analysis of the operation and safety record of these carriers by type of power and class of carrier is included. Author

N71-36438# Federal Aviation Administration, Washington, D.C. Flight Standards Service.

MULTIENGINE AIRPLANE CLASS OR TYPE RATING
1971 29 p Revised

(FAA-AC-61-4C) Avail: NTIS; SOD \$0.25

A guide was developed to assist applicants for multiengine rating in preparing for his certification or rating flight test. The guide provides explanations of the procedures, maneuvers, and the acceptable performance necessary to pass such a test according to Federal Aviation Regulations. The test is given in three phases: (1) oral operational test, (2) basic piloting techniques, and (3) multiengine emergency procedures. The failure of any required item constitutes the failure of the phase involved and of the flight test.
E.H.W.

N71-36439# Naval Air Development Center, Johnsville, Pa. Aero Mechanics Dept.

MATHEMATICAL MODELING OF F8-E WAVE-OFF

TRAJECTORIES FOR TSP (TERMINAL STATE PREDICTOR) Phase Report

David B. Bailey 1 Jul. 1971 26 p ref

(AD-727121; NADC-AM-7119) Avail: NTIS CSCL 01/2

F-8E wave-off trajectories are mathematically modeled for the terminal state predictor systems. A carrier-approach critical state identifier, using nonlinear range and altitude equations, is discussed.

GRA

N71-36548*# Old Dominion Univ. Research Foundation, Norfolk, Va. School of Engineering.

DOPPLER RADAR SIMULATION STUDIES

William D. Stanley Washington NASA Oct. 1971 121 p refs (Grant NGR-47-003-015)

(NASA-CR-1776) Avail: NTIS CSCL 171

A study of digital simulation and possible implementation techniques for Doppler radar altimeter signal processing is presented. A technique is described for generating simulated Doppler signals by employing a random number generator and a digital filter. Representative Doppler spectra are presented and are used in studying the measurement techniques considered. The development of a digital phase-locked concept is given. The simulation of such system on a digital computer is developed, and suggestions for possible implementation are presented. A study of processing Doppler signals with a fast Fourier transform spectrum processor is presented. Results of a computer simulation of a processor are discussed, and representative processed Doppler spectra are included.

Author

N71-36672*# National Aeronautics and Space Administration, Flight Research Center, Edwards, Calif.

MOTION CUE AND SIMULATION FIDELITY ASPECTS OF THE VALIDATION OF A GENERAL PURPOSE AIRBORNE SIMULATOR

Kenneth J. Szalai Washington Oct. 1971 36 p refs

(NASA-TN-D-6432; H-648) Avail: NTIS CSCL 14B

In the validation of the general purpose airborne simulator, certain motion and visual cues could not be duplicated because the airborne simulator could not be independently controlled in six degrees of freedom. According to pilot opinion, however, the XB-70 airplane at two flight conditions has been simulated satisfactorily. Because of the dependence of simulation results on simulator configuration, two areas were investigated after the validation program was completed. The first was the effect of mismatched cues on observed handling qualities. Experiments which varied lateral acceleration at the pilot's location and yaw rate, while keeping constant the lateral-directional dynamics displayed on the pilot's instruments, showed pilot sensitivity to directional motion cues to be different for the simulation of two XB-70 flight conditions. A technique for allowing consecutive evaluations of moving- and fixed-base configurations in flight was used successfully to determine motion cue effects. The second area investigated was the measurement and description of simulation fidelity. In-flight frequency-response measurements of the model-following system were taken to examine model-following fidelity for directly matched variables such as sideslip and roll rate as well as uncontrolled parameters such as lateral acceleration.

Author

N71-36674# Cincinnati Univ., Ohio. Design Research Collaborative.

ADVANCED LIGHTWEIGHT PORTABLE STRUCTURAL CONCEPTS FOR SHELTERS, HANGARS AND MAINTENANCE DOCKS Final Technical Report, 21 Apr. 1969 - 30 Sep. 1970

W. Randall Wakefield, James M. Alexander, Karl H. Merkel, and Jack R. Farrah Wright-Patterson, Ohio ASD 1971 356 p refs

(Contract F33615-69-C-1719)

(AD-727056; ASD-TR-71-34) Avail: NTIS HC \$6.00/MF \$0.95 CSCL 13/13

A lightweight, high-mobility structural concept for shelters used primarily for general purposes. Hangars used for temporary aircraft storage, and maintenance docks for support of aircraft maintenance crews is presented. Five shelter concepts are described. Several offer modular growth patterns. Four hangar concepts are described. Six maintenance dock concepts are described. The designs are both the aircraft-enclosing type and the access-platform type. One universal panel and beam shelter capable of various spans and shapes is discussed. Models were built of twelve of the concepts for design evaluation. Structural design feasibility analyses were performed and are included as an appendix.

Author

N71-36675*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

RAPID ESTIMATION OF WIND-TUNNEL CORRECTIONS WITH APPLICATION TO WIND-TUNNEL AND MODEL DESIGN

Harry H. Heyson Washington Sep. 1971 370 p refs

(NASA-TN-D-6416; L-7793) Avail: NTIS HC \$6.00/MF \$0.95 CSCL 14B

A chart method is developed for the rapid estimation of wind tunnel interference in closed and closed-on-bottom-only tunnels. In addition, testing limit charts, based on varying degrees of correction, are developed. Applications of these results indicate very powerful effects of wing sweep and the degree of correction on the usable testing range of wind tunnels.

Author

N71-36677*# Wyle Labs., Inc., Huntsville, Ala. Research Div.

PREDICTION OF IN-FLIGHT FLUCTUATING PRESSURE ENVIRONMENTS INCLUDING PROTUBERANCE INDUCED FLOW

J. E. Robertson Mar. 1971 96 p refs

(Contract NAS8-25700)

(NASA-CR-119947; WR-71-10) Avail: NTIS CSCL 20D

An investigation of the transonic fluctuating pressure environments is presented. Based on test results from many sources, prediction methods for various unsteady flow environments are formulated. In particular, prediction methods are proposed for basic fluctuating pressure phenomena which occur on virtually all aerospace vehicles during some phase of launch and protuberance induced fluctuating pressure phenomena which are typical of three-dimensional protuberances attached to the external surfaces of a vehicle. The prediction methods for the basic fluctuating pressure phenomena were developed for two-dimensional and axisymmetric configurations; however, the conclusions are of fairly general application. The prediction of overall levels, spectra and cross-spectra for both basic and protuberance induced fluctuating pressure phenomena are compared to show characteristics unique to the particular unsteady flow condition.

Author

N71-36679*# National Aeronautics and Space Administration, Ames Research Center, Moffett Field, Calif.

TIP VORTICES: VELOCITY DISTRIBUTIONS

N. A. Chigier and V. R. Corsiglia Sep. 1971 14 p refs Presented at the 27th Ann. Natl. Forum of the Am. Helicopter Soc., May 1971

(NASA-TN-X-62087) Avail: NTIS CSCL 20D

Detailed measurements of velocity distributions have been made in vortices generated at the tip of a square-tip, 18-inch-chord, 48-inch semispan blade mounted in the NASA-Ames 7-by 10-foot wind tunnel. Time-mean-average velocity components were measured using a triple sensor hot wire probe operated by three separate anemometers. With the blade at an angle of attack of 12 deg, traverses were made through the vortex centers at six axial stations, $x/c = -0.75, -0.50, -0.25, 0.0, 2.0, \text{ and } 4.0$, where $x/c = 0$ is the trailing edge. The dimensions of the vortex increase with distance downstream over the blade surface, and at $x/c = 4$ the vortex core radius is 1.7% of the span. Maximum circumferential

velocity of 42% of mainstream velocity was measured at $x/c = -0.50$, over the wing surface, followed by decay to 24.0% of mainstream velocity at $x/c = 4$. Axial velocity in excess of free stream velocity was measured in the vortex core with maximum axial velocity of 140% of free stream velocity at $x/c = -0.25$.

Author

**N71-36688# Sandia Corp., Albuquerque, N.Mex.
MAGNUS DATA ON THE STANDARD 10 DEG CONE
CALIBRATION MODEL**

Warren H. Curry, James F. Reed, and William C. Ragsdale (NOL, White Oak, Md.) Mar. 1971 24 p refs Presented at 35th Meeting of the Supersonic Tunnel Assoc., Dallas, 8-9 Mar. 1971 (SC-DC-71-3821; Conf-710306-1) Avail: NTIS

The standard 10 deg cone calibration model was run in a supersonic wind tunnel to obtain Magnus force and moment data at Mach numbers of 1.76, 2.02, and 3.02, at respective Reynolds numbers of 2.74, 2.44, and 1.79 million based on model length. The angle of attack was varied from zero to 12 degrees and the spin helix angle ranged from zero to approximately 0.25 radians. Boundary layer transition occurred on the model at all finite angles of attack. As expected, these results were not in agreement with the theoretical predictions for the all laminar boundary layer condition.

Author (NSA)

N71-36695# Imperial Coll. of Science and Technology, London (England). Dept. of Aeronautics.

AN INVESTIGATION OF THE FLOW AROUND RECTANGULAR CYLINDERS

P. W. Bearman and D. M. Trueman Jun. 1971 25 p refs (IC-Aero-71-15) Avail: NTIS

Measurements are presented of the base pressure coefficients, drag coefficient and Strouhal number of rectangular cylinders. The results confirm a finding in Japan that the drag coefficient rises to nearly 3 when the depth of the section is just over half the width. The flow around the sections is found to be strongly influenced by the presence of the trailing edge corners.

Author

N71-36697# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

CALCULATION OF NONLINEAR CONICAL FLOWS BY THE METHOD OF LINES

E. B. Klunker, Jerry C. South, Jr., and Ruby M. Davis Washington Oct. 1971 82 p refs

(NASA-TR-R-374; L-7813) Avail: NTIS CSCL 20D

A computational technique, called the method of lines, is developed for computing the flow field about conical configurations at incidence in a supersonic flow. The method, which makes use of the self-similarity property, is developed for the nonlinear flow equations. The method has proved to be an efficient and versatile procedure for constructing the numerical solutions to conical flow problems. It has been successful in computing the flow about circular and elliptic cones at conditions where small regions of supersonic cross flow develop and for the conical delta wings where the region of supersonic cross flow is extensive. The calculations made for circular and elliptic cones as well as for the compression side of various conical delta wings are in good agreement with experiment except in regions where viscous effects become important.

Author

N71-36704 National Lending Library for Science and Technology, Boston Spa (England).

THE EFFICIENCY OF SINGLE-ROW IMPULSE STAGES ON THE BASIS OF SOVIET TEST DATA

V. D. Pshenichny [1970] 10 p refs Transl. into ENGLISH from Energomashinostroenie (Moscow), v. 16, no. 6, Jun. 1970 p 9-11

(NLL-CE-Trans-5631-(9022.09)) Avail: Natl. Lending Library, Boston Spa, Engl.: 1 NLL photocopy coupon

Test data obtained by determining the internal efficiency of single-row impulse stages are presented. The maximum internal

efficiency of a single impulse stage is plotted against the parameters of the nozzle cascade and the leakages in the tip section are examined. It is found that the efficiency values obtained in all the experiments are in good agreement if they are reduced to the same test conditions.

Author

N71-36720# Aeronautical Research Associates of Princeton, Inc., N.J.

COMPUTING DISPERSAL OF ATMOSPHERIC POLLUTANTS NEAR AIRPORTS

Coleman duP. Donaldson and Glenn R. Hilst Jul. 1971 36 p refs

(Contract NAS1-10192)

(NASA-CR-111962; ARAP-162) Avail: NTIS CSCL 04A

The basic rationale of invariant modeling is demonstrated and verified in specifying the structure of atmospheric turbulence near the ground. A model capable of predicting the dispersal of inert airborne pollutants emanating from arbitrary source configurations was constructed and tested. This model depends upon the turbulence model for inputs of turbulence structure and, when the source configuration is specified, predicts the distribution of pollutant concentration downstream.

E.M.C.

N71-36748# Air Force Cambridge Research Labs., Bedford, Mass.

A REMOTE-SENSING INVESTIGATION OF FOUR MOJAVE PLAYAS. ENVIRONMENTAL RESEARCH PAPERS

Carlton E. Molineux, Emmanuel E. Bliamptis, and James T. Neal 16 Apr. 1971 73 p refs

(AD-727031; AFCRL-71-0235; AFCRL-ERP-352) Avail: NTIS CSCL 08/6

Dry lakebeds (playas) in the Mojave Desert are often hard and flat enough to serve as natural landing areas for aircraft. However, the surface physical properties of moisture, strength, and microrelief can vary with seasonal or local conditions. It is desirable to develop methods for determining and monitoring these properties and their variations. Airborne remote sensing enables collection of data on the reflectance, temperature, and emissivity of these surfaces that can be correlated with soil parameters. Four playas in the Mojave Desert that have a variety of surface properties were investigated. Airborne spectrophotography and thermal infrared imagery were obtained by overflights. Ground photometry and measurements of surface properties were obtained. Moisture-sensitive dyes were applied to one lakebed surface to evaluate the feasibility of monitoring its dryness through color changes apparent on the aerial photography. The report describes the results of the remote-sensing investigations and the correlation of photographic and imagery interpretation with actual surface conditions.

Author (GRA)

N71-36770# California Univ., Berkeley. Forestry Remote Sensing Lab.

REMOTE SENSING APPLICATIONS IN FORESTRY. THE DEVELOPMENT OF AN EARTH RESOURCES INFORMATION SYSTEM USING AERIAL PHOTOGRAPHS AND DIGITAL COMPUTERS PHOTOGRAPHS AND DIGITAL COMPUTERS

Annual Progress Report Philip G. Langley, Jan Van Roessel, David A. Sharpnack, and Robert M. Russel 30 Sep. 1970 33 p refs Sponsored in part by Dept. of Agr.

(NASA Order W-12996)

(NASA-CR-122922) Avail: NTIS CSCL 14B

Work continued: (1) to develop an operating earth resources information system oriented toward wildland application; (2) to provide techniques for scanning and interpreting aerial photographs automatically to provide inputs to the information system; and (3) to develop sampling designs which optimally utilize the information system and supplementary remote sensor and ground data for resource inventory and analysis. A systems analysis has been completed specifying the equipment and software packages needed to build the wildland information system and programs have been written for data input. Several image matching procedures for automatic mapping of forest

resources using digitized stereopairs of aerial photographs have been tested. A program package for simulating scanned aerial photographs in various orientations has been written. Development of a linear discriminate function (LDF) to automatically classify forest types on panchromatic prints continued. A large scale test of a five-stage forest inventory procedure using Apollo 9 and aerial photographs was conducted on 10 million acres with a sampling error of only 13 percent on an estimate of 2.2 billion cubic feet of timber growing on 5 million acres. Author

N71-36776# Advisory Group for Aerospace Research and Development, Paris (France).

RELIABILITY OF AVIONICS SYSTEMS

Jul. 1971 191 p refs Mostly in ENGLISH; partly in FRENCH Conf. held in Rome, 16-17 Sep. 1971 and London, 20-21 Sep. 1971; Sponsored by Avionics Panel and Exchange Programme of AGARD *Its Lecture Series No. 47* (AGARD-LS-47-71) Avail: NTIS

CONTENTS:

1. RELIABILITY AND SURVIVABILITY E. Keonjian (Grumman Aerospace Corp.)

2. TECHNIQUES OF SYSTEM RELIABILITY ESTIMATION, INCLUDING FAILURE EFFECT ANALYSIS (FAILURE CONSEQUENCE) W. T. Sumerlin (McDonnell Aircraft Co., St. Louis, Mo.) 29 p refs

3. CORRELATION BETWEEN ESTIMATION TESTS AND SYSTEM OPERATING DATA M. M. Tall (RCA, Moorestown, N.J.) 9 p refs

4. EFFECTIVENESS OF RELIABILITY PROGRAM ELEMENTS W. T. Sumerlin (McDonnell Aircraft, St. Louis, Mo.) 9 p

5. COST EFFECTIVENESS OF BUILT-IN TEST PROVISIONS M. M. Tall (RCA, Moorestown, N. J.) 8 p refs

6. HIGH RELIABILITY DESIGN TECHNIQUES APPLIED TO THE LUNAR MODULE J. J. Bussolini (Grumman Aerospace Corp.) 34 p refs

7. TESTING THE RELIABILITY OF AVIONIC EQUIPMENT FOR SPACECRAFT APPLICATIONS G. Vollhardt (Siemens AG) 10 p

8. METHODS OF SPECIFYING AND CONTROLLING DESIGN RELIABILITY J. J. Bussolini (Grumman Aerospace Corp.) 19 p refs

9. RELATIONSHIPS BETWEEN PROGRAM TEST AND USER SUPPORT COSTS M. M. Tall (RCA, Moorestown, N. J.) 9 p refs

9. RELATIONSHIPS BETWEEN PROGRAM TEST AND USER SUPPORT COSTS M. M. Tall (RCA, Moorestown, N. J.) 9 p refs

10. SYSTEM OPERATIONAL CONSIDERATIONS AND THEIR RELATIONSHIP TO THE TEST PROCESS W. T. Sumerlin (McDonnell Aircraft, St. Louis, Mo.) 8 p refs

11. TECHNIQUES OF ANALYZING ACCELERATION P. Blanquart (Centre Natl. d'Etudes des Telecommunication, Lannion, France) 8 p

12. THE BENEFITS OF A TOTALLY INTEGRATED RELIABILITY TEST PROGRAM J. J. Bussolini (Grumman Aerospace Corp.) 21 p refs

13. OPERATIONAL CONSIDERATIONS AND SYSTEMS RELIABILITY B. E. Baker (Royal Air Force, High Wycombe, England) 7 p

N71-36777# McDonnell Aircraft Corp., St. Louis, Mo. Engineering Reliability.

TECHNIQUES OF SYSTEM RELIABILITY ESTIMATION, INCLUDING FAILURE EFFECT ANALYSIS (FAILURE CONSEQUENCE)

c15
W. T. Sumerlin *In* AGARD Reliability of Avionics Systems Jul. 1971 29 p refs
Avail: NTIS

The reliability estimation of an avionic system, which includes gross estimates, rapid estimates, and detailed estimates

is discussed. Probability of attainment is then studied by selective reliability allocation among subsystems, followed by feasibility estimates based on experience, complexity, failure rate summations and/or other effective techniques. Constraints including allowable degradation, alternative mode operation, environment, operator effectiveness, and excellence of maintenance will permit improved estimates. Failure mode and effect analyses serves to guide conceptual design decisions so as to eliminate single point failures and identify areas for judicious application of redundancy, requirements for high reliability parts, special environmental control, and beneficial choice of operating profile. Author

N71-36779# McDonnell Aircraft Corp., St. Louis, Mo. Engineering Reliability.

EFFECTIVENESS OF RELIABILITY PROGRAM ELEMENTS

c15
W. T. Sumerlin *In* AGARD Reliability of Avionics Systems Jul. 1971 9 p
Avail: NTIS

An opinion is given of the probable relative importance of reliability program elements including reliability requirement evaluation and allocation, proof of attainment, parts control, design surveillance, failure analysis and design correction, and reliability progress measurement. Author

N71-36780# Radio Corp. of America, Moorestown, N.J.

COST EFFECTIVENESS OF BUILT-IN TEST PROVISIONS

c15
M. M. Tall *In* AGARD Reliability of Avionics Systems Jul. 1971 8 p refs
Avail: NTIS

The feasibility of using built in test provisions (BIT) as a means of improving operational effectiveness of aircraft is discussed. The primary purpose of BIT is to indicate to the user if the prime equipment is operating satisfactorily. It provides information upon which a decision to abort, modify, or continue a mission may be based. Bit may also be applied to passive devices. In highly complex equipment BIT may indicate degrade performance of portions of the equipment as well as catastrophic failure, and indicate the use of any alternate mode of operations. The cost effectiveness of BIT is also discussed. E.H.W.

N71-36784# Radio Corp. of America, Moorestown, N.J.

RELATIONSHIPS BETWEEN PROGRAM TEST AND USER SUPPORT COSTS

c15
M. M. Tall *In* AGARD Reliability of Avionics Systems Jul. 1971 9 p refs
Avail: NTIS

The significant factors that should be included in a cost ownership analysis of avionic equipments are discussed. The value of reliability improvement efforts, including AGREE type test programs, are assessed. Author

N71-36801# Joint Publications Research Service, Washington, D.C.

USE OF INFRARED DEVICES IN OBSERVATIONS OF ICE CONDITIONS

F. I. Melkov et al 30 Sep. 1971 15 p refs Transl. into ENGLISH from the publ. "Primeniye Radiofizicheskikh Metodov v Okeanograficheskikh i Ledovykh Issledovaniyakh" Leningrad, 1965 p 95-106 (JPRS-54162) Avail: NTIS

Observations of ice conditions from an airplane by photography, by the use of television, or by using passive or active radio-locating devices, infrared techniques, and other devices operating on the principle of receiving radiated or reflected electromagnetic waves are discussed. All of these devices have their advantages and disadvantages. Photography and television assure a high resolution capability but their use requires sufficient illumination and the absence of cloud and fog. Radio location equipment in the centimeter range can be used

for ice prospecting even in the presence of clouds and fog, but with extremely poor resolution. A complete solution of the problems of ice prospecting can be accomplished only with the use of a combination of devices operating in various parts of the electromagnetic wave spectrum. The use of a combination of various apparatus smooths out the disadvantages of any one system and reinforces their positive values. Author

N71-36830* National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

EXPERIMENTAL INVESTIGATION OF SELF-ACTING-LIFT-PAD CHARACTERISTICS FOR MAIN-SHAFT SEAL APPLICATIONS

William F. Hady and Lawrence P. Ludwig Washington Oct. 1971 21 p refs

(NASA-TN-D-6384; E-6186) Avail: NTIS CSCL 11A

Experimental studies on four acting lift geometries (shrouded step pads) for maintaining positive separation of seal surfaces are compared with theoretical calculations. Load capacities at measured film thicknesses were lower than those predicted by theory for parallel surfaces. Sufficient gas (air) film stiffness was generated so that dynamic tracking of the seal seat face runout was maintained. Seal seat runouts to 0.0035 in.) were accommodated. Tracking, however, is inhibited during startup under light loads when seal seat runouts exceed 0.0025 cm (0.001 in.). Author

N71-36845 ARO, Inc., Arnold Air Force Station, Tenn.

LASER DOPPLER VELOCIMETER DUAL SCATTER PROBE VOLUME Final Report, Jul. - Oct. 1970

W. H. Goethert AEDC Jul. 1971 40 p refs

(Contract F40600-72-C-0003)

(AD-727005; AEDC-TR-71-85; ARO-OMD-TR-71-24) Avail: NTIS CSCL 14/2

A further clarification of the volume from which data originate in the dual scatter laser Doppler velocimeter is presented. Several factors are noted that specify the primary dimensions of the probe volume which in some cases are totally specified by the collector optics. It was found experimentally that the lens aperture of the light collecting optics has a primary effect on the volume from which data originate. An equation is derived for reducing this data volume for both the on-axis and off-axis cases. Experimental verification is presented and compared to the derived equation. Author (GRA)

N71-36930 Midwest Research Inst., Kansas City, Mo.

THE VISCOSITY OF SYNTHETIC TURBINE ENGINE LUBRICANTS FROM 100 F TO 700 F Technical Report, Jul. 1969 - Jan. 1971

Ronald D. Butler Wright-Patterson AFB, Ohio AFAPL Jun. 1971 79 p refs

(Contract F33615-69-C-1265)

(AD-727060; AFAPL-TR-71-35) Avail: NTIS CSCL 11/8

The report describes a technique for the experimental determination of fluid viscosity over the temperature range 100 deg - 700 deg. The method incorporates standard procedures, and meets accepted specifications for data precision and for temperature control and measurement over the entire temperature range. Reliable data of high precision can be obtained for subsequent analysis and prediction of lubricant performance in operating turbine aircraft engines. Complete viscosity data are presented for 30 synthetic lubricants. The following fluid types were included in this study: MIL-L-7808, MIL-L-23699, MIL-L-27502, poly(phenyl ether), and silicone formulations. Statistical analysis of the data indicates that a logarithmic relationship accurately describes the variation of kinematic viscosity with temperature over the entire temperature range. Appropriate equation can be used to calculate fluid viscosity at any desired temperature up to 500 F (or 700 F for thermally stable lubricants) with an average error less than 2%. Author (GRA)

N71-36985 Environmental Science Services Administration, Boulder, Colo. Atmospheric Physics and Chemistry Lab.

AN AIRBORNE PYROTECHNIC CLOUD SEEDING SYSTEM AND ITS USE

Joanne Simpson, William L. Woodley, Howard A. Friedman, Thomas W. Slusher (Olin Mathieson Chem. Corp.), R. S. Scheffee (Atlantic Res. Corp.) et al In Atlantic Oceanog. and Meteorol. Labs. Collected Reprints, 1969, Vol. 2 Sep. 1970 47 p refs

(ESSA-TM-ERLTM-APCL-5) Avail: SOD \$3.75

The development, testing, and use of an airborne pyrotechnic cloud seeding system is described. Pyrotechnic flares producing 50 g of silver iodide smoke each were developed and tested for nucleation effectiveness in a cloud chamber. Night flight tests were made of the delivery rack and firing system reliability, burn time, and flare trajectory. A randomized seeding scheme was used on 19 supercooled cumuli, of which 14 were seeded and 5 were controls. Of the 14 seeded clouds, 13 grew explosively. Seeded clouds grew 10,900 ft higher than the controls, with the difference significant at better than the 1/2 percent level. Rainfall from seeded and control clouds were compared by means of calibrated ground radars. Large increases in rainfall were found from seeded clouds, but not at a satisfactory level. Author

N71-36990 Society of Motion Picture and Television Engineers, Inc., New York.

CLOUD PHOTOGRAMMETRY FROM AIRBORNE TIME LAPSE PHOTOGRAPHY

Luis M. H. Cantilo (Miami Univ.) and William L. Woodley (Miami Univ.) In Atlantic Oceanog. and Meteorol. Labs. Collected Reprints, 1969, Vol. 2 Sep. 1970 11 p refs Presented at 105th Tech. Conf., 20-25 Apr. 1969 Sponsored by ESSA Its Preprint No. 105-52

Avail: SOD \$3.75

The technique used to analyze the aerial cloud photographs, process the Doppler navigational information, and obtain the desired measurements of the clouds is described. The various problems inherent in this method are considered, and results of its application are presented. Author

N71-37038 National Aviation Facilities Experimental Center, Atlantic City, N.J.

MEASUREMENT AND ANALYSIS OF EN ROUTE ATC DIGITAL RADAR SYSTEM ERRORS Interim Report, Jul. 1970 - Mar. 1971

Clifford Chapman Sep. 1971 27 p refs

(FAA-NA-71-16) Avail: NTIS

Prior to the conduct of tests pertinent to radar separation standards, a review of previous efforts was accomplished to ascertain the application of existing data towards the establishment of separation criteria within the en route Air Traffic Control National Airspace System, Model 1 complex at Jacksonville, Florida. Data analyses and presentation were directed towards the range and azimuth resolution characteristics and aircraft separation measurement capability of the secondary radar/digitizer subsystem. Author

N71-37041 Civil Aeromedical Inst., Oklahoma City, Okla.

ATTITUDES AND MOTIVATIONAL FACTORS IN TERMINAL AREA AIR TRAFFIC CONTROL WORK

Roger C. Smith, Bart B. Cobb, and William E. Collins Jul. 1971 30 p refs

(FAA-AM-71-30) Avail: NTIS

A sample of 614 journeymen terminal ATCSs at 17 high-density IFR airports, and 514 ATC trainees were administered a questionnaire which asked them to list what they liked best and what they liked least about ATC work in general; in addition, ATCSs made similar lists for work at their assigned facilities. Responses were surveyed for clusters, and nine response categories were established. The frequency of responses within each category was tabulated. With minor variations the pattern of responses from ATCSs was highly similar from one facility to another. The categories of job

challenge, job tasks, career characteristics, and salary contained the most positive responses about ATC work, while the categories of management, work schedule, career characteristics, and job tasks had the most negative responses. Trainee attitude patterns were similar. Author

N71-37042# Lincoln Lab., Mass. Inst. of Tech., Lexington.
AN AIRBORNE TRAFFIC SITUATION DISPLAY SYSTEM
 Richard W. Bush, Howard Blatt, and Francis X. Brady 29 Oct. 1971 19 p
 (Contract F19628-70-C-0230)
 (AD-727769; TN-1971-19; ESD-TR-71-194) Avail: NTIS CSCL 17/7

An airborne traffic situation display system which could be used as an adjunct to the evolving National Airspace System/Automatic Radar Control Terminal System (NAS/ARTS) is described. In the proposed system, a contemporary realization of an old concept, the NAS/ARTS data are broadcast. A small digital computer in an aircraft then selects from the message stream the data on its own aircraft, nearby aircraft, and a local map. These data, plus aircraft heading data from a directional gyro, are used to generate a situation display that can be aircraft-centered and heading-oriented. Author (GRA)

N71-37113# Defence Research Establishment Toronto, Downsview (Ontario).
NOISE SURVEY: A TURBOSHAFT POWER PLANT COUPLED TO A MOBILE TEST BED
 R. A. Stong Mar. 1971 7 p refs
 (DRET-TM-788) Avail: NTIS

Measurements were made of the overall sound pressure levels and spectra of the noise generated by a turboshaft power plant coupled to a mobile engine test trailer and operated outdoors. Running at maximum power the system produced overall sound pressure levels as high as 125 dB with the significant sound energy distributed between 300 and 8000 Hz, equivalent to an ISO noise hazard rating of 125. Author

N71-37369# Anheuser-Busch, Inc., St. Louis, Mo.
CHEMICAL AND PHYSICAL STUDY OF FUELS GELLED WITH CARBOHYDRATE RESINS Final Report, 22 Jun. 1970 - 2 Feb. 1971
 James Teng and James M. Lucas Sep. 1971 90 p refs
 (Contract DOT-FA70NA-497)
 (FAA-NA-71-18; FAA-RD-71-43) Avail: NTIS

A carbohydrate derivative was designed as a gelling agent for turbine fuel. The gelling agent is effective in reducing the fire hazard of the fuel. The free flowing gelled fuel could be adapted readily to existing fuel systems. The rheological profile of this gelled fuel was established over a range of conditions by means of a rotating viscometer, equipped with special measuring heads. Among the rheological parameters which were measured, the viscoelasticity of the gelled fuel appears likely to be a major factor in contributing to the crash-safe character of the fuel. Pertinent physical properties and microbiological data were also compiled to demonstrate that the fuel gelled with the carbohydrate based gelling agent is compatible with present aircraft fuel systems. Author

N71-37373*# Pratt and Whitney Aircraft, East Hartford, Conn.
DEVELOPMENT OF COMPRESSOR END SEALS STATOR INTERSTAGE SEALS, AND STATOR PIVOT SEALS IN ADVANCED AIR BREATHING PROPULSION SYSTEMS. PART 2: EXPERIMENTAL DATA AND ANALYSIS Final Report, 26 Jun. 1965 - 23 Oct. 1970
 R. M. Hawkins and A. H. McKibbin 24 Nov. 1970 185 p refs
 (Contract NAS3-7605)
 (NASA-CR-72887; PWA-4059-Pt-2) Avail: NTIS CSCL 21E

The design and development of 28-inch diameter rotating seals for air breathing propulsion systems is discussed. The results of testing the compressor seals, an analysis of two improved self-acting compressor seal designs, and the performance tests of stator pivot seals are presented. Numerical analyses and graphs are used to further substantiate the test results. Author

N71-37378*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.
PEAK AXIAL-VELOCITY DECAY WITH MIXER-TYPE EXHAUST NOZZLES
 D. Groesbeck, R. Huff, and U. von Glahn Sep. 1971 27 p refs
 (NASA-TM-X-67934; E-6609) Avail: NTIS CSCL 21E

Preliminary results of an experimental study on the peak axial-velocity decay obtained with circular and non-circular nozzles and several mixer-type nozzles is summarized. Prime applications of nozzles having a rapid axial velocity decay are for: (1) reduction of jet exhaust-deflected flap interaction noise associated with STOL aircraft using an externally blown flap lift augmentation system; (2) VTOL downwash suppression resulting from vertically oriented exhaust nozzles; and (3) conventional exhaust noise suppressors with and without ejectors. With a multi-element nozzle, the velocity of the individual small jets decays rapidly by mixing with the surrounding air. At some distance downstream of the nozzle exit plane, the individual jets coalesce sufficiently to form a large diameter coalescing core and a very slow peak-velocity degradation occurs. Once the coalesced core has fully formed, rapid mixing again occurs with an associated rapid velocity degradation. Author

N71-37381# Pratt and Whitney Aircraft, West Palm Beach, Fla. Research and Development Center.
DESIGN AND EXPERIMENTAL EVALUATION OF A HIGH-TEMPERATURE RADIAL TURBINE, PHASE 2 Final Report, 18 Jul. 1967 - 31 Aug. 1970
 Glenn S. Calvert, Stephen C. Beck, and Uelo Okapuu Ft. Eustis, Va. Army Air Mobility Research and Development Lab. May 1971 223 p refs
 (Contract DAAJ02-68-C-0003)
 (AD-726466; PWA-FR-4058; USAAMESL-TR-71-20) Avail: NTIS CSCL 21/5

The report describes the design, fabrication and test of a radial turbine designed to produce 219.6 Btu/lb stage work at 87.5% efficiency, with a 5:1 stage pressure ratio. Turbine inlet gas conditions at design point were 257.5 psia and 2300 F. The resulting turbine configuration consisted of an air-cooled, 12-bladed rotor designed for 67,000 rpm, and a 20-vaned air-cooled nozzle section of a reflex-type (supersonic) design. Both parts were designed as IN100 (PWA 658) investment castings. As part of the preliminary design effort, a fabrication study was conducted to evaluate feasible methods of casting the turbine nozzle and rotor. Results showed that the nozzle section could be cast as an integral assembly, but fabrication of the rotor as an integral casting was much more difficult. Bicasting was evaluated as an alternate method of fabricating the rotor, and results showed substantial advantages for the bicasting technique. However, neither method could produce designed rotor properties, and testing was conducted with structurally limited rotors. A test rig was designed and fabricated by the contractor. The test rig consisted of a supercharged gas generator, which had the capability of controlling the turbine load by varying the compressor flow rate. Burner testing preceded turbine testing. Author (GRA)

N71-37384*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.
PERFORMANCE CHARACTERISTICS OF A SINGLE-ENGINE FIGHTER MODEL FITTED WITH AN IN-FLIGHT THRUST REVERSER
 Donald L. Maiden and Charles E. Mercer Washington Sep. 1971 130 p refs
 (NASA-TN-D-6460; L-7824) Avail: NTIS CSCL 21E

The investigation was conducted at the Langley 16-foot transonic tunnel at Mach numbers up to 1.30. The purpose of the investigation was to establish changes in thrust-minus-drag performance as well as longitudinal and directional stability and control characteristics attributable to an in-flight thrust reverser. The performance results and the effects of the thrust reverser on local surface temperatures and pressures are presented in this report. Test conditions simulated landing-approach conditions as well as high-speed maneuvering such as may be required for combat or steep descent from altitude. The results indicate that the developed thrust control unit will produce reverse thrust up to 52 percent of forward thrust at static conditions and that reverse-thrust effectiveness increased with an increase in Mach number over the speed range investigated. Secondary cooling during reverse thrust and local tail temperatures may require further design considerations. Author

N71-37387# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

AIRCRAFT ENGINES (SELECTED ARTICLES)

Yu. A. Bordovitsyn et al 7 May 1971 88 p refs. Transl. into ENGLISH from Tr. Inst. Aviats. (USSR), no. 110, 1969 p 11-15, 27-46, 56-66, 74-92

(AD-727175; FTD-MT-24-18-71) Avail: NTIS CSCL 21/2

Content: The effect of the form of an active gas jet on the characteristics of a gas ejector with short mixing chamber; calculation of the maximum degree of compression of an ejector; the rational method of selecting parameters and calculating single-stage gas turbines; a generalization of the results of measurements of the fineness of fuel atomization of mechanical and at air-mechanical injectors of the pressure-jet type; calculation of temperature field in a cooled turbine blade with longitudinal cooling channels; turbulence in the zone of interplay of jetstreams with the flow. GRA

N71-37524# Aeronautical Research Labs., Melbourne (Australia).

A SURVEY OF FATIGUE LIFE VARIABILITY IN ALUMINIUM ALLOY AIRCRAFT STRUCTURES

G. S. Jost and F. E. Verinder Feb. 1971 25 p refs

(ARL/SM-report-329) Avail: NTIS

The variability, or scatter, in the fatigue lives of aluminium alloy aircraft structures was tested under both symmetric and asymmetric variable amplitude loading spectra and programmed and random loading sequences. Physically and statistically compatible data have been pooled to increase the precision of scatter estimates and this has clarified the influence of loading conditions on scatter. It has been found that, although loading sequence is of little importance, the symmetry of the loading spectrum has a major influence on scatter. Author

N71-37540# Southampton Univ. (England). Inst. of Sound and Vibration Research.

THE REDUCTION OF RESONANT VIBRATIONS IN INTEGRALLY STIFFENED SKIN STRINGER PANELS USING VISCO-ELASTIC MATERIALS Final Report, 15 Feb. 1968 - 14 Feb. 1970

Fernando Cicci Wright-Patterson AFB, Ohio AFML 29 Oct. 1971 243 p refs

(Contract F61052-68-C-0027)

(AD-727773; AFML-TR-71-1) Avail: NTIS CSCL 01/3

The vibration characteristics of integrally stiffened skin-stringer panels have been investigated theoretically and experimentally. This type of structure was found to have mode shapes similar to those of flat plates due to the relatively low values of stringer bending stiffness. The experimental measurements were made by means of strain gauges and accelerometers, with the typical panel excited acoustically by travelling waves at approximately grazing incidence. Methods of damping the resonant vibrations were also investigated theoretically and experimentally. Predictions were verified using a beam taken from the cross section of an integrally stiffened

panel. It was found that an extremely efficient method was one in which a damper was attached to the free edges of the stringers. This damper could be either a strip of viscoelastic material or a shear system made up of metal skins and a viscoelastic shear layer. Author (GRA)

N71-37543 Stanford Univ., Calif.

IMPACT ON PLATES ON ELASTIC FOUNDATIONS

Arthur Gates Ware, III (Ph.D. Thesis) 1970 104 p

Avail: Univ. Microfilms Order No. 70-18501

The equations of motion for a plate-foundation system under a dynamic load are presented. By assuming that the load can be broken into the product of a space-dependent function and a time-dependent function two approaches are followed to separate the basic partial differential equations for the infinite plate. The final solutions are applied to the landing of an aircraft and numerical examples are carried out to illustrate the effect of the various parameters. The results show that the responses of plates on elastic foundations are almost identical whenever the bending rigidity of the plate is greater than that of the model. However, for plates possessing less bending rigidity than the foundation, the continuity of the foundation begins to assert itself. The concluding part of the work describes the cases of dual and multiple wheel assemblies and possible extensions of the investigation are outlined. Dissert. Abstr.

N71-37563# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

PROCEDURE FOR SCALING OF EXPERIMENTAL TURBINE VANE AIRFOIL TEMPERATURES FROM LOW TO HIGH GAS TEMPERATURES

Herbert J. Gladden and John N. B. Livingood Washington Sep. 1971 28 p refs

(NASA-TN-D-6510; E-6250) Avail: NTIS CSCL 20M

A procedure was developed based on conditions of similarity whereby cooled turbine vane airfoil temperatures measured at low levels of gas temperature can be used to accurately represent both the local and average airfoil temperatures that would be expected at a much higher level of gas temperature. The feasibility of this scaling procedure was verified experimentally in a four-vane cascade capable of operation at gas temperatures and pressures up to 1645 K (2500 F) and 103.4 newtons per square centimeter (150 psia), respectively. A comparison of these scaled airfoil temperatures with experimentally measured airfoil temperatures for the same high temperature conditions is presented. Author

N71-37590# Committee on Foreign Relations (U. S. Senate).

CONVENTION FOR THE SUPPRESSION OF UNLAWFUL SEIZURE OF AIRCRAFT

Richard Nixon Washington GPO 1971 19 p

Avail: US Capitol, Senate Document Room

The convention for the suppression of unlawful seizure of aircraft, signed at the Hague on 16 December 1970 is presented with an article by article analysis. J.M.

N71-37593# Scientific Translation Service, Santa Barbara, Calif.

REVIEW OF TESTING TECHNIQUES FOR TRANSONIC AIRFOILS [CRITIQUE DES TECHNIQUES D'ESSAIS DE PROFILS TRANSSONIQUES]

M. Bazin et al Washington NASA Oct. 1971 49 p refs. Transl. into ENGLISH from ONERA preprint of conf. paper Presented to 7th Colloq. on Appl. Aerodyn. Rhone, France, 4-6 Nov. 1970; sponsored by Assoc. Franc. Des Ingr. et Technicien de l'Aeronaut. et de l'Espace

(Contract NASW-2035)

(NASA-TT-F-13988) Avail: NTIS CSCL 01A

The testing of airfoils in two-dimensional flow in two types of wind tunnels is discussed. One apparatus makes it possible to

carry out tests on large models over a wide range of Reynolds numbers. The study of helicopter blade elements with chords identical to those of rotor blades tested in a similar wind tunnel makes comparisons possible. The systematic study of wall interactions was carried out in the second wind tunnel, which is well adapted for basic research at high Reynolds numbers. Preliminary results indicate corrections which are applicable to test conditions in the latter wind tunnel. Author

N71-37594* Lockheed-California Co., Van Nuys. Rotary Wing Div.

TRIM, CONTROL, AND STABILITY OF A GYRO-STABILIZED HINGELESS ROTOR AT HIGH ADVANCE RATIO AND LOW ROTOR SPEED

G. A. Watts, R. J. London, and R. J. Snoddy May 1971 312 p refs

(Contract NAS2-5168)

(NASA-CR-114362) Avail: NTIS CSCL 01B

Methods are developed for predicting the behavior of hingeless rotors with stiff blades, at high advance ratios and low rotor speeds. The methods are simple and expository in nature, and are developed for the purposes of: (1) providing insight into the influences of various rotor and control parameters on rotor system behavior, (2) examining the suitability of existing methods which contain more comprehensive analytic descriptions for predicting behavior of hingeless rotors at high advance ratios at low rotor speeds, and (3) providing analysis techniques which are flexible enough to be useful in preliminary design studies.

N71-37596* National Research Council of Canada, Ottawa (Ontario). Div. of Mechanical Engineering.

AERODYNAMIC TESTS ON A CENTRIFUGAL FAN IMPELLER MODEL WITH SWEEP-BACK BLADES

H. S. Fowler May 1971 64 p refs

(NRC-12020; ME-237) Avail: NTIS

A low speed centrifugal compressor rig was used to test a 58 1/2 inch diameter model of a fan impeller with highly swept-back vanes. The impeller was run over a range of speeds and throttle settings to explore the whole operating field. The flow was measured at inlet and impeller exit by hot-wire anemometer traverses, and motion pictures of the flow were made using smoke visualization. The flow through the impeller is described in detail, and is compared with that in other impellers investigated on the same test rig. A comparison is also made with the flow in a geometrically similar impeller tested in a water tunnel. The correspondence between the flows seen in these two experiments is shown to be very close. Author

N71-37597* Douglas Aircraft Co., Inc., Long Beach, Calif.

CALCULATION OF POTENTIAL FLOW ABOUT ARBITRARY THREE DIMENSIONAL LIFTING BODIES Final Report, Dec. 1969 - Oct. 1970

John L. Hess Oct. 1970 46 p refs

(Contract N00019-70-C-0100)

(AD-727628; MDC-J0971-01) Avail: NTIS CSCL 01/3

The report describes work accomplished during the second phase of a projected three-phase effort to develop a computer program to calculate potential flow about arbitrary three-dimensional lifting bodies. The main task of this phase was programming and checking-out logic that had been developed previously. Evaluation of the method by numerical experimentation has just begun, and the few results obtained so far comprise the body of this report. Simple wings of rectangular planform are considered. Preliminary results indicate that surface pressures are insensitive to wake shape but sensitive to the means of applying the Kutta condition. For some situations there is an anomaly in the surface dipole distribution, which fortunately does not affect the surface pressures. GRA

N71-37598* Pennsylvania State Univ., University Park. **EXPERIMENTAL STUDY OF ROTOR UNSTEADY AIRLOADS DUE TO BLADE-VORTEX INTERACTION**

Raghuvveera Padakannaya Washington NASA Nov. 1971 37 p ref

(Grant NGR-39-009-111)

(NASA-CR-1909; PSU-AERSP-71-1) Avail: NTIS CSCL 01A

Measurements of unsteady, rotor-blade airloads and their time derivatives are presented for a rotor blade intersecting a completely rolled-up vortex. These results, taken at the blade spanwise station of 0.9R, 0.85R, and 0.75R, complement measurements previously reported for the 0.95R station in CR-1573. Incremental values in the section lift coefficient as high as 1.17 were obtained at the 0.75R station. Generally, these values decreased with increasing radius. Author

N71-37800* Techtran Corp., Glen Burnie, Md.

DEPENDENCE OF AIRCRAFT BUFFETING IN THE STRATOSPHERE ON HORIZONTAL TEMPERATURE AND WIND DISTRIBUTION [ZAVISIMOST BOL'TANKI SAMOLETOV V STRATOSFERE OT GORIZONTALNOGO RASPREDELENIYA TEMPERATURY I VETRA]

G. S. Buldovskiy Washington NASA Oct. 1971 15 p refs

Transl. into ENGLISH from Russian report

(Contract NASw-2037)

(NASA-TT-F-13978) Avail: NTIS CSCL 01B

The relationship between buffeting of aircraft in the stratosphere and horizontal temperature and wind distributions is analyzed on the basis of data collected in previous studies and results of instrument measurements of stratospheric turbulence, done in a special aircraft laboratory at altitudes of 10 to 18-19 km. The task was to determine the critical values of the horizontal parameters that would insure the most successful diagnosis of buffeting. Of all examined parameters considering the horizontal temperature and wind distributions, horizontal wind shears along and across the stream are best for diagnosing stratospheric buffeting. Author

N71-37801* National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

NOISE REDUCTION BY MEANS OF VARIABLE-GEOMETRY INLET GUIDE VANES IN A CASCADE APPARATUS

David Chestnut and Lorenzo R. Clark Washington Oct. 1971 24 p refs

(NASA-TM-X-2392; L-7852) Avail: NTIS CSCL 01C

Noise reduction studies involving variable geometry inlet guide vanes for choking have been made by using a two-sector cascade apparatus with three different inlet configurations: a rotating offset inlet guide vane (IGV), a translating wave IGV, and a stationary uncambered IGV. All three configurations were operated in both the choked and unchoked modes for a range of airflows. The acoustic and aerodynamic performances were found to be dependent on the geometry of the test configurations. Choking in an uncambered IGV resulted in a noise reduction of 49 dB for the fundamental frequency. Choking in the offset IGV and in the wave IGV resulted in noise reductions of 21 dB and 34 dB, respectively. The total-pressure recovery for the uncambered IGV was 0.94 out of 1.00, whereas total-pressure recoveries in the choked mode for the offset IGV and the wave IGV were 0.57 and 0.66, respectively. Author

N71-37802* Air Force Systems Command, Wright-Patterson AFB, Ohio.

FLIGHT DYNAMICS; AIRCRAFT TRAJECTORIES

I. V. Ostoslavskii et al 7 Jun. 1971 693 p refs Transl. into ENGLISH from the book "Dinamika Poleta. Trayektorii Letatelnykh Apparatov" Moscow, Mashgiz., 2d edition, revised and enlarged, 1969 p 5-294 and 299-499

(AD-727474; FTD-HC-23-637-70) Avail: NTIS CSCL 01/2

The book presents methods of calculating flight trajectories of various aircraft and spacecraft. Equations of motion in inertial and noninertial reference systems are derived, along with fundamental laws of flight dynamics and background information on the mathematics of investigation of flight trajectories. Quasi-steady and unsteady motion are examined in relation to

additional kinematic couplings, along with general and variational methods of solving problems in flight dynamics. Methods of calculating elements of trajectories, and takeoff and landing characteristics of aircraft, including ballistic rockets, orbital aircraft, artificial satellites, and spacecraft are given. Methods of calculating the trajectory of ballistic rockets over powered and passive phases is given, along with methods of calculating the trajectory of motion of artificial satellites when injected into orbit. Methods of optimal control of spacecraft are examined briefly. Author (GRA)

N71-37603# - National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.

EXPLORATORY WIND-TUNNEL INVESTIGATION OF DEPLOYABLE FLEXIBLE VENTRAL FINS FOR USE AS AN EMERGENCY SPIN-RECOVERY DEVICE

Sanger M. Burk, Jr. Washington Oct. 1971 33 p refs Film Supplement Number L-1103 to this report is available on loan from NASA. Langley Research Center

(NASA-TN-D-6509; L-7877) Avail: NTIS CSCL 01A

Spin-tunnel tests have been conducted on dynamic models of two fighter airplanes to explore the feasibility of using deployable flexible ventral fins as an emergency spin-recovery device. Various fin configurations, deflections, and locations were tested. The results indicated that the fins provided satisfactory spin recoveries for the models tested. Author

N71-37604# Coordinating Research Council, Inc., New York. Aviation, Fuel, Lubricant and Equipment Research Committee.

THE 1969 CRC AVIATION EMISSION-TREATMENT TECHNIQUE EVALUATION

Mar. 1970 58 p ref

(Rept-43C) Avail: NTIS

Methods for sampling, handling, and measuring emissions from aircraft gas turbine engines were evaluated. Agreement among three particulate methods in measuring carbonaceous materials was fairly good. Flame ionization detectors were quite satisfactory for measuring hydrocarbon concentrations in the range of 200 to 300 ppm by volume. The Fisher partitioner and the nondispersive infrared absorption (NDIR) analyzer were well suited for measuring carbon monoxide and carbon dioxide. The phenol disulphonic acid method for measuring nitrogen oxides and the NDIR analyzer for measuring nitric oxide performed well. The 3-methyl 2-benzothiazolinone hydrazone hydrochloride method gave fair results when the engine was operated at low rpm and concentrations of oxygenated materials were in the range of 10 ppm. Traverses of the tail pipe plane showed significant variations in emissions among sampling points. The length of sample hydrocarbon sample line was unimportant, but the use of Teflon rather than stainless steel as line material, high line temperature, and high sample flow rate were all judged desirable. Author

N71-37605# Federal Aviation Administration, Washington, D.C. **STOL: THE AGONY AND THE ECSTASY**

Ronald W. Pulling Jun. 1971 31 p refs Presented at the Greater Miami Chamber of Com. V/STOL Conf. Workshop, Miami, Fla., Feb. 1971

(WRCN-2; AV71-2) Avail: NTIS

The nature of intercity travel is discussed, and the historical growth of air transportation is reviewed. Some of the significant factors concerning the air transportation penetration into the intercity travel market are presented and discussed. As a result of this penetration, air transportation now accounts for the majority of commercial passenger miles traveled. Commercial air transportation is short-haul oriented with half of all scheduled flights covering distances of 500 miles or less. Commercial air transportation is also oriented toward areas of high population density, with 11 communities accounting for half of all passenger enplanements. The growth in air transportation has resulted in many acute problem areas such as noise, pollution, and traffic congestion. The population increase and the resulting increase in

travel demand over the next 10 years will cause a corresponding increase in the severity of these problems. Author

N71-37606# Royal Aircraft Establishment, Farnborough (England).

CATEGORY 2: A SIMULATION STUDY OF APPROACHES AND LANDINGS AT NIGHT

A. D. Brown Jun. 1970 81 p refs

(RAE-TM-Avionics-59(bleu)) Avail: NTIS

The design, execution and preliminary results of a flight simulator experiment to investigate the problems of aircraft operating in Category 2 conditions are described. Both military and airline pilots participated and over 500 approaches were performed. The effects of decision height, contact time, lateral offset, visual sequence and visual segment on the approach success (ratio of landings to approaches) are examined and a curve relating this parameter to visual segment, the predominant factor, is determined. The influence of different visual sequences on pilot performance during the approach and landing is also considered and some observations are made about the crew techniques employed during the experiment which appeared to have certain deficiencies. A full analysis of the flight path performance and pilot comments was omitted. Author

N71-37607# Tippetts-Abbett-McCarthy-Stratton, Washington, D.C.

AIRCRAFT GROUND OPERATIONS SIMULATION

Peter C. Sih Mar. 1971 24 p Presented at 4th Ann. Simulation Symp., Tampa, Fla., 10-12 Mar. 1971

Avail: NTIS

A description is given of an aircraft ground operations simulation program coded in GPSS/360. The physical elements of the airfield are described in terms of GPSS entities and inputted through GPSS matrix savevalues. The aircraft transactions are generated into the model through deterministic flight schedules projected for the simulated target years. The program logic is related to GPSS block actions. Indirect addressing is used extensively to give the program a flexible structure. Supplementary output to standard utilization statistics includes a computer produced movie film. Author

N71-37608# McDonnell Aircraft Corp., St. Louis, Mo.

SURVIVABLE FLIGHT CONTROL SYSTEM. STUDIES, ANALYSES AND APPROACH. SUPPLEMENT FOR HYDRAULIC POWER AND ACTUATION STUDIES Interim Report, Jul. 1969 - May 1971

Gerald E. Amies, Cecil Clark, Charles L. Jones, and M. Sheppard Smyth Wright-Patterson AFB, Ohio AFFDL 29 Oct. 1971 268 p refs.

(Contract F33615-69-C-1827)

(AD-727763; AFFDL-TR-71-20-Suppl-3; IR-1) Avail: NTIS CSCL 13/7

The Survivable Flight Control System (SFCS) Program is an advanced development program of which the principal objective is the development and flight test demonstration of an SFCS utilizing Fly-By-Wire and Integrated Actuator Package techniques. The studies and analyses conducted to date have sufficiently defined the system requirements to provide a definition of an approach to the implementation of the SFCS. The results of these studies and the definition of the approach are presented in the basic report. The details of the Control Criteria and Control Law Development studies are presented in report supplements 1 and 2, respectively. The details of the Hydraulic Power and Actuation studies are reported in this supplement 3.

Author (GRA)

N71-37609# Mississippi State Univ., State College. Dept. of Aerophysics and Aerospace Engineering.

FEASIBILITY STUDY OF A COMBINED LAMINAR AND TURBULENT BOUNDARY LAYER CONTROL SYSTEM

USING DISTRIBUTED SUCTION Final Report, May 1969 - Jan. 1971

Lawrence J. Mertaugh Wright-Patterson AFB, Ohio AFFDL 29 Oct. 1971 83 p refs
(Contract F33615-69-C-1582)
(AD-727767; AASE-71-42; AFFDL-TR-71-47) Avail: NTIS CSCL 20/4

The objective of the investigation was to determine the feasibility of a combined low-drag, high-lift boundary layer control system intended for use in the XV-11A aircraft. The XV-11A is a low-speed aerodynamic research aircraft constructed entirely of glass reinforced plastic. The combined boundary layer control system to provide full chord laminar flow over the wing surfaces in cruise flight and prevent separation of the turbulent boundary layer under conditions of high lift coefficients in the approach configuration will utilize distributed suction over the wing surfaces with the porosity provided by rows of closely spaced suction holes. The evaluation of the laminar system was accomplished on a glove section installed on the wing of a TG-3 glider. Author (GRA)

N71-37610# Pennsylvania Univ., Philadelphia. Moore School of Electrical Engineering.**PENNSYLVANIA-PRINCETON ARMY AVIONICS RESEARCH PROGRAM: FORMATION FLIGHT**

Kenneth A. Fegley Jun. 1971 214 p refs
(Contract DA-28-043-AMC-02411-E)
(AD-727635; ECOM-02411-21) Avail: NTIS CSCL 01/2

The report summarizes the results of a task whose objective was to determine the problems and functional requirements associated with the non-visual formation flight of helicopters. It also gives the requirements of the stationkeeping system required for non-visual formation flight. Author (GRA)

N71-37611# Army Test and Evaluation Command, Aberdeen Proving Ground, Md.**AUTO PILOT** Final Report

10 Jun. 1971 18 p
(AD-727789; MTP-6-3-121) Avail: NTIS CSCL 01/4

Procedures are given for service testing automatic pilots used for control of rotary and fixed wing aircraft. Author (GRA)

N71-37612# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.**AERODYNAMICS OF THE TU-134**

T. I. Ligum et al 29 Jan. 1971 434 p Transl. into ENGLISH from the monograph "Aerodinamika Samoleta Tu-134" Moscow, 1969 p 1-304
(AD-727196; FTD-MT-24-138-70) Avail: NTIS CSCL 01/3

The book states the practical aerodynamics of the new passenger aircraft Tu-134. Construction and aerodynamic peculiarities are described of the aircraft and power plant with D-30 engines. Basic flight conditions during take-off, climb, horizontal flight and landing stability and maneuverability of the aircraft; special cases in flight; loads acting on the aircraft and its strength are discussed. Author (GRA)

N71-37613# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.**TECHNICAL AVIATION HANDBOOK**

V. G. Aleksandrov et al 7 Apr. 1971 798 p Transl. into ENGLISH from the monograph "Aviatsionnyi Tekhnicheskii Spravochnik" Moscow, 1969 p 1-495
(AD-727195; FTD-MT-24-126-70) Avail: NTIS CSCL 01/2

The material in this handbook is generalized, systematized and set forth with respect to the following questions: practical aerodynamics; technical operation and maintenance of aircraft (helicopter) airframes, their systems, gas-turbine and piston engines, oxygen and high-altitude equipment, instrument-flying navigation devices; electronic equipment; lubricants employed in the operation and repair of the aviation equipment; wear of

components, subassemblies and mechanisms, repair and routine maintenance operations; maintenance of the components and systems of the aircraft, gas-turbine and piston engines, inspection and checking operations, anticorrosive treatments; aviation materials being employed, fuels, lubricants and working fluids; article defects and strength of materials. This handbook is intended for flight and technical-engineering personnel of all branches of aviation, the aviation industry, scientific institutions, students of the higher and intermediate aviation educational institutions. Author (GRA)

N71-37614# Stevens Inst. of Tech., Hoboken, N.J. Davidson Lab.**IMPACT LOADS ON WARPED PLANING SURFACES LANDING ON SMOOTH AND ROUGH WATER** Final Report

John A. Mercier Mar. 1971 53 p refs
(Contract N00600-69-C-1072)
(AD-727753; SIT-DL-71-1514) Avail: NTIS CSCL 01/3

The impact of planing surfaces on waves is analyzed according to an extension of the theory for smooth-water impacts in a way that takes account of the influence of wave kinematics. Impacts of the type incurred by seaplanes, in which the weight of the craft is sustained by wing lift, are studied. Data for planing, which is a special case of impact, are used to obtain the needed relationship between virtual mass and hull geometry. Impact tests with two models having different amounts of warp, or longitudinal variation of deadrise, are compared with theoretical calculations. Observations are made concerning the influence of trim, deadrise, beam loading, glide path, warp rate and waves on the initial stages of the impact, when the vertical velocity is practically uniform, on the basis of the derived differential equation of motion. Author (GRA)

N71-37615# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.**VARIABLE SWEEP. CHAPTERS 1-5**

S. Yu. Skripnichenko 25 Feb. 1971 79 p Transl. into ENGLISH from the book "Izmenyayemaya Strelovidnost" Moscow, Izd-vo Min. Oborony SSSR, 1969 p 1-72
(AD-727210; FTD-MT-24-264-70) Avail: NTIS CSCL 01/3

Contents: the aerodynamics of variable-sweep wing; the stability and control of variable-sweep wing; variety of operating conditions - a feature of variable-sweep; flight at low altitudes; short take-off and landing of variable-sweep wing. Author (GRA)

N71-37616# McDonnell Aircraft Corp., St. Louis, Mo.**SURVIVABLE FLIGHT CONTROL SYSTEM. STUDIES, ANALYSES AND APPROACH. SUPPLEMENT FOR CONTROL CRITERIA STUDIES** Interim Report, Jul. 1969 - May 1971

Robert L. Kisslinger and Michael J. Wendl Wright-Patterson AFB, Ohio AFFDL May 1971 201 p refs See also Supplement 3; AD-727763
(Contract F33615-69-C-1827)
(AD-727762; AFFDL-TR-71-20-Suppl-1; ir-1) Avail: NTIS CSCL 01/3

The Survival Flight Control System (SFCS) Program is an advanced development program of which the principal objective is the development and flight test demonstration of an SFCS utilizing fly-by-wire and integrated actuator package techniques. The studies and analyses conducted to date have sufficiently defined the system requirements to provide a definition of an approach to the implementation of the SFCS. The results of these studies and the definition of the approach are presented in the basic report. Details of the Control Law Development, and Hydraulic Power Actuation studies are presented in report supplements 2 and 3, respectively. The results of the Control Criteria studies are presented in this supplement. Author (GRA)

N71-37617# School of Aerospace Medicine, Brooks AFB, Tex.
PILOTS, TAKE HEED OF BIRDS

V. S. Lavrik et al 1971 101 p refs Transl. into ENGLISH of the book "Letchik, Vnimanaye-Pitsayl" Moscow, 1970 (AD-727881; SAM-TT-R-1093-0771) Avail: NTIS CSCL 01/2

Contents: analysis of statistical data on cases of collision of aircraft with birds; analysis of physical discoveries, observed when aircraft and birds collide, and basic types of damage to aviation equipment; measures for preventing collisions of aircraft with birds. GRA

N71-37618# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

ROCKET CARRYING AVIATION (SELECTED CHAPTERS)

A. N. Ponomarev 2 Mar. 1971 281 p refs Transl. into ENGLISH from the book "Raketsonosnaya Aviatsiya" Moscow, Izd-vo Ministerstva, 1964 p 1-23; 99-340 (AD-727860; FTD-MT-24-258-70) Avail: NTIS CSCL 19/7

Contents: aircraft; air navigation and takeoff and landing aids; flight support at high altitudes and equipment for rescuing the pilot (crew member) in an emergency situation. GRA

N71-37619# Naval Air Development Center, Johnsville, Pa. Aero structures Dept.

STRUCTURAL INTEGRITY INVESTIGATION OF REWORKED S-2 CORRUGATED WING SKIN PANELS

H. Lystad and Louis Berman 1 Apr. 1971 40 p refs (AD-728009; NADC-ST-7107) Avail: NTIS CSCL 01/3

Laboratory fatigue tests were performed on reworked S-2 corrugated wing skin panels to determine the effect on the structural integrity of skin material removal due to corrosion damage. Reworking of the S-2 aircraft corrugated wing skin panels, as performed by the Naval Air Rework Facilities, to remove corrosion damaged material, does not adversely affect the structural integrity of the panels. Author (GRA)

N71-37621# Royal Aircraft Establishment, Farnborough (England).

THE EFFECT OF DAZZLE ON ELECTRONIC DISPLAY [EINFLUSS DER BLENDUNG AUF DAS ERKENNEN ELEKTRONISCHER ANZEIGEN IN KANZELN MODERNER HOCHLEISTUNGSFLUGZEUGE: KURZFASSUNG]

P. Jainski Mar. 1971 27 p Transl. into ENGLISH of Ger. Federal Min. of Defence report T-808-I-203 (RAE-Lib-Trans-1545; T-808-I-203) Avail: NTIS

The performance of pilots in testing electronic head-up and head-down display systems is discussed. Measurements were made of the dazzle effect in the cockpit of high performance aircraft during daylight conditions. The measuring criteria include wength of display from subject, color used on symbols, and intensity of light. Results indicate red to be particularly suitable for recognition of display symbols and that the head-down display is favored over the head-up display. E.H.W.

N71-37682# Civil Aeromedical Inst., Oklahoma City, Okla. AURAL GLIDE SLOPE CUES: THEIR EFFECT ON PILOT PERFORMANCE DURING IN-FLIGHT SIMULATED ILS INSTRUMENT APPROACHES

A. Howard Hasbrook and Paul G. Rasmussen May 1971 27 p refs (FAA-AM-71-24) Avail: NTIS

Forty instrument rated commercial and ATR pilots with 250 to 12,271 flight hours each flew ten simulated ILS approaches in a single engine, general aviation aircraft. Divided into five groups, each group used a different glide slope cue display in combination with a modified T instrument panel configuration. Two types of aural glide slope cue displays were utilized: (1) voice, and (2) Morse code signals. No significant differences were found among the five groups relative to accuracy in glide slope tracking. There was no apparent improvement with practice. The presence of aural glide slope cues resulted in the aircraft being flown slightly higher across the middle marker than when only the conventional visual display was utilized. Localizer

performance showed a slight but significant initial decrease in the presence of aural glide slope cues with respect to only one performance measure. Transition from the conventional visual cross-pointer display to the aural (voice) glide slope cues was achieved with a minimum of familiarization and with no apparent difficulty. Author

N71-37707# Naval Research Lab., Washington, D.C.

A VERSATILE C BAND RADAR TRANSMITTER

W. T. Davis, N. R. Mills, and J. A. Weston Jun. 1971 38 p (AD-727086; NRL-MR-2278) Avail: NTIS CSCL 17/9

The C band transmitter is one of the four radar transmitters which are included in the Four-Frequency Radar System. The Four-Frequency Radar in its entirety is an airborne system capable of measuring target characteristics and terrain backscatter, and has been used in the synthetic aperture mode to map sea ice, waterborne oil pollution, and land and sea surfaces. The four radar transmitters operate at P/UHF (428 MHz), L band (1228 MHz), C band (4455 MHz), and X band (8910 MHz). Previous attempts to produce the required power and versatility at C band netted only partial success, and in due course, it was decided to replace and update the C band transmitter. A new transmitter has been produced by NRL and installed as a part of the airborne Four-Frequency Radar System. The new transmitter uses an electrostatic focused Klystron and meets its design goals while having approximately one-half the weight and cubic displacement of the older transmitter. The Four-Frequency Radar is a valuable research tool and the addition of a stable dependable transmitter in the C band region gives it the balance and continuity envisioned in its inception. Author (GRA)

N71-37712# National Resource Analysis Center, Washington, D.C. Information Systems Div.

ALTERNATIVE ATC CO-CHANNEL SEPARATION CRITERIA BASED ON PROBABILITY-OF-INTERFERENCE CONSIDERATIONS

Richard H. Wilcox and Marvin E. Hoepken Aug. 1970 26 p refs (IST-101) Avail: NTIS

Current air traffic control standards for separation between locations using the same frequency are discussed. Two aspects are considered: relative signal strength differential between interfering signals, and conditions under which this differential is applied to determine acceptable ground transmitter separations. The general geometrical relationships among controlled aircraft and their respective ground transmitters are considered in order to permit analysis of the probability of interference occurring which exceeds the differential specified. High altitude enroute control is used as a vehicle for developing specific analysis procedures and resulting quantitative results. It appears that use of probability-of-interference criteria, instead of worst case, would permit reductions in co-channel RCAG separations sufficient for a minimum increase of 50 percent in use of any given frequency; if lesser signal strength differentials were accepted and normal sector traffic were considered, improvement by a factor of six might be possible for high altitude enroute service. Extension of the method to other classes of ATC service should be straightforward. Substitution of probability-of-interference criteria for separation standards represents a desirable approach to improvement because safety is not compromised. Author

N71-37723# Scope Electronics, Inc., Reston, Va.

VOICE INITIATED COCKPIT CONTROL AND INTERROGATION (VICCI) SYSTEM TEST FOR ENVIRONMENTAL FACTORS Final Report, 16 Feb. 1970 - 30 Apr. 1971

James W. Glenn, Ronald N. Gordon, and Gabriel Moschetti 30 Apr. 1971 112 p refs

(Contract N00019-70-C-0426)

(AD-727574) Avail: NTIS CSCL 17/2

The objectives of the contract were to investigate the effects of the pilot's acoustic environment, optimize system

parameters for operation in the cockpit environment, provide system performance statistics, and investigate the availability of on-board computing systems which may be utilized. Voice data were recorded in aircraft cockpits and in an altitude test chamber. These data were analyzed to determine the effects of the environment and of physiological stresses experienced by the speakers. The results of the analyses determined modifications to be made to a simulated voice control system. The recorded data were then processed by the simulated system to obtain performance statistics. Lack of positive control over environmental variables and the inability to provide an immediate indication of system response to the speaker resulted in a data base inadequate to support statistically significant results. However it was noted that the main sources of interference to reliable speech recognition in the cockpit environment are sounds made by the pilot's oxygen supply equipment and his own breathing sounds. Methods for accommodating such sources are suggested. Author (GRA)

N71-37742# Information Processing Association of Israel, Jerusalem.
PROCEEDINGS OF THE NATIONAL CONFERENCE ON DATA PROCESSING
 Asa Kasher, ed. (Bar-Ilan Univ.) 1970 478 p refs Partly in ENGLISH; partly in HEBREW Conf. held in Tel-Aviv, 12 Oct. 1970

Avail: NTIS HC \$6.00/MF \$0.95

CONTENTS:

1. TECHNOLOGICAL FORECAST 1970 I. L. Auerbach (Auerbach Corp.) p E1-E18
2. MADAP: A COMPUTERIZED AIR-TRAFFIC CONTROL SYSTEM L. Borocin (Eurosystems) p E19-E33
3. THE IMPACT OF AUTOMATION UPON HEALTH DELIVERY SYSTEMS IN THE 1970's N. M. Trowe (Med. and Applied Res. System, Inc.) p E35-E45
4. A GENERAL APPROACH TO HEURISTIC RESOURCE ANALYSIS R. Karny (Inform. Process. Assoc. of Israel) p E47-E60 refs
5. APL: BASIC CHARACTERISTICS AND APPLICATIONS TO MATHEMATICAL PROGRAMMING AND TO DATA PROCESSING E. Sharon (Hebrew Univ.) p E61-E90 refs
6. A "COMPUTER-SYSTEM LANGUAGE" (CSL): A LANGUAGE FOR JOB CONTROL N. Minsky and I. Rotbard (Hebrew Univ.) p E91-E99 ref
7. MANAGEMENT INFORMATION SYSTEMS N. S. Prywes (Penna. Univ.) p E101-E109 refs
8. AUTOMATIC READING OF HANDWRITTEN HEBREW A. J. van der Toorn (Neth. Postal and Telecommunications Service) p E111-E126 refs

N71-37744# Eurosystem, Paris (France).

MADAP: A COMPUTERIZED AIR-TRAFFIC CONTROL SYSTEM c21
 Leon Borocin /In Inform. Process. Assoc. of Israel Proc. of the Natl. Conf. on Data Process. 1970 p E19-E33

Avail: NTIS HC \$6.00/MF \$0.95

MADAP - Maastricht Automatic Data Processing and Display System in a real time system intended to facilitate the air traffic control in the upper airspace of a region covering Belgium, Luxembourg, the Netherlands and the Federal Republic of Germany. The goal as the system is to help the human controller in memorizing all the elements of the situation, to present synthetic information for quick decision making, and to initiate a warning when a decision has to be made. The system uses for input flight plans, radar data, meteorological data, and radio-links with aircrafts. Its subfunctions are divided in such a way that each corresponds to a programming module of three to

four thousand instructions. An extension of the system is projected by replacing older computers with newer hardware having strong storage facilities. G.G.

N71-37765# Naval Air Systems Command, Washington, D.C.
ADVANCED AVIONIC DIGITAL COMPUTER DEVELOPMENT PROGRAM Progress Report
 Ronald S. Entner 1 Jul. 1971 108 p refs
 (AD-727607; PR-8) Avail: NTIS CSCL 09/2

The report contains the following: Preliminary statement of work for an analytical study to establish the feasibility of a tactical interactive programming facility; Summary sheets of AADC program review; Papers entitled, the programmer as a computer designer; AADC status report; Storage technology and advanced computer architecture; Agenda of the advanced digital technology conference. GRA

N71-37766# Naval Air Systems Command, Washington, D.C.
ADVANCED AVIONIC DIGITAL COMPUTER DEVELOPMENT PROGRAM Progress Report
 Ronald S. Entner 4 Feb. 1971 52 p refs
 (AD-727605; PR-7) Avail: NTIS CSCL 09/2

Contents: AADC bibliography; Preliminary statement of work for a high level programming language development; On software modularity. GRA

N71-37772# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.
CONVERSION OF SEVERAL COMPUTATIONAL ALGORITHMS FOR DECREASING THE LENGTH OF THE WORD FORM AT OF CONTROL COMPUTERS FOR AIRCRAFT
 I. N. Kornet et al 3 Mar. 1971 9 p Transl. into ENGLISH from Samoletost. Tekhn. Vozdush. Flota (USSR), no. 14, 1969 p 21-24
 (AD-727917; FTD-HC-23-865-70) Avail: NTIS CSCL 09/2

The report discusses the transformation of certain computational algorithms to a form convenient for computer adaptation. It is shown that, by reducing an algorithm to a form that makes it possible to obtain the values of a function from its increments, the length of the digital network of the computer can be shortened with a very small accuracy penalty. This is of particular importance in the case of aircraft computers, as it simplifies their structure and reduces the speed requirements. Author (GRA)

N71-37774# Royal Aircraft Establishment, Farnborough (England).

TUT-3: A COMPUTER PROGRAM FOR SIMULATING THE ATTACK OF LOW FLYING AIRCRAFT BY ANTI-AIRCRAFT MISSILES [MASKINPROGRAM FOER SIMULERING AV LV-ROBOT MOT LAGT FLYGANDE FLYPAN]

J. Palme et al May 1971 17 p refs Transl. into ENGLISH from FOA-P rept., C 8188-13, 1968
 (RAE-Lib-Trans-1578) Avail: NTIS

Intervisibility distances are distances along the aircraft's flight course where there exists alternately a line of sight and no line of sight. The means by which these distances are obtained are described in a separate report. The computer program to be described in this paper uses these intervisibility distances, obtaining them either from magnetic tape, or alternately generating them from a built in Monte Carlo type subroutine. TUT-3 computer program simulates an anti-aircraft defence with the aircraft flying along a course divided into intervisibility distance. Results are given in the form of average number of engagements per shot. In the simulation, the aircraft is assumed to be flying at constant speed along a straight-line course. The missile is assumed to fly on an intercept path, i.e. towards a point ahead of the aircraft. The missile acceleration can if necessary be varied

in the time of flight. The time for a relaunch after an interception, or after a line of sight interruption may be fixed as a constant or as a probability with some time distribution.

Author

N71-37792# Westinghouse Research Labs., Pittsburgh, Pa. Astronuclear Lab.

HIGH TEMPERATURE ELECTRONICS Final Technical Report, 11 Nov. 1969 - 15 May 1971

R. B. Campbell, H. S. Berman, W. D. Loftus, and C. E. Hardies
Jul. 1971 80 p refs

(Contract F33615-70-C-1053)

(AD-727761; AFAPL-TR-71-46) Avail: NTIS CSCL 09/5

The fabrication of a silicon carbide (SiC) junction field effect transistor (J-FET) was shown practicable. Several amplifier designs were breadboarded with silicon devices to study the required parameters. A simplified building block amplifier was constructed and tested.

Author (GRA)

N71-37820# Federal Aviation Administration, Washington, D.C.
MEASUREMENT OF RUNWAY FRICTION Minutes of Meeting

15 Apr. 1971 189 p refs Conf. held in Washington, D. C., 2-3 Feb. 1971

(FS-160-65-68-2) Avail: NTIS

Four basic problems associated with wet, icy, and slush or snow covered runways were identified as aircraft stopping distance, aircraft directional control in a crosswind, engine ingestion effects, and slush drag effects. The first two of these problems were treated in detail. Nine influences on aircraft stopping distance and seven influences on directional control were listed and the effects of each were discussed. Statistics were presented on veer-off and overrun accidents for the 1967 to 1969 period. Traction test data were presented to illustrate the effect of rubber deposits on slipperiness of normal, grooved, and sealed runways. The proceedings are summarized and the minutes of the discussion session are included.

J.G.M.

N71-37821# Naval Ordnance Lab., White Oak, Md.
NOL HYPERVELOCITY WIND TUNNEL. REPORT NO. 2: NOZZLE DESIGN

Walter J. Glowacki 30 Apr. 1971 129 p refs

(AD-727591; NOLTR-71-6; Rept-2) Avail: NTIS CSCL 14/2

The NOL hypervelocity wind tunnel will provide a high Reynolds number turbulent flow simulation in the Mach number range 10 to 20. This facility, much needed for large-scale testing of hypersonic vehicles, will be operational late in 1972. This report presents the detailed procedure used to design three nozzles for the facility. Pressure and temperature effects on the thermodynamic properties of nitrogen are taken into account in both the inviscid core and the boundary layer calculations. The supersonic portion of the inviscid core is calculated by the method of characteristics and the subsonic portion is approximated as a one-dimensional flow. The boundary layer calculation procedure is based on an integral moment of momentum equation and is valid for thick as well as thin boundary layers.

GRA

N71-37823*# National Aeronautics and Space Administration, Flight Research Center, Edwards, Calif.

VALIDATION OF A GENERAL PURPOSE AIRBORNE SIMULATOR FOR SIMULATION OF LARGE TRANSPORT AIRCRAFT HANDLING QUALITIES

Kenneth J. Szalai Washington Oct. 1971 73 p refs

(NASA-TN-D-6431; H-591) Avail: NTIS CSCL 148

A flight simulation program was conducted to validate the general purpose airborne simulator (GPAS) for handling-qualities studies of large transport aircraft in cruise. Pilots compared flying qualities of the XB-70-1 with those simulated on the GPAS during consecutive flights of the two vehicles. In addition, various handling-qualities parameters and time histories for the XB-70 and the airborne simulator were compared to assess

simulator fidelity. The GPAS was shown to be capable of accurate and realistic simulation of the XB-70 at two flight conditions (Mach 1.2 at 12,200 meters (40,000 feet) altitude and Mach 2.35 at 16,800 meters (55,000 feet) altitude). In-flight changes to the programed model were required to obtain a satisfactory simulation from the pilot's point of view. In most instances, these changes were necessary to improve model representation of the XB-70 rather than to correct for possible simulator-introduced distortions.

Author

N71-37824# Federal Aviation Administration, Washington, D.C.
NATIONAL TRANSPORTATION PLANNING MANUAL (1970 - 1990). MANUAL D: AIRPORTS AND OTHER INTERCITY TERMINALS

Apr. 1971 121 p

(OMB-04-S71002) Avail: NTIS

General instructions relating this manual to the 1972 National Transportation Needs study are presented as well as instructions for the preparation of information related to airports and other intercity terminals. Needs estimates for 1970 to 1990 and capital improvement programs for fiscal years 1974 to 1978 and 1979 to 1990 are discussed. The development of airport needs estimates, capital improvement programs, and reporting requirements are included. Terminal issues and the development of needs estimates and capital improvement programs for other intercity terminals are also covered.

Author

N71-37826# National Aviation Facilities Experimental Center, Atlantic City, N.J.

DALLAS-FORT WORTH TOWER CAB DESIGN EVALUATION Final Report, Jul. 1970 - May 1971

J. Roy Bradley, Jr. Nov. 1971 19 p

(FAA-NA-71-37; FAA-RD-71-77) Avail: NTIS

The design concept and operational feasibility of an undecagon (11-sided) control tower cab for the new Dallas-Fort Worth Regional Airport are discussed. A report was made on position and equipment arrangements, tower console design, and operational factors resulting from the study. A full-scale plywood mockup of the tower cab and consoles was constructed. After installation of equipments and displays, a 30-day evaluation was conducted. Results indicate that the design concept of the 11-sided tower cab for the Dallas-Fort Worth Regional Airport is valid and that it is highly feasible from an operational aspect. Position arrangements and the console design are considered excellent. An improved equipment arrangement was developed and recommended.

Author

N71-37827# Boeing Scientific Research Labs., Seattle, Wash. Aerospace Group.

DESIGN AND OPERATION OF THE BSRL WATER TUNNEL

John N. Olsen Sep. 1971 28 p refs

(D180-14130-1) Avail: NTIS

The design, construction, and performance of a water tunnel for two-dimensional testing of pitching airfoils is described. The test section is 4.5 inches x 12 inches x 36 inches long. The tunnel can run at 40 feet/second, but cavitation may even occur at lower speeds depending on the pressure coefficients on the model. A practical limit for say an NACA 0012 airfoil is 20 feet/second if cavitation is to be avoided. The velocity profile is uniform within at least 1% and the turbulence level is below .15%.

Author

N71-37835*# Hamilton Standard, Windsor Locks, Conn.
DEVELOPMENT OF ATMOSPHERIC GUST CRITERIA FOR SUPERSONIC INLET DESIGN Final Report

Frank W. Barry Dec. 1968 205 p refs

(Contract NAS2-4515)

(NASA-CR-114372; HSER-5195) Avail: NTIS CSCL 20D

A method was developed for relating transient tolerances in inlet throat Mach number and shock position to the frequency of unstarts of a supersonic inlet due to atmospheric disturbances.

Data on high-altitude atmospheric turbulence was collected and evaluated. A general linear analytical model was developed to compute changes in inlet throat Mach number and shock position. The relation of inlet transient tolerances to propulsion system performance is presented. A stepwise procedure for relating frequency of inlet unstarts to transient tolerances is given and applied to a representative example. Author

N71-37836*# Pratt and Whitney Aircraft, East Hartford, Conn. **SINGLE STAGE EVALUATION OF HIGHLY LOADED HIGH MACH NUMBER COMPRESSOR STAGES. 4: DATA AND PERFORMANCE OF HUB SLIT SUCTION STATOR** G. D. Burger and G. Bogardus 10 Nov. 1971 133 p refs (Contract NAS3-10482) (NASA-CR-120802; PWA-4186) Avail: NTIS CSCL 20D

A single stage compressor with a rotor tip speed of 1600 fps and 0.5 hub/tip ratio was used to demonstrate the effects of boundary layer suction through slits at the intersection of the stator suction surface and the hub wall. No efficiency benefit was obtained at design speed; 1.5 percentage points improvement was obtained at part speed. Maximum design speed stage efficiency of 82.7 percent was obtained at a pressure ratio of 1.935. Accounting for rotor work on the flow bled through the stator hub slit decreases this efficiency 0.5 percent. Author

N71-37850# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div. **A WEAKLY SUPERSONIC FLOW AROUND THIN BODIES** S. V. Falkovich et al 12 Mar. 1971 21 p refs Transl. into ENGLISH from Transvukovye Tech. Gaza (USSR), 1964 p 9-21 (AD-727854; FTD-HT-23-31-71) Avail: NTIS CSCL 20/4

A two-dimensional steady gas flow past a thin symmetrical body is studied under the assumption that the mach number at infinity is close to unity. The continuous nature of shock-wave formation during transition from sonic to supersonic flow is established mathematically. This solution, also explains the 'bursts' in the values of the current function calculated by Vincenti and Wagoner. As a result of the numerical calculations, the first 20 coefficients are found and the transition to plane (x,y) is made. GRA

N71-37851# Imperial Coll. of Science and Technology, London (England). Dept. of Aeronautics. **USE OF A REFINED BOUNDARY-LAYER CALCULATION METHOD TO CALIBRATE A SIMPLE ONE** P. Bradshaw Oct. 1971 12 p refs (IC/71/23) Avail: NTIS

A technique is described which enables refined standards of accuracy to be obtained from a simple boundary layer calculation method, over a small range of pressure distributions near the one used for calibration. The technique can be applied to multi-run problems such as parametric studies or the iterative calculation of aerofoil pressure distribution with allowance for viscous effects. Author

N71-37853# Aircraft Research Association, Ltd., Bedford (England). **SOME MEASUREMENTS OF POROUS TUNNEL WALL INTERFERENCE IN THE ARA 8 FOOT BY 9 FOOT TUNNEL** E. C. Carter Sep. 1971 28 p refs (ARA-19) Avail: NTIS

Results are presented of measurements made in a 8 ft x 9 ft transonic tunnel to determine the constraint and blockage corrections at subsonic Mach numbers. Corrections were determined initially for a transport type of model at Mach numbers up to 0.88. These indicate the existence of a simple upwash constraint factor invariant with Mach number and equal

to 50% of the open tunnel value, a zero blockage correction, and a blockage buoyancy correction equal to 50% of the theoretical value calculated for the wall characteristics giving zero blockage. This latter 50% factor is associated with the graded porosity opposite the forward part of the model. These corrections were applied to results in the porous section obtained on a very different type of model - a large canard configuration with low drag-rise Mach number. These corrected results were compared with tests on the model in the tunnel with closed walls. Agreement in lift and drag is generally very good. Author

N71-37862*# Michigan Univ., Ann Arbor. Infrared and Optics Lab. **WATER-DEPTH MEASUREMENT BY WAVE REFRACTION AND MULTISPECTRAL TECHNIQUES** Technical Report, 1 Jul. 1969 - 30 Sep. 1970 W. L. Brown, F. C. Polcyn, A. N. Sellman, and S. R. Stewart Aug. 1971 49 p refs (Contract NAS9-9784) (NASA-CR-123194; WRL-31850-31-T) Avail: NTIS CSCL 20F

Two remote sensing techniques which measure water depth were investigated. One technique involves photographic observation of wave refraction phenomena and of wave length changes measured in Fourier transforms. The transforms were obtained by optical processing. Test sites near Puerto Rico and Barbadoes were used to study wave changes which occur near nonuniform bottom profiles of shallow reefs. The second technique makes use of multispectral scanner to measure radiation reflected from the ocean floor. Measurement occurs in several spectral intervals in the visible region. The depth is calculated when the ratio of signals in pairs of spectral bands is taken. The technique was tested for sloping sandy beach gradients, as well as for coral reef areas which contained a variety of materials of different reflectances. Examples of computer-generated depth maps are included. Author

N71-37896# Deutsche Lufthansa Aktiengesellschaft, Hamburg (West Germany). **PROBLEMS OF AIR NAVIGATION** c21 J. P. Hach /n Max-Planck-Inst. fuer Aeronomie Future Appl. of Satellite Beacon Expt. Nov. 1970 6 p

Avail: NTIS HC \$6.00/MF \$0.95

Problems in air navigation from the airline operations point of view are presented. Aids to final approach and landing, short distance aids, and long distance aids are also discussed. ESRO

N71-37922# Nova Univ., Dania, Fla. Physical Oceanographic Lab. **DEVELOPMENT OF AN OPERATIONAL SYSTEM FOR MEASURING OCEAN SURFACE CURRENT FROM AIRCRAFT** Final Report William S. Richardson May 1971 17 p (Contract DOT-CG-10737-A) (AD-726568) Avail: NTIS CSCL 08/3

The report contains the development of an operational system which permits surface current measurements (and, incidentally, volume transport measurements per unit width) to be made in the ocean from aircraft. It is assumed that this method will have applications to the Coast Guard's efforts in search and rescue and in pollution monitoring. An inexpensive, expendable probe is launched from the airplane and, on contacting the sea surface, a dye package separates and floats on the surface. The remainder of the probe is carried to the bottom by its weight and from its fixed location on the bottom releases two floats at separate, predetermined times. The floats return to the surface under their own buoyancy. At the surface the three parts (surface marker and two floats) emit florescent dye which can be photographed or otherwise relatively positioned. Author (GRA)

N71-37924# Florida Atlantic Univ., Boca Raton. Remote Sensing and Interpretation Lab. **TIDEWATER SHORELINES IN BROWARD AND PALM**

BEACH COUNTIES, FLORIDA: AN ANALYSIS OF CHARACTERISTICS AND CHANGES INTERPRETED FROM COLOR, COLOR INFRARED AND THERMAL AERIAL IMAGERY

L. Alan Eyre Jun. 1971 30 p ref
(Contracts N00014-67-A-0320-0003; Nonr-4761(00))
(AD-727630; TR-11) Avail: NTIS CSCL 14/5

In South Florida, pressures to extend and modify tidewater shorelines are very strong. These modifications include canal excavations, dredging and filling, bulkheading, erection of sea walls, and dock construction. Access to tidewater is much coveted and competition for such access is keen. Using color infrared aerial photography flown at 5000 ft., eight types of tidal shorelines are distinguished in a portion of NASA Test Site 164. Comparisons are made with other imagery, including high-altitude (60,000 ft.) photography and that from the Reconafax and Bendix Thermal Infrared sensor systems; and the degree to which these shoreline types are observable is noted. Some changes over time are also indicated, in particular the extent of additional modifications during a period of approximately one year.

Author (GRA)

N71-37928* National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

SOME CONSIDERATIONS IN THE SELECTION OF AIRCRAFT FOR EARTH RESOURCE OBSERVATIONS

Roger D. Arno and Jerry M. Deerwester Washington Oct. 1971 18 p refs

(NASA-TM-X-2418; A-4046) Avail: NTIS CSCL 08G

The logistics problems and cost aspects of earth resource surveys using various types of aircraft are discussed. Eight categories of aircraft (from piston engine to large jet) as well as commercial air carriers are examined on the basis of quantity needed, coverage afforded, and annual program cost. Independent parameters in the analysis include (1) the requirements of a typical group of resource features, (2) number and location of bases, (3) cloud cover uncertainty, and (4) aircraft cost and the parametric influence of payload associated costs. The results obtained in this analysis show an advantage in cost and rate of coverage for a special fleet of twin engine turbojets over all other aircraft options. Special fleets of turboprop, large turbojet, piston engine planes and commercial air carriers were found to be inferior, principally because of the greater number of aircraft required to achieve comparable coverage. To illustrate, to cover 45 to 95 percent of the resources considered about every two weeks, the special fleet of twin-engine jets requires 6 to 30 aircraft, while the commercial air carrier numbers range from 36 to 180 for coverage ranging from 40 to 80 percent. Annual program operating costs would appear to run between \$2 and \$10 million plus the costs associated with payload and data handling. Total costs might average between \$10 and \$100 million annually.

Author

N71-38013* South Dakota School of Mines and Technology. Rapid City. Inst. of Atmospheric Sciences.

COMPARISON OF INFORMATION CONTENT OF SPACE PHOTOGRAPHY AND LOW ALTITUDE AERIAL PHOTOGRAPHY Final Report

Lewis H. Shapiro Jun. 1971 47 p refs
(Contract Di-14-08-001-12682)

(IR-USGS-229; USGS-DO-71-012) Avail: NTIS

Three problems are discussed. First it is shown, through the use of information theory, that the capability of space photography to transmit information compares favorably to that of conventional aerial photography. Secondly, results indicate that there is a significant overlap between the size of the smallest features which can be identified on the space photography and the larger features which can be identified on low altitude photography at scales of less than 1:15,000. Last is the determination of the geologic information content of space and conventional aerial photography.

Author

N71-38022* Pratt and Whitney Aircraft, East Hartford, Conn.
DEVELOPMENT OF MAINSHAFT SEALS FOR ADVANCED

AIR BREATHING PROPULSION SYSTEMS, PHASE 3 Final Report

V. P. Povinelli and A. H. McKibbin 25 Jul. 1971 111 p refs
(Contract NAS3-7609)

(NASA-CR-72987; PWA-4263) Avail: NTIS CSCL 11A

Five self-acting gas-film face seals for advanced gas-turbine engines were analyzed and four were tested. All five seal designs incorporated shrouded Rayleigh step lift pads at the primary seal surfaces to provide the gas-film lubrication. The wide pad and revised narrow pad seal were successfully operated at seal sliding speeds up to 500 ft/sec (17,300 rpm), pressure differential up to 300 psi, and gas temperatures up to 1200 F. The air leakages for both seals were in good agreement with calculated values and were about 1/10 of leakages expected from labyrinth seals at comparable conditions. The operating range of the narrow pad seal was limited due to insufficient film thickness. The ceramic seal suffered damage due to chipping during testing.

Author

N71-38032* Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

DESIGN OF COMPRESSORS: AERODYNAMIC CALCULATIONS

A. N. Sherstyuk 26 May 1971 337 p refs Transl. into ENGLISH from the book "Osevyte Kompressory: Aerodinamiches-kii Raschet" 1955 p 1-250

(AD-727191; FTD-HC-23-781-70) Avail: NTIS CSCL 13/7

The book sets forth the foundations of the theory and design of axial compressors. Particular attention is devoted to compressors of stationary installations. The book is intended for engineers who design axial compressors. In addition, the book can be used by students in higher technical training institutions.

GRA

N71-38132* Dow Chemical Co., Midland, Mich.

LATEX MODIFICATION OF FAST-FIX C-1 CEMENT FOR THE RAPID REPAIR OF BOMB-DAMAGED RUNWAYS Report for 16 Apr. 1970 - 12 May 1971

R. Eash and G. M. Hart May 1971 204 p refs

(Contract DACA39-70-C-0022)

(AD-727728; AEWES-TR-C-71-1) Avail: NTIS CSCL 11/3

The report consists, essentially, of two parts: a state-of-the-art review and laboratory testing of the effects of adding two Dow polymeric latexes to Fast-Fix C-1. The state-of-the-art review covers several basic studies in which many materials, both organic and inorganic, were investigated. The study was then focused on the study of fast-setting inorganic cements and methods to obtain high strength concrete, silicate concrete, and cementitious ceramic materials, are also covered. The state-of-the-art review also has a section indicating areas in which fast-setting cements can serve and the requirements placed on this service. Topics covered are runway design, pavement requirements, pavement evaluation, surface repair, and cold weather construction. In the lab study, two polymeric latexes, Dow Latex 460 and Dow Latex 464, were incorporated at selected concentrations in Fast-Fix C-1 mortars. Tests were conducted to determine freeze-thaw durability, tensile strength, compressive strength, flexural strength, and shear bond. All latex concentrations improved bond strength and freeze-thaw durability and decreased 24-hour water absorption. All concentrations tended to retard set and early strength gain. Low concentrations (4%) of Latex 464 produced a modest improvement in compressive and flexural strengths, but no change in the elastic modulus.

Author (GRA)

N71-38133* Southern Research Inst., Birmingham, Ala.

DEVELOPMENT OF RAIN-EROSION-RESISTANT COATINGS FOR HIGH SPEED AIRCRAFT Final Report, 15 Jan. 1970 - 14 Jan. 1971

A. C. Tanquary, Robert E. Burks, Jr., and M. Virginia Jackson Mar. 1971 41 p refs

(Contract N00019-70-C-0330)

(AD-727750; A-579-2406-6) Avail: NTIS CSCL 11/3

A polymer prepared as a prospective rain-erosion-resistant coating from hexafluoroacetone, propylene, and bis(dimethylamino)-dimethylsilane had a glass-transition temperature of -50C, and it had good resistance to heat and aliphatic or aromatic hydrocarbons. However, it was not successfully cured to an elastomer. A polymer prepared from 1,4-bis(dimethylhydroxysilyl) benzene and bis(dimethylamino)dimethylsilane had a glass-transition temperature of -62C, excellent thermal stability, but less resistance to hydrocarbons than the fluoropolymer. It was cured to a tough elastomer at room temperature. The coating obtained when this elastomer was sprayed onto air-foil test specimens was found to have much greater resistance to simulated rain erosion at ordinary temperatures than a silicone coating and slightly less than neoprene. It suffered no degradation on being heated 4 hours at 250C, as indicated by sand-erosion tests.

Author (GRA)

N71-38149# National Aviation Facilities Experimental Center, Atlantic City, N.J.

SMALL SCALE FIRE TESTS OF HIGH TEMPERATURE CABIN PRESSURE SEALANT AND INSULATING MATERIALS Final Report, 1970 - 1971

Constantine P. Sarkos Nov. 1971 37 p refs
(FAA-NA-71-22; FAA-RD-71-67) Avail: NTIS

A 2 sq ft stainless steel panel was constructed with the same dimensions between the fuselage skin and cabin wall as those of a titanium fuselage previously exposed to an external fuel fire. The panel was subjected to a 2 gal/hr kerosene burner which simulates the heat flux and temperature from a large JP-4 fuel fire. Testing of the panel utilizing the same materials found in the titanium fuselage caused phenomena and temperature distribution very similar to those observed during the full-scale test, thus giving credence to the test method as being representative of what would occur to a titanium or stainless-steel aircraft during a post-crash fire. Two commercially available high-temperature insulations tested without any sealant maintained survivable conditions for at least 15 minutes. Viton, a hydrofluorocarbon elastomer, was found not to flame or cause a flash-fire under conditions which silicone did. The propensity of the formation of a flash-fire was strongly influenced by the compactness of the insulation and the presence of any voids or passageways between the fuselage skin and cabin wall interface.

Author

N71-38210# Royal Aircraft Establishment, Farnborough (England).

SEVENTH MEETING OF THE NAT SYSTEMS PLANNING (SPANISH DELEGATION)
Apr. 1971 88 p Transl. into ENGLISH from the Spanish report (RAE-LIB-TRANS-1580) Avail: NTIS

Details are given of the aircraft traffic over the North Atlantic for the years 1966 to 1969. An estimation of the minimum time routes to North America is made together with a comparative study of flights at various Mach numbers and below level 310. Penalties are given for deviations of 2 deg in latitude from these minimum time routes. In a mathematical study, the numbers of tracks necessary for the period 1970 to 1980 are worked out, leading to work on track compensation and the establishment of the NAT structure for each characteristic meteorological situation, with particular emphasis on an equitable distribution of penalties between users from various geographical regions.

Author

N71-38211# National Bureau of Standards, Washington, D.C. Signal Lighting Group.

DEVELOPMENT, TESTING, AND EVALUATION OF VISUAL LANDING AIDS Consolidated Progress Report, 1 Jan. - 31 Mar. 1971

1 Jul. 1971 12 p refs Sponsored by the Navy and FAA (NBS-10604) Avail: NTIS

Continuing research of visual landing aids is reported and includes the results of studies on: (1) visibility meters and their

application, and (2) airfield lighting and marking. The operational performance of two models of backscatter visibility meters is described, and modifications made to enhance their performance are discussed. Another research effort involved an analysis of sky luminance measurements as a consideration of factors affecting the visual range of runway lights. An investigation was made to determine the performance characteristics of selected organic coatings for use on panels of control tower consoles. The coatings systems were tested for abrasion resistance, adhesion, and stain resistance. Tables are presented of the results obtained. In another study, the performance of a narrow-beam deck floodlight using a 400-watt high pressure sodium lamp was evaluated. The characteristics of the lamp as compared to those of incandescent fixtures is discussed.

D.L.G.

N71-38213# Federal Aviation Administration, Washington, D.C. Office of Aviation Economics.

FAA PROGRAM EFFECTIVENESS AND FACILITY CRITERIA. AN ANALYSIS OF THE COSTS AND EFFECTIVENESS OF AIR TRAFFIC CONTROL TOWERS

James Gansle Apr. 1971 92 p

Avail: NTIS

Analytical data was developed on the effectiveness of VFR control towers. The results of a research effort which was conducted as a special issue study are presented. The analytical substance is included, as well as summaries of two interim reports prepared earlier and a summary of a draft report by the National Bureau of Standards. The major finding, based on statistical analysis, is that for airports with low and medium amounts of annual traffic, those airports with VFR control towers have a significantly lesser rate of aircraft accidents than airports without towers. Another finding indicates that VFR towers can help to reduce aircraft time in approach and landing at airports.

Author

N71-38214# Federal Aviation Administration, Washington, D.C. Systems Research and Development Service.

SRDS PROGRAM: GOALS, ACHIEVEMENTS, TRENDS, 1 APRIL 1970 - 31 MARCH 1971

31 Mar. 1971 159 p refs

Avail: NTIS

The material is presented in separate chapters for each of the SRDS technical development divisions: Air Traffic Control, Communications, Navigation, Frequency Management, Systems Analysis, and Aircraft. Subprograms are listed in sequential numeric order along with key descriptive words on each effort.

Author

N71-38215 Air Traffic Control Evaluation Unit, Bournemouth (England).

AN EVALUATION OF THE AUTOMATIC FLIGHT PROGRESS STRIP CUTTER AND LOADER

A. E. Windebank and T. Anderson Jun. 1971 17 p

(ACTEU-330) Avail: Issuing Activity

The results are presented of performance evaluation tests conducted on the strip cutter and loader machine to determine its acceptability for use at air traffic control centers. The function of the machine is to cut and load flight progress strips in page form, and it was designed to load into special plastic strip holders which were modified to work with the machine. The evaluation tests consisted of an analysis of the percentage of misloaded strips and strips not loaded in comparison with the total number of loads. In addition, cutter wear and the noise level of the machine were assessed. Based on the results, the machine was judged to be acceptable for operational use.

D.L.G.

N71-38277# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

LARGE NUCLEAR-POWERED SUBSONIC AIRCRAFT FOR TRANSOCEANIC COMMERCE

Frank E. Rom and Charles C. Masser Washington Nov. 1971 47 p refs

(NASA-TM-X-2386; E-6271) Avail: NTIS CSCL 21F

Large subsonic aircraft, greater than 905 metric tons (1000 tons) gross weight, have the potential for hauling transoceanic cargo at rates in the range of \$0.008 to \$0.036 per metric ton-kilometer (\$0.01 to \$0.06/ton-n mi) at speeds of 740 to 925 kilometers per hour (400 to 500 knots). It theoretically would take a fleet of 500 such aircraft to handle 1 percent of the forecast world ocean trade in 1980. For gross weights of 3620 metric tons (4000 tons) the cargo rate would be reduced to less than \$0.012 per metric ton-kilometer (\$0.02/ton mi). It theoretically would take a fleet of over 1000 such aircraft to carry 8 percent of the world transoceanic trade projected for 1980 or 4 percent of the projected trade in 1995. Aircraft with a gross weight of 3620 metric tons (4000 tons) using compact lightweight nuclear reactors show better performance than chemical aircraft for ranges greater than 5565 kilometers (3000 n mi). Nuclear aircraft performance is less sensitive than that of chemical aircraft to the operating and cost assumptions used. Relatively large variations in any of the important assumptions have a relatively small effect on nuclear aircraft performance.

Author

N71-38283*# Hamilton Standard, Windsor Locks, Conn.

RESULTS OF PROP-FAN/STOL WING ACOUSTICS TESTS

T. G. Ganger 29 Jul. 1971 79 p

(Contract NAS1-11019)

(NASA-CR-111956; HSER-5910) Avail: NTIS CSCL 20A

The results of a test conducted to determine the noise characteristics of a STOL wing with externally blown flaps in the vicinity of an aircraft propulsor are summarized. The STOL wing used for these tests was a 0.43 scale model with 60 deg and 0 deg flap capabilities; however, this wing system was not an optimum configuration, nor was it representative of all STOL wing/flap systems. The propulsor used was a low tip speed, high bypass ratio, low pressure ratio, variable pitch prop-fan model. Far field noise data and directional character were determined for a 60 deg and 0 deg flap configuration. In addition, the noise character of the 21 inch diameter prop-fan model without the STOL wing was evaluated.

Author

N71-38530# Dynamic Science, Irvine, Calif.

SUPERSONIC COMBUSTION CHEMISTRY AND MIXING OF HIGH ENERGY DENSITY FUELS RELATED TO ADVANCED AIR-BREATHING ENGINE DESIGN Final Report

Stuart Hersh 30 Apr. 1971 45 p refs

(Contract F44620-70-C-0061)

(AD-727782; SN-209) Avail: NTIS CSCL 21/2

The program is directed towards answering the following question. Given a boron combustible particle of known initial size and composition moving at a high relative velocity in a gaseous medium, how are the combustion behavior and particle dynamics influenced by the particle/gas relative velocity, gas composition, temperature, and pressure anticipated in operational combustors? The role of the shock tube in answering this question is discussed. An 'ideal' experiment is postulated and several possible practical experimental techniques are assessed relative to this standard. To aid in the assessment of the practicality of an experimental technique, a computer program was developed to compute particle trajectories for shock tube flows. Some preliminary experiments aimed at establishing the applicability of a reflected shock technique to the measurement of burning particle drag coefficients were carried out. The results of these experiments yielded very high values of the drag coefficient. At the present time, it is not known if this result was due to the roughness of the particles, static charge effects, the effect of combustion or the preliminary nature of the experiments. In all probability a combination of the above factors is involved.

Author (GRA)

N71-38531# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

AVIATION FUELS, LUBRICANTS AND SPECIAL LIQUIDS

A. F. Aksenov 14 May 1971 367 p refs Transl. into

ENGLISH of the book "Aviatsionnye Topliva, Smazochnye Materialy i Spetsialnye Zhidkosti" Moscow, Izd-vo Transport, 1970 p 1-255

(AD-727199; FTD-MT-24-07-71) Avail: NTIS CSCL 21/4

The report presents the methods of obtaining, the chemical composition of the operational properties, and the methods of controlling the applicable fuels, lubricants, and special liquids. Main attention is paid to the heat of combustion of fuels; to the stability of fuels, oils, of lubricants, and liquids under various operating conditions; to the pumpability of fuels and oils, the corrosion, antiwear, and antiseizing properties. Attention is also paid to fuels for supersonic aviation, promising lubricating materials, including solid lubricants, and promising liquids. The book is intended as a textbook for students of aviation higher educational institutions.

Author (GRA)

N71-38535*# Scientific Translation Service, Santa Barbara, Calif.

REMARKS ON THE PAPER OF M. D. C. WHITLEY (PAPER NO. 13): SOME ASPECTS OF PROPULSION FOR THE AUGMENTOR WING CONCEPT [SUITE A LA COMMUNICATION DE M. D. C. WHITLEY (PAPER NO. 13)]

M. H. Schmitt Washington NASA Oct. 1971 10 p Transl. into ENGLISH from Paper Presented at 38th Meeting of AGARD Propulsion and Energetics Panel, Inlet and Nozzles for Aerospace Engines, Sep. 1971 p 1-8

(Contract NASW-2035)

(NASA-TT-F-14005) Avail: NTIS CSCL 21E

A summary of the work in Europe on dilution systems is given which falls into the category of the propulsive wing. The first application was the aircraft ARADO 232 in Germany in 1943. After that, the ONERA in France took on the development of a combined suction and blowing system, beginning with its inception in 1945. Finally, the BERTIN Society in 1959 proposed the false wing system. New techniques of dilution, which have become available, seem to indicate that considerable improvements can be made.

Author

N71-38538# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

DESIGN AND OPERATION OF AIRCRAFT GAS TURBINE ENGINES

N. A. Sherygin et al 27 May 1971 484 p refs Transl. into ENGLISH of the book "Konstruktsiya i Eksploatatsiya Aviatsionnykh Gazoturbinnnykh Dvigateli" Moscow, 1969 p 1-371

(AD-727188; FTD-HC-23-519-70) Avail: NTIS HC \$6.00/MF \$0.95 CSCL 21/5

The textbook presents an analysis of the designs of modern gas turbine engines. It discusses forces acting on the essential units, and their dependence on the operating regimes of the engine and the flight conditions. The construction and the operation of the engine components and parts are described. Methods of calculating safety factors for the most heavily loaded parts are given. Problems of vibration and methods of computing the vibrational load factors for engines are discussed. The operation and construction of the lubrication, fuel supply, start-up, and automatic engine control systems are examined. Brief data are given on the servicing of the engines when in operation.

Author (GRA)

N71-38541# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

GAS TURBINE ENGINES FOR HELICOPTERS

M. M. Maslennikov et al 24 Jun. 1971 488 p refs Transl. into ENGLISH of the publ. "Gazoturbinnnyye Dvigateli dlya Vertoletov" Moscow, Mashinost., 1969 p 1-380

(AD-727959; FTD-MT-24-141-70) Avail: NTIS HC \$6.00/MF \$0.95 CSCL 21/5

The first part, basically, elucidates questions connected with the use of gas turbine engines with a free power turbine for helicopters: the characteristics of thermal calculation and, the

calculation of characteristics, conditions of synchronizing the operation of the engine and the rotor, the means of adjustment, and the design. Briefly, mainly for purposes of comparison with engines with a free turbine, single shaft engines are also considered. The operating conditions of gas turbine engines on helicopters in service are elucidated. In the second part, questions are considered regarding the use of a jet drive of the rotor of a helicopter both by means of turbojet engines mounted on the blade tips and also by means of turbojet engines mounted on the blade tips and also by means of supplying compressed gas to jet nozzles on the blade tips. This book is intended for technical engineering workers who are engaged in designing and operation of helicopters and helicopter engines. It may also be useful for teachers and students of the respective specialities in aviation technical schools. Author (GRA)

N71-38542# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.
COMBUSTION CHAMBERS OF GAS TURBINE ENGINES
 Yu. M. Pchelkin 6 May 1971 274 p refs Transl. into ENGLISH of the publ. "Kamery Sgoraniya Gazoturbinnikh Dvigatelye" Moscow, Mashinostro, 1967 p 1-207
 (AD-727960; FTD-MT-24-306-70) Avail: NTIS CSCL 21/2

The report is a textbook for students studying power-engineering and machine building and it may also be useful to technical and engineering personnel and to advanced aeronautical engineering students. The book deals with gas-turbine fuels, fuel production, processing properties, and characteristics, combustion, combustion theory and products, combustion-chamber design, construction, and operation. GRA

N71-38552# California Univ., Berkeley. Lawrence Radiation Lab.
AN EXPERIMENTAL MEASUREMENT OF GALACTIC COSMIC RADIATION DOSE IN CONVENTIONAL AIRCRAFT BETWEEN SAN FRANCISCO AND LONDON COMPARED TO THEORETICAL VALUES FOR CONVENTIONAL AND SUPERSONIC AIRCRAFT
 Roger Wallace and Michael F. Boyer 25 Feb. 1971 23 p refs Presented at the Symp. on Natural and Manmade Radiation in Space, Las Vegas, Nev., 1 Mar. 1971
 (Contract W-7405-eng-48)
 (UCRL-20209; Conf-710304-11) Avail: NTIS

By utilizing beta-gamma and NTA photographic emulsions and thermoluminescent dosimeters, measurements of radiation dose were made in conventional jet aircraft. These direct measurements were in fair agreement with computations made using a program that takes into consideration both basic cosmic ray atmospheric physics and the focusing effect of the earth's magnetic field. These measurements also agreed with those made at supersonic jet aircraft altitudes in RB-57 aircraft. It was concluded that both experiments and theory show that the doses received at conventional jet aircraft altitudes are slightly higher than those encountered in supersonic flights at much higher altitudes, when the long time of exposure at the lower altitudes is taken into consideration. Author (NSA)

N71-38626# National Research Council of Canada, Ottawa (Ontario).
QUARTERLY BULLETIN OF THE DIVISION OF MECHANICAL ENGINEERING AND THE NATIONAL AERONAUTICAL ESTABLISHMENT, 1 APRIL - 30 JUNE 1971
 Jun. 1971 113 p refs
 (DME/NAE-1971(2)) Avail: NTIS

CONTENTS:

1. LOW SPEED AERODYNAMICS AND THE SCIENCE COUNCIL'S NATIONAL GOALS R. J. Templin (Natl. Aeron. Estab., Ottawa, Ontario) p 1-20 refs
2. EXPERIMENTS WITH AN ON-LINE PICTURE LANGUAGE T. Kasvand p 21-56 refs
3. THE UNBOUNDED TURBULENT JET AS A TRANSDUCER

ELEMENT J. W. Tanney (Natl. Aeron. Estab., Ottawa, Ontario) p 57-87 refs

4. CURRENT PROJECTS p 89-111

N71-38627# National Aeronautical Establishment, Ottawa (Ontario). Low Speed Aerodynamics Lab.
LOW SPEED AERODYNAMICS AND THE SCIENCE COUNCIL'S NATIONAL GOALS c01
 R. J. Templin In NRC of Can. Quart. Bull. of the Div. of Mech. Eng. and the Natl. Aeron. Estab., 1 Apr. - 30 Jun. 1971 Jun. 1971 p 1-20 refs
 Avail: NTIS

A simple version of the so-called relevance tree forecasting method was used to relate the Science Council's list of National Goals to relevant research gaps in low speed aerodynamics. The exercise was performed mainly out of curiosity, partly as to the nature of the method itself, and partly as to the results it can produce. The numerical results of the relevance marking system used appear to be sensitive to individual judgment, and may merely indicate which bandwagon the scorer prefers. On the other hand, the relevance tree provides a simple graphic display of the possible connections between specific research areas, and broad national goals. Author

N71-38668# Chrysler Corp., New Orleans, La. Space Div.
SPACE SHUTTLE: AERODYNAMIC HEATING TO THE GRUMMAN SPACE SHUTTLE ORBITERS (ROS-NB1 AND ROS-WB1) AT MACH NUMBER 8.0
 A. D'Errico (Grumman Aerospace Corp.) Jul. 1971 78 p
 (Contract NAS8-4016)
 (NASA-CR-119984; DMS-DR-1154) Avail: NTIS CSCL 22B

The results are presented for a heat transfer wind tunnel test conducted on 0.0067 scale models utilizing the phase-change paint technique. Two delta wing orbiter configurations were investigated. One configuration was tested with a ventral fin on selected runs. Data were obtained for an angle of attack range from 0 to 50 degrees. The test was conducted in a hypersonic wind tunnel at a Mach number of 8.0 and nominal Reynolds numbers per foot of 5 x 10 to the fifth power, 7 x 10 to the fifth power, and 2.0 x 10 to the sixth power. Author

N71-38734# AirResearch Mfg. Co., Los Angeles, Calif.
LOW-CYCLE FATIGUE EVALUATION FOR REGENERATIVELY COOLED PANELS
 C. E. Richard, J. D. Duncan, C. Demogenes, and W. G. Flieder Washington NASA Oct. 1971 72 p refs
 (Contract NAS1-50024)
 (NASA-CR-1884; Rept-68-4313) Avail: NTIS CSCL 20K

Results of low cycle fatigue evaluations at room and elevated temperatures of Inconel 625 and Hastelloy X, brazed, plate-fin sandwiches suitable for regeneratively cooled structural panel applications are presented and compared with available theory. Also presented are results of supplemental parent metal tensile and fatigue tests. Author

N71-38758# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.
AERODYNAMIC HEATING AT MACH 8 OF ATTACHED INFLATABLE DECELERATOR CONFIGURATIONS
 Theodore R. Creel, Jr. and Robert Miserentino Washington Oct. 1971 78 p refs
 (NASA-TM-X-2355; L-7864) Avail: NTIS CSCL 20M

Heat transfer coefficients on four attached inflatable decelerator (AID) configurations were obtained in a Mach 8 variable-density tunnel at angles of attack of 0, 5, and 10 deg for a Reynolds number range of 220,000 to 1,230,000 in air. A fusible-temperature-indicator technique which employs a temperature-sensitive material that changes from an opaque solid to a clear liquid at a known temperature was used to obtain these coefficients. The results of this investigation indicate

that the heat transfer coefficients on the ram-air inlets and the burble fence are up to five times larger than the coefficients at identical locations on a smooth AID body. Moving the ram-air inlets rearward reduces the heating rates immediately behind the aft row of inlets. This placement of the inlets also increases the heating rate on the burble fence. Increasing Reynolds number resulted in an increase in heat transfer coefficient primarily on the burble fence. Author

N71-38760# Curtiss-Wright Corp., Wood-Ridge, N.J.
**EXPLORATORY DEVELOPMENT PROGRAM ON THE
 ROTATING COMBUSTION ENGINE USING THE RC1-90
 TEST RIG**

C. Jones, H. Lamping, and H. R. Corwin Jan. 1971 15 p refs
 (Contract N00019-70-C-0371)
 (AD-727745; CW-WR-70-052.S) Avail: NTIS CSCL 21/2

The report covers additional testing of the stratified charge RC-90 engine to explore its exhaust emission characteristics plus a brief evaluation of the Texaco ignition system. Author (GRA)

N71-38767*# National Aeronautics and Space Administration.
 Lewis Research Center, Cleveland, Ohio.

**PERFORMANCE OF A MODULAR COMBUSTOR DE-
 SIGN FOR A VTOL TIP-TURBINE LIFT FAN**

Nicholas R. Marchionna Washington Nov. 1971 18 p refs
 (NASA-TN-D-6542; E-6441) Avail: NTIS CSCL 20M

An array of 16 swirl-can modules was tested with liquid ASTM A-1 fuel in a 10.75-in. diameter circular duct at conditions simulating the design operating point of a combustor for a 10,000-lbf thrust VTOL lift engine with an inlet air temperature of 600 F, an inlet total pressure of 111 psia, and a reference velocity of 165 ft/sec. Performance of flat plate and conical flame holders were compared for combustion efficiency, total pressure loss, and pattern factor. At the design operating point requiring an exhaust gas temperature of 1440 F, combustion efficiency was close to 100 percent for all models tested. The flat plate flame holders gave better exhaust gas temperature profile characteristics than the conical flame holders. With a burning length of 18 in., the pattern factor was 0.36 and the total-pressure loss was 5.1 percent. Author

N71-38789# Air Force Systems Command, Washington, D.C.
**AIR FORCE RESEARCH REVIEW. NO. 2, MARCH
 APRIL 1971**

Ethel Gamer Apr. 1971 31 p refs
 (AD-727338; AFSCR-80-2) Avail: NTIS CSCL 20/12

Contents: Vortex interactions in modern aerodynamics; Methods of eliminating phased array blind spots; Signal processing with elastic surface waves; Rare earth cobalt magnets; A new vacuum microbalance; Vuilleumier cycle cryogenic coolers demonstrate a new era in aircraft reliability; Laser research; Irradiation defects and the electrical quality of ion implanted silicon; High resolution chemical ionization mass spectroscopy; Design and synthesis of materials for lasers; Geodetic application of long base interferometry; A model for evaluating the utility of forecasting natural environmental phenomena; Research advances; Research needs. GRA

N71-38792# Federal Aviation Administration, Washington, D.C.
 Office of Environmental Quality.

**FEDERAL POLICY AND PLANNING ON THE AIRCRAFT
 ENVIRONMENT**

John O. Powers 1 Apr. 1971 22 p
 Avail: NTIS

The impact of man's activity on the environment is discussed. A short history of federal environmental legislation is presented. The activity of the FAA in environmental studies is outlined, with particular stress on the influence of aircraft and related factors. A position paper is being prepared utilizing a

systematic interdisciplinary approach which integrates the use of the natural and social sciences and the environmental design arts. Author

N71-38793# Civil Aeronautics Board, Washington, D.C.
**FORECAST OF SCHEDULED DOMESTIC AIR CARGO FOR
 THE 50 STATES, 1971 - 1975**

Irving Saginor and David B. Richards Feb. 1971 30 p
 Avail: NTIS

Forecasts are presented for domestic air cargo for the next five years. The forecasts are in terms of revenue ton-miles and are summations of freight (including express) and mail revenue ton-miles forecast over this period. Domestic cargo includes freight, express, and mail flown in scheduled service. These forecasts are based on a statistical analysis of historical data for the domestic operations of the carriers. The analysis indicated that the gross national product (GNP) and the levels of rates were the most important factors associated with the growth of express and freight traffic and that the GNP is the most important factor associated with mail ton-miles. The forecasts include a projection of mail ton-miles and projections of freight plus express ton-miles. This division was necessary due to the different growth pattern exhibited by express and freight on the one hand and mail on the other. Author

N71-38794# Civil Aeronautics Board, Washington, D.C. Bureau
 of International Affairs.

US INTERNATIONAL AIR CARGO MARKETS, 1970

Mary Irene Pett Apr. 1971 23 p refs
 Avail: NTIS

Tables covering the growth in U.S. air cargo markets in 1970 as compared to prior years and the U.S. carries participation in these markets are given. E.H.W.

N71-38795# Federal Aviation Administration, Washington, D.C.
 Office of Aviation Economics.

DOMESTIC AIR PASSENGER TRIP LENGTH

[1971] 24 p
 Avail: NTIS

An analysis of the distances traveled by domestic air passengers is submitted which is a significant characteristic of the air commerce traffic pattern. The study is a planning tool showing the extent to which domestic air travel is short, medium, or long distance. In addition to providing a basis for estimating future passenger traffic by length of trip, the data presented indicate in broad terms the size of the national market potentially available to various passenger aircraft types such as V/STOL aircraft which are economically of technically efficient over particular stage lengths. These surveys include statistics on the number of passengers, passenger-miles, and city pairs by passenger length of trip intervals. Author

N71-38798# Federal Aviation Administration, Washington, D.C.
**A POLICY PAPER GUIDELINES FOR NATIONAL AVIATION
 SYSTEM PLANNING AND R AND D POLICY Final Report**
 Benjamin F. L. Darden, Thomas P. Messier, and Milton B.
 Meisner Jun. 1971 109 p refs
 (FAA-AV-71-2; FAA-AV-100) Avail: NTIS


In most long range aviation system planning, a singleness of purpose is missing. The proposed Goals Approach method of aviation system planning gives clear direction for system development. Aviation system goals should relate to broad societal needs as well as internal system requirements. Levels of research and development strongly affect rate of goal achievement. Industry and government program information indicates FAA research expenditures are appropriate at an annual expenditure rate of \$100-200 million. Author

SUBJECT INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 13)

JANUARY 1972

Typical Subject Index Listing



The subject heading is a key to the subject content of the document. The Notation of Content (NOC), rather than the title of the document, is used to provide a more exact description of the subject matter. The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the Notation of Content, e.g., N71-11466. Under any one subject heading, the accession numbers are arranged in sequence with the /AA accession numbers appearing first.

A

ABORT TRAJECTORIES

Mathematical modeling of F-8 aircraft wave off trajectories for aircraft carrier approaches
[AD-727121] N71-36439

ACCELERATION (PHYSICS)

Aircraft accelerate-stop factors and regulations, pilot reaction times and accidents during takeoff
A71-43380

ACCIDENT PREVENTION

Aircraft wake turbulence and trailing vortices, investigating physical characteristics, hazard potential and avoidance techniques
A71-43234

ACCURACY

Technique for improving calibration accuracy standards from boundary layer calculations
[IC/71/23] N71-37851

ACOUSTIC EXCITATION

Vortex shedding from blunt trailing edge of flat plate spanning wind tunnel under oscillating flap and acoustic resonance excitations
A71-44558

ACOUSTIC MEASUREMENTS

Acoustic noise output from round interfering subsonic jets, considering suppressor nozzle attenuation
A71-44560

ACOUSTIC PROPAGATION

Low speed wind tunnel measurements correction for acoustic effects due to fan noise propagation
A71-44763

ACROBATICS

Acrostar Mk II all wood single seat acrobatic light weight aircraft designed for plus/minus 8g and inverted flight
A71-43887

ACTUATORS

Hydraulic power and actuation requirements of survivable flight control system utilizing fly by wire control for F-4 aircraft
[AD-727763] N71-37608

ADAPTIVE CONTROL

Longitudinal adaptive aircraft control through sum of normal acceleration and pitch rate
A71-44093

Adaptive guaranteed cost control for systems with parametric variation, demonstrating system stability and airframe pitch control
A71-44111

ADDITIVES

Jet aircraft fuel additives covering functions and

applications

A71-45325

ADHESION TESTS

Statistical analysis of spot welded and adhesive joints of high strength Al alloy sheet in aircraft structures
A71-45012

ADIABATIC CONDITIONS

Flare induced laminar boundary layer/shock wave interactions on axisymmetric bodies at zero incidence in supersonic flow under adiabatic conditions
A71-44604

AERIAL PHOTOGRAPHY

Arctic ocean pack ice terrain profiling by airborne laser altimeter and coincident photography, analyzing data for ice development stages interpretation
A71-44986

Remote aerial sensing and automatic mapping for forest resources information system
[NASA-CR-122922] N71-36770

Techniques for aerial time-lapse cloud photographic analysis, Doppler navigation data analysis, and photogrammetric data acquisition
N71-36990

Shallow ocean depth measurements by aerial photographs of wave refraction and wavelength changes and by multispectral scanning of wave reflection
[NASA-CR-123194] N71-37862

Interpretation of color infrared photography of Florida tidewater coastline
[AD-727630] N71-37924

Quantity and quality of geodetic information transmitted by space photography compared with low altitude aerial photography
[IR-USGS-229] N71-38013

AERIAL RECONNAISSANCE

Characteristics of sensors for aerial observation of ice formations and comparison of effectiveness of various methods
[JPRS-54162] N71-36801

AERODYNAMIC BALANCE

Active flutter mode control system synthesis for flight test, showing mass balancing as possible artificial symmetrical wing destabilization
A71-44106

AERODYNAMIC CHARACTERISTICS

Minimum drag and lifting line characteristics of large aspect ratio wing in uniform shear flow with velocity variations along span
A71-43312

Flight test measurements for improved estimates of aircraft states and aerodynamic parameters, using relinearized Kalman filter
A71-44089

Slender two dimensional wedge wings aerodynamic characteristics in hypersonic strong interaction flow, determining wall shear stress and lift drag ratio effects
A71-44621

Wind tunnel study of tip vortex modification by mass flow injection
[AD-726736] N71-36406

Development of near-field method for determining supersonic flow properties about bodies of revolution
[NASA-TN-D-6508] N71-36413

Partial admission performance of single stage supersonic turbine at low Reynolds numbers
[NASA-TN-X-2382] N71-36414

Single degree of freedom roll response due to vertical random two dimensional vertical gusts
[NASA-CR-111966] N71-36421

- Magnus force and moment data for standard 10 degree cone calibration model as determined in supersonic wind tunnel
[SC-DC-71-3821] N71-36688
- Development of methods for measuring and predicting behavior of rigid rotors with stiff blades at high advance ratios and low rotor speeds
[NASA-CR-114362] N71-37594
- Tu-134 aerodynamic characteristics during takeoff, climb, horizontal flight, landing stability and maneuverability, and strength under various loads
[AD-727196] N71-37612
- Aerodynamic characteristics of variable sweep wings under a variety of operating conditions
[AD-727210] N71-37615
- Aircraft takeoff, navigation, and landing aids, aerodynamics characteristics, and crew rescue equipment
[AD-727860] N71-37618
- Aerodynamic calculations in designing axial compressors with emphasis on compressors of stationary installations - handbook
[AD-727191] N71-38032
- AERODYNAMIC COEFFICIENTS**
- Performance prediction and evaluation of propulsion-augmented high lift systems for STOL aircraft, considering weight, thrust and wing loading
[AIAA PAPER 71-990] A71-44585
- AGARD report on engine-airplane interference and wall correction in transonic wind tunnel tests
[AGARD-AR-36-71] N71-36400
- Conclusions and recommendations concerning wind tunnel tests of interaction between engine flow and wall corrections in transonic wind tunnels
N71-36401
- Wall corrections for airplanes with interference lift in transonic wind tunnel tests
N71-36403
- Drag coefficient measurements in flow around rectangular cylinders
[IC-AERO-71-15] N71-36695
- AERODYNAMIC CONFIGURATIONS**
- Leading edge suction of thin aerofoil theory
[ARL/SM-NOTE-360] N71-36399
- Minimum drag airfoil shape solutions with supersonic flow and turbulent boundary layers for given chord length and heat transfer rate
[AD-726767] N71-36409
- Theoretical method for calculating aerodynamic loading on wing-body combinations
[NASA-TN-D-6441] N71-36411
- Methods for prediction of centerline shock layer thickness and pressure distribution on delta wing body configurations
[NASA-TN-D-6550] N71-36418
- Prediction formulations for transonic fluctuating pressure environments including protuberance induced turbulent boundary layer flows
[NASA-CR-119947] N71-36677
- Aerodynamic characteristics of variable sweep wings under a variety of operating conditions
[AD-727210] N71-37615
- AERODYNAMIC FORCES**
- Resultant aerodynamic forces on circular arc profile with normal jet in subsonic steady compressible flow, using Imai-Lamla approximation method
A71-44271
- Subsonic force effect calculations on rectangular wings, using downwash velocity potential method
A71-44613
- AERODYNAMIC HEAT TRANSFER**
- Minimum drag airfoil shape solutions with supersonic flow and turbulent boundary layers for given chord length and heat transfer rate
[AD-726767] N71-36409
- AERODYNAMIC HEATING**
- Mach 8 variable-density tunnel used for determination of aerodynamic heating of attached inflatable decelerator configurations
[NASA-TM-X-2355] N71-38758
- AERODYNAMIC LOADS**
- Theoretical method for calculating aerodynamic loading on wing-body combinations
[NASA-TN-D-6441] N71-36411
- Measurements of unsteady, rotary wing air loads and time derivatives for rotor blade intersecting completely rolled up vortex
[NASA-CR-1909] N71-37598
- AERODYNAMIC NOISE**
- Aerodynamic combustion noise generation from premixed or diffusion open turbulent flames, using fluid mechanics and Lighthill method
A71-43448
- AERODYNAMIC STABILITY**
- Principles of helicopter flight including flight stability
[AD-726841] N71-36429
- AERODYNAMIC STALLING**
- Analytical investigation of effects of blade flexibility, unsteady aerodynamics, and variable inflow on helicopter rotor stall characteristics
[NASA-CR-1769] N71-36404
- AERODYNAMICS**
- V/stol aircraft lift fan aerodynamics, discussing optimum fan pressure ratios, augmentation ratio, noise constraints, wing loading and fan configurations
[AIAA PAPER 71-981] A71-44577
- Canadian National Science Council research in low speed aerodynamics, machine learning, and turbulent jet transducer
[DME/NAE-1971(2)] N71-38626
- National Science Council goals in low speed aerodynamics - Canada
N71-38627
- Summaries of air force research activities
[AD-727338] N71-38789
- AEROSPACE INDUSTRY**
- Commercial air transportation industry trends and optimal planning requirements, discussing airline economic viability, industry regulation, public service and environmental compatibility
[AIAA PAPER 71-1022] A71-44600
- AFTERBODIES**
- Thrust-minus-drag forces and pressure distributions of closely spaced twin-jet afterbodies with different inboard-outboard fairing and nozzle shapes
[NASA-TM-X-2329] N71-36412
- AIR BREATHING ENGINES**
- Performance tests of compressor seals and stator pivot seals used with air breathing propulsion systems - Part 2
[NASA-CR-72887] N71-37373
- AIR CARGO**
- Technology developments in rotor, drive, flight controls and cargo handling systems of heavy lift helicopter system, noting military and commercial applications
[AIAA PAPER 71-994] A71-45296
- Freight, express, and mail tonnage forecasts for domestic airline operations
N71-38793
- Growth rate of US air cargo markets - tables
N71-38794
- AIR FLOW**
- Visualized flow patterns of airflow in centrifugal rotors with thin plate blading and with thick airfoil blades
[ME-238] N71-36410
- AIR MAIL**
- Freight, express, and mail tonnage forecasts for domestic airline operations
N71-38793
- AIR NAVIGATION**
- Corporate aircraft operations in Latin America, discussing communication and navigation, fuel, paper work, food, vaccinations and weather
A71-43391
- Mobile LP air navigation AN/MRN-13 equipment, operation and maintenance
A71-43878
- Airline view of air navigation problems
N71-37896
- AIR PIRACY**
- Convention for suppression of unlawful aircraft seizure and article by article analysis
N71-37590
- AIR POLLUTION**
- Operating variables effect on pollutant exhaust from

SUBJECT INDEX

AIRCRAFT ACCIDENTS

- jet aircraft turbine engines, discussing combustor design techniques for emissions reduction A71-43600
- SST operation climatic impact assessment program, considering carbon dioxide, water vapor, contrails, particulates, nitrogen oxides and carbon monoxide A71-44982
- AIR TRAFFIC**
 - Canadian STOL program, discussing Quebec- Windsor corridor passenger traffic [AIAA PAPER 71-982] A71-44578
 - STOL aircraft system, discussing ground installations, runways, three dimensional area navigational aids, noise reduction, air traffic and short haul productivity [AIAA PAPER 71-983] A71-44579
 - Graphs and tables of aircraft traffic over North America - 1966 through 1969 [RAE-LIB-FRANS-1580] N71-38210
- AIR TRAFFIC CONTROL**
 - IBM 9020 multiprocessor computer application to ATC, discussing control sectors for inflight control at air route traffic control centers in U.S. A71-43888
 - Stochastic optimal control theory application to airplane rescheduling model, obtaining dynamic programming algorithm for optimal landing and takeoff rules A71-44104
 - Computer-aided decision algorithm for ATC problem in near terminal area, emphasizing scheduling and holding strategies A71-44105
 - Supersonic transports and ATC, discussing taxiing, takeoff, landing and terminal area operations A71-44352
 - Civil aviation research and development policy review covering aircraft noise, congestion, ATC, runway capacity and airport development problems [AIAA PAPER 71-1024] A71-44602
 - Range and azimuth resolution characteristics and aircraft separation measurement capability of radar beacon-digitizer subsystem [FAA-NA-71-16] N71-37038
 - Attitudes and motivational factors in job performance of terminal area air traffic control personnel [FAA-AH-71-30] N71-37041
 - Airborne traffic situation display system for use with radar control terminal system [AD-727769] N71-37042
 - Alternate air traffic control co-channel separation criteria based on probability-of-interference considerations [IST-101] N71-37712
 - Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines N71-37742
 - Computerized real time data processing and display system for air traffic control in airspace over Belgium, Luxemburg, the Netherlands, and Germany N71-37744
 - Evaluation of design concept and operational feasibility of 11-sided control tower cab [FAA-NA-71-37] N71-37826
 - Effectiveness of control towers in reducing aircraft accidents and approach time N71-38213
 - Air traffic control, communications, navigation, frequency management, systems analysis, and aircraft SRDS program developments N71-38214
 - Performance evaluation of automatic flight progress strip cutter and loader used in air traffic control facility [ACTEU-330] N71-38215
- AIR TRANSPORTATION**
 - Future transportation technology impact, considering system design evaluation criteria and civil aviation and urban mass transit systems contributions [AIAA PAPER 71-1010] A71-44594
 - Commercial air transportation industry trends and optimal planning requirements, discussing airline economic viability, industry regulation, public service and environmental compatibility [AIAA PAPER 71-1022] A71-44600
 - Weather interruption effects on air transportation operations and economics, considering fog, snow, freezing rain, thunderstorms, winds, CAT and runway conditions A71-44983
 - Design, development, and performance requirements for large rigid airships for freight and cargo transportation [REPT-5] N71-36425
 - Guidelines for national aviation system planning and R and D policy [FAA-AV-71-2] N71-38798
- AIRBORNE EQUIPMENT**
 - Solid state airborne weather radar for civil aviation, discussing design, weight and power requirement reduction A71-44273
 - Cost ownership analysis of avionic equipment N71-36784
 - Characteristics of sensors for aerial observation of ice formations and comparison of effectiveness of various methods [JPRS-54162] N71-36801
 - Airborne traffic situation display system for use with radar control terminal system [AD-727769] N71-37042
 - C band radar transmitter for airborne radar system [AD-727086] N71-37707
- AIRBORNE/SPACEBORNE COMPUTERS**
 - Advanced avionic digital computer development program [AD-727607] N71-37765
- AIRCRAFT**
 - Cost effectiveness of built in test provisions in aircraft operations N71-36780
 - Flight dynamics and calculation of flight trajectories of various aircraft and spacecraft [AD-727474] N71-37602
 - Development of rain erosion resistant plastic coatings as high speed aircraft surface finish [AD-727750] N71-38133
 - Air traffic control, communications, navigation, frequency management, systems analysis, and aircraft SRDS program developments N71-38214
 - Impact of air activity on environment and federal interest in environmental studies N71-38792
- AIRCRAFT ACCIDENT INVESTIGATION**
 - Corporate aircraft 1970 accident statistics analysis stressing pilot selection, training and supervision A71-43227
 - Aircraft skidding accidents investigation, comparing airplane stopping distance computations and observations A71-43228
 - Aircraft accident briefs for 1969 including date, location, aircraft data, injuries, flight purpose, and pilot data [NTSB-BA-71-2] N71-36433
 - Aircraft accident investigation of Alaska Airlines Flight 1866 on Sept. 4, 1971 [SB-71-87] N71-36434
- AIRCRAFT ACCIDENTS**
 - Aircraft ditching and flying personnel survival, stressing passenger briefing and crew jacket equipment with VHF transceiver for rescue operations coordination A71-43229
 - Aircraft accelerate-stop factors and regulations, pilot reaction times and accidents during takeoff A71-43380
 - Barometric altimetry system inadequacies and approach/landing accidents, noting pitot static components blocking hazards A71-43384
 - Corporate aircraft pilot ground and flight phase training, errors and accidents A71-43388
 - Airport crash fire fighting equipment requirements and rescue operations A71-43389
 - Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969

AIRCRAFT BRAKES

SUBJECT INDEX

- [NTSB-ARC-7L-1] N71-36437
 Aircraft hazards and accidents due to birds
 [AD-727881] N71-37617
 Effectiveness of control towers in reducing aircraft
 accidents and approach time N71-38213
- AIRCRAFT BRAKES**
 Evaluation of braking performance of light, twin
 engine airplane on grooved and ungrooved runway
 surfaces N71-36431
 [NASA-TN-D-6444]
- AIRCRAFT CARRIERS**
 Mathematical modeling of F-8 aircraft wave off
 trajectories for aircraft carrier approaches
 [AD-727121] N71-36439
- AIRCRAFT COMMUNICATION**
 Corporate aircraft operations in Latin America,
 discussing communication and navigation, fuel,
 paper work, food, vaccinations and weather
 A71-43391
 Alternate air traffic control co-channel separation
 criteria based on probability-of-interference
 considerations N71-37712
 [IST-101]
- AIRCRAFT CONFIGURATIONS**
 Supersonic aircraft shape for shock waves
 minimization based on channel configuration with
 converging inlet and diverging outlet section
 A71-44572
 Panavia 200 multipurpose military aircraft,
 describing variable geometry design concept,
 performance characteristics, engines, armament and
 electronics A71-44766
- AIRCRAFT CONTROL**
 Fluid amplifiers theory and use as temperature and
 pressure sensors, discussing applications in
 chemical and ammunition industries and jet
 aircraft control A71-42921
 [IEEE PAPER 70-TP-120-IGA]
 SST handling qualities, takeoff speeds and
 performance evaluation on six degree of freedom
 flight simulator A71-42922
 Nonreversible hydraulic control design and emergency
 maintenance for Tu 154 aircraft subsonic cruising
 at 11 km altitude A71-42927
 Minimum order state vector reconstruction linear
 filters for constant plants optimal control,
 applying to aircraft flight multiple control-point
 problem A71-44077
 Flight test measurements for improved estimates of
 aircraft states and aerodynamic parameters, using
 relinearized Kalman filter A71-44089
 Longitudinal adaptive aircraft control through sum
 of normal acceleration and pitch rate A71-44093
 Integrated system for aircraft control and operation
 with visualization and manual regulation
 techniques, emphasizing interconnections with
 onboard electronic equipment A71-44353
 American development in automatic flight control,
 noting FAA requirements, pilot involvement and
 visibility enhancement A71-44455
 STOL aircraft flight control problems, discussing
 Mach trim, artificial feel, stability, feedback
 system responses and lateral/directional laws
 [AIAA PAPER 71-993] A71-45297
 Wind tunnel tests of stability and control
 characteristics of large scale model
 representative of propeller-driven STOL transport
 aircraft N71-36435
 [NASA-TN-D-6393]
 Feasibility study of combined laminar and turbulent
 boundary layer control system using distributed
 suction with application to low-speed research
 aircraft of glass reinforced plastic N71-37609
 [AD-72767]
 Analysis of criteria for survivable flight control
 system using fly-by-wire and integrated actuator
 package techniques N71-37616
 [AD-72762]
 Conversion of computational algorithms for
 decreasing length of word format of control
- computers for aircraft
 [AD-727917] N71-37772
- AIRCRAFT DESIGN**
 High lift device application to high performance
 competition gliders, considering merit of design
 for conflicting climb/cruise requirements A71-43089
 Acrostar Mk II all wood single seat acrobatic light
 weight aircraft designed for plus/minus 8g and
 inverted flight A71-43887
 Sailplane circling cross-country speed increase by
 variable geometry in high lift flap form for
 better compromise between cruise and climb
 performance A71-44342
 AIAA members comments on STOL, VTOL and V/STOL
 aircraft merits and developments
 [AIAA PAPER 71-1015] A71-44596
 Panavia 200 multipurpose military aircraft,
 describing variable geometry design concept,
 performance characteristics, engines, armament and
 electronics A71-44766
- AIRCRAFT ENGINES**
 In-flight monitoring of aircraft turbine engine
 reliability A71-43233
 Operating variables effect on pollutant exhaust from
 jet aircraft turbine engines, discussing combustor
 design techniques for emissions reduction A71-43600
 Digital algorithm for automatic aircraft engine
 monitoring system, using Boolean algebra and
 events/states theory A71-43897
 Nondestructive detection of hot corrosion-
 sulfidation in U.S. Navy aircraft turbine engines
 A71-45280
 Conclusions and recommendations concerning wind
 tunnel tests of interaction between engine flow
 and wall corrections in transonic wind tunnels
 N71-36401
 Combustion characteristics of gas turbine aircraft
 engines
 [AD-727175] N71-37387
 Analysis of gas turbine design and application to
 aircraft operation with description of components,
 safety factors, and vibration problems
 [AD-727188] N71-38538
- AIRCRAFT EQUIPMENT**
 Aircraft permanent magnetic fields strength
 variation, observing magnetic anomaly detection
 equipment performance degradation A71-42923
 Aircraft takeoff, navigation, and landing aids,
 aerodynamics characteristics, and crew rescue
 equipment N71-37618
 [AD-727860]
- AIRCRAFT FUELS**
 Jet engine advent impact on aviation fuels safety,
 discussing gasoline hazards in prejet aircraft
 A71-43231
 Liquid hydrogen as future replacement for
 hydrocarbon fuels in surface and air
 transportation, noting advantages in energy per
 unit weight and pollution-free combustion A71-44365
 Jet aircraft fuel additives covering functions and
 applications A71-45325
 Aviation fuels lubricating characteristics,
 discussing refining methods, viscosity, service
 performance and load testing A71-45383
 Determination of physical and chemical properties of
 fuels gelled with carbohydrate resins to evaluate
 effectiveness in reducing aircraft fire hazards
 [FAA-WA-71-18] N71-37369
 Control and chemical composition of aircraft fuels,
 lubricants, and special liquids
 [AD-727199] N71-38531
- AIRCRAFT HAZARDS**
 Aircraft wake turbulence and trailing vortices,
 investigating physical characteristics, hazard
 potential and avoidance techniques A71-43234
 Aircraft generated vortex wakes and core air motions
 hazards for encountering light airplane

SUBJECT INDEX

AIRCRAFT STABILITY

- A71-43381
Aircraft hazards and accidents due to birds
[AD-727881] N71-37617
- AIRCRAFT HYDRAULIC SYSTEMS**
Nonreversible hydraulic control design and emergency maintenance for Tu 154 aircraft subsonic cruising at 11 km altitude A71-42927
- AIRCRAFT INDUSTRY**
Soviet aircraft industry R and D organizations and management A71-44189
- AIRCRAFT INSTRUMENTS**
Angle of attack instrumentation for evaluating aircraft lift performance and phugoid oscillations A71-43382
Altitude instrumentation for aircraft pilot, discussing three pointer, servo and drum pointer altimeters, digital readout, radar alert and automatic reporting systems A71-43383
Aircraft pitot static systems design with removable drain plug, noting line installation problems A71-43387
Astatic gyroscope mounted on aircraft moving arbitrarily near earth surface, obtaining integrals of kinematic equations A71-45160
Aircraft mechanical and battery operated clocks resistant to high intensity magnetic fields [AD-726700] N71-36430
Pilot performance in recognizing electronic display systems under varying dazzle and color conditions in cockpits [RAE-LIB-TRANS-1545] N71-37621
- AIRCRAFT LANDING**
Mathematical modeling of F-8 aircraft wave off trajectories for aircraft carrier approaches [AD-727121] N71-36439
Airborne remote sensing of Mojave Desert playas for use as natural landing areas [AD-727031] N71-36748
Equations of motion for elastic plate foundation system under dynamic load applied to aircraft landing N71-37543
Tu-134 aerodynamic characteristics during takeoff, climb, horizontal flight, landing stability and maneuverability, and strength under various loads [AD-727196] N71-37612
Effect of wet, icy, and snow covered runways on aircraft stopping distance and directional control in crosswinds, effect of surface texture and contamination on runway slipperiness [FS-160-65-68-2] N71-37820
- AIRCRAFT MAINTENANCE**
Nonreversible hydraulic control design and emergency maintenance for Tu 154 aircraft subsonic cruising at 11 km altitude A71-42927
Aircraft part repair-throwaway decisions for minimizing costs over life cycle by economic graphic screening techniques A71-43197
Civil transport aircraft and equipment maintenance and reliability problems solutions with best time, cost and weight compromises A71-44765
- AIRCRAFT NOISE**
Civil aviation research and development policy review covering aircraft noise, congestion, ATC, runway capacity and airport development problems [AIAA PAPER 71-1024] A71-44602
Flight dynamics of noise optimal flight profiles for V/STOL aircraft, minimization of gust effects on aircraft and nonlinear dynamic stability of parachute-load systems A71-44761
Prop rotor and lift fan VTOL aircraft ground noise level reduction, using flight trajectory management [AIAA PAPER 71-991] A71-45295
Noise characteristics of model STOL wing with externally blown flaps in vicinity of aircraft propulsor [NASA-CR-111956] N71-38283
- AIRCRAFT PARTS**
Aircraft parts damage by corrosive friction forces, hot gases and intercrystalline attack, noting worn universal joint and blade grain boundary damage A71-44574
- AIRCRAFT PERFORMANCE**
SST handling qualities, takeoff speeds and performance evaluation on six degree of freedom flight simulator A71-42922
High lift device application to high performance competition gliders, considering merit of design for conflicting climb/cruise requirements A71-43089
Angle of attack instrumentation for evaluating aircraft lift performance and phugoid oscillations A71-43382
Sailplane circling cross-country speed increase by variable geometry in high lift flap form for better compromise between cruise and climb performance A71-44342
Performance prediction and evaluation of propulsion-augmented high lift systems for STOL aircraft, considering weight, thrust and wing loading [AIAA PAPER 71-990] A71-44585
Transient dynamic characteristics of aircraft under unsteady flight, using Laplace-Carson integral transforms A71-45016
Aircraft fuselage antisymmetric loading strain effects on small aspect delta wing performance A71-45018
Compilation of responses to questionnaire on engine-airframe interference in transonic tests N71-36402
Wall corrections for airplanes with interference lift in transonic wind tunnel tests N71-36403
Wind tunnel performance characteristics of single-engine fighter model fitted with in-flight thrust reverser [NASA-TN-D-6460] N71-37384
Computer program for analyzing and simulating attack of low flying aircraft by antiaircraft missiles and probability of aircraft survival [RAE-LIB-TRANS-1578] N71-37774
Performance and costs of nuclear aircraft used in transoceanic commerce [NASA-TM-X-2386] N71-38277
- AIRCRAFT PILOTS**
Aircraft accident briefs for 1969 including date, location, aircraft data, injuries, flight purpose, and pilot data [NTSB-BA-71-2] N71-36433
- AIRCRAFT RELIABILITY**
Civil transport aircraft and equipment maintenance and reliability problems solutions with best time, cost and weight compromises A71-44765
- AIRCRAFT SAFETY**
Corporate aircraft safety - Conference, Washington, D.C. April 1971 A71-43226
Jet engine advent impact on aviation fuels safety, discussing gasoline hazards in prejet aircraft A71-43231
Corporate aircraft safety - Conference, San Antonio, May 1970 A71-43379
Determination of physical and chemical properties of fuels gelled with carbohydrate resins to evaluate effectiveness in reducing aircraft fire hazards [FAA-WA-71-18] N71-37369
- AIRCRAFT STABILITY**
Stability augmentation system for aircraft elastic modes control, discussing active flutter suppression technology A71-44107
Flexible ram air inflated keel and leading edge parawing design optimization for increased stability and reliability, introducing semirigid member concept [AIAA PAPER 71-986] A71-44582
STOL aircraft flight control problems, discussing Mach trim, artificial feel, stability, feedback system responses and lateral/directional laws [AIAA PAPER 71-993] A71-45297
Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from

AIRCRAFT STRUCTURES

SUBJECT INDEX

- radiosonde data A71-44983
- [NASA-TT-F-13981] N71-36398
- Horizontal temperature and wind distribution effects on aircraft buffeting in stratosphere N71-36780
- [NASA-TT-F-13978] N71-37600
- Spin tunnel tests to determine effectiveness of deployable, flexible ventral fins for spin recovery device on fighter aircraft N71-37607
- [NASA-TN-D-6509] N71-37603
- AIRCRAFT STRUCTURES**
- Statistical analysis of spot welded and adhesive joints of high strength Al alloy sheet in aircraft structures N71-38793
- A71-45012
- Variability of aluminum alloy aircraft structure fatigue life under symmetric and asymmetric loads [ARL/SM-REPORT-329] N71-37524
- Reduction of resonant vibrations in integrally stiffened skin-stringer panels using viscoelastic materials N71-37540
- [AD-727773]
- Structural analysis of corrugated aircraft wing skin panels to determine effects of corrosion damage [AD-728009] N71-37619
- AIRCRAFT TIRES**
- Folding sidewall aircraft tires design, construction and flight tests, noting advantages and disadvantages A71-44975
- AIRCRAFT WAKES**
- Aircraft wake turbulence and trailing vortices, investigating physical characteristics, hazard potential and avoidance techniques A71-43234
- Aircraft generated vortex wakes and core air motions hazards for encountering light airplane A71-43381
- AIRFOIL PROFILES**
- Resultant aerodynamic forces on circular arc profile with normal jet in subsonic steady compressible flow, using Imai-Lamla approximation method A71-44271
- Transonic airfoil cascade analytical design, determining efficiency from velocity distribution A71-45381
- AIRFOILS**
- Transonic flows about two dimensional airfoils, calculating far field boundary conditions with coordinate transformation A71-44620
- Leading edge suction of thin aerofoil theory [ARL/SM-NOTE-360] N71-36399
- Wind tunnel study of tip vortex modification by mass flow injection N71-36406
- [AD-726736]
- Visualized flow patterns of airflow in centrifugal rotors with thin plate blading and with thick airfoil blades N71-36410
- [ME-238]
- Development of procedure for scaling of experimental turbine vane airfoil temperatures from low to high gas temperatures N71-37563
- [NASA-TN-D-6510]
- Two dimensional flow tests of transonic airfoils [NASA-TT-F-13988] N71-37593
- Design, construction, and performance of water tunnel for two dimensional testing of pitching airfoils N71-37827
- [D180-14130-1]
- AIRFRAMES**
- Technical aviation handbook covering aircraft maintenance, navigation aids, airframes, lubricants, piston and gas turbine engines, and checkout procedures N71-37613
- [AD-727195]
- AIRLINE OPERATIONS**
- Corporate aircraft operations in Latin America, discussing communication and navigation, fuel, paper work, food, vaccinations and weather A71-43391
- Commercial air transportation industry trends and optimal planning requirements, discussing airline economic viability, industry regulation, public service and environmental compatibility A71-44600
- [AIAA PAPER 71-1022]
- Weather interruption effects on air transportation operations and economics, considering fog, snow, freezing rain, thunderstorms, winds, CAT and runway conditions
- Coct effectiveness of built in test provisions in aircraft operations N71-37607
- Simulation of aircraft ground operations for Dallas-Fort worth Regional Airport N71-37607
- Airline view of air navigation problems N71-37896
- Freight, express, and mail tonnage forecasts for domestic airline operations N71-38793
- AIRPORT PLANNING**
- Airport crash fire fighting equipment requirements and rescue operations A71-43389
- Civil aviation research and development policy review covering aircraft noise, congestion, ATC, runway capacity and airport development problems [AIAA PAPER 71-1024] A71-44602
- AIRPORT TOWERS**
- Evaluation of design concept and operational feasibility of 11-sided control tower cab [FAA-WA-71-37] N71-37826
- Effectiveness of control towers in reducing aircraft accidents and approach time N71-38213
- AIRPORTS**
- Airport certification and safety inspection program mandated by Airport and Airway Development Act of 1971 A71-43235
- Computing dispersal of atmospheric pollutants near airports by use of mean wind and temperature profiles N71-36720
- [NASA-CR-111962]
- Manual for development of needs estimates and capital improvement programs for airports and other intercity terminals for 1970 to 1990 N71-37824
- [OMB-04-S71002]
- AIRSHIPS**
- Design, development, and performance requirements for large rigid airships for freight and cargo transportation N71-36425
- [REPT-5]
- AIRSPEED**
- Pressure altimeter, airspeed and vertical velocity instruments, discussing selection, installation, pilot verification, error identification, repair and use A71-43385
- Sailplane circling cross-country speed increase by variable geometry in high lift flap form for better compromise between cruise and climb performance A71-44342
- ALASKA**
- Aircraft accident investigation of Alaska Airlines Flight 1866 on Sept. 4, 1971 N71-36434
- [SB-71-87]
- ALGORITHMS**
- Digital algorithm for automatic aircraft engine monitoring system, using Boolean algebra and events/states theory A71-43897
- Stochastic optimal control theory application to airplane rescheduling model, obtaining dynamic programming algorithm for optimal landing and takeoff rules A71-44104
- Computer-aided decision algorithm for ATC problem in near terminal area, emphasizing scheduling and holding strategies A71-44105
- Suboptimal fixed point data smoothing algorithm for parameter and initial state estimation of nonlinear dynamic systems A71-44113
- Algorithm for dual compromise control problems arising from each subsystem of inner level in multilevel static hierarchical system A71-44393
- Conversion of computational algorithms for decreasing length of word format of control computers for aircraft N71-37772
- [AD-727917]
- ALTIMETERS**
- Altitude instrumentation for aircraft pilot, discussing three pointer, servo and drum pointer

- altimeters, digital readout, radar alert and automatic reporting systems
A71-43383
- Barometric altimetry system inadequacies and approach/landing accidents, noting pitot static components blocking hazards
A71-43384
- Pressure altimeter, airspeed and vertical velocity instruments, discussing selection, installation, pilot verification, error identification, repair and use
A71-43385
- General aviation aircraft altimeter errors, tolerances and static system tests
A71-43386
- ALUMINUM ALLOYS**
Statistical analysis of spot welded and adhesive joints of high strength Al alloy sheet in aircraft structures
A71-45012
- Variability of aluminum alloy aircraft structure fatigue life under symmetric and asymmetric loads [ARL/SM-REPORT-329]
N71-37524
- AMMUNITION**
Fluid amplifiers theory and use as temperature and pressure sensors, discussing applications in chemical and ammunition industries and jet aircraft control
[IEEE PAPER 70-TP-120-IGA]
A71-42921
- ANGLE OF ATTACK**
Angle of attack instrumentation for evaluating aircraft lift performance and phugoid oscillations
A71-43382
- Lifting rectangular thin airfoil in symmetrical incompressible steady uniform orthogonal flow at small angle of attack, deriving Weissinger integral equation
A71-43487
- ANTI-AIRCRAFT MISSILES**
Computer program for analyzing and simulating attack of low flying aircraft by anti-aircraft missiles and probability of aircraft survival [RAE-LIB-TRANS-1578]
N71-37774
- APPROACH**
Mathematical modeling of F-8 aircraft wave off trajectories for aircraft carrier approaches [AD-727121]
N71-36439
- Effectiveness of control towers in reducing aircraft accidents and approach time
N71-38213
- APPROACH CONTROL**
Flight simulator for studying problems of aircraft during approaches and landings at night under category 2 visual conditions [RAE-TM-AVIONICS-59(BLEU)]
N71-37606
- ARCTIC OCEAN**
Arctic ocean pack ice terrain profiling by airborne laser altimeter and coincident photography, analyzing data for ice development stages interpretation
A71-44986
- ATMOSPHERIC ATTENUATION**
Laser technique for runway and slant visibility range, lower cloud boundary and atmospheric damping coefficient
A71-43889
- ATMOSPHERIC TEMPERATURE**
Computing dispersal of atmospheric pollutants near airports by use of mean wind and temperature profiles [NASA-CR-111962]
N71-36720
- ATMOSPHERIC TURBULENCE**
Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from radiosonde data [NASA-TT-P-13981]
N71-36398
- Technique for relating transient tolerances in inlet throat Mach number and shock position to supersonic unstart frequency due to atmospheric turbulence for supersonic inlet design [NASA-CR-114372]
N71-37835
- AUTOMATIC CONTROL**
IBM 9020 multiprocessing computer application to ATC, discussing control sectors for inflight control at air route traffic control centers in U.S.
A71-43888
- Trends in automatic control field in last two decades, emphasizing optimal control and performance criteria selection [AIAA PAPER 71-1001]
A71-44591
- Computerized real time data processing and display system for air traffic control in airspace over Belgium, Luxemburg, the Netherlands, and Germany
N71-37744
- AUTOMATIC FLIGHT CONTROL**
Automatic flight control systems, discussing pilot as systems manager or retained in control loop
A71-44454
- American development in automatic flight control, noting FAA requirements, pilot involvement and visibility enhancement
A71-44455
- AUTOMATIC LANDING CONTROL**
European automatic flight control systems for landing in category IIIA conditions, discussing triplex system in Trident and simplex in Caravelle
A71-44456
- AUTOMATIC PILOTS**
Automatic pilots for control of rotary and fixed wing aircraft [AD-727789]
N71-37611
- AUTOMATIC TEST EQUIPMENT**
Digital algorithm for automatic aircraft engine monitoring system, using Boolean algebra and events/states theory
A71-43897
- AUTOROTATION**
Helicopter optimal autorotation landing parameters for touchdown at zero speed, including rotor rpm drop due to flow separation on blades
A71-43090
- AVIONICS**
Cost effectiveness, failure analysis, and design techniques for measuring reliability of avionics systems [AGARD-LS-47-71]
N71-36776
- Reliability estimation, including failure effect analysis of avionic systems
N71-36777
- Effectiveness of reliability programs for avionic equipment
N71-36779
- Cost ownership analysis of avionic equipment
N71-36784
- AXIAL FLOW**
Axial flow compressors stable operation, using rotating guide vanes regulation
A71-43554
- AXIAL FLOW TURBINES**
Streamline curvature analysis of compressible subsonic, transonic and supersonic cascade flows in axial turbine blades
A71-44347
- AXISYMMETRIC BODIES**
Flare induced laminar boundary layer/shock wave interactions on axisymmetric bodies at zero incidence in supersonic flow under adiabatic conditions
A71-44604
- Ideal weight of axisymmetric fuselage shells, taking into account load distribution and cabin pressurization
A71-45180
- AZIMUTH**
Range and azimuth resolution characteristics and aircraft separation measurement capability of radar beacon-digitizer subsystem [FAA-WA-71-16]
N71-37038
- B**
- BALLUTES**
Mach 8 variable-density tunnel used for determination of aerodynamic heating of attached inflatable decelerator configurations [NASA-TM-X-2355]
N71-38758
- BAROMETERS**
Barometric altimetry system inadequacies and approach/landing accidents, noting pitot static components blocking hazards
A71-43384
- BENARD CELLS**
Radar observation of convective process in clear air, presenting turreted top cell contour tracings from PPI sequence

BIBLIOGRAPHIES

SUBJECT INDEX

- BIBLIOGRAPHIES** A71-43088
Digital computer bibliography, programming techniques and applications, and software standardization and reliability [AD-727605] N71-37766
- BIRDS**
Aircraft hazards and accidents due to birds [AD-727881] N71-37617
- BODIES OF REVOLUTION**
Development of near-field method for determining supersonic flow properties about bodies of revolution [NASA-TN-D-6508] N71-36413
Pressure distributions and drag coefficients of 18 constant length and volume slender bodies of revolution at zero incidence for Mach numbers 2.0 to 12.0 - graphs [NASA-TN-D-6536] N71-36416
- BOEING AIRCRAFT**
Aircraft accident investigation of Alaska Airlines Flight 1866 on Sept. 4, 1971 [SB-71-87] N71-36434
- BORON**
Supersonic combustion chemistry and mixing of high energy density fuels related to advanced air-breathing engine design, using boron particles [AD-727782] N71-38530
- BOUNDARY LAYER CONTROL**
Feasibility study of combined laminar and turbulent boundary layer control system using distributed suction with application to low-speed research aircraft of glass reinforced plastic [AD-727767] N71-37609
- BOUNDARY LAYER FLOW**
Design, construction, and performance of water tunnel for two dimensional testing of pitching airfoils [D180-14130-1] N71-37827
Performance tests and efficiency measurement of hub-slit-suction stator in single stage compressor [NASA-CR-120802] N71-37836
- BOUNDARY LAYERS**
Technique for improving calibration accuracy standards from boundary layer calculations [IC/71/23] N71-37851
- BOUNDARY VALUE PROBLEMS**
Transonic flows about two dimensional airfoils, calculating far field boundary conditions with coordinate transformation A71-44620
- BRAKING**
Evaluation of braking performance of light, twin engine airplane on grooved and ungrooved runway surfaces [NASA-TN-D-6444] N71-36431
- BUFFETING**
Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from radiosonde data [NASA-TT-F-13981] N71-36398
Horizontal temperature and wind distribution effects on aircraft buffeting in stratosphere [NASA-TT-F-13978] N71-37600
- C BAND**
C band radar transmitter for airborne radar system [AD-727086] N71-37707
- C-5 AIRCRAFT**
Tests on scale model configurations of C-5 aircraft to obtain data correlation on three transonic wind tunnels [AD-727006] N71-36408
- CALIBRATING**
Aeronautical radio navigation aids photo-optical calibration, describing photogrammetric procedure and ground equipment for checking out airport ILS systems A71-43587
Technique for improving calibration accuracy standards from boundary layer calculations [IC/71/23] N71-37851

C

- CALIFORNIA**
Airborne remote sensing of Mojave Desert playas for use as natural landing areas [AD-727031] N71-36748
- CANADA**
Canadian National Science Council research in low speed aerodynamics, machine learning, and turbulent jet transducer [DME/NAE-1971(2)] N71-38626
National Science Council goals in low speed aerodynamics - Canada N71-38627
- CANARD CONFIGURATIONS**
Wind tunnel static longitudinal stability and control characteristics of cruciform delta winged missile with various horizontal canards and trailing-edge flap control between Mach 1.50 and 4.63 [NASA-TM-X-2367] N71-36415
- CARBOHYDRATES**
Determination of physical and chemical properties of fuels gelled with carbohydrate resins to evaluate effectiveness in reducing aircraft fire hazards [FAA-NA-71-18] N71-37369
- CASCADE FLOW**
Streamline curvature analysis of compressible subsonic, transonic and supersonic cascade flows in axial turbine blades A71-44347
Noise reduction studies involving variable geometry inlet guide vanes for choking using two-sector cascade apparatus with three inlet configurations [NASA-TM-X-2392] N71-37601
- CASCADES**
Transonic airfoil cascade analytical design, determining efficiency from velocity distribution A71-45381
- CAVITATION FLOW**
Design, construction, and performance of water tunnel for two dimensional testing of pitching airfoils [D180-14130-1] N71-37827
- CEMENTS**
Laboratory tests of polymeric latex modified fast-fix C-1 cement for repair of damaged runway pavements [AD-727728] N71-38132
- CENTRIFUGAL COMPRESSORS**
Compressors and turbines centripetal stages operational characteristics, investigating airflow rate and pressure ratio effects on power A71-45380
Visualized flow patterns of airflow in centrifugal rotors with thin plate blading and with thick airfoil blades [ME-238] N71-36410
Swept-back vane impeller tested on low speed centrifugal compressor rig [NRC-12020] N71-37596
- CERTIFICATION**
Airport certification and safety inspection program mandated by Airport and Airway Development Act of 1971 A71-43235
Guide to private and commercial multiengine aircraft pilot certification [FAA-AC-61-4C] N71-36438
- CHANNEL FLOW**
Supersonic aircraft shape for shock waves minimization based on channel configuration with converging inlet and diverging outlet section A71-44572
- CHECKOUT**
Technical aviation handbook covering aircraft maintenance, navigation aids, airframes, lubricants, piston and gas turbine engines, and checkout procedures [AD-727195] N71-37613
- CHEMICAL COMPOSITION**
Control and chemical composition of aircraft fuels, lubricants, and special liquids [AD-727199] N71-38531
- CHRONOPHOTOGRAPHY**
Techniques for aerial time-lapse cloud photographic analysis, Doppler navigation data analysis, and photogrammetric data acquisition N71-36990
- CIRCULAR SHELLS**
Ideal weight of axisymmetric fuselage shells, taking

- into account load distribution and cabin pressurization
A71-45180
- CIVIL AVIATION**
- Solid state airborne weather radar for civil aviation, discussing design, weight and power requirement reduction
A71-44273
- Future transportation technology impact, considering system design evaluation criteria and civil aviation and urban mass transit systems contributions
[AIAA PAPER 71-1010] A71-44594
- Civil aviation research and development policy review covering aircraft noise, congestion, ATC, runway capacity and airport development problems
[AIAA PAPER 71-1024] A71-44602
- Aircraft accident briefs for 1969 including date, location, aircraft data, injuries, flight purpose, and pilot data
[NTSB-BA-71-2] N71-36433
- Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969
[NTSB-ARC-71-1] N71-36437
- Planning short-haul intercity commercial air transportation with STOL aircraft
[WRCN-2] N71-37605
- Survey of domestic air passenger trip length including number of passengers and aircraft types
N71-38795
- CLEAR AIR TURBULENCE**
- Radar observation of convective process in clear air, presenting turreted top cell contour tracings from PPI sequence
A71-43088
- CLIMATOLOGY**
- SST operation climatic impact assessment program, considering carbon dioxide, water vapor, contrails, particulates, nitrogen oxides and carbon monoxide
A71-44982
- CLIMBING FLIGHT**
- Tu-134 aerodynamic characteristics during takeoff, climb, horizontal flight, landing stability and maneuverability, and strength under various loads
[AD-727196] N71-37612
- CLOCKS**
- Aircraft mechanical and battery operated clocks resistant to high intensity magnetic fields
[AD-726700] N71-36430
- CLOUD PHOTOGRAPHY**
- Techniques for aerial time-lapse cloud photographic analysis, Doppler navigation data analysis, and photogrammetric data acquisition
N71-36990
- CLOUD SEEDING**
- Development, testing, and utilization of silver iodide pyrotechnic cloud seeding system
[ESSA-TM-EHLT-APCL-5] N71-36985
- CLOUDS (METEOROLOGY)**
- Laser technique for runway and slant visibility range, lower cloud boundary and atmospheric damping coefficient
A71-43889
- COASTS**
- Interpretation of color infrared photography of Florida tidewater coastline
[AD-727630] N71-37924
- COCKPITS**
- Pilot performance in recognizing electronic display systems under varying dazzle and color conditions in cockpits
[RAE-LIB-TRANS-1545] N71-37621
- Environmental and performance tests of voice initiated cockpit control and interrogation system
[AD-727574] N71-37723
- COLLISION AVOIDANCE**
- Analysis of problems and requirements for nonvisual formation flight of helicopters
[AD-727635] N71-37610
- COMBUSTION**
- Supersonic combustion chemistry and mixing of high energy density fuels related to advanced air-breathing engine design, using boron particles
[AD-727782] N71-38530
- COMBUSTION CHAMBERS**
- Operating variables effect on pollutant exhaust from jet aircraft turbine engines, discussing combustor design techniques for emissions reduction
A71-43600
- Textbook on combustion chambers of gas turbine engines
[AD-727960] N71-38542
- Combustion efficiency and performance of swirl can modules under conditions simulating operation of 10,000 pound thrust lift engine for vertical takeoff
[NASA-TN-D-6542] N71-38767
- COMBUSTION EFFICIENCY**
- Combustion efficiency and performance of swirl can modules under conditions simulating operation of 10,000 pound thrust lift engine for vertical takeoff
[NASA-TN-D-6542] N71-38767
- COMBUSTION PRODUCTS**
- Condensate particle crystallization retardation effect on energy characteristics of jet engine, calculating nonequilibrium flows of two phase combustion products in nozzle
A71-45004
- COMBUSTION VIBRATION**
- Aerodynamic combustion noise generation from premixed or diffusion open turbulent flames, using fluid mechanics and Lighthill method
A71-43448
- COMMERCE**
- Growth rate of US air cargo markets - tables
N71-38794
- COMMERCIAL AIRCRAFT**
- Corporate aircraft operations in Latin America, discussing communication and navigation, fuel, paper work, food, vaccinations and weather
A71-43391
- Survey of domestic air passenger trip length including number of passengers and aircraft types
N71-38795
- COMPRESSED GAS**
- Some aspects of propulsion for augmentor wind concept
[NASA-TT-F-14005] N71-38535
- COMPRESSIBLE FLOW**
- Compressible flow across shaft face seals and narrow slots, examining fluid inertia, viscous friction and entrance losses
A71-43592
- Streamline curvature analysis of compressible subsonic, transonic and supersonic cascade flows in axial turbine blades
A71-44347
- COMPRESSOR ROTORS**
- Visualized flow patterns of airflow in centrifugal rotors with thin plate blading and with thick airfoil blades
[ME-238] N71-36410
- Performance tests and efficiency measurement of hub-slit-suction stator in single stage compressor
[NASA-CR-120802] N71-37836
- COMPUTER PROGRAMMING**
- Computer program development for potential flow calculation about lifting bodies
[AD-727628] N71-37597
- Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines
N71-37742
- Advanced avionic digital computer development program
[AD-727607] N71-37765
- Digital computer bibliography, programming techniques and applications, and software standardization and reliability
[AD-727605] N71-37766
- Conversion of computational algorithms for decreasing length of word format of control computers for aircraft
[AD-727917] N71-37772
- Computer program for analyzing and simulating attack of low flying aircraft by antiaircraft missiles and probability of aircraft survival
[RAE-LIB-TRANS-1578] N71-37774
- COMPUTER PROGRAMS**
- Computer program for numerical integration of downwash subsonic flow about rectangular planforms, for different aspect ratios
[NPL-MA-99] N71-36405

COMPUTER TECHNIQUES

SUBJECT INDEX

- Digital computer bibliography, programming techniques and applications, and software standardization and reliability
[AD-727605] N71-37766
- COMPUTER TECHNIQUES**
- IBM 9020 multiprocessing computer application to ATC, discussing control sectors for inflight control at air route traffic control centers in U.S.
A71-43888
- Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines
N71-37742
- Computerized real time data processing and display system for air traffic control in airspace over Belgium, Luxemburg, the Netherlands, and Germany
N71-37744
- COMPUTERIZED SIMULATION**
- Computer program for calculating lift interference factors of wind tunnel test sections by vortex lattice method
[TAE-124] N71-36407
- Simulation of aircraft ground operations for Dallas-Fort Worth Regional Airport
N71-37607
- CONDENSATES**
- Condensate particle crystallization retardation effect on energy characteristics of jet engine, calculating nonequilibrium flows of two phase combustion products in nozzle
A71-45004
- CONFERENCES**
- Corporate aircraft safety - Conference, Washington, D.C. April 1971
A71-43226
- Corporate aircraft safety - Conference, San Antonio, May 1970
A71-43379
- Photogrammetry of moving objects - Conference, Saint-Mande, France, September 1970
A71-43586
- Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines
N71-37742
- CONGRESS**
- Convention for suppression of unlawful aircraft seizure and article by article analysis
N71-37590
- CONICAL BODIES**
- Magnus force and moment data for standard 10 degree cone calibration model as determined in supersonic wind tunnel
[SC-DC-71-3821] N71-36688
- CONICAL FLOW**
- Approximate solution for position and strength of shock waves about cones in steady supersonic flow
A71-44624
- Method of lines technique for computing flow field about conical configurations at incidence in supersonic flow
[NASA-TR-R-374] N71-36697
- CONTAMINANTS**
- Computing dispersal of atmospheric pollutants near airports by use of mean wind and temperature profiles
[NASA-CR-111962] N71-36720
- CONTROL EQUIPMENT**
- Analysis of criteria for survivable flight control system using fly-by-wire and integrated actuator package techniques
[AD-727762] N71-37616
- CONTROL STABILITY**
- Active flutter mode control system synthesis for flight test, showing mass balancing as possible artificial symmetrical wing destabilization
A71-44106
- CONTROL SURFACES**
- Control surfaces and direct jet force flutter suppression system shown to increase flutter speed of wing
A71-44108
- CONTROL THEORY**
- Algorithm for dual compromise control problems arising from each subsystem of inner level in multilevel static hierarchical system
- Trends in automatic control field in last two decades, emphasizing optimal control and performance criteria selection
[AIAA PAPER 71-1001] A71-44591
- CONTROLLABILITY**
- SST handling qualities, takeoff speeds and performance evaluation on six degree of freedom flight simulator
A71-42922
- CONVECTIVE FLOW**
- Radar observation of convective process in clear air, presenting turreted top cell contour tracings from PPI sequence
A71-43088
- COORDINATE TRANSFORMATIONS**
- Transonic flows about two dimensional airfoils, calculating far field boundary conditions with coordinate transformation
A71-44620
- CORRELATION**
- Correlation system of equations for mathematical expectations and phase coordinate correlation moments for accuracy analysis in flight vehicle dynamics problems
A71-44692
- Tests on scale model configurations of C-5 aircraft to obtain data correlation on three transonic wind tunnels
[AD-727006] N71-36408
- CORROSION**
- Aircraft parts damage by corrosive friction forces, hot gases and intercrystalline attack, noting worn universal joint and blade grain boundary damage
A71-44574
- Structural analysis of corrugated aircraft wing skin panels to determine effects of corrosion damage
[AD-728009] N71-37619
- CORROSION TESTS**
- Nondestructive detection of hot corrosion-sulfidation in U.S. Navy aircraft turbine engines
A71-45280
- COST ANALYSIS**
- Adaptive guaranteed cost control for systems with parametric variation, demonstrating system stability and airframe pitch control
A71-44111
- Cost ownership analysis of avionic equipment
N71-36784
- Performance and costs of nuclear aircraft used in transoceanic commerce
[NASA-TM-X-2386] N71-38277
- COST EFFECTIVENESS**
- Civil transport aircraft and equipment maintenance and reliability problems solutions with best time, cost and weight compromises
A71-44765
- Cost effectiveness, failure analysis, and design techniques for measuring reliability of avionics systems
[AGARD-LS-47-71] N71-36776
- Cost effectiveness of built in test provisions in aircraft operations
N71-36780
- COST ESTIMATES**
- Comparison of logistics problems and cost aspects in selection of aircraft for earth resources surveys
[NASA-TM-X-2418] N71-37928
- COST REDUCTION**
- Aircraft part repair-throwaway decisions for minimizing costs over life cycle by economic graphic screening techniques
A71-43197
- CRASH LANDING**
- Airport crash fire fighting equipment requirements and rescue operations
A71-43389
- CROSS SECTIONS**
- Computer program for calculating lift interference factors of wind tunnel test sections by vortex lattice method
[TAE-124] N71-36407
- CRYSTALLIZATION**
- Condensate particle crystallization retardation effect on energy characteristics of jet engine, calculating nonequilibrium flows of two phase combustion products in nozzle
A71-45004

CYLINDRICAL BODIES

Drag coefficient measurements in flow around rectangular cylinders
[IC-AERO-71-15] N71-36695

D

DAMAGE

Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969
[NTSB-ARC-71-1] N71-36437

DATA REDUCTION

Corporate aircraft 1970 accident statistics analysis stressing pilot selection, training and supervision
A71-43227

DATA SMOOTHING

Suboptimal fixed point data smoothing algorithm for parameter and initial state estimation of nonlinear dynamic systems
A71-44113

DATA SYSTEMS

Performance evaluation of automatic flight progress strip cutter and loader used in air traffic control facility
[ACTEU-330] N71-38215

DECISION MAKING

Aircraft part repair-throwaway decisions for minimizing costs over life cycle by economic graphic screening techniques
A71-43197

Computer-aided decision algorithm for ATC problem in near terminal area, emphasizing scheduling and holding strategies
A71-44105

DEGREES OF FREEDOM

Single degree of freedom roll response due to vertical random two dimensional vertical gusts
[NASA-CR-111966] N71-36421

DELTA WINGS

Slender two dimensional wedge wings aerodynamic characteristics in hypersonic strong interaction flow, determining wall shear stress and lift drag ratio effects
A71-44621

Wind tunnel static longitudinal stability and control characteristics of cruciform delta winged missile with various horizontal canards and trailing-edge flap control between Mach 1.50 and 4.63
[NASA-TN-X-2367] N71-36415

Methods for prediction of centerline shock layer thickness and pressure distribution on delta wing body configurations
[NASA-TN-D-6550] N71-36418

Hypersonic wind tunnel test of two delta wing orbiter models
[NASA-CR-119984] N71-38668

DEPTH MEASUREMENT

Shallow ocean depth measurements by aerial photographs of wave refraction and wavelength changes and by multispectral scanning of wave reflection
[NASA-CR-123194] N71-37862

DESERTS

Airborne remote sensing of Mojave Desert playas for use as natural landing areas
[AD-727031] N71-36748

DB 121 AIRCRAFT

European automatic flight control systems for landing in category IIIA conditions, discussing triplex system in Trident and simplex in Caravelle
A71-44456

DIFFUSION PLANES

Aerodynamic combustion noise generation from premixed or diffusion open turbulent flames, using fluid mechanics and Lighthill method
A71-43448

DIGITAL COMPUTERS

Digital computer bibliography, programming techniques and applications, and software standardization and reliability
[AD-727605] N71-37766

DIGITAL NAVIGATION

Range and azimuth resolution characteristics and aircraft separation measurement capability of radar beacon-digitizer subsystem
[FAA-NA-71-16] N71-37038

Advanced avionic digital computer development program
[AD-727607] N71-37765

DIGITAL SIMULATION

Digital simulation and implementation techniques for Doppler radar altimeter signal processing
[NASA-CR-1776] N71-36548

DIGITAL TECHNIQUES

Digital algorithm for automatic aircraft engine monitoring system, using Boolean algebra and events/states theory
A71-43897

DISPLAY DEVICES

Integrated system for aircraft control and operation with visualization and manual regulation techniques, emphasizing interconnections with onboard electronic equipment
A71-44353

Airborne traffic situation display system for use with radar control terminal system
[AD-727769] N71-37042

Pilot performance in recognizing electronic display systems under varying dazzle and color conditions in cockpits
[RAE-LIB-TRANS-1545] N71-37621

Pilot transition from conventional visual cross pointer display to aural glide slope cues
[FAA-AM-71-24] N71-37682

DISTANCE

Survey of domestic air passenger trip length including number of passengers and aircraft types
N71-38795

DITCHING (LANDING)

Aircraft ditching and flying personnel survival, stressing passenger briefing and crew jacket equipment with VHF transceiver for rescue operations coordination
A71-43229

DOPPLER NAVIGATION

Techniques for aerial time-lapse cloud photographic analysis, Doppler navigation data analysis, and photogrammetric data acquisition
N71-36990

DOPPLER RADAR

Digital simulation and implementation techniques for Doppler radar altimeter signal processing
[NASA-CR-1776] N71-36548

DOWNWASH

Subsonic force effect calculations on rectangular wings, using downwash velocity potential method
A71-44613

Computer program for numerical integration of downwash subsonic flow about rectangular planforms, for different aspect ratios
[NPL-NA-99] N71-36405

DRAG MEASUREMENT

Pressure distributions and drag coefficients of 18 constant length and volume slender bodies of revolution at zero incidence for Mach numbers 2.0 to 12.0 - graphs
[NASA-TN-D-6536] N71-36416

Drag coefficient measurements in flow around rectangular cylinders
[IC-AERO-71-15] N71-36695

Comparison of blockage corrections in porous tunnel wall to closed wall tunnel at subsonic Mach numbers
[ARA-19] N71-37853

DUCTED FANS

Low speed wind tunnel measurements correction for acoustic effects due to fan noise propagation
A71-44763

DYES

Development of operational system for measuring ocean surface current from aircraft using floats and fluorescent dyes
[AD-726568] N71-37922

DYNAMIC CHARACTERISTICS

Suboptimal fixed point data smoothing algorithm for parameter and initial state estimation of nonlinear dynamic systems
A71-44113

Transient dynamic characteristics of aircraft under unsteady flight, using Laplace-Carson integral transforms
A71-45016

DYNAMIC LOADS

Longitudinal stability of plate-like load towed beneath helicopter in horizontal forward flight

Equations of motion for elastic plate foundation system under dynamic load applied to aircraft landing A71-44346

DYNAMIC PROGRAMMING N71-37543

Stochastic optimal control theory application to airplane rescheduling model, obtaining dynamic programming algorithm for optimal landing and takeoff rules

DYNAMIC RESPONSE A71-44104

Lifting rotors aerodynamic damping in forward flight, describing methods for blade response variance matrix computation A71-44559

E

EARTH RESOURCES PROGRAM

Remote aerial sensing and automatic mapping for forest resources information system [NASA-CR-122922] N71-36770

EARTH RESOURCES SURVEY AIRCRAFT

Comparison of logistics problems and cost aspects in selection of aircraft for earth resources surveys [NASA-TM-X-2418] N71-37928

ECONOMIC ANALYSIS

Aircraft part repair-throwaway decisions for minimizing costs over life cycle by economic graphic screening techniques A71-43197

ECONOMIC FACTORS

Weather interruption effects on air transportation operations and economics, considering fog, snow, freezing rain, thunderstorms, winds, CAT and runway conditions A71-44983

EFFECTIVENESS

Effectiveness of reliability programs for avionic equipment N71-36779

ELASTIC PROPERTIES

Equations of motion for elastic plate foundation system under dynamic load applied to aircraft landing N71-37543

ELECTRONIC EQUIPMENT

Integrated system for aircraft control and operation with visualization and manual regulation techniques, emphasizing interconnections with onboard electronic equipment A71-44353

EMISSION

Stratified charge engine tests to determine exhaust emission characteristics [AD-727745] N71-38760

ENGINE DESIGN

Supersonic combustion chemistry and mixing of high energy density fuels related to advanced air-breathing engine design, using boron particles [AD-727782] N71-38530

Analysis of gas turbine design and application to aircraft operation with description of components, safety factors, and vibration problems [AD-727188] N71-38538

ENGINE FAILURE

In-flight monitoring of aircraft turbine engine reliability A71-43233

ENGINE MONITORING INSTRUMENTS

Digital algorithm for automatic aircraft engine monitoring system, using Boolean algebra and events/states theory A71-43897

ENGINE PARTS

Supersonic propulsion system inlet, engine and exhaust nozzle in wind tunnel and flight tests, discussing boundary layer effects on performance A71-43599

ENGINE TESTS

Condensate particle crystallization retardation effect on energy characteristics of jet engine, calculating nonequilibrium flows of two phase combustion products in nozzle A71-45004

Test bed engine studies of overall excess air ratio permissible deviation, obtaining diagram for constraints calculation

ENVIRONMENT POLLUTION A71-45022

Environment degradation relation to technology, discussing priorities [AIAA PAPER 71-1016] A71-44597

Impact of air activity on environment and federal interest in environmental studies N71-38792

ENVIRONMENTAL CONTROL

Environment degradation relation to technology, discussing priorities [AIAA PAPER 71-1016] A71-44597

SST operation climatic impact assessment program, considering carbon dioxide, water vapor, contrails, particulates, nitrogen oxides and carbon monoxide A71-44982

ENVIRONMENTAL ENGINEERING

Computing dispersal of atmospheric pollutants near airports by use of mean wind and temperature profiles [NASA-CR-111962] N71-36720

ENVIRONMENTAL TESTS

Development, testing, and utilization of silver iodide pyrotechnic cloud seeding system [ESSA-TM-ERLTM-APCL-5] N71-36985

Environmental and performance tests of voice initiated cockpit control and interrogation system [AD-727574] N71-37723

ENVIRONMENTS

Impact of air activity on environment and federal interest in environmental studies N71-38792

EQUATIONS OF MOTION

Equations of motion for elastic plate foundation system under dynamic load applied to aircraft landing N71-37543

ERROR ANALYSIS

Correlation system of equations for mathematical expectations and phase coordinate correlation moments for accuracy analysis in flight vehicle dynamics problems A71-44692

ESTIMATES

Reliability estimation, including failure effect analysis of avionic systems N71-36777

Manual for development of needs estimates and capital improvement programs for airports and other intercity terminals for 1970 to 1990 [OMB-04-S71002] N71-37824

ESTIMATING

Wind tunnel interference estimation for model design applications using chart method [NASA-TN-D-6416] N71-36675

EXHAUST GASES

Operating variables effect on pollutant exhaust from jet aircraft turbine engines, discussing combustor design techniques for emissions reduction A71-43600

Sampling, handling, and measuring emissions from aircraft gas turbine engines [REPT-430] N71-37604

Stratified charge engine tests to determine exhaust emission characteristics [AD-727745] N71-38760

EXHAUST NOZZLES

Supersonic propulsion system inlet, engine and exhaust nozzle in wind tunnel and flight tests, discussing boundary layer effects on performance A71-43599

Exhaust jet mixing flow nozzles with peak axial velocity degradation for noise suppression [NASA-TM-X-67934] N71-37378

EXTERNAL STORES

Active feedback wing/store flutter control for fighter aircraft, using computer programs based on frequency and time domains for linear analysis A71-44109

F

F-4 AIRCRAFT

Hydraulic power and actuation requirements of survivable flight control system utilizing fly by wire control for F-4 aircraft [AD-727763] N71-37608

F-8 AIRCRAFT

Mathematical modeling of F-8 aircraft wave off trajectories for aircraft carrier approaches
[AD-727121] N71-36439

FAILURE ANALYSIS

Cost effectiveness, failure analysis, and design techniques for measuring reliability of avionics systems
[AGARD-LS-47-71] N71-36776
Reliability estimation, including failure effect analysis of avionic systems
N71-36777

FAR FIELDS

Transonic flows about two dimensional airfoils, calculating far field boundary conditions with coordinate transformation
A71-44620

FATIGUE LIFE

Variability of aluminum alloy aircraft structure fatigue life under symmetric and asymmetric loads
[ARL/SM-REPORT-329] N71-37524

FATIGUE TESTS

Design data for regeneratively cooled panels from low cycle fatigue evaluation of Hastelloy X and Inconel 625 sheet and sandwich panel specimens
[NASA-CR-1884] N71-38734

FEEDBACK CONTROL

Stability augmentation system for aircraft elastic modes control, discussing active flutter suppression technology
A71-44107
Active feedback wing/store flutter control for fighter aircraft, using computer programs based on frequency and time domains for linear analysis
A71-44109
Adaptive guaranteed cost control for systems with parametric variation, demonstrating system stability and airframe pitch control
A71-44111
Automatic flight control systems, discussing pilot as systems manager or retained in control loop
A71-44454

FIELD EFFECT TRANSISTORS

Breadboard models of silicon carbide junction field effect transistor amplifiers
[AD-727761] N71-37792

FIGHTER AIRCRAFT

Active feedback wing/store flutter control for fighter aircraft, using computer programs based on frequency and time domains for linear analysis
A71-44109
wind tunnel performance characteristics of single-engine fighter model fitted with in-flight thrust reverser
[NASA-TN-D-6460] N71-37384

FINITE ELEMENT METHOD

Leading edge suction of thin aerofoil theory
[ARL/SM-NOTE-360] N71-36399

FIRE FIGHTING

Airport crash fire fighting equipment requirements and rescue operations
A71-43389

FIRE PREVENTION

Simulated JP-4 jet fuel fire tests of high temperature cabin pressure sealant and insulating plastics and rubbers
[FAA-NA-71-22] N71-38149

FIXED POINTS (MATHEMATICS)

Suboptimal fixed point data smoothing algorithm for parameter and initial state estimation of nonlinear dynamic systems
A71-44113

FLAPS (CONTROL SURFACES)

Sailplane circling cross-country speed increase by variable geometry in high lift flap form for better compromise between cruise and climb performance
A71-44342

Aerodynamic characteristics of twin jet, swept wing fighter aircraft model with leading edge Kreuger flaps at subsonic speeds
[NASA-TN-X-2325] N71-36426

FLARED BODIES

Flare induced laminar boundary layer/shock wave interactions on axisymmetric bodies at zero incidence in supersonic flow under adiabatic conditions
A71-44604

FLAT PLATES

Vortex shedding from blunt trailing edge of flat plate spanning wind tunnel under oscillating flap and acoustic resonance excitations
A71-44558

FLEXIBILITY

Analytical investigation of effects of blade flexibility, unsteady aerodynamics, and variable inflow on helicopter rotor stall characteristics
[NASA-CR-1769] N71-36404

FLEXIBLE WINGS

Flexible ram air inflated keel and leading edge parawing design optimization for increased stability and reliability, introducing semirigid member concept
[AIAA PAPER 71-986] A71-44582

FLIGHT CHARACTERISTICS

Flight dynamics and calculation of flight trajectories of various aircraft and spacecraft
[AD-727474] N71-37602

FLIGHT CONTROL

Minimum order state vector reconstruction linear filters for constant plants optimal control, applying to aircraft flight multiple control-point problem
A71-44077

Stability augmentation system for aircraft elastic modes control, discussing active flutter suppression technology
A71-44107

Technology developments in rotor, drive, flight controls and cargo handling systems of heavy lift helicopter system, noting military and commercial applications
[AIAA PAPER 71-994] A71-45296

STOL aircraft flight control problems, discussing Mach trim, artificial feel, stability, feedback system responses and lateral/directional laws
[AIAA PAPER 71-993] A71-45297

Hydraulic power and actuation requirements of survivable flight control system utilizing fly by wire control for F-4 aircraft
[AD-727763] N71-37608

Analysis of criteria for survivable flight control system using fly-by-wire and integrated actuator package techniques
[AD-727762] N71-37616

FLIGHT INSTRUMENTS

Pressure altimeter, airspeed and vertical velocity instruments, discussing selection, installation, pilot verification, error identification, repair and use
A71-43385

FLIGHT MECHANICS

Correlation system of equations for mathematical expectations and phase coordinate correlation moments for accuracy analysis in flight vehicle dynamics problems
A71-44692

Flight dynamics of noise optimal flight profiles for V/STOL aircraft, minimization of gust effects on aircraft and nonlinear dynamic stability of parachute-load systems
A71-44761

FLIGHT PATHS

Prop rotor and lift fan VTOL aircraft ground noise level reduction, using flight trajectory management
[AIAA PAPER 71-991] A71-45295

FLIGHT RECORDERS

Performance evaluation of automatic flight progress strip cutter and loader used in air traffic control facility
[ACTEU-330] N71-38215

FLIGHT SAFETY

Aircraft ditching and flying personnel survival, stressing passenger briefing and crew jacket equipment with VHF transceiver for rescue operations coordination
A71-43229

FLIGHT SIMULATORS

Motion cue and simulation fidelity aspects of validation of general purpose airborne simulator
[NASA-TN-D-6432] N71-36672

Flight simulator for studying problems of aircraft during approaches and landings at night under category 2 visual conditions
[RAE-TN-AVIONICS-59 (BLEU)] N71-37606

FLIGHT STABILITY TESTS

SUBJECT INDEX

- Analysis and validation of characteristics of general purpose airborne simulator for simulation of aerodynamic characteristics of large transport aircraft
[NASA-TN-D-6431] N71-37823
- FLIGHT STABILITY TESTS**
Transient dynamic characteristics of aircraft under unsteady flight, using Laplace-Carson integral transforms A71-45016
- FLIGHT TESTS**
Flight test measurements for improved estimates of aircraft states and aerodynamic parameters, using relinearized Kalman filter A71-44089
- Active flutter mode control system synthesis for flight test, showing mass balancing as possible artificial symmetrical wing destabilization A71-44106
- Folding sidewall aircraft tires design, construction and flight tests, noting advantages and disadvantages A71-44975
- Guide to private and commercial multiengine aircraft pilot certification [FAA-AC-61-4C] N71-36438
- FLIGHT TRAINING**
Corporate aircraft pilot ground and flight phase training, errors and accidents A71-43388
- FLIGHT VEHICLES**
Correlation system of equations for mathematical expectations and phase coordinate correlation moments for accuracy analysis in flight vehicle dynamics problems A71-44692
- FLOATS**
Development of operational system for measuring ocean surface current from aircraft using floats and fluorescent dyes [AD-726568] N71-37922
- FLORIDA**
Interpretation of color infrared photography of Florida tidewater coastline [AD-727630] N71-37924
- FLOW CHARACTERISTICS**
Compressors and turbines centripetal stages operational characteristics, investigating airflow rate and pressure ratio effects on power A71-45380
- Computer program development for potential flow calculation about lifting bodies [AD-727628] N71-37597
- FLOW DISTRIBUTION**
Drag coefficient measurements in flow around rectangular cylinders [IC-ABRO-71-15] N71-36695
- Factors effecting volume from which data originate in laser Doppler velocimeter dual scatter probe [AD-727005] N71-36845
- FLOW GEOMETRY**
Flow angularity prediction near supersonic fuselage forebody with arbitrary cross section and zero sideslip, using small perturbation theory [AIAA PAPER 71-996] A71-44588
- FLOW MEASUREMENT**
Helicopter, tilt wing and jet lift hovering aircraft outflow measurements to determine suitability as rescue vehicles [AIAA PAPER 71-992] A71-44586
- FLOW STABILITY**
Aerodynamic sound radiation from lifting surfaces in smooth and turbulent flow [NASA-CR-114370] N71-36422
- FLOW VISUALIZATION**
Photogrammetric recording of helicopter rotor induced aerodynamic effects using wind tunnel test smoke visualization technique A71-43588
- FLOWMETERS**
Factors effecting volume from which data originate in laser Doppler velocimeter dual scatter probe [AD-727005] N71-36845
- FLUID AMPLIFIERS**
Fluid amplifiers theory and use as temperature and pressure sensors, discussing applications in chemical and ammunition industries and jet aircraft control [IEEE PAPER 70-TP-120-IGA] A71-42921
- FLUORESCENCE**
Development of operational system for measuring ocean surface current from aircraft using floats and fluorescent dyes [AD-726568] N71-37922
- FLUTTER ANALYSIS**
Active flutter mode control system synthesis for flight test, showing mass balancing as possible artificial symmetrical wing destabilization A71-44106
- Stability augmentation system for aircraft elastic modes control, discussing active flutter suppression technology A71-44107
- Control surfaces and direct jet force flutter suppression system shown to increase flutter speed of wing A71-44108
- Active feedback wing/store flutter control for fighter aircraft, using computer programs based on frequency and time domains for linear analysis A71-44109
- FLY-BY-WIRE CONTROL**
Hydraulic power and actuation requirements of survivable flight control system utilizing fly-by-wire control for F-4 aircraft [AD-727763] N71-37608
- Analysis of criteria for survivable flight control system using fly-by-wire and integrated actuator package techniques [AD-727762] N71-37616
- FOLDING STRUCTURES**
Folding sidewall aircraft tires design, construction and flight tests, noting advantages and disadvantages A71-44975
- FORCE DISTRIBUTION**
Control surfaces and direct jet force flutter suppression system shown to increase flutter speed of wing A71-44108
- FOREBODIES**
Flow angularity prediction near supersonic fuselage forebody with arbitrary cross section and zero sideslip, using small perturbation theory [AIAA PAPER 71-996] A71-44588
- FORECASTING**
Freight, express, and mail tonnage forecasts for domestic airline operations N71-38793
- FORESTS**
Remote aerial sensing and automatic mapping for forest resources information system [NASA-CR-122922] N71-36770
- FRACTIONATION**
Aviation fuels lubricating characteristics, discussing refining methods, viscosity, service performance and load testing A71-45383
- FRICTION FACTOR**
Aircraft parts damage by corrosive friction forces, hot gases and intercrystalline attack, noting worn universal joint and blade grain boundary damage A71-44574
- FUEL COMBUSTION**
Combustion characteristics of gas turbine aircraft engines [AD-727175] N71-37387
- FUEL-AIR RATIO**
Test bed engine studies of overall excess air ratio permissible deviation, obtaining diagram for constraints calculation A71-45022
- FUSELAGES**
Flow angularity prediction near supersonic fuselage forebody with arbitrary cross section and zero sideslip, using small perturbation theory [AIAA PAPER 71-996] A71-44588
- Aircraft fuselage antisymmetric loading strain effects on small aspect delta wing performance A71-45018
- Ideal weight of axisymmetric fuselage shells, taking into account load distribution and cabin pressurization A71-45180

G

GALACTIC RADIATION

Jet aircraft measurements of galactic cosmic radiation dose and comparison with theoretical values for supersonic flights
[UCRL-20209] N71-38552

GAS DISSOCIATION

Nitrous oxide dissociation as natural source of stratospheric nitric oxide, noting estimates use as yardstick for artificial source
A71-43347

GAS FLOW

Analysis of maximum internal efficiency of single impulse stage of turbine engine
[NLL-CE-TRANS-5631-(9022.09)] N71-36704

GAS LUBRICANTS

Analysis and tests of self-acting mainshaft seals to provide gas film lubrication for advanced gas turbine engines
[NASA-CR-72987] N71-38022

GAS TURBINE ENGINES

Temperature field profiling along radius in front of gas turbine stage, applying to regeneratively cooled turbine engine
A71-45011

Combustion characteristics of gas turbine aircraft engines
[AD-727175] N71-37387

Sampling, handling, and measuring emissions from aircraft gas turbine engines
[REPT-430] N71-37604

Technical aviation handbook covering aircraft maintenance, navigation aids, airframes, lubricants, piston and gas turbine engines, and checkout procedures
[AD-727195] N71-37613

Analysis and tests of self-acting mainshaft seals to provide gas film lubrication for advanced gas turbine engines
[NASA-CR-72987] N71-38022

Design and performance characteristics of gas turbine engines for helicopters
[AD-727959] N71-38541

Textbook on combustion chambers of gas turbine engines
[AD-727960] N71-38542

GAS TURBINES

Heavy load transportation Mi 12 helicopter design and performance, noting gas turbine rigid shaft connection
A71-42926

Design and tests of high temperature, air cooled radial turbine configurations
[AD-726466] N71-37381

GELLED PROPELLANTS

Determination of physical and chemical properties of fuels gelled with carbohydrate resins to evaluate effectiveness in reducing aircraft fire hazards
[FAA-NA-71-18] N71-37369

GENERAL AVIATION AIRCRAFT

Corporate aircraft 1970 accident statistics analysis stressing pilot selection, training and supervision
A71-43227

Corporate aircraft safety - Conference, San Antonio, May 1970
A71-43379

General aviation aircraft altimeter errors, tolerances and static system tests
A71-43386

Corporate aircraft pilot ground and flight phase training, errors and accidents
A71-43388

Aircraft accident briefs for 1969 including date, location, aircraft data, injuries, flight purpose, and pilot data
[NTSB-BA-71-2] N71-36433

GEOLOGY

Quantity and quality of geodetic information transmitted by space photography compared with low altitude aerial photography
[IR-USGS-229] N71-38013

GLIDERS

High lift device application to high performance competition gliders, considering merit of design for conflicting climb/cruise requirements
A71-43089

Sailplane circling cross-country speed increase by variable geometry in high lift flap form for better compromise between cruise and climb performance
A71-44342

GOALS

National Science Council goals in low speed aerodynamics - Canada
N71-38627

GOVERNMENTS

Impact of air activity on environment and federal interest in environmental studies
N71-38792

GRAIN BOUNDARIES

Aircraft parts damage by corrosive friction forces, hot gases and intercrystalline attack, noting worn universal joint and blade grain boundary damage
A71-44574

GRAPHS (CHARTS)

Pressure distributions and drag coefficients of 18 constant length and volume slender bodies of revolution at zero incidence for Mach numbers 2.0 to 12.0 - graphs
[NASA-TN-D-6536] N71-36416
Wind tunnel interference estimation for model design applications using chart method
[NASA-TN-D-6416] N71-36675
Graphs and tables of aircraft traffic over North America - 1966 through 1969
[RAE-LIB-TRANS-1580] N71-38210

GROUND EFFECT MACHINES

One dimensional channel flow theory for designing ram wing surface effect vehicle
[AD-727774] N71-36419

GROUND STATIONS

Development and characteristics of lightweight, mobile structures for aircraft storage and maintenance
[AD-727056] N71-36674

GROUND SUPPORT EQUIPMENT

Mobile LF air navigation AN/MRN-13 equipment, operation and maintenance
A71-43878
Simulation of aircraft ground operations for Dallas-Fort Worth Regional Airport
N71-37607

GUIDE VANES

Axial flow compressors stable operation, using rotating guide vanes regulation
A71-43554

Noise reduction studies involving variable geometry inlet guide vanes for choking using two-sector cascade apparatus with three inlet configurations
[NASA-TN-X-2392] N71-37601

GUST LOADS

Flight dynamics of noise optimal flight profiles for V/STOL aircraft, minimization of gust effects on aircraft and nonlinear dynamic stability of parachute-load systems
A71-44761

Single degree of freedom roll response due to vertical random two dimensional vertical gusts
[NASA-CR-111966] N71-36421

GYROSCOPES

Astatic gyroscope mounted on aircraft moving arbitrarily near earth surface, obtaining integrals of kinematic equations
A71-45160

H

HANDBOOKS

Guide to private and commercial multiengine aircraft pilot certification
[FAA-AC-61-4C] N71-36438
Aerodynamic calculations in designing axial compressors with emphasis on compressors of stationary installations - handbook
[AD-727191] N71-38032

Design and performance characteristics of gas turbine engines for helicopters
[AD-727959] N71-38541

HANGARS

Development and characteristics of lightweight, mobile structures for aircraft storage and maintenance
[AD-727056] N71-36674

HASTELLOY (TRADEMARK)

Design data for regeneratively cooled panels from

HELICOPTER CONTROL

SUBJECT INDEX

- low cycle fatigue evaluation of Hastelloy X and Inconel 625 sheet and sandwich panel specimens [NASA-CR-1884] N71-38734
- HELICOPTER CONTROL**
- Helicopter optimal autorotation landing parameters for touchdown at zero speed, including rotor rpm drop due to flow separation on blades A71-43090
- Analysis of problems and requirements for nonvisual formation flight of helicopters [AD-727635] N71-37610
- HELICOPTER DESIGN**
- Heavy load transportation Mi 12 helicopter design and performance, noting gas turbine rigid shaft connection A71-42926
- Technology developments in rotor, drive, flight controls and cargo handling systems of heavy lift helicopter system, noting military and commercial applications [AIAA PAPER 71-994] A71-45296
- HELICOPTER ENGINES**
- Design and performance characteristics of gas turbine engines for helicopters [AD-727959] N71-38541
- HELICOPTER PERFORMANCE**
- Heavy load transportation Mi 12 helicopter design and performance, noting gas turbine rigid shaft connection A71-42926
- HELICOPTERS**
- Longitudinal stability of plate-like load towed beneath helicopter in horizontal forward flight A71-44346
- Helicopter, tilt wing and jet lift hovering aircraft outflow measurements to determine suitability as rescue vehicles [AIAA PAPER 71-992] A71-44586
- Principles of helicopter flight including flight stability [AD-726841] N71-36429
- Analysis of problems and requirements for nonvisual formation flight of helicopters [AD-727635] N71-37610
- HIERARCHIES**
- Algorithm for dual compromise control problems arising from each subsystem of inner level in multilevel static hierarchical system A71-44393
- HIGH TEMPERATURE GASES**
- Aircraft parts damage by corrosive friction forces, hot gases and intercrystalline attack, noting worn universal joint and blade grain boundary damage A71-44574
- HIGH TEMPERATURE TESTS**
- Simulated JP-4 jet fuel fire tests of high temperature cabin pressure sealant and insulating plastics and rubbers [FAA-NA-71-22] N71-38149
- HORIZONTAL FLIGHT**
- Longitudinal stability of plate-like load towed beneath helicopter in horizontal forward flight A71-44346
- Tu-134 aerodynamic characteristics during takeoff, climb, horizontal flight, landing stability and maneuverability, and strength under various loads [AD-727196] N71-37612
- HOT-WIRE ANEMOMETERS**
- Hot-wire anemometer measurements of streamwise magnitudes and normal velocity components of wing tip vortex [NASA-TN-X-62087] N71-36679
- HOVERING**
- Helicopter, tilt wing and jet lift hovering aircraft outflow measurements to determine suitability as rescue vehicles [AIAA PAPER 71-992] A71-44586
- HYDRAULIC EQUIPMENT**
- Hydraulic power and actuation requirements of survivable flight control system utilizing fly by wire control for F-4 aircraft [AD-727763] N71-37608
- HYDRAULIC TEST TUNNELS**
- Design, construction, and performance of water tunnel for two dimensional testing of pitching airfoils [D180-14130-1] N71-37827
- HYDROCARBON FUELS**
- Liquid hydrogen as future replacement for hydrocarbon fuels in surface and air transportation, noting advantages in energy per unit weight and pollution-free combustion A71-44365
- HYDROGEN FUELS**
- Liquid hydrogen as future replacement for hydrocarbon fuels in surface and air transportation, noting advantages in energy per unit weight and pollution-free combustion A71-44365
- HYPERSONIC FLOW**
- Slender two dimensional wedge wings aerodynamic characteristics in hypersonic strong interaction flow, determining wall shear stress and lift drag ratio effects A71-44621
- HYPERSONIC WAKES**
- Two dimensional and three dimensional wakes in supersonic and hypersonic rarefied gas wind tunnels, comparing cone and dihedral configurations A71-43357
- HYPERVELOCITY WIND TUNNELS**
- Pressure distributions and drag coefficients of 18 constant length and volume slender bodies of revolution at zero incidence for Mach numbers 2.0 to 12.0 - graphs [NASA-TN-D-6536] N71-36416
- Nozzle design procedure and calculations for hypervelocity wind tunnel including thermodynamic properties of nitrogen and inviscid core and boundary layer calculations [AD-727591] N71-37821
- Hypersonic wind tunnel test of two delta wing orbiter models [NASA-CR-119984] N71-38668
- IBM COMPUTERS**
- IBM 9020 multiprocessing computer application to ATC, discussing control sectors for inflight control at air route traffic control centers in U.S. A71-43888
- ICE FORMATION**
- Arctic ocean pack ice terrain profiling by airborne laser altimeter and coincident photography, analyzing data for ice development stages interpretation A71-44986
- ICE REPORTING**
- Characteristics of sensors for aerial observation of ice formations and comparison of effectiveness of various methods [JPRS-54162] N71-36801
- IMPACT STRENGTH**
- Equations of motion for elastic plate foundation system under dynamic load applied to aircraft landing N71-37543
- IMPACT TESTS**
- Analysis of seaplane impact on planing deadrise in smooth and rough water [AD-727753] N71-37614
- IMPELLERS**
- Swept-back vane impeller tested on low speed centrifugal compressor rig [NRC-12020] N71-37596
- IN-FLIGHT MONITORING**
- In-flight monitoring of aircraft turbine engine reliability A71-43233
- INCOMPRESSIBLE FLOW**
- Lifting rectangular thin airfoil in symmetrical incompressible steady uniform orthogonal flow at small angle of attack, deriving Weissinger integral equation A71-43487
- INCONEL (TRADEMARK)**
- Design data for regeneratively cooled panels from low cycle fatigue evaluation of Hastelloy X and Inconel 625 sheet and sandwich panel specimens [NASA-CR-1884] N71-38734
- INERTIA**
- Compressible flow across shaft face seals and narrow slots, examining fluid inertia, viscous friction and entrance losses A71-43592

INFLATABLE STRUCTURES

Flexible ram air inflated keel and leading edge paraving design optimization for increased stability and reliability, introducing semirigid member concept
[AIAA PAPER 71-986] A71-44582
Design, development, and performance requirements for large rigid airships for freight and cargo transportation
[REPT-5] N71-36425

INJURIES

Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969
[NTSB-ARC-7L-1] N71-36437

INLET NOZZLES

Supersonic propulsion system inlet, engine and exhaust nozzle in wind tunnel and flight tests, discussing boundary layer effects on performance
A71-43599

INSTRUMENT ERRORS

Pressure altimeter, airspeed and vertical velocity instruments, discussing selection, installation, pilot verification, error identification, repair and use
A71-43385
General aviation aircraft altimeter errors, tolerances and static system tests
A71-43386

INSTRUMENT LANDING SYSTEMS

Aeronautical radio navigation aids photo-optical calibration, describing photogrammetric procedure and ground equipment for checking out airport ILS systems
A71-43587

INTEGRAL EQUATIONS

Lifting rectangular thin airfoil in symmetrical incompressible steady uniform orthogonal flow at small angle of attack, deriving Weissinger integral equation
A71-43487

INTERFERENCE DRAG

Conclusions and recommendations concerning wind tunnel tests of interaction between engine flow and wall corrections in transonic wind tunnels
N71-36401
Compilation of responses to questionnaire on engine-airframe interference in transonic tests
N71-36402
Wall corrections for airplanes with interference lift in transonic wind tunnel tests
N71-36403
Thrust-minus-drag forces and pressure distributions of closely spaced twin-jet afterbodies with different inboard-outboard fairing and nozzle shapes
[NASA-TM-X-2329] N71-36412

INTERFERENCE LIFT

Computer program for calculating lift interference factors of wind tunnel test sections by vortex lattice method
[TAE-124] N71-36407

INVISCID FLOW

Nozzle design procedure and calculations for hypervelocity wind tunnel including thermodynamic properties of nitrogen and inviscid core and boundary layer calculations
[AD-727591] N71-37821

ITERATIVE SOLUTION

Technique for improving calibration accuracy standards from boundary layer calculations
[IC/71/23] N71-37851

J**JET AIRCRAFT**

Fluid amplifiers theory and use as temperature and pressure sensors, discussing applications in chemical and ammunition industries and jet aircraft control
[IEEE PAPER 70-TP-120-IGA] A71-42921
Jet aircraft fuel additives covering functions and applications
A71-45325

JET AIRCRAFT NOISE

Acoustic noise output from round interfering subsonic jets, considering suppressor nozzle attenuation
A71-44560

JET ENGINE FUELS

Jet aircraft fuel additives covering functions and applications
A71-45325

JET ENGINES

Condensate particle crystallization retardation effect on energy characteristics of jet engine, calculating nonequilibrium flows of two phase combustion products in nozzle
A71-45004
Stratified charge engine tests to determine exhaust emission characteristics
[AD-727745] N71-38760
Combustion efficiency and performance of swirl can modules under conditions simulating operation of 10,000 pound thrust lift engine for vertical takeoff
[NASA-TN-D-6542] N71-38767

JET FLOW

Resultant aerodynamic forces on circular arc profile with normal jet in subsonic steady compressible flow, using Imai-Lamla approximation method
A71-44271

JET LIFT

Helicopter, tilt wing and jet lift hovering aircraft outflow measurements to determine suitability as rescue vehicles
[AIAA PAPER 71-992] A71-44586

JET MIXING FLOW

Exhaust jet mixing flow nozzles with peak axial velocity degradation for noise suppression
[NASA-TM-X-67934] N71-37378

K**KINEMATIC EQUATIONS**

Astatic gyroscope mounted on aircraft moving arbitrarily near earth surface, obtaining integrals of kinematic equations
A71-45160

L**LAMINAR BOUNDARY LAYER**

Flare induced laminar boundary layer/shock wave interactions on axisymmetric bodies at zero incidence in supersonic flow under adiabatic conditions
A71-44604
Feasibility study of combined laminar and turbulent boundary layer control system using distributed suction with application to low-speed research aircraft of glass reinforced plastic
[AD-727767] N71-37609

LANDING AIDS

Flight simulator for studying problems of aircraft during approaches and landings at night under category 2 visual conditions
[RAE-TM-AVIONICS-59(BLEU)] N71-37606
Aircraft takeoff, navigation, and landing aids, aerodynamics characteristics, and crew rescue equipment
[AD-727860] N71-37618
Evaluation of visual landing aids involving visibility meters and airfield lighting and marking
[NBS-10604] N71-38211

LANDING LOADS

Analysis of seaplane impact on planing deadrise in smooth and rough water
[AD-727753] N71-37614

LASER ALTIMETERS

Arctic ocean pack ice terrain profiling by airborne laser altimeter and coincident photography, analyzing data for ice development stages interpretation
A71-44986

LASER OUTPUTS

Laser technique for runway and slant visibility range, lower cloud boundary and atmospheric damping coefficient
A71-43889

LASERS

Factors effecting volume from which data originate in laser Doppler velocimeter dual scatter probe
[AD-727005] N71-36845

LATEX

Laboratory tests of polymeric latex modified fast-fix C-1 cement for repair of damaged runway

- pavements
[AD-727728] N71-38132
- LAW (JURISPRUDENCE)**
Convention for suppression of unlawful aircraft seizure and article by article analysis N71-37590
- LEADING EDGES**
Leading edge suction of thin aerofoil theory [ARL/SM-NOTE-360] N71-36399
- LEARNING MACHINES**
Canadian National Science Council research in low speed aerodynamics, machine learning, and turbulent jet transducer [DHE/NAE-1971(2)] N71-38626
- LIFT**
Angle of attack instrumentation for evaluating aircraft lift performance and phugoid oscillations A71-43382
Performance prediction and evaluation of propulsion-augmented high lift systems for STOL aircraft, considering weight, thrust and wing loading [AIAA PAPER 71-990] A71-44585
- LIFT AUGMENTATION**
Noise reduction effectiveness of mixer nozzle for increasing lift capability in STOL aircraft [NASA-TN-X-67938] N71-36424
Some aspects of propulsion for augmentor wind concept [NASA-TT-F-14005] N71-38535
- LIFT DEVICES**
High lift device application to high performance competition gliders, considering merit of design for conflicting climb/cruise requirements A71-43089
Sailplane circling cross-country speed increase by variable geometry in high lift flap form for better compromise between cruise and climb performance A71-44342
Aerodynamic sound radiation from lifting surfaces in smooth and turbulent flow [NASA-CR-114370] N71-36422
- LIFT FANS**
V/stol aircraft lift fan aerodynamics, discussing optimum fan pressure ratios, augmentation ratio, noise constraints, wing loading and fan configurations [AIAA PAPER 71-981] A71-44577
- LIFTING BODIES**
Computer program development for potential flow calculation about lifting bodies [AD-727628] N71-37597
- LIFTING ROTORS**
Photogrammetric recording of helicopter rotor induced aerodynamic effects using wind tunnel test smoke visualization technique A71-43588
Lifting rotors aerodynamic damping in forward flight, describing methods for blade response variance matrix computation A71-44559
- LIGHT AIRCRAFT**
Aircraft generated vortex wakes and core air motions hazards for encountering light airplane A71-43381
Acrostar Mk.II all wood single seat acrobatic light weight aircraft designed for plus/minus 8g and inverted flight A71-43887
- LIGHTHILL METHOD**
Aerodynamic combustion noise generation from premixed or diffusion open turbulent flames, using fluid mechanics and Lighthill method A71-43448
- LINEAR FILTERS**
Minimum order state vector reconstruction linear filters for constant plants optimal control, applying to aircraft flight multiple control-point problem A71-44077
Flight test measurements for improved estimates of aircraft states and aerodynamic parameters, using relinearized Kalman filter A71-44089
- LINEAR PREDICTION**
Flight test measurements for improved estimates of aircraft states and aerodynamic parameters, using relinearized Kalman filter
- LIQUID HYDROGEN** A71-44089
Liquid hydrogen as future replacement for hydrocarbon fuels in surface and air transportation, noting advantages in energy per unit weight and pollution-free combustion A71-44365
- LOAD DISTRIBUTION (FORCES)**
Aircraft fuselage antisymmetric loading strain effects on small aspect delta wing performance A71-45018
- LOADS (FORCES)**
Variability of aluminum alloy aircraft structure fatigue life under symmetric and asymmetric loads [ARL/SM-REPORT-329] N71-37524
- LOGISTICS**
Comparison of logistics problems and cost aspects in selection of aircraft for earth resources surveys [NASA-TN-X-2418] N71-37928
- LONGITUDINAL CONTROL**
Longitudinal adaptive aircraft control through sum of normal acceleration and pitch rate A71-44093
Adaptive guaranteed cost control for systems with parametric variation, demonstrating system stability and airframe pitch control A71-44111
- LONGITUDINAL STABILITY**
Longitudinal stability of plate-like load towed beneath helicopter in horizontal forward flight A71-44346
- LOW ASPECT RATIO WINGS**
Aircraft fuselage antisymmetric loading strain effects on small aspect delta wing performance A71-45018
- LOW FREQUENCIES**
Mobile LF air navigation AN/MRN-13 equipment, operation and maintenance A71-43878
- LOW SPEED**
National Science Council goals in low speed aerodynamics - Canada N71-38627
- LUBRICANTS**
Technical aviation handbook covering aircraft maintenance, navigation aids, airframes, lubricants, piston and gas turbine engines, and checkout procedures [AD-727195] N71-37613
Control and chemical composition of aircraft fuels, lubricants, and special liquids [AD-727199] N71-38531
- LUBRICATING OILS**
Technique for experimental determination of fluid viscosity of synthetic turbine engine lubricants over temperature range of 100 to 700 F [AD-727060] N71-36930
- LUBRICATION**
Aviation fuels lubricating characteristics, discussing refining methods, viscosity, service performance and load testing A71-45383
- M**
- MACH NUMBER**
Two dimensional supersonic variable area nozzle geometry calculation as function of Mach number A71-44071
Comparison of blockage corrections in porous tunnel wall to closed wall tunnel at subsonic Mach numbers [ARA-19] N71-37853
- MAGNETIC ANOMALIES**
Aircraft permanent magnetic fields strength variation, observing magnetic anomaly detection equipment performance degradation A71-42923
- MAGNETIC FIELDS**
Aircraft mechanical and battery operated clocks resistant to high intensity magnetic fields [AD-726700] N71-36430
- MAGNETIC FLUX**
Aircraft permanent magnetic fields strength variation, observing magnetic anomaly detection equipment performance degradation A71-42923
- MAGNUS EFFECT**
Magnus force and moment data for standard 10 degree

- cone calibration model as determined in supersonic wind tunnel
[SC-DC-71-3821] N71-36688
- MAINTENANCE**
Basic engineering technology for Automatic Inspection Diagnostic And Prognostic Systems (AIDAPS) for Army aircraft
[AD-726951] N71-36432
Technical aviation handbook covering aircraft maintenance, navigation aids, airframes, lubricants, piston and gas turbine engines, and checkout procedures
[AD-727195] N71-37613
Laboratory tests of polymeric latex modified fast-fix C-1 cement for repair of damaged runway pavements
[AD-727728] N71-38132
- MAN MACHINE SYSTEMS**
Automatic flight control systems, discussing pilot as systems manager or retained in control loop
A71-44454
- MANAGEMENT INFORMATION SYSTEMS**
Basic engineering technology for Automatic Inspection Diagnostic And Prognostic Systems (AIDAPS) for Army aircraft
[AD-726951] N71-36432
- MANAGEMENT PLANNING**
Soviet aircraft industry R and D organizations and management
A71-44189
Commercial air transportation industry trends and optimal planning requirements, discussing airline economic viability, industry regulation, public service and environmental compatibility
[AIAA PAPER 71-1022] A71-44600
Planning short-haul intercity commercial air transportation with SPOL aircraft
[WRCN-2] N71-37605
Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines
N71-37742
Guidelines for national aviation system planning and R and D policy
[FAA-AV-71-2] N71-38798
- MANEUVERABILITY**
Tu-134 aerodynamic characteristics during takeoff, climb, horizontal flight, landing stability and maneuverability, and strength under various loads
[AD-727196] N71-37612
- MANUAL CONTROL**
Integrated system for aircraft control and operation with visualization and manual regulation techniques, emphasizing interconnections with onboard electronic equipment
A71-44353
- MAPPING**
Remote aerial sensing and automatic mapping for forest resources information system
[NASA-CR-122922] N71-36770
- MATERIALS HANDLING**
Sampling, handling, and measuring emissions from aircraft gas turbine engines
[BEPT-430] N71-37604
- MATHEMATICAL MODELS**
Stochastic optimal control theory application to airplane rescheduling model, obtaining dynamic programming algorithm for optimal landing and takeoff rules
A71-44104
Mathematical modeling of F-8 aircraft wave off trajectories for aircraft carrier approaches
[AD-727121] N71-36439
Method of lines technique for computing flow field about conical configurations at incidence in supersonic flow
[NASA-TR-R-374] N71-36697
Computing dispersal of atmospheric pollutants near airports by use of mean wind and temperature profiles
[NASA-CR-111962] N71-36720
Aerodynamic calculations in designing axial compressors with emphasis on compressors of stationary installations - handbook
[AD-727191] N71-38032
- MEASURE AND INTEGRATION**
Astatic gyroscope mounted on aircraft moving arbitrarily near earth surface, obtaining integrals of kinematic equations
A71-45160
- MEASURING INSTRUMENTS**
Canadian National Science Council research in low speed aerodynamics, machine learning, and turbulent jet transducer
[DNE/NAE-1971(2)] N71-38626
- MEDICAL SERVICES**
Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines
N71-37742
- METAL JOINTS**
Statistical analysis of spot welded and adhesive joints of high strength Al alloy sheet in aircraft structures
A71-45012
- METEOROLOGICAL PARAMETERS**
Weather interruption effects on air transportation operations and economics, considering fog, snow, freezing rain, thunderstorms, winds, CAT and runway conditions
A71-44983
Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from radiosonde data
[NASA-TT-F-13981] N71-36398
- METEOROLOGICAL RADAR**
Solid state airborne weather radar for civil aviation, discussing design, weight and power requirement reduction
A71-44273
- MILITARY AIR FACILITIES**
Development and characteristics of lightweight, mobile structures for aircraft storage and maintenance
[AD-727056] N71-36674
- MILITARY AIRCRAFT**
Basic engineering technology for Automatic Inspection Diagnostic And Prognostic Systems (AIDAPS) for Army aircraft
[AD-726951] N71-36432
Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969
[NTSB-ARC-7L-1] N71-36437
- MINIMUM DRAG**
Minimum drag and lifting line characteristics of large aspect ratio wing in uniform shear flow with velocity variations along span
A71-43312
Minimum drag airfoil shape solutions with supersonic flow and turbulent boundary layers for given chord length and heat transfer rate
[AD-726767] N71-36409
- MISSILE CONTROL**
Wind tunnel static longitudinal stability and control characteristics of cruciform delta winged missile with various horizontal canards and trailing-edge flap control between Mach 1.50 and 4.63
[NASA-TM-X-2367] N71-36415
- MOTIVATION**
Attitudes and motivational factors in job performance of terminal area air traffic control personnel
[FAA-AM-71-30] N71-37041
- MULTIENGINE VEHICLES**
Guide to private and commercial multiengine aircraft pilot certification
[FAA-AC-61-4C] N71-36438
- MULTISPECTRAL BAND SCANNERS**
Shallow ocean depth measurements by aerial photographs of wave refraction and wavelength changes and by multispectral scanning of wave reflection
[NASA-CR-123194] N71-37862
- N**
- NATIONAL AVIATION SYSTEM**
IBM 9020 multiprocessing computer application to ATC, discussing control sectors for inflight control at air route traffic control centers in U.S.
A71-43888

NAVIGATION

SUBJECT INDEX

NAVIGATION

Aircraft takeoff, navigation, and landing aids, aerodynamics characteristics, and crew rescue equipment
[AD-727860] N71-37618
Air traffic control, communications, navigation, frequency management, systems analysis, and aircraft SRDS program developments N71-38214

NAVIGATION AIDS

Aeronautical radio navigation aids photo-optical calibration, describing photogrammetric procedure and ground equipment for checking out airport ILS systems A71-43587

STOL aircraft system, discussing ground installations, runways, three dimensional area navigational aids, noise reduction, air traffic and short haul productivity
[AIAA PAPER 71-983] A71-44579

NITRIC OXIDE

Nitrous oxide dissociation as natural source of stratospheric nitric oxide, noting estimates use as yardstick for artificial source A71-43347

NITROGEN

Nozzle design procedure and calculations for hypervelocity wind tunnel including thermodynamic properties of nitrogen and inviscid core and boundary layer calculations
[AD-727591] N71-37821

NITROUS OXIDES

Nitrous oxide dissociation as natural source of stratospheric nitric oxide, noting estimates use as yardstick for artificial source A71-43347

NOISE INJURIES

Determining sound pressure and noise spectra of turboshaft engines to assess potential noise injury
[DRET-TH-788] N71-37113

NOISE REDUCTION

Prop rotor and lift fan VTOL aircraft ground noise level reduction, using flight trajectory management
[AIAA PAPER 71-991] A71-45295

Noise reduction effectiveness of mixer nozzle for increasing lift capability in STOL aircraft
[NASA-TM-X-67938] N71-36424

Exhaust jet mixing flow nozzles with peak axial velocity degradation for noise suppression
[NASA-TM-X-67934] N71-37378

Noise reduction studies involving variable geometry inlet guide vanes for choking using two-sector cascade apparatus with three inlet configurations
[NASA-TM-X-2392] N71-37601

NOISE SPECTRA

Acoustic noise output from round interfering subsonic jets, considering suppressor nozzle attenuation A71-44560

Determining sound pressure and noise spectra of turboshaft engines to assess potential noise injury
[DRET-TH-788] N71-37113

NONDESTRUCTIVE TESTS

Nondestructive detection of hot corrosion-sulfidation in U.S. Navy aircraft turbine engines A71-45280

Nonequilibrium Flow

Condensate particle crystallization retardation effect on energy characteristics of jet engine, calculating nonequilibrium flows of two phase combustion products in nozzle A71-45004

NONLINEAR SYSTEMS

Suboptimal fixed point data smoothing algorithm for parameter and initial state estimation of nonlinear dynamic systems A71-44113

NORTH AMERICA

Graphs and tables of aircraft traffic over North America - 1966 through 1969
[RAE-LIB-TRANS-1580] N71-38210

NORTH ATLANTIC TREATY ORGANIZATION (NATO)

AGARD report on engine-airplane interference and wall correction in transonic wind tunnel tests
[AGARD-AR-36-71] N71-36400

NOZZLE DESIGN

Nozzle design procedure and calculations for hypervelocity wind tunnel including thermodynamic properties of nitrogen and inviscid core and boundary layer calculations
[AD-727591] N71-37821

Technique for relating transient tolerances in inlet throat Mach number and shock position to supersonic unstart frequency due to atmospheric turbulence for supersonic inlet design.
[NASA-CR-114372] N71-37835

NOZZLE EFFICIENCY

Supersonic propulsion system inlet, engine and exhaust nozzle in wind tunnel and flight tests, discussing boundary layer effects on performance A71-43599

Noise reduction effectiveness of mixer nozzle for increasing lift capability in STOL aircraft
[NASA-TM-X-67938] N71-36424

NOZZLE FLOW

Exhaust jet mixing flow nozzles with peak axial velocity degradation for noise suppression
[NASA-TM-X-67934] N71-37378

NOZZLE GEOMETRY

Two dimensional supersonic variable area nozzle geometry calculation as function of Mach number A71-44071

Thrust-minus-drag forces and pressure distributions of closely spaced twin-jet afterbodies with different inboard-outboard fairing and nozzle shapes
[NASA-TM-X-2329] N71-36412

NUCLEAR PROPELLED AIRCRAFT

Performance and costs of nuclear aircraft used in transoceanic commerce
[NASA-TM-X-2386] N71-38277

NUMERICAL ANALYSIS

Theoretical method for calculating aerodynamic loading on wing-body combinations
[NASA-TN-D-6441] N71-36411

OCEAN BOTTOM

Shallow ocean depth measurements by aerial photographs of wave refraction and wavelength changes and by multispectral scanning of wave reflection
[NASA-CR-123194] N71-37862

OCEAN CURRENTS

Development of operational system for measuring ocean surface current from aircraft using floats and fluorescent dyes
[AD-726568] N71-37922

OCEAN SURFACE

Development of operational system for measuring ocean surface current from aircraft using floats and fluorescent dyes
[AD-726568] N71-37922

ONE DIMENSIONAL FLOW

One dimensional channel flow theory for designing ram wing surface effect vehicle
[AD-727774] N71-36419

OPERATIONS RESEARCH

Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines N71-37742

OPTICAL MEASUREMENT

Aeronautical radio navigation aids photo-optical calibration, describing photogrammetric procedure and ground equipment for checking out airport ILS systems A71-43587

OPTICAL REFLECTION

Pilot performance in recognizing electronic display systems under varying dazzle and color conditions in cockpits
[RAE-LIB-TRANS-1545] N71-37621

OPTIMAL CONTROL

Helicopter optimal autorotation landing parameters for touchdown at zero speed, including rotor rpm drop due to flow separation on blades A71-43090

Minimum order state vector reconstruction linear filters for constant plants optimal control, applying to aircraft flight multiple control-point problem

SUBJECT INDEX

PILOT PERFORMANCE

A71-44077
Stochastic optimal control theory application to
airplane rescheduling model, obtaining dynamic
programming algorithm for optimal landing and
takeoff rules

A71-44104
Computer-aided decision algorithm for ATC problem in
near terminal area, emphasizing scheduling and
holding strategies

A71-44105
Trends in automatic control field in last two
decades, emphasizing optimal control and
performance criteria selection
[AIAA PAPER 71-1001]

A71-44591
OPTIMIZATION
Flexible ram air inflated keel and leading edge
parawing design optimization for increased
stability and reliability, introducing semirigid
member concept
[AIAA PAPER 71-986]

A71-44582
OSCILLATIONS
Angle of attack instrumentation for evaluating
aircraft lift performance and phugoid oscillations
A71-43382

P

PACKINGS (SEALS)
Performance tests of compressor seals and stator
pivot seals used with air breathing propulsion
systems - Part 2
[NASA-CR-72887] N71-37373

PANAVIA MILITARY AIRCRAFT
Panavia 200 multipurpose military aircraft,
describing variable geometry design concept,
performance characteristics, engines, armament and
electronics
A71-44766

PANELS
Reduction of resonant vibrations in integrally
stiffened skin-stringer panels using viscoelastic
materials
[AD-727773] N71-37540
Design data for regeneratively cooled panels from
low cycle fatigue evaluation of Hastelloy X and
Inconel 625 sheet and sandwich panel specimens
[NASA-CR-1884] N71-38734

PARACHUTE DESCENT
Flight dynamics of noise optimal flight profiles for
V/STOL aircraft, minimization of gust effects on
aircraft and nonlinear dynamic stability of
parachute-load systems
A71-44761
Guided parachute-payload system analog simulation
device for pilot training in maneuvering remotely
controlled parachute-payloads
[SC-DR-710097] N71-36427

PARAGLIDERS
Flexible ram air inflated keel and leading edge
parawing design optimization for increased
stability and reliability, introducing semirigid
member concept
[AIAA PAPER 71-986] A71-44582

PARTICULATE SAMPLING
Sampling, handling, and measuring emissions from
aircraft gas turbine engines
[REPT-430] N71-37604

PASSENGERS
Survey of domestic air passenger trip length
including number of passengers and aircraft types
N71-38795

PAVEMENTS
Evaluation of braking performance of light, twin
engine airplane on grooved and ungrooved runway
surfaces
[NASA-TN-D-6444] N71-36431

PAYLOADS
Guided parachute-payload system analog simulation
device for pilot training in maneuvering remotely
controlled parachute-payloads
[SC-DR-710097] N71-36427

PERFORMANCE PREDICTION
Performance prediction and evaluation of
propulsion-augmented high lift systems for STOL
aircraft, considering weight, thrust and wing
loading
[AIAA PAPER 71-990] A71-44585
Conclusions and recommendations concerning wind
tunnel tests of interaction between engine flow

and wall corrections in transonic wind tunnels
N71-36401
Compilation of responses to questionnaire on
engine-airframe interference in transonic tests
N71-36402
Development of methods for measuring and predicting
behavior of rigid rotors with stiff blades at high
advance ratios and low rotor speeds
[NASA-CR-114362] N71-37594

PERFORMANCE TESTS
Aircraft permanent magnetic fields strength
variation, observing magnetic anomaly detection
equipment performance degradation
A71-42923
Aviation fuels lubricating characteristics,
discussing refining methods, viscosity, service
performance and load testing
A71-45383
Partial admission performance of single stage
supersonic turbine at low Reynolds numbers
[NASA-TN-X-2382] N71-36414
Design and tests of high temperature, air cooled
radial turbine configurations
[AD-726466] N71-37381
Performance evaluation of automatic flight progress
strip cutter and loader used in air traffic
control facility
[ACTE-330] N71-38215
Stratified charge engine tests to determine exhaust
emission characteristics
[AD-727745] N71-38760

PERSONNEL
Attitudes and motivational factors in job
performance of terminal area air traffic control
personnel
[FAA-AM-71-30] N71-37041

PHOTOGRAMMETRY
Photogrammetry of moving objects - Conference,
Saint-Mande, France, September 1970
A71-43586
Aeronautical radio navigation aids photo-optical
calibration, describing photogrammetric procedure
and ground equipment for checking out airport ILS
systems
A71-43587
Photogrammetric recording of helicopter rotor
induced aerodynamic effects using wind tunnel test
smoke visualization technique
A71-43588
Techniques for aerial time-lapse cloud photographic
analysis, Doppler navigation data analysis, and
photogrammetric data acquisition
N71-36990

PHOTOGRAPHS
Design, construction, and performance of water
tunnel for two dimensional testing of pitching
airfoils
[D180-14130-1] N71-37827
Development of operational system for measuring
ocean surface current from aircraft using floats
and fluorescent dyes
[AD-726568] N71-37922

PHOTOINTERPRETATION
Interpretation of color infrared photography of
Florida tidewater coastline
[AD-727630] N71-37924

PILOT ERROR
Corporate aircraft pilot ground and flight phase
training, errors and accidents
A71-43388

PILOT PERFORMANCE
Aircraft accelerate-stop factors and regulations,
pilot reaction times and accidents during takeoff
A71-43380
Automatic flight control systems, discussing pilot
as systems manager or retained in control loop
A71-44454
American development in automatic flight control,
noting FAA requirements, pilot involvement and
visibility enhancement
A71-44455
Statistical, cause/factor and injury tables,
accident rates, and briefs of accidents involving
US carriers in 1969
[NTSB-ARC-7L-1] N71-36437
Motion cue and simulation fidelity aspects of
validation of general purpose airborne simulator
[NASA-TN-D-6432] N71-36672

PILOT SELECTION

SUBJECT INDEX

Flight simulator for studying problems of aircraft during approaches and landings at night under category 2 visual conditions
[RAE-TM-AVIONICS-59(BLEU)] N71-37606

Pilot performance in recognizing electronic display systems under varying dazzle and color conditions in cockpits
[RAE-LIB-TRANS-1545] N71-37621

Pilot transition from conventional visual cross pointer display to aural glide slope cues
[FAA-AM-71-24] N71-37682

PILOT SELECTION
Corporate aircraft 1970 accident statistics analysis stressing pilot selection, training and supervision
A71-43227

PILOT TRAINING
Corporate aircraft 1970 accident statistics analysis stressing pilot selection, training and supervision
A71-43227

Corporate aircraft pilot ground and flight phase training, errors and accidents
A71-43388

Guided parachute-payload system analog simulation device for pilot training in maneuvering remotely controlled parachute-payloads
[SC-DR-710097] N71-36427

PILOTS (PERSONNEL)
Guide to private and commercial multiengine aircraft pilot certification
[FAA-AC-61-4C] N71-36438

PISTON ENGINES
Technical aviation handbook covering aircraft maintenance, navigation aids, airframes, lubricants, piston and gas turbine engines, and checkout procedures
[AD-727195] N71-37613

PITCH (INCLINATION)
Angle of attack instrumentation for evaluating aircraft lift performance and phugoid oscillations
A71-43382

PITCHING MOMENTS
Design, construction, and performance of water tunnel for two dimensional testing of pitching airfoils
[D180-14130-1] N71-37827

PITOT TUBES
Aircraft pitot static systems design with removable drain plug, noting line installation problems
A71-43387

PLAN POSITION INDICATORS
Radar observation of convective process in clear air, presenting turreted top cell contour tracings from PPI sequence
A71-43088

PLASTIC COATINGS
Development of rain erosion resistant plastic coatings as high speed aircraft surface finish
[AD-727750] N71-38133

PLASTICS
Simulated JP-4 jet fuel fire tests of high temperature cabin pressure sealant and insulating plastics and rubbers
[FAA-NA-71-22] N71-38149

PLATES (STRUCTURAL MEMBERS)
Equations of motion for elastic plate foundation system under dynamic load applied to aircraft landing
N71-37543

POLICIES
Guidelines for national aviation system planning and R and D policy
[FAA-AV-71-2] N71-38798

POROUS WALLS
Comparison of blockage corrections in porous tunnel wall to closed wall tunnel at subsonic Mach numbers
[ARA-19] N71-37853

POTENTIAL FLOW
Computer program development for potential flow calculation about lifting bodies
[AD-727628] N71-37597

POWER EFFICIENCY
Compressors and turbines centripetal stages operational characteristics, investigating airflow rate and pressure ratio effects on power
A71-45380

Transonic airfoil cascade analytical design, determining efficiency from velocity distribution
A71-45381

PRECIPITATION (METEOROLOGY)
Development, testing, and utilization of silver iodide pyrotechnic cloud seeding system
[ESSA-TM-ERLTM-APCL-5] N71-36985

PREDICTIONS
Prediction formulations for transonic fluctuating pressure environments including protuberance induced turbulent boundary layer flows
[NASA-CR-119947] N71-36677

PREMIXED FLAMES
Aerodynamic combustion noise generation from premixed or diffusion open turbulent flames, using fluid mechanics and Lighthill method
A71-43448

PRESSURE DISTRIBUTION
Thrust-minus-drag forces and pressure distributions of closely spaced twin-jet afterbodies with different inboard-outboard fairing and nozzle shapes
[NASA-TM-X-2329] N71-36412

Pressure distributions and drag coefficients of 18 constant length and volume slender bodies of revolution at zero incidence for Mach numbers 2.0 to 12.0 - graphs
[NASA-TN-D-6536] N71-36416

Methods for prediction of centerline shock layer thickness and pressure distribution on delta wing body configurations
[NASA-TN-D-6550] N71-36418

PRESSURE EFFECTS
Leading edge suction of thin aerofoil theory
[ARL/SM-NOTE-360] N71-36399

PRESSURE OSCILLATIONS
Prediction formulations for transonic fluctuating pressure environments including protuberance induced turbulent boundary layer flows
[NASA-CR-119947] N71-36677

PRESSURE SENSORS
Fluid amplifiers theory and use as temperature and pressure sensors, discussing applications in chemical and ammunition industries and jet aircraft control
[IEEE PAPER 70-TP-120-IGA] A71-42921

PROJECT PLANNING
Manual for development of needs estimates and capital improvement programs for airports and other intercity terminals for 1970 to 1990
[OHB-04-S71002] N71-37824

PROPULSION SYSTEM CONFIGURATIONS
Performance tests of compressor seals and stator pivot seals used with air breathing propulsion systems - Part 2
[NASA-CR-72887] N71-37373

PROPULSION SYSTEM PERFORMANCE
Supersonic propulsion system inlet, engine and exhaust nozzle in wind tunnel and flight tests, discussing boundary layer effects on performance
A71-43599

PSYCHOLOGY
Attitudes and motivational factors in job performance of terminal area air traffic control personnel
[FAA-AM-71-30] N71-37041

R

RADAR BEACONS
Range and azimuth resolution characteristics and aircraft separation measurement capability of radar beacon-digitizer subsystem
[FAA-NA-71-16] N71-37038

RADAR EQUIPMENT
Solid state airborne weather radar for civil aviation, discussing design, weight and power requirement reduction
A71-44273

C band radar transmitter for airborne radar system
[AD-727086] N71-37707

RADAR RESOLUTION
Range and azimuth resolution characteristics and aircraft separation measurement capability of radar beacon-digitizer subsystem
[FAA-NA-71-16] N71-37038

RADAR TRACKING
Radar observation of convective process in clear air, presenting turreted top cell contour tracings

- from PPI sequence
A71-43088
- RADIAL DISTRIBUTION**
Temperature field profiling along radius in front of gas turbine stage, applying to regeneratively cooled turbine engine
A71-45011
- RADIATION DOSAGE**
Jet aircraft measurements of galactic cosmic radiation dose and comparison with theoretical values for supersonic flights
[UCRL-20209]
N71-38552
- RADIO EQUIPMENT**
Mobile LP air navigation AN/MRN-13 equipment, operation and maintenance
A71-43878
- RADIO FREQUENCY INTERFERENCE**
Alternate air traffic control co-channel separation criteria based on probability-of-interference considerations
[IST-101]
N71-37712
- RADIO NAVIGATION**
Aeronautical radio navigation aids photo-optical calibration, describing photogrammetric procedure and ground equipment for checking out airport ILS systems
A71-43587
- RADIOSONDES**
Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from radiosonde data
[NASA-TT-F-13981]
N71-36398
- RAMPS (STRUCTURES)**
One dimensional channel flow theory for designing ram wing surface effect vehicle
[AD-727774]
N71-36419
- RAMS (PUMPS)**
Flexible ram air inflated keel and leading edge parawing design optimization for increased stability and reliability, introducing semirigid member concept
[AIAA PAPER 71-986]
A71-44582
- RANGEFINDING**
Range and azimuth resolution characteristics and aircraft separation measurement capability of radar beacon-digitizer subsystem
[FAA-NA-71-16]
N71-37038
- RAREFIED GAS DYNAMICS**
Two dimensional and three dimensional wakes in supersonic and hypersonic rarefied gas wind tunnels, comparing cone and dihedral configurations
A71-43357
- READERS**
Automatic data processing systems for air traffic control, health services, operations research, management planning, information systems, and reading machines
N71-37742
- RECTANGULAR PLANFORMS**
Lifting rectangular thin airfoil in symmetrical incompressible steady uniform orthogonal flow at small angle of attack, deriving Weissinger integral equation
A71-43487
- Computer program for numerical integration of downwash subsonic flow about rectangular planforms, for different aspect ratios
[NPL-MA-99]
N71-36405
- RECTANGULAR WINGS**
Subsonic force effect calculations on rectangular wings, using downwash velocity potential method
A71-44613
- REFERENCE SYSTEMS**
Nitrous oxide dissociation as natural source of stratospheric nitric oxide, noting estimates use as yardstick for artificial source
A71-43347
- REGENERATIVE COOLING**
Temperature field profiling along radius in front of gas turbine stage, applying to regeneratively cooled turbine engine
A71-45011
- RELIABILITY**
Reliability estimation, including failure effect analysis of avionic systems
N71-36777
- Effectiveness of reliability programs for avionic equipment
N71-36779
- RELIABILITY ANALYSIS**
Digital computer bibliography, programming techniques and applications, and software standardization and reliability
[AD-727605]
N71-37766
- RELIABILITY ENGINEERING**
In-flight monitoring of aircraft turbine engine reliability
A71-43233
- Cost effectiveness, failure analysis, and design techniques for measuring reliability of avionics systems
[AGARD-LS-47-71]
N71-36776
- REMOTE CONTROL**
Guided parachute-payload system analog simulation device for pilot training in maneuvering remotely controlled parachute-payloads
[SC-DR-710097]
N71-36427
- REMOTE SENSORS**
Airborne remote sensing of Mojave Desert playas for use as natural landing areas
[AD-727031]
N71-36748
- Remote aerial sensing and automatic mapping for forest resources information system
[NASA-CR-122922]
N71-36770
- Characteristics of sensors for aerial observation of ice formations and comparison of effectiveness of various methods
[JPRS-54162]
N71-36801
- REQUIREMENTS**
Manual for development of needs estimates and capital improvement programs for airports and other intercity terminals for 1970 to 1990
[OMB-04-S71002]
N71-37824
- RESCUE OPERATIONS**
Airport crash fire fighting equipment requirements and rescue operations
A71-43389
- Helicopter, tilt wing and jet lift hovering aircraft outflow measurements to determine suitability as rescue vehicles
[AIAA PAPER 71-992]
A71-44586
- Aircraft takeoff, navigation, and landing aids, aerodynamics characteristics, and crew rescue equipment
[AD-727860]
N71-37618
- RESEARCH AIRCRAFT**
Feasibility study of combined laminar and turbulent boundary layer control system using distributed suction with application to low-speed research aircraft of glass reinforced plastic
[AD-727767]
N71-37609
- Development of operational system for measuring ocean surface current from aircraft using floats and fluorescent dyes
[AD-726568]
N71-37922
- RESEARCH AND DEVELOPMENT**
Soviet aircraft industry R and D organizations and management
A71-44189
- Civil aviation research and development policy review covering aircraft noise, congestion, ATC, runway capacity and airport development problems
[AIAA PAPER 71-1024]
A71-44602
- Evaluation of visual landing aids involving visibility meters and airfield lighting and marking
[NBS-10604]
N71-38211
- Summaries of air force research activities
[AD-727338]
N71-38789
- Guidelines for national aviation system planning and R and D policy
[FAA-AV-71-2]
N71-38798
- RESONANT VIBRATION**
Reduction of resonant vibrations in integrally stiffened skin-stringer panels using viscoelastic materials
[AD-727773]
N71-37540
- RIGID ROTORS**
Development of methods for measuring and predicting behavior of rigid rotors with stiff blades at high advance ratios and low rotor speeds
[NASA-CR-114362]
N71-37594
- ROLL**
Single degree of freedom roll response due to vertical random two dimensional vertical gusts

[NASA-CR-111966] N71-36421

ROTARY WINGS

Photogrammetric recording of helicopter rotor induced aerodynamic effects using wind tunnel test smoke visualization technique A71-43588

Technology developments in rotor, drive, flight controls and cargo handling systems of heavy lift helicopter system, noting military and commercial applications [AIAA PAPER 71-994] A71-45296

Analytical investigation of effects of blade flexibility, unsteady aerodynamics, and variable inflow on helicopter rotor stall characteristics [NASA-CR-1769] N71-36404

Wind tunnel study of tip vortex modification by mass flow injection [AD-726736] N71-36406

Development of methods for measuring and predicting behavior of rigid rotors with stiff blades at high advance ratios and low rotor speeds [NASA-CR-114362] N71-37594

Measurements of unsteady, rotary wing air loads and time derivatives for rotor blade intersecting completely rolled up vortex [NASA-CR-1909] N71-37598

ROTATING SHAFTS

Heavy load transportation Mi 12 helicopter design and performance, noting gas turbine rigid shaft connection A71-42926

ROTOR AERODYNAMICS

Photogrammetric recording of helicopter rotor induced aerodynamic effects using wind tunnel test smoke visualization technique A71-43588

Lifting rotors aerodynamic damping in forward flight, describing methods for blade response variance matrix computation A71-44559

Principles of helicopter flight including flight stability [AD-726841] N71-36429

ROTOR BLADES (TURBOMACHINERY)

Visualized flow patterns of airflow in centrifugal rotors with thin plate blading and with thick airfoil blades [ME-238] N71-36410

RUNWAY CONDITIONS

Aircraft skidding accidents investigation, comparing airplane stopping distance computations and observations A71-43228

Laser technique for runway and slant visibility range, lower cloud boundary and atmospheric damping coefficient A71-43889

Evaluation of braking performance of light, twin engine airplane on grooved and ungrooved runway surfaces [NASA-TN-D-6444] N71-36431

Effect of wet, icy, and snow covered runways on aircraft stopping distance and directional control in crosswinds, effect of surface texture and contamination on runway slipperiness [FS-160-65-68-2] N71-37820

RUNWAYS

STOL aircraft system, discussing ground installations, runways, three dimensional area navigational aids, noise reduction, air traffic and short haul productivity [AIAA PAPER 71-983] A71-44579

Evaluation of braking performance of light, twin engine airplane on grooved and ungrooved runway surfaces [NASA-TN-D-6444] N71-36431

Laboratory tests of polymeric latex modified fast-fix C-1 cement for repair of damaged runway pavements [AD-727728] N71-38132

SAFETY DEVICES

Aircraft ditching and flying personnel survival, stressing passenger briefing and crew jacket equipment with VHF transceiver for rescue operations coordination A71-43229

S

SAFETY FACTORS

Jet engine advent impact on aviation fuels safety, discussing gasoline hazards in prejet aircraft A71-43231

SAFETY MANAGEMENT

Airport certification and safety inspection program mandated by Airport and Airway Development Act of 1971 A71-43235

SANDWICH STRUCTURES

Design data for regeneratively cooled panels from low cycle fatigue evaluation of Hastelloy X and Inconel 625 sheet and sandwich panel specimens [NASA-CR-1884] N71-38734

SCHEDULING

Stochastic optimal control theory application to airplane rescheduling model, obtaining dynamic programming algorithm for optimal landing and takeoff rules A71-44104

SE-210 AIRCRAFT

European automatic flight control systems for landing in category IIIA conditions, discussing triplex system in Trident and simplex in Caravelle A71-44456

SEALERS

Simulated JP-4 jet fuel fire tests of high temperature cabin pressure sealant and insulating plastics and rubbers [FAA-NA-71-22] N71-38149

SEALS (STOPPERS)

Compressible flow across shaft face seals and narrow slots, examining fluid inertia, viscous friction and entrance losses A71-43592

Shrouded step pads for separating seal surfaces [NASA-TN-D-6384] N71-36830

Analysis and tests of self-acting mainshaft seals to provide gas film lubrication for advanced gas turbine engines [NASA-CR-72987] N71-38022

SEAPLANES

Analysis of seaplane impact on planing deadrise in smooth and rough water [AD-727753] N71-37614

SELF SEALING

Analysis and tests of self-acting mainshaft seals to provide gas film lubrication for advanced gas turbine engines [NASA-CR-72987] N71-38022

SEPARATION

Shrouded step pads for separating seal surfaces [NASA-TN-D-6384] N71-36830

SERVICE LIFE

Automatic pilots for control of rotary and fixed wing aircraft [AD-727789] N71-37611

SHAFTS (MACHINE ELEMENTS)

Compressible flow across shaft face seals and narrow slots, examining fluid inertia, viscous friction and entrance losses A71-43592

SHEAR FLOW

Minimum drag and lifting line characteristics of large aspect ratio wing in uniform shear flow with velocity variations along span A71-43312

SHOCK LAYERS

Methods for prediction of centerline shock layer thickness and pressure distribution on delta wing body configurations [NASA-TN-D-6550] N71-36418

SHOCK WAVE ATTENUATION

Supersonic aircraft shape for shock waves minimization based on channel configuration with converging inlet and diverging outlet section A71-44572

SHOCK WAVE INTERACTION

Flare induced laminar boundary layer/shock wave interactions on axisymmetric bodies at zero incidence in supersonic flow under adiabatic conditions A71-44604

SHOCK WAVE PROPAGATION

Numerical analysis of two-dimensional steady gas flow around thin symmetrical wings and shock wave formation during transition from sonic to supersonic flow [AD-727854] N71-37850

SHOCK WAVES

Approximate solution for position and strength of shock waves about cones in steady supersonic flow
A71-44624

Technique for relating transient tolerances in inlet throat Mach number and shock position to supersonic unstart frequency due to atmospheric turbulence for supersonic inlet design
[NASA-CR-114372] N71-37835

SHORT HAUL AIRCRAFT

STOL aircraft system, discussing ground installations, runways, three dimensional area navigational aids, noise reduction, air traffic and short haul productivity
[AIAA PAPER 71-983] A71-44579

SHORT TAKEOFF AIRCRAFT

Canadian STOL program, discussing Quebec- Windsor corridor passenger traffic
[AIAA PAPER 71-982] A71-44578

STOL aircraft system, discussing ground installations, runways, three dimensional area navigational aids, noise reduction, air traffic and short haul productivity
[AIAA PAPER 71-983] A71-44579

Performance prediction and evaluation of propulsion-augmented high lift systems for STOL aircraft, considering weight, thrust and wing loading

[AIAA PAPER 71-990] A71-44585
AIAA members comments on STOL, VTOL and V/STOL aircraft merits and developments

[AIAA PAPER 71-1015] A71-44596
STOL aircraft flight control problems, discussing Mach trim, artificial feel, stability, feedback system responses and lateral/directional laws

[AIAA PAPER 71-993] A71-45297
Noise reduction effectiveness of mixer nozzle for increasing lift capability in STOL aircraft

[NASA-TN-X-67938] N71-36424
Wind tunnel tests of stability and control characteristics of large scale model representative of propeller-driven STOL transport aircraft

[NASA-TN-D-6393] N71-36435
Wind tunnel tests of propeller driven, deflected slipstream, short takeoff aircraft model to determine longitudinal and lateral-directional stability when in ground effect

[NASA-TN-X-2313] N71-36436
Planning short-haul intercity commercial air transportation with STOL aircraft

[WRCN-2] N71-37605
Noise characteristics of model STOL wing with externally blown flaps in vicinity of aircraft propulsor

[NASA-CR-111956] N71-38283
SHROUDS

Shrouded step pads for separating seal surfaces
[NASA-TN-D-6384] N71-36830

SIGNAL PROCESSING

Digital simulation and implementation techniques for Doppler radar altimeter signal processing
[NASA-CR-1776] N71-36548

SILICON CARBIDES

Breadboard models of silicon carbide junction field effect transistor amplifiers
[AD-727761] N71-37792

SILVER IODIDES

Development, testing, and utilization of silver iodide pyrotechnic cloud seeding system
[ESSA-TN-ERLTH-APCL-5] N71-36985

SKID LANDINGS

Aircraft skidding accidents investigation, comparing airplane stopping distance computations and observations
A71-43228

SLENDER WINGS

Minimum drag and lifting line characteristics of large aspect ratio wing in uniform shear flow with velocity variations along span
A71-43312

Slender two dimensional wedge wings aerodynamic characteristics in hypersonic strong interaction flow, determining wall shear stress and lift drag ratio effects
A71-44621

SLOTS

Compressible flow across shaft face seals and narrow slots, examining fluid inertia, viscous friction

and entrance losses

Feasibility study of combined laminar and turbulent boundary layer control system using distributed suction with application to low-speed research aircraft of glass reinforced plastic
[AD-727767] N71-37609

SOLID STATE DEVICES

Solid state airborne weather radar for civil aviation, discussing design, weight and power requirement reduction
A71-44273

SOUND PRESSURE

Determining sound pressure and noise spectra of turboshaft engines to assess potential noise injury
[DRET-TM-788] N71-37113

SOUND PROPAGATION

Aerodynamic sound radiation from lifting surfaces in smooth and turbulent flow
[NASA-CR-114370] N71-36422

SPACEBORNE PHOTOGRAPHY

Quantity and quality of geodetic information transmitted by space photography compared with low altitude aerial photography
[IR-USGS-229] N71-38013

SPACECRAFT TRAJECTORIES

Flight dynamics and calculation of flight trajectories of various aircraft and spacecraft
[AD-727474] N71-37602

SPEECH RECOGNITION

Environmental and performance tests of voice initiated cockpit control and interrogation system
[AD-727574] N71-37723

SPEED INDICATORS

Aircraft pitot static systems design with removable drain plug, noting line installation problems
A71-43387

SPIN TESTS

Spin tunnel tests to determine effectiveness of deployable, flexible ventral fins for spin recovery device on fighter aircraft
[NASA-TN-D-6509] N71-37603

SPOT WELDS

Statistical analysis of spot welded and adhesive joints of high strength Al alloy sheet in aircraft structures
A71-45012

STANDARDIZATION

Digital computer bibliography, programming techniques and applications, and software standardization and reliability
[AD-727605] N71-37766

STATE VECTORS

Minimum order state vector reconstruction linear filters for constant plants optimal control, applying to aircraft flight multiple control-point problem
A71-44077

STATISTICAL ANALYSIS

Flight test measurements for improved estimates of aircraft states and aerodynamic parameters, using relinearized Kalman filter
A71-44089

STEADY FLOW

Statistical analysis of spot welded and adhesive joints of high strength Al alloy sheet in aircraft structures
A71-45012

STEADY FLOW

Lifting rectangular thin airfoil in symmetrical incompressible steady uniform orthogonal flow at small angle of attack, deriving Weissinger integral equation
A71-43487

STOCHASTIC PROCESSES

Approximate solution for position and strength of shock waves about cones in steady supersonic flow
A71-44624

STOCHASTIC PROCESSES

Stochastic optimal control theory application to airplane rescheduling model, obtaining dynamic programming algorithm for optimal landing and takeoff rules
A71-44104

STOPPING

Aircraft accelerate-stop factors and regulations, pilot reaction times and accidents during takeoff
A71-43380

STRATOSPHERE

Nitrous oxide dissociation as natural source of

STRUCTURAL ANALYSIS

SUBJECT INDEX

- stratospheric nitric oxide, noting estimates use as yardstick for artificial source A71-43347
- Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from radiosonde data [NASA-TT-P-13981] N71-36398
- Horizontal temperature and wind distribution effects on aircraft buffeting in stratosphere [NASA-TT-P-13978] N71-37600
- STRUCTURAL ANALYSIS**
- Structural analysis of corrugated aircraft wing skin panels to determine effects of corrosion damage [AD-728009] N71-37619
- STRUCTURAL DESIGN**
- Development and characteristics of lightweight, mobile structures for aircraft storage and maintenance [AD-727056] N71-36674
- STRUCTURAL STRAIN**
- Aircraft fuselage antisymmetric loading strain effects on small aspect delta wing performance A71-45018
- STRUCTURAL WEIGHT**
- Civil transport aircraft and equipment maintenance and reliability problems solutions with best time, cost and weight compromises A71-44765
- Ideal weight of axisymmetric fuselage shells, taking into account load distribution and cabin pressurization A71-45180
- SUBSONIC FLOW**
- Resultant aerodynamic forces on circular arc profile with normal jet in subsonic steady compressible flow, using Imai-Iamla approximation method A71-44271
- Streamline curvature analysis of compressible subsonic, transonic and supersonic cascade flows in axial turbine blades A71-44347
- Acoustic noise output from round interfering subsonic jets, considering suppressor nozzle attenuation A71-44560
- Subsonic force effect calculations on rectangular wings, using downwash velocity potential method A71-44613
- SUBSONIC SPEED**
- Nonreversible hydraulic control design and emergency maintenance for Tu 154 aircraft subsonic cruising at 11 km altitude A71-42927
- SUBSONIC WIND TUNNELS**
- Low speed wind tunnel measurements correction for acoustic effects due to fan noise propagation A71-44763
- SUCTION**
- Leading edge suction of thin aerofoil theory [ARL/SM-NOTE-360] N71-36399
- Feasibility study of combined laminar and turbulent boundary layer control system using distributed suction with application to low-speed research aircraft of glass reinforced plastic [AD-727767] N71-37609
- SULFIDES**
- Nondestructive detection of hot corrosion-sulfidation in U.S. Navy aircraft turbine engines A71-45280
- SUPERSONIC AIRCRAFT**
- Supersonic aircraft shape for shock waves minimization based on channel configuration with converging inlet and diverging outlet section A71-44572
- Jet aircraft measurements of galactic cosmic radiation dose and comparison with theoretical values for supersonic flights [UCRL-20209] N71-38552
- SUPERSONIC AIRFOILS**
- Minimum drag airfoil shape solutions with supersonic flow and turbulent boundary layers for given chord length and heat transfer rate [AD-726767] N71-36409
- SUPERSONIC FLOW**
- Flow angularity prediction near supersonic fuselage forebody with arbitrary cross section and zero sideslip, using small perturbation theory [AIAA PAPER 71-996] A71-44588
- Flare induced laminar boundary layer/shock wave interactions on axisymmetric bodies at zero incidence in supersonic flow under adiabatic conditions A71-44604
- Approximate solution for position and strength of shock waves about cones in steady supersonic flow A71-44624
- Development of near-field method for determining supersonic flow properties about bodies of revolution [NASA-TN-D-6508] N71-36413
- Method of lines technique for computing flow field about conical configurations at incidence in supersonic flow [NASA-TR-R-374] N71-36697
- Numerical analysis of two-dimensional steady gas flow around thin symmetrical wings and shock wave formation during transition from sonic to supersonic flow [AD-727854] N71-37850
- SUPERSONIC INLETS**
- Supersonic aircraft shape for shock waves minimization based on channel configuration with converging inlet and diverging outlet section A71-44572
- Noise reduction studies involving variable geometry inlet guide vanes for choking using two-sector cascade apparatus with three inlet configurations [NASA-TM-X-2392] N71-37601
- Technique for relating transient tolerances in inlet throat Mach number and shock position to supersonic unstart frequency due to atmospheric turbulence for supersonic inlet design [NASA-CR-114372] N71-37835
- SUPERSONIC NOZZLES**
- Supersonic propulsion system inlet, engine and exhaust nozzle in wind tunnel and flight tests, discussing boundary layer effects on performance A71-43599
- Two dimensional supersonic variable area nozzle geometry calculation as function of Mach number A71-44071
- SUPERSONIC SPEEDS**
- Supersonic combustion chemistry and mixing of high energy density fuels related to advanced air-breathing engine design, using boron particles [AD-727782] N71-38530
- SUPERSONIC TRANSPORTS**
- SST handling qualities, takeoff speeds and performance evaluation on six degree of freedom flight simulator A71-42922
- Supersonic transports and ATC, discussing taxiing, takeoff, landing and terminal area operations A71-44352
- SST operation climatic impact assessment program, considering carbon dioxide, water vapor, contrails, particulates, nitrogen oxides and carbon monoxide A71-44982
- SUPERSONIC TURBINES**
- Partial admission performance of single stage supersonic turbine at low Reynolds numbers [NASA-TM-X-2382] N71-36414
- SUPERSONIC WAKES**
- Two dimensional and three dimensional wakes in supersonic and hypersonic rarefied gas wind tunnels, comparing cone and dihedral configurations A71-43357
- SUPPRESSORS**
- Acoustic noise output from round interfering subsonic jets, considering suppressor nozzle attenuation A71-44560
- SURFACE FINISHING**
- Development of rain erosion resistant plastic coatings as high speed aircraft surface finish [AD-727750] N71-38133
- SURFACE ROUGHNESS**
- Analysis of seaplane impact on planing deadrise in smooth and rough water [AD-727753] N71-37614
- SURFACE VEHICLES**
- Liquid hydrogen as future replacement for hydrocarbon fuels in surface and air transportation, noting advantages in energy per unit weight and pollution-free combustion

- SWEEPBACK** A71-44365
Swept-back vane impeller tested on low speed centrifugal compressor rig [NRC-12020] N71-37596
- SWEEP WINGS**
Aerodynamic characteristics of twin jet, swept wing fighter aircraft model with leading edge Kreuger flaps at subsonic speeds [NASA-TN-X-2325] N71-36426
- SYSTEMS ANALYSIS**
Algorithm for dual compromise control problems arising from each subsystem of inner level in multilevel static hierarchical system A71-44393
Evaluation of visual landing aids involving visibility meters and airfield lighting and marking [NBS-10604] N71-38211
Air traffic control, communications, navigation, frequency management, systems analysis, and aircraft SRDS program developments N71-38214
- SYSTEMS ENGINEERING**
Aircraft pitot static systems design with removable drain plug, noting line installation problems A71-43387
Future transportation technology impact, considering system design evaluation criteria and civil aviation and urban mass transit systems contributions [AIAA PAPER 71-1010] A71-44594
Design and tests of high temperature, air cooled radial turbine configurations N71-37381
- SYSTEMS STABILITY**
Axial flow compressors stable operation, using rotating guide vanes regulation A71-43554
Adaptive guaranteed cost control for systems with parametric variation, demonstrating system stability and airframe pitch control A71-44111
- T**
- TABLES (DATA)**
Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969 [NTSB-ARC-7L-1] N71-36437
Graphs and tables of aircraft traffic over North America - 1966 through 1969 [RAE-LIB-TRANS-1580] N71-38210
Growth rate of US air cargo markets - tables N71-38794
- TAKEOFF**
SST handling qualities, takeoff speeds and performance evaluation on six degree of freedom flight simulator A71-42922
Tu-134 aerodynamic characteristics during takeoff, climb, horizontal flight, landing stability and maneuverability, and strength under various loads [AD-727196] N71-37612
Aircraft takeoff, navigation, and landing aids, aerodynamics characteristics, and crew rescue equipment [AD-727860] N71-37618
- TAKEOFF RUNS**
Aircraft accelerate-stop factors and regulations, pilot reaction times and accidents during takeoff A71-43380
- TECHNOLOGY ASSESSMENT**
Technology developments in rotor, drive, flight controls and cargo handling systems of heavy lift helicopter system, noting military and commercial applications [AIAA PAPER 71-994] A71-45296
- TECHNOLOGY UTILIZATION**
Stability augmentation system for aircraft elastic modes control, discussing active flutter suppression technology A71-44107
Future transportation technology impact, considering system design evaluation criteria and civil aviation and urban mass transit systems contributions [AIAA PAPER 71-1010] A71-44594
- Environment degradation relation to technology, discussing priorities [AIAA PAPER 71-1016] A71-44597
- TELECOMMUNICATION**
Air traffic control, communications, navigation, frequency management, systems analysis, and aircraft SRDS program developments N71-38214
- TEMPERATURE DISTRIBUTION**
Development of procedure for scaling of experimental turbine vane airfoil temperatures from low to high gas temperatures [NASA-TN-D-6510] N71-37563
- TEMPERATURE EFFECTS**
Horizontal temperature and wind distribution effects on aircraft buffeting in stratosphere [NASA-TT-F-13978] N71-37600
- TEMPERATURE GRADIENTS**
Technique for experimental determination of fluid viscosity of synthetic turbine engine lubricants over temperature range of 100 to 700 F [AD-727060] N71-36930
- TEMPERATURE MEASUREMENT**
Development of procedure for scaling of experimental turbine vane airfoil temperatures from low to high gas temperatures [NASA-TN-D-6510] N71-37563
- TEMPERATURE PROFILES**
Temperature field profiling along radius in front of gas turbine stage, applying to regeneratively cooled turbine engine A71-45011
- TEMPERATURE SENSORS**
Fluid amplifiers theory and use as temperature and pressure sensors, discussing applications in chemical and ammunition industries and jet aircraft control [IEEE PAPER 70-TP-120-IGA] A71-42921
- TERMINAL FACILITIES**
STOL aircraft system, discussing ground installations, runways, three dimensional area navigational aids, noise reduction, air traffic and short haul productivity [AIAA PAPER 71-983] A71-44579
Airborne traffic situation display system for use with radar control terminal system [AD-727769] N71-37042
Manual for development of needs estimates and capital improvement programs for airports and other intercity terminals for 1970 to 1990 [OMB-04-S71002] N71-37824
Evaluation of design concept and operational feasibility of 11-sided control tower cab [FAA-NA-71-37] N71-37826
- TERRAIN ANALYSIS**
Arctic ocean pack ice terrain profiling by airborne laser altimeter and coincident photography, analyzing data for ice development stages interpretation A71-44986
- TEST EQUIPMENT**
Test bed engine studies of overall excess air ratio permissible deviation, obtaining diagram for constraints calculation A71-45022
Effectiveness of reliability programs for avionic equipment N71-36779
Cost effectiveness of built in test provisions in aircraft operations N71-36780
- TEST FACILITIES**
Analysis and validation of characteristics of general purpose airborne simulator for simulation of aerodynamic characteristics of large transport aircraft [NASA-TN-D-6431] N71-37823
- TEXTBOOKS**
Textbook on combustion chambers of gas turbine engines [AD-727960] N71-38542
- THERMAL INSULATION**
Simulated JP-4 jet fuel fire tests of high temperature cabin pressure sealant and insulating plastics and rubbers [FAA-NA-71-22] N71-38149
- THERMAL SIMULATION**
Simulated JP-4 jet fuel fire tests of high temperature cabin pressure sealant and insulating

- plastics and rubbers
[FAA-NA-71-22] N71-38149
- THERMODYNAMIC PROPERTIES**
Nozzle design procedure and calculations for hypervelocity wind tunnel including thermodynamic properties of nitrogen and inviscid core and boundary layer calculations
[AD-727591] N71-37821
- THIN AIRFOILS**
Lifting rectangular thin airfoil in symmetrical incompressible steady uniform orthogonal flow at small angle of attack, deriving Weissinger integral equation
A71-43487
- THIN WINGS**
Numerical analysis of two-dimensional steady gas flow around thin symmetrical wings and shock wave formation during transition from sonic to supersonic flow
[AD-727854] N71-37850
- THREE DIMENSIONAL FLOW**
Two dimensional and three dimensional wakes in supersonic and hypersonic rarefied gas wind tunnels, comparing cone and dihedral configurations
A71-43357
- THRUST AUGMENTATION**
Performance prediction and evaluation of propulsion-augmented high lift systems for STOL aircraft, considering weight, thrust and wing loading
[AIAA PAPER 71-990] A71-44585
- THRUST REVERSAL**
Wind tunnel performance characteristics of single-engine fighter model fitted with in-flight thrust reverser
[NASA-TN-D-6460] N71-37384
- TILT WING AIRCRAFT**
Helicopter, tilt wing and jet lift hovering aircraft outflow measurements to determine suitability as rescue vehicles
[AIAA PAPER 71-992] A71-44586
- TIME FUNCTIONS**
Measurements of unsteady, rotary wing air loads and time derivatives for rotor blade intersecting completely rolled up vortex
[NASA-CR-1909] N71-37598
- TIP SPEED**
Wind tunnel study of tip vortex modification by mass flow injection
[AD-726736] N71-36406
- Hot-wire anemometer measurements of streamwise magnitudes and normal velocity components of wing tip vortex
[NASA-TN-X-62087] N71-36679
- TOLERANCES (MECHANICS)**
Technique for relating transient tolerances in inlet throat Mach number and shock position to supersonic unstart frequency due to atmospheric turbulence for supersonic inlet design
[NASA-CR-114372] N71-37835
- TOUCHDOWN**
Helicopter optimal autorotation landing parameters for touchdown at zero speed, including rotor rpm drop due to flow separation on blades
A71-43090
- TOWED BODIES**
Longitudinal stability of plate-like load towed beneath helicopter in horizontal forward flight
A71-44346
- TRAILING EDGES**
Vortex shedding from blunt trailing edge of flat plate spanning wind tunnel under oscillating flap and acoustic resonance excitations
A71-44558
- TRAILING-EDGE FLAPS**
Wind tunnel static longitudinal stability and control characteristics of cruciform delta winged missile with various horizontal canards and trailing-edge flap control between Mach 1.50 and 4.63
[NASA-TN-X-2367] N71-36415
- TRAINING SIMULATORS**
Guided parachute-payload system analog simulation device for pilot training in maneuvering remotely controlled parachute-payloads
[SC-DR-710097] N71-36427
- TRANSIENT RESPONSE**
Transient dynamic characteristics of aircraft under unsteady flight, using Laplace-Carson integral transforms
A71-45016
- Technique for relating transient tolerances in inlet throat Mach number and shock position to supersonic unstart frequency due to atmospheric turbulence for supersonic inlet design
[NASA-CR-114372] N71-37835
- TRANSISTOR AMPLIFIERS**
Breadboard models of silicon carbide junction field effect transistor amplifiers
[AD-727761] N71-37792
- TRANSMITTERS**
C band radar transmitter for airborne radar system
[AD-727086] N71-37707
- TRANSOCEANIC SYSTEMS**
Performance and costs of nuclear aircraft used in transoceanic commerce
[NASA-TM-X-2386] N71-38277
- TRANSONIC FLOW**
Streamline curvature analysis of compressible subsonic, transonic and supersonic cascade flows in axial turbine blades
A71-44347
- Transonic flows about two dimensional airfoils, calculating far field boundary conditions with coordinate transformation
A71-44620
- Transonic airfoil cascade analytical design, determining efficiency from velocity distribution
A71-45381
- Prediction formulations for transonic fluctuating pressure environments including protuberance induced turbulent boundary layer flows
[NASA-CR-119947] N71-36677
- Numerical analysis of two-dimensional steady gas flow around thin symmetrical wings and shock wave formation during transition from sonic to supersonic flow
[AD-727854] N71-37850
- TRANSONIC SPEED**
Two dimensional flow tests of transonic airfoils
[NASA-TT-F-13988] N71-37593
- TRANSONIC WIND TUNNELS**
AGARD report on engine-airplane interference and wall correction in transonic wind tunnel tests
[AGARD-AR-36-71] N71-36400
- Conclusions and recommendations concerning wind tunnel tests of interaction between engine flow and wall corrections in transonic wind tunnels
N71-36401
- Compilation of responses to questionnaire on engine-airframe interference in transonic tests
N71-36402
- Wall corrections for airplanes with interference lift in transonic wind tunnel tests
N71-36403
- Tests on scale model configurations of C-5 aircraft to obtain data correlation on three transonic wind tunnels
[AD-727006] N71-36408
- Wind tunnel performance characteristics of single-engine fighter model fitted with in-flight thrust reverser
[NASA-TN-D-6460] N71-37384
- Comparison of blockage corrections in porous tunnel wall to closed wall tunnel at subsonic Mach numbers
[ARA-19] N71-37853
- TRANSPORT AIRCRAFT**
Civil transport aircraft and equipment maintenance and reliability problems solutions with best time, cost and weight compromises
A71-44765
- Wind tunnel tests of stability and control characteristics of large scale model representative of propeller-driven STOL transport aircraft
[NASA-TN-D-6393] N71-36435
- Analysis and validation of characteristics of general purpose airborne simulator for simulation of aerodynamic characteristics of large transport aircraft
[NASA-TN-D-6431] N71-37823
- Survey of domestic air passenger trip length including number of passengers and aircraft types
N71-38795
- TU-134 AIRCRAFT**
Tu-134 aerodynamic characteristics during takeoff,

- climb, horizontal flight, landing stability and maneuverability, and strength under various loads
[AD-727196] N71-37612
- TURPOLEV AIRCRAFT**
Nonreversible hydraulic control design and emergency maintenance for Tu 154 aircraft subsonic cruising at 11 km altitude A71-42927
- TURBINE BLADES**
Streamline curvature analysis of compressible subsonic, transonic and supersonic cascade flows in axial turbine blades A71-44347
Analysis of gas turbine design and application to aircraft operation with description of components, safety factors, and vibration problems [AD-727188] N71-38538
- TURBINE ENGINES**
In-flight monitoring of aircraft turbine engine reliability A71-43233
Operating variables effect on pollutant exhaust from jet aircraft turbine engines, discussing combustor design techniques for emissions reduction A71-43600
Nondestructive detection of hot corrosion-sulfidation in U.S. Navy aircraft turbine engines A71-45280
Analysis of maximum internal efficiency of single impulse stage of turbine engine [NLL-CE-TRANS-5631-(9022.09)] N71-36704
Determining sound pressure and noise spectra of turboshaft engines to assess potential noise injury [DRET-TM-788] N71-37113
Analysis of gas turbine design and application to aircraft operation with description of components, safety factors, and vibration problems [AD-727188] N71-38538
- TURBINES**
Compressors and turbines centripetal stages operational characteristics, investigating airflow rate and pressure ratio effects on power A71-45380
- TURBOCOMPRESSORS**
Axial flow compressors stable operation, using rotating guide vanes regulation A71-43554
Analysis of maximum internal efficiency of single impulse stage of turbine engine [NLL-CE-TRANS-5631-(9022.09)] N71-36704
Performance tests and efficiency measurement of hub-slit-suction stator in single stage compressor [NASA-CR-120802] N71-37836
Aerodynamic calculations in designing axial compressors with emphasis on compressors of stationary installations - handbook [AD-727191] N71-38032
- TURBOJET ENGINES**
Technique for experimental determination of fluid viscosity of synthetic turbine engine lubricants over temperature range of 100 to 700 F [AD-727060] N71-36930
- TURBOSHAPTS**
Determining sound pressure and noise spectra of turboshaft engines to assess potential noise injury [DRET-TM-788] N71-37113
- TURBULENCE EFFECTS**
Aircraft wake turbulence and trailing vortices, investigating physical characteristics, hazard potential and avoidance techniques A71-43234
- TURBULENT BOUNDARY LAYER**
Prediction formulations for transonic fluctuating pressure environments including protuberance induced turbulent boundary layer flows [NASA-CR-119947] N71-36677
Feasibility study of combined laminar and turbulent boundary layer control system using distributed suction with application to low-speed research aircraft of glass reinforced plastic [AD-727767] N71-37609
- TURBULENT FLOW**
Aerodynamic combustion noise generation from premixed or diffusion open turbulent flames, using fluid mechanics and Lighthill method A71-43448
- Aerodynamic sound radiation from lifting surfaces in smooth and turbulent flow [NASA-CR-114370] N71-36422
- TURBULENT JETS**
Canadian National Science Council research in low speed aerodynamics, machine learning, and turbulent jet transducer [DME/NAE-1971(2)] N71-38626
- TURBULENT WAKES**
Aircraft generated vortex wakes and core air motions hazards for encountering light airplane A71-43381
- TWO DIMENSIONAL BODIES**
Transonic flows about two dimensional airfoils, calculating far field boundary conditions with coordinate transformation A71-44620
Slender two dimensional wedge wings aerodynamic characteristics in hypersonic strong interaction flow, determining wall shear stress and lift drag ratio effects A71-44621
- TWO DIMENSIONAL FLOW**
Two dimensional and three dimensional wakes in supersonic and hypersonic rarefied gas wind tunnels, comparing cone and dihedral configurations A71-43357
Single degree of freedom roll response due to vertical random two dimensional vertical gusts [NASA-CR-111966] N71-36421
Two dimensional flow tests of transonic airfoils [NASA-TT-P-13988] N71-37593
Design, construction, and performance of water tunnel for two dimensional testing of pitching airfoils [D180-14130-1] N71-37827
Numerical analysis of two-dimensional steady gas flow around thin symmetrical wings and shock wave formation during transition from sonic to supersonic flow [AD-727854] N71-37850
- U**
- UNITED STATES OF AMERICA**
Statistical, cause/factor and injury tables, accident rates, and briefs of accidents involving US carriers in 1969 [NTSB-ARC-7L-1] N71-36437
Freight, express, and mail tonnage forecasts for domestic airline operations N71-38793
Growth rate of US air cargo markets - tables N71-38794
- UNSTEADY FLOW**
Analytical investigation of effects of blade flexibility, unsteady aerodynamics, and variable inflow on helicopter rotor stall characteristics [NASA-CR-1769] N71-36404
- URBAN TRANSPORTATION**
Future transportation technology impact, considering system design evaluation criteria and civil aviation and urban mass transit systems contributions [AIAA PAPER 71-1010] A71-44594
- V**
- V/STOL AIRCRAFT**
V/stol aircraft lift fan aerodynamics, discussing optimum fan pressure ratios, augmentation ratio, noise constraints, wing loading and fan configurations [AIAA PAPER 71-981] A71-44577
AIAA members comments on STOL, VTOL and V/STOL aircraft merits and developments [AIAA PAPER 71-1015] A71-44596
Flight dynamics of noise optimal flight profiles for V/STOL aircraft, minimization of gust effects on aircraft and nonlinear dynamic stability of parachute-load systems A71-44761
- VANES**
Swept-back vane impeller tested on low speed centrifugal compressor rig [NRC-12020] N71-37596
- VARIABLE SWEEP WINGS**
Panavia 200 multipurpose military aircraft,

VARIANCE (STATISTICS)

SUBJECT INDEX

describing variable geometry design concept, performance characteristics, engines, armament and electronics
A71-44766

Aerodynamic characteristics of variable sweep wings under a variety of operating conditions
[AD-727210] N71-37615

VARIANCE (STATISTICS)
Tests on scale model configurations of C-5 aircraft to obtain data correlation on three transonic wind tunnels
[AD-727005] N71-36408

VELOCITY DISTRIBUTION
Minimum drag and lifting line characteristics of large aspect ratio wing in uniform shear flow with velocity variations along span
A71-43312

Subsonic force effect calculations on rectangular wings, using downwash velocity potential method
A71-44613

VELOCITY MEASUREMENT
Pressure altimeter, airspeed and vertical velocity instruments, discussing selection, installation, pilot verification, error identification, repair and use
A71-43385

Hot-wire anemometer measurements of streamwise magnitudes and normal velocity components of wing tip vortex
[NASA-TM-X-62087] N71-36679

Factors effecting volume from which data originate in laser Doppler velocimeter dual scatter probe
[AD-727005] N71-36845

VERTICAL DISTRIBUTION
Relation between turbulence in stratosphere causing aircraft buffeting, and vertical distribution of meteorological parameters calculated from radiosonde data
[NASA-TT-F-13981] N71-36398

VERTICAL LANDING
Helicopter optimal autorotation landing parameters for touchdown at zero speed, including rotor rpm drop due to flow separation on blades
A71-43090

VERTICAL TAKEOFF AIRCRAFT
AIAA members comments on STOL, VTOL and V/STOL aircraft merits and developments
[AIAA PAPER 71-1015] A71-44596

Prop rotor and lift fan VTOL aircraft ground noise level reduction, using flight trajectory management
[AIAA PAPER 71-991] A71-45295

Combustion efficiency and performance of swirl can modules under conditions simulating operation of 10,000 pound thrust lift engine for vertical takeoff
[NASA-TN-D-6542] N71-38767

VIBRATION DAMPING
Stability augmentation system for aircraft elastic modes control, discussing active flutter suppression technology
A71-44107

Control surfaces and direct jet force flutter suppression system shown to increase flutter speed of wing
A71-44108

Lifting rotors aerodynamic damping in forward flight, describing methods for blade response variance matrix computation
A71-44559

Reduction of resonant vibrations in integrally stiffened skin-stringer panels using viscoelastic materials
[AD-727773] N71-37540

VIBRATION MODE
Active flutter mode control system synthesis for flight test, showing mass balancing as possible artificial symmetrical wing destabilization
A71-44106

VISCOELASTICITY
Reduction of resonant vibrations in integrally stiffened skin-stringer panels using viscoelastic materials
[AD-727773] N71-37540

VISCOSITY
Aviation fuels lubricating characteristics, discussing refining methods, viscosity, service performance and load testing
A71-45383

VISCOUS DRAG
Compressible flow across shaft face seals and narrow slots, examining fluid inertia, viscous friction and entrance losses
A71-43592

VISIBILITY
Laser technique for runway and slant visibility range, lower cloud boundary and atmospheric damping coefficient
A71-43889

American development in automatic flight control, noting FAA requirements, pilot involvement and visibility enhancement
A71-44455

Flight simulator for studying problems of aircraft during approaches and landings at night under category 2 visual conditions
[BAE-TM-AVIONICS-59 (BLEU)] N71-37606

VISUAL FLIGHT RULES
European automatic flight control systems for landing in category IIIA conditions, discussing triplex system in Trident and simplex in Caravelle
A71-44456

VISUAL PERCEPTION
Motion cue and simulation fidelity aspects of validation of general purpose airborne simulator
[NASA-TN-D-6432] N71-36672

VOICE COMMUNICATION
Environmental and performance tests of voice initiated cockpit control and interrogation system
[AD-727574] N71-37723

VORTEX STREETS
Aircraft generated vortex wakes and core air motions hazards for encountering light airplane
A71-43381

VORTICES
Aircraft wake turbulence and trailing vortices, investigating physical characteristics, hazard potential and avoidance techniques
A71-43234

Vortex shedding from blunt trailing edge of flat plate spanning wind tunnel under oscillating flap and acoustic resonance excitations
A71-44558

Wind tunnel study of tip vortex modification by mass flow injection
[AD-726736] N71-36406

Hot-wire anemometer measurements of streamwise magnitudes and normal velocity components of wing tip vortex
[NASA-TM-X-62087] N71-36679

VULNERABILITY
Computer program for analyzing and simulating attack of low flying aircraft by anti-aircraft missiles and probability of aircraft survival
[BAE-LIB-TRANS-1578] N71-37774

W

WALL FLOW
AGARD report on engine-airplane interference and wall correction in transonic wind tunnel tests
[AGARD-AR-36-71] N71-36400

WATER EROSION
Development of rain erosion resistant plastic coatings as high speed aircraft surface finish
[AD-727750] N71-38133

WATER WAVES
Analysis of seaplane impact on planing deadrise in smooth and rough water
[AD-727753] N71-37614

WEATHER
Weather interruption effects on air transportation operations and economics, considering fog, snow, freezing rain, thunderstorms, winds, CAT and runway conditions
A71-44983

WEATHER MODIFICATION
SST operation climatic impact assessment program, considering carbon dioxide, water vapor, contrails, particulates, nitrogen oxides and carbon monoxide
A71-44982

WIND (METEOROLOGY)
Computing dispersal of atmospheric pollutants near airports by use of mean wind and temperature profiles
[NASA-CR-111962] N71-36720


- Effect of wet, icy, and snow covered runways on aircraft stopping distance and directional control in crosswinds, effect of surface texture and contamination on runway slipperiness
[PS-160-65-68-2] N71-37820
- WIND EFFECTS**
Horizontal temperature and wind distribution effects on aircraft buffeting in stratosphere
[NASA-TT-F-13978] N71-37600
- WIND TUNNEL CALIBRATION**
Low speed wind tunnel measurements correction for acoustic effects due to fan noise propagation
A71-44763
- WIND TUNNEL MODELS**
Two dimensional and three dimensional wakes in supersonic and hypersonic rarefied gas wind tunnels, comparing cone and dihedral configurations
A71-43357
- Wind tunnel study of tip vortex modification by mass flow injection
[AD-726736] N71-36406
- Tests on scale model configurations of C-5 aircraft to obtain data correlation on three transonic wind tunnels
[AD-727006] N71-36408
- Aerodynamic characteristics of twin jet, swept wing fighter aircraft model with leading edge Krueger flaps at subsonic speeds
[NASA-TM-X-2325] N71-36426
- Wind tunnel tests of propeller driven, deflected slipstream, short takeoff aircraft model to determine longitudinal and lateral-directional stability when in ground effect
[NASA-TM-X-2313] N71-36436
- Wind tunnel interference estimation for model design applications using chart method
[NASA-TN-D-6416] N71-36675
- Magnus force and moment data for standard 10 degree cone calibration model as determined in supersonic wind tunnel
[SC-DC-71-3821] N71-36688
- Hypersonic wind tunnel test of two delta wing orbiter models
[NASA-CR-119984] N71-38668
- WIND TUNNEL STABILITY TESTS**
Wind tunnel static longitudinal stability and control characteristics of cruciform delta winged missile with various horizontal canards and trailing-edge flap control between Mach 1.50 and 4.63
[NASA-TM-X-2367] N71-36415
- Wind tunnel tests of stability and control characteristics of large scale model representative of propeller-driven STOL transport aircraft
[NASA-TN-D-6393] N71-36435
- Wind tunnel tests of propeller driven, deflected slipstream, short takeoff aircraft model to determine longitudinal and lateral-directional stability when in ground effect
[NASA-TM-X-2313] N71-36436
- Spin tunnel tests to determine effectiveness of deployable, flexible ventral fins for spin recovery device on fighter aircraft
[NASA-TN-D-6509] N71-37603
- WIND TUNNELS**
Computer program for calculating lift interference factors of wind tunnel test sections by vortex lattice method
[TAE-124] N71-36407
- Wind tunnel interference estimation for model design applications using chart method
[NASA-TN-D-6416] N71-36675
- Mach 8 variable-density tunnel used for determination of aerodynamic heating of attached inflatable decelerator configurations
[NASA-TM-X-2355] N71-38758
- WING FLAPS**
Noise characteristics of model STOL wing with externally blown flaps in vicinity of aircraft propulsor
[NASA-CR-111956] N71-38283
- WING OSCILLATIONS**
Active feedback wing/store flutter control for fighter aircraft, using computer programs based on frequency and time domains for linear analysis
A71-44109
- WING PANELS**
Structural analysis of corrugated aircraft wing skin panels to determine effects of corrosion damage
[AD-728009] N71-37619
- WING PROFILES**
Some aspects of propulsion for augmentor wind concept
[NASA-TT-F-14005] N71-38535
- WING SPAN**
Minimum drag and lifting line characteristics of large aspect ratio wing in uniform shear flow with velocity variations along span
A71-43312
- WINGS**
Theoretical method for calculating aerodynamic loading on wing-body combinations
[NASA-TN-D-6441] N71-36411
- Noise characteristics of model STOL wing with externally blown flaps in vicinity of aircraft propulsor
[NASA-CR-111956] N71-38283

PERSONAL AUTHOR INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 13)

JANUARY 1972

Typical Personal Author Index Listing



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the title, e.g., N71-11019. Under any one author's name the accession numbers are arranged in sequence with the /AA accession numbers appearing first.

A

- ABRAMS, R.**
FAA flight test research approach to the SST airworthiness standards
A71-42922
- ADLER, H. V.**
Possible modes of operation of a centripetal stage
A71-45380
- AIKEN, T. H.**
Stability and control characteristics of a large scale deflected slipstream STOL model with a wing of 5.7 aspect ratio
[NASA-TN-D-6393] N71-36435
Large-scale wind-tunnel tests of a propeller-driven deflected slipstream STOL model in ground effect
[NASA-TN-X-2313] N71-36436
- AIRD, R. T.**
The lubricating quality of aviation fuels
A71-45383
- AKHMEZIANOV, A. M.**
Substantiation of the constraints placed on the overall excess air ratio
A71-45022
- AKSENOV, A. P.**
Aviation fuels, lubricants and special liquids
[AD-727199] N71-38531
- ALATORTSEV, V. P.**
Substantiation of the constraints placed on the overall excess air ratio
A71-45022
- ALEKSANDROV, V. G.**
Technical aviation handbook
[AD-727195] N71-37613
- ALEXANDER, A. J.**
R and D in Soviet aviation
A71-44189
- ALEXANDER, J. H.**
Advanced lightweight portable structural concepts for shelters, hangars and maintenance docks
[AD-727056] N71-36674
- ALLEGRE, J.**
Comparative study of two-dimensional and three-dimensional wakes in supersonic and hypersonic rarefied-gas flows
A71-43357
- ANIES, G. E.**
Survivable flight control system. Studies, analyses and approach. Supplement for hydraulic power and actuation studies
[AD-727763] N71-37608
- ANDERSON, T.**
An evaluation of the automatic flight progress strip

- cutter and loader
[ACTEU-330] N71-38215
- ANGUS, J. W.**
Pressure instruments - Their use and misuse
A71-43385
- ARNO, R. D.**
Some considerations in the selection of aircraft for earth resource observations
[NASA-TN-X-2418] N71-37928
- ATHANS, M.**
An approach to semiautomated optimal scheduling and holding strategies for air traffic control
A71-44105
- AVRAMITO, M.**
The trends of the STOL system
[AIAA PAPER 71-983] A71-44579

B

- BAILEY, D. B.**
Mathematical modeling of P8-E wave off trajectories for TSP (Terminal State Predictor)
[AD-727121] N71-36439
- BALCERAK, J. C.**
An experimental study of tip vortex modification by mass flow injection
[AD-726736] N71-36406
- BARONTI, P. O.**
Transonic flows by coordinate transformation
A71-44620
- BARRY, F. W.**
Development of atmospheric gust criteria for supersonic inlet design
[NASA-CR-114372] N71-37835
- BARSONY-NAGY, A.**
Imai-Tamla's approximation method for the circular profile with a normal jet
A71-44271
- BAZIN, H.**
Review of testing techniques for transonic airfoils
[NASA-TT-F-13988] N71-37593
- BAZOV, D. I.**
Helicopter aerodynamics
[AD-726841] N71-36429
- BEARMAN, P. W.**
An investigation of the flow around rectangular cylinders
[IC-AERO-71-15] N71-36695
- BECK, S. C.**
Design and experimental evaluation of a high-temperature radial turbine, PHASE 2
[AD-726466] N71-37381
- BECKWITH, W. B.**
The effect of weather on the operations and economics of air transportation today
A71-44983
- BELLINGER, E. D.**
Analytical investigation of the effects of blade flexibility, unsteady aerodynamics, and variable inflow on helicopter rotor stall characteristics
[NASA-CR-1769] N71-36404
- BERMAN, H. S.**
High temperature electronics
[AD-727761] N71-37792
- BERMAN, L.**
Structural integrity investigation of reworked S-2 corrugated wing skin panels
[AD-728009] N71-37619
- BILLINGTON, A. E.**
On the fiction of leading edge suction
[ARL/SH-NOTE-360] N71-36399
- BINDON, J. P.**
Streamline curvature analysis of compressible and high Mach number cascade flows
A71-44347

- BLACK, J. A.**
Tests conducted in the AEDC 16-ft transonic tunnel on a 0.0226-scale model of the C-5A aircraft for data correlation between three transonic wind tunnels
[AD-727006] N71-36408
- BLADES, L. G.**
Development and evaluation of aircraft clocks insensitive to high intensity magnetic fields
[AD-726700] N71-36430
- BLATT, H.**
An airborne traffic situation display system
[AD-727769] N71-37042
- BLIANPTIS, E. E.**
A remote-sensing investigation of four Mojave playas. Environmental research papers
[AD-727031] N71-36748
- BOGARDUS, G.**
Single stage evaluation of highly loaded high Mach number compressor stages. 4: Data and performance of hub slit suction stator
[NASA-CR-120802] N71-37836
- BORDOVITSYN, Y. A.**
Aircraft engines (selected articles)
[AD-727175] N71-37387
- BOROCIN, L.**
MADAP: A computerized air-traffic control system
[AD-727175] N71-37744
- BOROVNIK, Y.**
Calculation of lift interference corrections due to wind tunnel test section boundaries by the vortex lattice method
[TAE-124] N71-36407
- BOSWINKLE, R. W., JR.**
Aircraft vortex wakes
[AD-727175] A71-43381
- BOWDITCH, D. H.**
Inlet-engine-nozzle wind tunnel test techniques
[AD-727175] A71-43599
- BOYER, M. P.**
An experimental measurement of galactic cosmic radiation dose in conventional aircraft between San Francisco and London compared to theoretical values for conventional and supersonic aircraft
[UCRL-20209] N71-38552
- BRADLEY, J. R., JR.**
Dallas-Fort Worth tower cab design evaluation
[FAA-NA-71-37] N71-37826
- BRADSHAW, P.**
Use of a refined boundary-layer calculation method to calibrate a simple one
[IC/71/23] N71-37851
- BRADY, F. X.**
An airborne traffic situation display system
[AD-727769] N71-37042
- BRANDENBERGER, A.-J.**
Photogrammetric analysis of the aerodynamics of a rotating airfoil
[AD-727175] A71-43588
- BRENNAN, J. S.**
Radar observations of the convective process in the clear air - A review. II
[AD-727175] A71-43088
- BROWN, A. D.**
Category 2: A simulation study of approaches and landings at night
[RAE-TH-AVIONICS-59(BLEU)] N71-37606
- BROWN, W. L.**
Water-depth measurement by wave refraction and multispectral techniques
[NASA-CR-123194] N71-37862
- BRUNER, G.**
The multi-purpose military aircraft Panavia 200 /MRCA Program/
[AD-727175] A71-44766
- BULDOVSKIY, G. S.**
Relation between stratosphere turbulence causing aircraft buffeting and the verticle distribution of meteorological parameters
[NASA-TT-F-13981] N71-36398
- BURK, S. M., JR.**
Dependence of aircraft buffeting in the stratosphere on horizontal temperature and wind distribution
[NASA-TT-F-13978] N71-37600
- BURGER, G. D.**
Single stage evaluation of highly loaded high Mach number compressor stages. 4: Data and performance of hub slit suction stator
[NASA-CR-120802] N71-37836
- BURK, S. M., JR.**
Exploratory wind-tunnel investigation of deployable flexible ventral fins for use as an emergency spin-recovery device
[NASA-TN-D-6509] N71-37603
- BURKS, R. E., JR.**
Development of rain-erosion-resistant coatings for high speed aircraft
[AD-727750] N71-38133
- BURNISTROV, V. P.**
Applicability of statistical methods to the analysis of the characteristics of sheet joints in aircraft structures
[AD-727175] A71-45012
- BUSH, R. W.**
An airborne traffic situation display system
[AD-727769] N71-37042
- BUTLER, R. D.**
The viscosity of synthetic turbine engine lubricants from 100 F to 700 F
[AD-727060] N71-36930

C

- CALVERT, G. S.**
Design and experimental evaluation of a high-temperature radial turbine, PHASE 2
[AD-726466] N71-37381
- CAMPBELL, R. B.**
High temperature electronics
[AD-727761] N71-37792
- CANNON, R. H., JR.**
Planning a program for assessing the possibility that SST aircraft might modify climate
[AD-727175] A71-44982
- CANTILLO, L. M. H.**
Cloud photogrammetry from airborne time lapse photography
[AD-727175] N71-36990
- CARMICHAEL, A. D.**
Streamline curvature analysis of compressible and high Mach number cascade flows
[AD-727175] A71-44347
- CARMICHAEL, J. G., JR.**
Subsonic characteristics of a twin-jet swept-wing fighter model with leading edge Krueger flaps
[NASA-TN-X-2325] N71-36426
- CARROLL, J. J.**
Altitude . . . or pressure
[AD-727175] A71-43384
- CARTER, E. C.**
Some measurements of porous tunnel wall interference in the ARA 8 foot by 9 foot tunnel
[ARA-19] N71-37853
- CHANG, S. S. L.**
Adaptive guaranteed cost control of systems with uncertain parameters
[AD-727175] A71-44111
- CHAPMAN, C.**
Measurement and analysis of en route ATC digital radar system errors
[FAA-NA-71-16] N71-37038
- CHARAK, M. T.**
Aircraft wake turbulence progress and plans
[AD-727175] A71-43234
- CHARLTON, P.**
On the variation of intensity of aircraft 'permanent' magnetic fields
[AD-727175] A71-42923
- CHATTOPADHYAY, T. K.**
Aerodynamic characteristics of slender wedge- wings in hypersonic strong interaction flows
[AD-727175] A71-44621
- CHEN, R. T. H.**
Parameter and model identification of nonlinear dynamical systems using a suboptimal fixed- point smoothing algorithm
[AD-727175] A71-44113
- CHEKTOV, IA. B.**
Additives to fuels for jet-propelled aircraft /Survey/
[AD-727175] A71-45325
- CHESTNUT, D.**
Noise reduction by means of variable-geometry inlet guide vanes in a cascade apparatus
[NASA-TN-X-2392] N71-37601
- CHIGIER, N. A.**
Tip vortices: Velocity distributions
[NASA-TN-X-62087] N71-36679

- CHIZHOV, B. M.
Substantiation of the constraints placed on the overall excess air ratio
A71-45022
- CICCI, F.
The reduction of resonant vibrations in integrally stiffened skin stringer panels using visco-elastic materials
[AD-727773] N71-37540
- CLARK, C.
Survivable flight control system. Studies, analyses and approach. Supplement for hydraulic power and actuation studies
[AD-727763] N71-37608
- CLARK, L. R.
Noise reduction by means of variable-geometry inlet guide vanes in a cascade apparatus
[NASA-TM-X-2392] N71-37601
- COBB, B. B.
Attitudes and motivational factors in terminal area air traffic control work
[FAA-AM-71-30] N71-37041
- COLLINS, W. E.
Attitudes and motivational factors in terminal area air traffic control work
[FAA-AM-71-30] N71-37041
- CORSIGLIA, V. R.
Tip vortices: Velocity distributions
[NASA-TM-X-62087] N71-36679
- CORWIN, H. R.
Exploratory development program on the rotating combustion engine using the RC1-90 test rig
[AD-727745] N71-38760
- COSGROVE, J. P.
The heavy lift helicopter program - An advanced technology solution to transportation problems
[AIAA PAPER 71-994] A71-45296
- CREEEL, T. R., JR.
Aerodynamic heating at Mach 8 of attached inflatable decelerator configurations
[NASA-TM-X-2355] N71-38758
- CURRY, W. H.
Magnus data on the standard 10 deg cone calibration model
[SC-DC-71-3821] N71-36688
- CURTIS, H.
Corporate operations in Latin America
A71-43391

D

- D'ERRICO, A.
Space shuttle: Aerodynamic heating to the Grumman space shuttle orbiters (ROS-NB1 and ROS-WB1) at Mach number 8.0
[NASA-CR-119984] N71-38668
- DARDEN, B. P. L.
A policy paper guidelines for national aviation system planning and R and D policy
[FAA-AV-71-2] N71-38798
- DAVIS, R. M.
Calculation of nonlinear conical flows by the method of lines
[NASA-TR-R-374] N71-36697
- DAVIS, S. S.
Approximate analytic solution for the position and strength of shock waves about cones in supersonic flow
A71-44624
- DAVIS, W. T.
A versatile C band radar transmitter
[AD-727086] N71-37707
- DEAL, P. L.
Evaluation of breaking performance of a light, twin-engine airplane on grooved and ungrooved pavements
[NASA-TM-D-6444] N71-36431
- DEERWESTER, J. H.
Some considerations in the selection of aircraft for earth resource observations
[NASA-TM-X-2418] N71-37928
- DEMOGENES, C.
Low-cycle fatigue evaluation for regeneratively cooled panels
[NASA-CR-1884] N71-38734
- DONALDSON, C. D.
Computing dispersal of atmospheric pollutants near airports
[NASA-CR-111962] N71-36720

- DORSCH, R. G.
Preliminary tests of the mixer nozzle concept for reducing blown flap noise
[NASA-TM-X-67938] N71-36424
- DROZD, E. E.
Analytical design of a transonic airfoil cascade
A71-45381
- DUNCAN, J. D.
Low-cycle fatigue evaluation for regeneratively cooled panels
[NASA-CR-1884] N71-38734

E

- EASH, R.
Latex modification of fast-fix C-1 cement for the rapid repair of bomb-damaged runways
[AD-727728] N71-38132
- ELLIS, R. S.
An application of stochastic optimal control theory to the optimal rescheduling of airplanes
A71-44104
- ELZWEIG, S.
Transonic flows by coordinate transformation
A71-44620
- EMERY, J.
Maintenance and reliability of civil transport aircraft
A71-44765
- ENTNER, R. S.
Advanced avionic digital computer development program
[AD-727607] N71-37765
- Advanced avionic digital computer development program
[AD-727605] N71-37766
- EULRICH, B. J.
Parameter and model identification of nonlinear dynamical systems using a suboptimal fixed-point smoothing algorithm
A71-44113
- EYERMANN, K.-H.
M1-12 - A new dimension in helicopter design
A71-42926
- EYRE, L. A.
Tidewater shorelines in Broward and Palm Beach Counties, Florida: An analysis of characteristics and changes interpreted from color, color infrared and thermal aerial imagery
[AD-727630] N71-37924

F

- FALKOVICH, S. V.
A weakly supersonic flow around thin bodies
[AD-727854] N71-37850
- FARRAH, J. R.
Advanced lightweight portable structural concepts for shelters, hangars and maintenance docks
[AD-727056] N71-36674
- PEGLEY, K. A.
Pennsylvania-Princeton army avionics research program: Formation flight
[AD-727635] N71-37610
- FERRI, A.
Conclusions and recommendations on engine airplane interference and wall corrections in transonic wind tunnel tests
N71-36401
- FLIEDER, W. G.
Low-cycle fatigue evaluation for regeneratively cooled panels
[NASA-CR-1884] N71-38734
- FLUEGGE-LOTZ, I.
Trends in the field of automatic control in the last two decades /Von Karman Lecture/
[AIAA PAPER 71-1001] A71-44591
- FORGHAN, S. L.
The lubricating quality of aviation fuels
A71-45383
- FORNER, J. A.
Prediction of flow angularity near a supersonic fuselage forebody with arbitrary cross-section
[AIAA PAPER 71-996] A71-44588
- FORREST, R. D.
FAA flight test research approach to the SST airworthiness standards
A71-42922

- POWLER, H. S.
Comparison of thin plate and thick aerofoil blades
in a centrifugal fan
[ME-238] N71-36410
Aerodynamic tests on a centrifugal fan impeller
model with swept-back blades
[NRC-12020] N71-37596
FOXWORTH, T. G.
Another look at accelerate-stop criteria
A71-43380
FRIEDMAN, H. A.
An airborne pyrotechnic cloud seeding system and its
use
[ESSA-TN-BRLTH-APCL-5] N71-36985
PROGER, C.
Measurements of velocities in a subsonic wind tunnel
/0.10 less than V less than 20 m/sec/
A71-44763

G

- GABRIELLI, G.
Expression for the ideal weight of shell fuselages
A71-45180
GALLINGTON, R. W.
The ram-wing surface effect vehicle comparison of
one dimensional theory with wind tunnel and free
flight results
[AD-727774] N71-36419
GAMER, E.
Air Force Research Review. No. 2, March - April 197
[AD-727338] N71-38789
GANGER, T. G.
Results of Prop-Fan/STOL wing acoustics tests
[NASA-CR-111956] N71-38283
GANSLE, J.
FAA program effectiveness and facility criteria. An
analysis of the costs and effectiveness of air
traffic control towers
N71-38213
GAONKAR, G. H.
Interpolation of aerodynamic damping of lifting
rotors in forward flight from measured response
variance
A71-44559
GARNER, H. C.
Analytical and numerical studies of downwash over
rectangular planforms
[NPL-MA-99] N71-36405
GEARHART, B. E.
Low frequency air navigation in Southeast Asia
A71-43878
GIELOW, R. L.
Performance prediction and evaluation of
propulsion-augmented high lift systems for STOL
aircraft
[AIAA PAPER 71-990] A71-44585
GILEWSKI, K.
The shape of a supersonic aircraft
A71-44572
GLADDEN, H. J.
Procedure for scaling of experimental turbine vane
airfoil temperatures from low to high gas
temperatures
[NASA-TN-D-6510] N71-37563
GLENN, J. W.
Voice Initiated Cockpit Control and Interrogation
(VICCI) system test for environmental factors
[AD-727574] N71-37723
GLOWACKI, W. J.
NOL hypervelocity wind tunnel. Report no. 2:
Nozzle design
[AD-727591] N71-37821
GOETHEERT, W. H.
Laser doppler velocimeter dual scatter probe volume
[AD-727005] N71-36845
GOLDMAN, L. J.
Experimental investigation of a low Reynolds number
partial admission single stage supersonic turbine
[NASA-TN-X-2382] N71-36414
GOODHART, W.
The application of high lift devices to competition
gliders
A71-43089
GOODYKOONTZ, J. H.
Preliminary tests of the mixer nozzle concept for
reducing blown flap noise
[NASA-TN-X-67938] N71-36424

- GORDON, R. N.
Voice Initiated Cockpit Control and Interrogation
(VICCI) system test for environmental factors
[AD-727574] N71-37723
GRAHAM, J. M. R.
The effects of an oscillating flap and an acoustic
resonance on vortex shedding
A71-44558
GROBMAN, J.
Effect of operating variables on pollutant emissions
from aircraft turbine engine combustors
A71-43600
GROESBECK, D.
Peak axial-velocity decay with mixer-type exhaust
nozzles
[NASA-TN-X-67934] N71-37378
GRUSZCZYNSKI, E.
Damage of aircraft parts by corrosion
A71-44574

H

- HACH, J. P.
Problems of air navigation
N71-37896
HADY, W. P.
Experimental investigation of self-acting-lift-pad
characteristics for main-shaft seal applications
[NASA-TN-D-6384] N71-36830
HAKODA, T.
Solid-state airborne weather radar fully satisfying
ARINC and TSO specifications
A71-44273
HALL, L. P.
Aerodynamics of lift fan V/STOL aircraft
[AIAA PAPER 71-981] A71-44577
HALTON, C. C.
Canada's STOL program - A progress report
[AIAA PAPER 71-982] A71-44578
HAMEL, P.
Some new results of flight dynamics. II
A71-44761
HARDIES, C. E.
High temperature electronics
[AD-72761] N71-37792
HARRIS, W. P. A.
Factors in STOL flight control configuration
[AIAA PAPER 71-993] A71-45297
HART, G. M.
Latex modification of fast-fix C-1 cement for the
rapid repair of bomb-damaged runways
[AD-727728] N71-38132
HASBROOK, A. H.
Aural glide slope cues: Their effect on pilot
performance during in-flight simulated ILS
instrument approaches
[FAA-AE-71-24] N71-37682
HAVILAND, J. K.
Downwash-velocity potential method for lifting
surfaces
A71-44613
HAWKINS, R. M.
Development of compressor end seals stator
interstage seals, and stator pivot seals in
advanced air breathing propulsion systems. Part
2: Experimental data and analysis
[NASA-CR-72887] N71-37373
HAYDEN, R. E.
Aerodynamic sound radiation from lifting surfaces
with and without leading-edge serrations
[NASA-CR-114370] N71-36422
HAZANOVSKY, D.
Calculation of lift interference corrections due to
wind tunnel test section boundaries by the vortex
lattice method
[TAE-124] N71-36407
HEMINGWAY, J. L.
Trust your altimeter
A71-43386
HERSH, A. S.
Aerodynamic sound radiation from lifting surfaces
with and without leading-edge serrations
[NASA-CR-114370] N71-36422
HERSH, S.
Supersonic combustion chemistry and mixing of high
energy density fuels related to advanced
air-breathing engine design
[AD-727782] N71-38530

- BESS, J. L.
 Calculation of potential flow about arbitrary three dimensional lifting bodies
 [AD-727628] N71-37597
- HEYSON, H. H.
 Rapid estimation of wind-tunnel corrections with application to wind-tunnel and model design
 [NASA-TN-D-6416] N71-36675
- HILST, G. R.
 Computing dispersal of atmospheric pollutants near airports
 [NASA-CR-111962] N71-36720
- HODDER, B. K.
 Aerodynamics of lift fan V/STOL aircraft
 [AIAA PAPER 71-981] A71-44577
- HOEPKEN, H. E.
 Alternative ATC co-channel separation criteria based on probability-of-interference considerations
 [IST-101] N71-37712
- HOFMANN, L. G.
 Minimum order state reconstruction filters for constant plants
 A71-44077
- HORNE, W. B.
 Determining causation of aircraft skidding accidents or incidents
 A71-43228
- HORTON, H. P.
 Adiabatic laminar boundary-layer/shock-wave interactions on flared axisymmetric bodies
 A71-44604
- HOUBOLT, J. C.
 Single-degree-of-freedom roll response due to two-dimensional vertical gusts
 [NASA-CR-111966] N71-36421
- HOWE, D.
 The feasibility of the large freight airship
 [REPT-5] N71-36425
- HUFF, R.
 Peak axial-velocity decay with mixer-type exhaust nozzles
 [NASA-TM-X-67934] N71-37378
- HULL, D. J.
 Supersonic airfoils of minimum total drag
 [AD-726767] N71-36409
- HUTCHESON, E. L.
 Corporate training
 A71-43388
- ILLSTON, F.
 Altitude awareness
 A71-43383
- IVANOVA, E. A.
 Influence of fuselage strains on the work of a small-aspect-ratio wing
 A71-45018
- JAARSMA, F.
 Engine-airplane interference in transonic tests
 N71-36402
- JACKSON, C. H., JR.
 A method for calculating the aerodynamic loading on wing-body combinations at small angles of attack in supersonic flow
 [NASA-TN-D-6441] N71-36411
- JACKSON, M. V.
 Development of rain-erosion-resistant coatings for high speed aircraft
 [AD-727750] N71-38133
- JAINSKI, P.
 The effect of dazzle on electronic display
 [RAE-LIB-TRANS-1545] N71-37621
- JOHANNES, R. P.
 Active flutter control - flight test system synthesis
 A71-44106
- JOHNSON, R. L.
 Compressible flow across shaft face seals
 A71-43592
- JONES, C.
 Exploratory development program on the rotating combustion engine using the RC1-90 test rig
 [AD-727745] N71-38760
- JONES, C. L.
 Survivable flight control system. Studies, analyses and approach. Supplement for hydraulic power and actuation studies
 [AD-727763] N71-37608
- JONES, L. W.
 Liquid hydrogen as a fuel for the future
 A71-44365
- JUST, G. S.
 A survey of fatigue life variability in aluminum alloy aircraft structures
 [ARL/SM-REPORT-329] N71-37524
- JOYNER, U. T.
 Determining causation of aircraft skidding accidents or incidents
 A71-43228
- JULLIEN, M. J.
 Integrated system of control and operation of aircraft
 A71-44353
- K**
- KAATARI, G. E.
 Prediction of centerline shock-layer thickness and pressure distribution on delta wing-body configurations
 [NASA-TN-D-6550] N71-36418
- KARPOV, V. G.
 Experimental study of the operation of axial-flow compressors during rotation of the guide vanes
 A71-43554
- KASHER, A.
 Proceedings of the National Conference on Data Processing
 N71-37742
- KASS, G. J.
 Active flutter suppression - An emerging technology
 A71-44107
- KEEGAN, E. W.
 The challenge of aircraft crash fire rescue
 A71-43389
- KETCHUM, R. D., JR.
 Airborne laser profiling of the Arctic pack ice
 A71-44986
- KHUDIYAKOV, V. A.
 Retardation of condensate particle crystallization in a jet engine nozzle
 A71-45004
- KIRK, J. V.
 Aerodynamics of lift fan V/STOL aircraft
 [AIAA PAPER 71-981] A71-44577
- KISSLINGER, R. L.
 Survivable flight control system. Studies, analyses and approach. Supplement for control criteria studies
 [AD-727762] N71-37616
- KLUNKER, E. B.
 Calculation of nonlinear conical flows by the method of lines
 [NASA-TR-R-374] N71-36697
- KOMAROV, V. A.
 Influence of fuselage strains on the work of a small-aspect-ratio wing
 A71-45018
- KONRAD, T. G.
 Radar observations of the convective process in the clear air - A review. II
 A71-43088
- KORNET, I. N.
 Conversion of several computational algorithms for decreasing the length of the word form at of control computers for aircraft
 [AD-727917] N71-37772
- KOSTIN, V. N.
 Retardation of condensate particle crystallization in a jet engine nozzle
 A71-45004
- KOZHENKOVA, L. P.
 Selecting the geometry of a two-dimensional variable-geometry nozzle for a supersonic wind tunnel
 A71-44071
- KROY, W. H., JR.
 Identification of aircraft states and parameters
 A71-44089
- KUROKAWA, A.
 Solid-state airborne weather radar fully satisfying ARINC and TSO specifications
 A71-44273

L

- LAMPING, H.**
Exploratory development program on the rotating combustion engine using the RC1-90 test rig
[AD-727745] N71-38760
- LANGE, W.**
Operational considerations of angle of attack
A71-43382
- LANGLEY, P. G.**
Remote sensing applications in forestry. The development of an earth resources information system using aerial photographs and digital computers photographs and digital computers
[NASA-CR-122922] N71-36770
- LARSON, G.**
Technology and the environment - Friends or foes
[AIAA PAPER 71-1016] A71-44597
- LAVERIK, V. S.**
Pilots, take heed of birds
[AD-727881] N71-37617
- LAZARENKO, E. G.**
Analytical design of a transonic airfoil cascade
A71-45381
- LEE, E. E., JR.**
Performance of closely spaced twin-jet afterbodies with different inboard-outboard fairing and nozzle shapes
[NASA-TN-X-2329] N71-36412
- LESUER, R. F.**
FAA flight test research approach to the SST airworthiness standards
A71-42922
- LIGUM, T. I.**
Aerodynamics of the Tu-134
[AD-727196] N71-37612
- LIVINGOOD, J. M. B.**
Procedure for scaling of experimental turbine vane airfoil temperatures from low to high gas temperatures
[NASA-TN-D-6510] N71-37563
- LOFTUS, W. D.**
High temperature electronics
[AD-727761] N71-37792
- LONDON, R. J.**
Trim, control, and stability of a gyro-stabilized hingeless rotor at high advance ratio and low rotor speed
[NASA-CR-114362] N71-37594
- LUCAS, J. M.**
Chemical and physical study of fuels gelled with carbohydrate resins
[FAA-NA-71-18] N71-37369
- LUDWIG, L. P.**
Compressible flow across shaft face seals
A71-43592
- Experimental investigation of self-acting-lift-pad characteristics for main-shaft seal applications
[NASA-TN-D-6384] N71-36830
- LYSTAD, H.**
Structural integrity investigation of reworked S-2 corrugated wing skin panels
[AD-728009] N71-37619

M

- MACK, R. J.**
An improved method for calculating supersonic pressure fields about bodies of revolution
[NASA-TN-D-6508] N71-36413
- MAIDEN, D. L.**
Performance characteristics of a single-engine fighter model fitted with an in-flight thrust reverser
[NASA-TN-D-6460] N71-37384
- MAIGRET, J.**
Supersonic transport aviation and air traffic control
A71-44352
- MARCHIONNA, H. R.**
Performance of a modular combustor designed for a VTOL tip-turbine lift fan
[NASA-TN-D-6542] N71-38767
- MARSSEN, D. J.**
Circling performance of sailplanes
A71-44342
- MARTINSEN, H. P.**
Another look at accelerate-stop criteria

- MASLENNIKOV, M. M.**
Gas turbine engines for helicopters
[AD-727959] N71-38541
- MASSEE, C. C.**
Large nuclear-powered subsonic aircraft for transoceanic commerce
[NASA-TN-X-2386] N71-38277
- MATRAND, C.**
Comparative study of two-dimensional and three-dimensional wakes in supersonic and hypersonic rarefied-gas flows
A71-43357
- MAULL, D. J.**
The effects of an oscillating flap and an acoustic resonance on vortex shedding
A71-44558
- MAXWELL, R. L.**
The impact of future transportation technology
[AIAA PAPER 71-1010] A71-44594
- MCCONNELL, J. C.**
Nitrous oxide - A natural source of stratospheric NO
A71-43347
- MCDONALD, R. O.**
Fluidics
[IEEE PAPER 70-TP-120-IGA] A71-42921
- MCELROY, M. B.**
Nitrous oxide - A natural source of stratospheric NO
A71-43347
- MCGOWAN, W. A.**
Aircraft wake turbulence progress and plans
A71-43234
- MCKIBBIN, A. H.**
Development of compressor end seals stator interstage seals, and stator pivot seals in advanced air breathing propulsion systems. Part 2: Experimental data and analysis
[NASA-CR-72887] N71-37373
- Development of mainshaft seals for advanced air breathing propulsion systems, phase 3
[NASA-CR-72987] N71-38022
- MCKINNON, C. A.**
1970 corporate accident statistics
A71-43227
- MEISNER, M. B.**
A policy paper guidelines for national aviation system planning and R and D policy
[FAA-AV-71-2] N71-38798
- MELKOV, F. I.**
Use of infrared devices in observations of ice conditions
[JPRS-54162] N71-36801
- MELTS, I. O.**
Use of a correlation system of equations for accuracy analysis in flight dynamics problems
A71-44692
- MERCER, C. E.**
Performance characteristics of a single-engine fighter model fitted with an in-flight thrust reverser
[NASA-TN-D-6460] N71-37384
- MERCIER, J. A.**
Impact loads on warped planing surfaces landing on smooth and rough water
[AD-727753] N71-37614
- MERKEL, K. H.**
Advanced lightweight portable structural concepts for shelters, hangars and maintenance docks
[AD-727056] N71-36674
- MERTAUGH, L. J.**
Feasibility study of a combined laminar and turbulent boundary layer control system using distributed suction
[AD-727767] N71-37609
- MESSIER, T. P.**
A policy paper guidelines for national aviation system planning and R and D policy
[FAA-AV-71-2] N71-38798
- MICHAELSEN, O. E.**
A comparison of outflows from a helicopter, tilt wing and jet lift hovering aircraft
[AIAA PAPER 71-992] A71-44586
- MIDDLETON, D.**
A note on the acoustic output from round and interfering jets
A71-44560
- MILLER, G. P.**
Analytical and numerical studies of downwash over rectangular planforms

[HPL-MA-99] N71-36405
MILLER, M. K.
 The ram-wing surface effect vehicle comparison of one dimensional theory with wind tunnel and free flight results
 [AD-727774] N71-36419
MILLS, M. R.
 A versatile C band radar transmitter
 [AD-727086] N71-37707
MISENENTINO, R.
 Aerodynamic heating at Mach 8 of attached inflatable decelerator configurations
 [NASA-TN-X-2355] N71-38758
MOINARD, J.
 Measurements of velocities in a subsonic wind tunnel /0.10 less than V less than 20 m/sec/
 A71-44763
MOLINEUX, C. E.
 A remote-sensing investigation of four Mojave plays. Environmental research papers
 [AD-727031] N71-36748
MONTI, R.
 Wall corrections for airplanes with lift in transonic wind tunnel tests
 N71-36403
MORITA, K.
 Lifting line theory of a wing in uniform shear flow
 A71-43312
MOSCHETTI, G.
 Voice Initiated Cockpit Control and Interrogation (VICCI) system test for environmental factors
 [AD-727574] N71-37723
MOTYLKOV, L. A.
 Integration of the kinematic equations of an astatic gyroscope
 A71-45160

N

NEAL, J. T.
 A remote-sensing investigation of four Mojave plays. Environmental research papers
 [AD-727031] N71-36748
NEWHART, J. E.
 The detection of hot corrosion-sulfidation in Navy aircraft turbine engines
 A71-45280
NIXON, R.
 Convention for the suppression of unlawful seizure of aircraft
 N71-37590

O

OGSTON, A. R.
 Aviation fuels and their safety aspects
 A71-43231
OKAPUU, U.
 Design and experimental evaluation of a high-temperature radial turbine, PHASE 2
 [AD-726466] N71-37381
OLSEN, J. W.
 Design and operation of the BSR water tunnel
 [D180-14130-1] N71-37827
OLSEN, W. A.
 Preliminary tests of the mixer nozzle concept for reducing blown flap noise
 [NASA-TN-X-67938] N71-36424
OSTOSLAVSKII, I. V.
 Flight dynamics; Aircraft trajectories
 [AD-727474] N71-37602

P

PADAKANNAYA, R.
 Experimental study of rotor unsteady airloads due to blade-vortex interaction
 [NASA-CR-1909] N71-37598
PAGE, V. R.
 Stability and control characteristics of a large scale deflected slipstream STOL model with a wing of 5.7 aspect ratio
 [NASA-TN-D-6393] N71-36435
 Large-scale wind-tunnel tests of a propeller-driven deflected slipstream STOL model in ground effect
 [NASA-TN-X-2313] N71-36436
PALKE, J.
 TUT-3: A computer program for simulating the attack of low flying aircraft by anti-aircraft missiles

[RAE-LIB-TRANS-1578] N71-37774
PAPADALE, B. S., JR.
 The design and analysis of a fully-flexible ram-air inflated parawing
 [AIAA PAPER 71-986] A71-44582
PCHELKIN, Y. M.
 Combustion chambers of gas turbine engines
 [AD-727960] N71-38542
PEIGNEY, J. C.
 Integrated system of control and operation of aircraft
 A71-44353
PENG, T. K. C.
 Adaptive guaranteed cost control of systems with uncertain parameters
 A71-44111
PETT, M. I.
 US international air cargo markets, 1970
 N71-38794
PHILLIPS, W. P.
 Evaluation of breaking performance of a light, twin-engine airplane on grooved and ungrooved pavements
 [NASA-TN-D-6444] N71-36431
POLCYN, F. C.
 Water-depth measurement by wave refraction and multispectral techniques
 [NASA-CR-123194] N71-37862
POHONAREV, A. N.
 Rocket carrying aviation (selected chapters)
 [AD-727860] N71-37618
POPE, J. C.
 Don't call them air carrier airports
 A71-43235
PORTER, L. W.
 An approach to semiautomated optimal scheduling and holding strategies for air traffic control
 A71-44105
POVINELLI, V. P.
 Development of mainshaft seals for advanced air breathing propulsion systems, phase 3
 [NASA-CR-72987] N71-38022
POWERS, J. O.
 Federal policy and planning on the aircraft environment
 N71-38792
PSHENICHNY, V. D.
 The efficiency of single-row impulse stages on the basis of Soviet test data
 [NLL-CE-TRANS-5631-(9022.09)] N71-36704
PULLING, R. W.
 STOL: The agony and the ecstasy
 [WRCN-2] N71-37605
PYKHOVA, T. A.
 Use of a correlation system of equations for accuracy analysis in flight dynamics problems
 A71-44692

R

RADOMSKII, M. P.
 An algorithm for search of compromise control in static hierarchical systems
 A71-44393
RAPPIN, M.
 Comparative study of two-dimensional and three-dimensional wakes in supersonic and hypersonic rarefied-gas flows
 A71-43357
RAGSDALE, W. C.
 Magnus data on the standard 10 deg cone calibration model
 [SC-DC-71-3821] N71-36688
RANG, E. R.
 A nonvarying-C' control scheme for aircraft
 A71-44093
RASHUSSEN, P. G.
 Aural glide slope cues: Their effect on pilot performance during in-flight simulated ILS instrument approaches
 [FAA-AM-71-24] N71-37682
RAY, E. J.
 Subsonic characteristics of a twin-jet swept-wing fighter model with leading edge Krueger flaps
 [NASA-TN-X-2325] N71-36426
REED, J. F.
 Magnus data on the standard 10 deg cone calibration model
 [SC-DC-71-3821] N71-36688

- REIS, G. E.
Analog simulation of a guided parachute-payload system
[SC-DR-710097] N71-36427
- REMETEY-FUELOEPP, G.
Photo-optical calibration of aeronautics radio navigation aids A71-43587
- RICHARD, C. E.
Low-cycle fatigue evaluation for regeneratively cooled panels
[NASA-CR-1884] N71-38734
- RICHARDS, D. B.
Forecast of scheduled domestic air cargo for the 50 States, 1971 - 1975 N71-38793
- RICHARDSON, W. S.
Development of an operational system for measuring ocean surface current from aircraft
[AD-726568] N71-37922
- RINEHART, S. A.
An experimental study of tip vortex modification by mass flow injection
[AD-726736] N71-36406
- RISHEL, R. W.
An application of stochastic optimal control theory to the optimal rescheduling of airplanes A71-44104
- ROBERTSON, J. E.
Prediction of in flight fluctuating pressure environments including protuberance induced flow
[NASA-CR-119947] N71-36677
- RODKIEWICZ, C. E.
Aerodynamic characteristics of slender wedge- wings in hypersonic strong interaction flows A71-44621
- ROM, F. E.
Large nuclear-powered subsonic aircraft for transoceanic commerce
[NASA-TM-X-2386] N71-38277
- ROM, J.
Calculation of lift interference corrections due to wind tunnel test section boundaries by the vortex lattice method
[TAE-124] N71-36407
- RUNCKEL, J. P.
Performance of closely spaced twin-jet afterbodies with different inboard-outboard fairing and nozzle shapes
[NASA-TM-X-2329] N71-36412
- RUSSEL, R. M.
Remote sensing applications in forestry. The development of an earth resources information system using aerial photographs and digital computers photographs and digital computers
[NASA-CR-122922] N71-36770
- RUSSELL, W. K.
In-flight monitoring and engine reliability A71-43233
- S**
- SAGINOR, I.
Forecast of scheduled domestic air cargo for the 50 States, 1971 - 1975 N71-38793
- SANNIKOV, V. A.
Determination of transient functions and impulse transient functions for an aircraft in its unsteady motion by the method of Laplace-Carson integral transforms A71-45016
- SARKOS, C. P.
Small scale fire tests of high temperature cabin pressure sealant and insulating materials
[FAA-NA-71-22] N71-38149
- SAWYER, W. C.
A method for calculating the aerodynamic loading on wing-body combinations at small angles of attack in supersonic flow
[NASA-TN-D-6441] N71-36411
- SCHAEFFER, R. S.
An airborne pyrotechnic cloud seeding system and its use
[ESSA-TM-ERLTH-APCL-5] N71-36985
- SCHMITT, M. H.
Remarks on the paper of M. D. C. Whittley (paper no. 13): Some aspects of propulsion for the augmentor wing concept
- [NASA-TT-P-14005] N71-38535
- SCHMITZ, F. H.
The reduction of VTOL operational noise through flight trajectory management
[AIAA PAPER 71-991] A71-45295
- SCHUBERT, H.
The integral equation of the supporting rectangular plane in symmetric flow A71-43487
- SCHULZ, W.
Some new results of flight dynamics. II A71-44761
- SEEBACH, N. C.
Ditching and survival A71-43229
- SEGAR, J. K.
Repair or throwaway - Graphic screening techniques help supply the answer A71-43197
- SELLMAN, A. N.
Water-depth measurement by wave refraction and multispectral techniques
[NASA-CR-123194] N71-37862
- SEN, A.
Single-degree-of-freedom roll response due to two-dimensional vertical gusts
[NASA-CR-111966] N71-36421
- SEVART, J. A.
Pitot static systems A71-43387
- SHAPIRO, L. H.
Comparison of information content of space photography and low altitude aerial photography
[IR-USGS-229] N71-38013
- SHARPWACK, D. A.
Remote sensing applications in forestry. The development of an earth resources information system using aerial photographs and digital computers photographs and digital computers
[NASA-CR-122922] N71-36770
- SHELDON, D. F.
A study of the stability of a plate-like load towed beneath a helicopter A71-44346
- SHERLYGIN, N. A.
Design and operation of aircraft gas turbine engines
[AD-727188] N71-38538
- SHERSTYUK, A. N.
Design of compressors: Aerodynamic calculations
[AD-727191] N71-38032
- SHIBANOV, G. P.
Principles of automated checking of the operational capability of aircraft engines and the systems functionally connected to them A71-43897
- SIH, P. C.
Aircraft ground operations simulation N71-37607
- SIMPSON, J.
An airborne pyrotechnic cloud seeding system and its use
[ESSA-TM-ERLTH-APCL-5] N71-36985
- SKRIPNICHENKO, S. Y.
Variable sweep. Chapters 1-5
[AD-727210] N71-37615
- SLUSHER, T. W.
An airborne pyrotechnic cloud seeding system and its use
[ESSA-TM-ERLTH-APCL-5] N71-36985
- SMITH, R. C.
Attitudes and motivational factors in terminal area air traffic control work
[FAA-AM-71-30] N71-37041
- SMITH, W. D.
The ram-wing surface effect vehicle comparison of one dimensional theory with wind tunnel and free flight results
[AD-727774] N71-36419
- SMYTH, M. S.
Survivable flight control system. Studies, analyses and approach. Supplement for hydraulic power and actuation studies
[AD-727763] N71-37608
- SNODDY, R. J.
Trim, control, and stability of a gyro-stabilized hingeless rotor at high advance ratio and low rotor speed
[NASA-CR-114362] N71-37594

- SOLOVEVA, G. S.
Possible modes of operation of a centripetal stage
A71-45380
- SOUTH, J. C., JR.
Calculation of nonlinear conical flows by the method
of lines
[NASA-TR-R-374] N71-36697
- STANLEY, W. D.
Doppler radar simulation studies
[NASA-CR-1776] N71-36548
- STARK, J. A.
Analog simulation of a guided parachute-payload
system
[SC-DR-710097] N71-36427
- STEPNIEWSKI, W. Z.
The reduction of VTOL operational noise through
flight trajectory management
[AIAA PAPER 71-991] A71-45295
- STEWART, S. R.
Water-depth measurement by wave refraction and
multispectral techniques
[NASA-CR-123194] N71-37862
- STIVERS, L. S., JR.
Calculated pressure distributions and components of
total-drag coefficients for 18 constant-volume,
slender bodies of revolution at zero incidence for
Mach numbers from 2.0 to 12.0, with experimental
aerodynamic characteristics for three of the
bodies
[NASA-TN-D-6536] N71-36416
- STONG, R. A.
Noise survey: A turboshaft power plant coupled to a
mobile test bed
[DRET-TN-788] N71-37113
- STRAHLE, W. C.
On combustion generated noise
A71-43448
- SUEISHI, Y.
Solid-state airborne weather radar fully satisfying
ARINC and TSO specifications
A71-44273
- SUMERLIN, W. T.
Techniques of system reliability estimation,
including failure effect analysis (failure
consequence)
N71-36777
Effectiveness of reliability program elements
N71-36779
- SYCHOWICZ, E.
Damage of aircraft parts by corrosion
A71-44574
- SYVERTSON, C. A.
The CARD Study - What is its impact
[AIAA PAPER 71-1024] A71-44602
- SZALAI, K. J.
Motion cue and simulation fidelity aspects of the
validation of a general purpose airborne simulator
[NASA-TN-D-6432] N71-36672
Validation of a general purpose airborne simulator
for simulation of large transport aircraft
handling qualities
[NASA-TN-D-6431] N71-37823
- SZUMANSKI, K.
Optimal autorotation landing parameters for a
helicopter
A71-43090
- T**
- TALL, H. H.
Cost effectiveness of built-in test provisions
N71-36780
Relationships between program test and user support
costs
N71-36784
- TANQUARY, A. C.
Development of rain-erosion-resistant coatings for
high speed aircraft
[AD-727750] N71-38133
- TEMPLE, R. J.
Low speed aerodynamics and the Science Council's
national goals
N71-38627
- TENCER, B.
The heavy lift helicopter program - An advanced
technology solution to transportation problems
[AIAA PAPER 71-994] A71-45296
- TENG, J.
Chemical and physical study of fuels gelled with
carbohydrate resins
[FAA-NA-71-18] N71-37369
- THOMPSON, G. O.
Active flutter suppression - An emerging technology
A71-44107
- TISHIN, A. P.
Retardation of condensate particle crystallization
in a jet engine nozzle
A71-45004
- TITENSKII, V. I.
Experimental study of the operation of axial- flow
compressors during rotation of the guide vanes
A71-43554
- TOPP, L. J.
Potential performance gains by use of a flutter
suppression system
A71-44108
- TOPTUNOV, A. M.
Profiling the temperature field along the radius in
front of a turbine stage
A71-45011
- TRESCOT, C. D., JR.
Longitudinal aerodynamic characteristics at Mach
1.50 to 4.63 of a missile model employing various
canards and a trailing edge flap control
[NASA-TM-X-2367] N71-36415
- TRIPLETT, W. E.
A feasibility study of active wing/store flutter
control
A71-44109
- TRUMAN, D. M.
An investigation of the flow around rectangular
cylinders
[IC-AERO-71-15] N71-36695
- U**
- USKOV, G. V.
Use of a correlation system of equations for
accuracy analysis in flight dynamics problems
A71-44692
- V**
- VAGLIO-LAURIN, R.
Transonic flows by coordinate transformation
A71-44620
- VAN ROESSEL, J.
Remote sensing applications in forestry. The
development of an earth resources information
system using aerial photographs and digital
computers photographs and digital computers
[NASA-CR-122922] N71-36770
- VAUGHN, R.
Analog simulation of a guided parachute-payload
system
[SC-DR-710097] N71-36427
- VERINDER, P. E.
A survey of fatigue life variability in aluminum
alloy aircraft structures
[ARL/SM-REPORT-329] N71-37524
- VOLKOVICH, V. L.
An algorithm for search of compromise control in
static hierarchical systems
A71-44393
- VON GLAHN, U.
Peak axial-velocity decay with mixer-type exhaust
nozzles
[NASA-TM-X-67934] N71-37378
- W**
- WAGNER, P. M.
Folding sidewall aircraft tires
A71-44975
- WAKEFIELD, W. R.
Advanced lightweight portable structural concepts
for shelters, hangars and maintenance docks
[AD-727056] N71-36674
- WALLACE, R.
An experimental measurement of galactic cosmic
radiation dose in conventional aircraft between
San Francisco and London compared to theoretical
values for conventional and supersonic aircraft
[UCRL-20209] N71-38552
- WARE, A. G., III
Impact on plates on elastic foundations
N71-37543

- WASSERSTROM, E.
Calculation of lift interference corrections due to
wind tunnel test section boundaries by the vortex
lattice method
[TAE-124] N71-36407
- WATTS, G. A.
Trim, control, and stability of a gyro-stabilized
hingeless rotor at high advance ratio and low
rotor speed
[NASA-CR-114362] N71-37594
- WENDL, M. J.
Survivable flight control system. Studies, analyses
and approach. Supplement for control criteria
studies
[AD-727762] N71-37616
- WESTON, J. A.
A versatile C band radar transmitter
[AD-727086] N71-37707
- WHITE, R. P., JR.
An experimental study of tip vortex modification by
mass flow injection
[AD-726736] N71-36406
- WILCOX, R. H.
Alternative ATC co-channel separation criteria based
on probability-of-interference considerations
[IST-101] N71-37712
- WINDEBANK, A. E.
An evaluation of the automatic flight progress strip
cutter and loader
[ACTEU-330] N71-38215
- WITTIG, W.
The integral equation of the supporting rectangular
plane in symmetric flow
A71-43487
- WOLFRUM, W.
Test report- Acrostar Mk. II
A71-43887
- WOLOSCHIN, F.
The control system of the Tu-154
A71-42927
- WOODLEY, W. L.
An airborne pyrotechnic cloud seeding system and its
use
[ESSA-TN-ERLTH-APCL-5] N71-36985
Cloud photogrammetry from airborne time lapse
photography
N71-36990

Y

- YAGER, T. J.
Evaluation of breaking performance of a light,
twin-engine airplane on grooved and ungrooved
pavements
[NASA-TN-D-6444] N71-36431

Z


- ZIEGLER, R.
Laser technique for determining the meteorological
visibility range at airports
A71-43889
- ZUK, J.
Compressible flow across shaft face seals
A71-43592
- ZUSCHLAG, W. E.
A step toward automatic air traffic control
A71-43888

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 13)

JANUARY 1972

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number. Under each contract number, the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the IAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in either the IAA or STAR section.

AF 33/615/-69-C-1359	N00014-67-A-0320-0003
A71-44077	N71-37924
AF-AFOSR-1744-69	N00014-69-C-1069
N71-36409	N71-36406
DA-28-043-AMC-02411-E	N00014-71-C-0197
N71-37610	A71-44620
DAAJ01-71-C-0503	N00019-69-0534
N71-36432	A71-44113
DAAJ02-68-C-0003	N00019-70-C-0100
N71-37381	N71-37597
DACA39-70-C-0022	N00019-70-C-0330
N71-38132	N71-38133
DI-14-08-001-12682	N00019-70-C-0371
N71-38013	N71-38760
DOT-CG-10737-A	N00019-70-C-0426
N71-37922	N71-37723
DOT-FA70NA-497	N00600-69-C-1072
N71-37369	N71-37614
DRHE-525/68 A71-43357	W-7405-ENG-48
P19628-70-C-0230	N71-38552
N71-37042	110-06-02-96-15
P33615-69-C-1265	N71-37928
N71-36930	117-07-04-08 N71-38758
F33615-69-C-1582	120-34 N71-36414
N71-37609	124-07-28-01-21
F33615-69-C-1719	N71-36418
N71-36674	126-00-00-00-00
F33615-69-C-1827	N71-37594
N71-37608	N71-36830
N71-37616	N71-38277
P33615-70-C-1053	126-63-11-45 N71-37384
N71-37792	133-61-12-01 N71-36431
P40600-72-C-0003	136-13-02-01 N71-36413
N71-36408	136-13-05-01 N71-36697
N71-36845	136-62-02-03 N71-37603
F44620-70-C-0061	136-63-02-37 N71-36426
N71-38530	136-80-01-04 N71-37601
F61052-68-C-0027	720-01-11-01 N71-36411
N71-37540	720-03 N71-37563
NASA ORDER W-12996	720-06-00-01-24
N71-36770	N71-36672
NASW-2035	N71-37823
N71-38535	721-01-00-16-21
NASW-2037	N71-36435
NASW-2038	N71-38767
NAS1-8350	721-60-10-05-21
NAS1-9200	N71-36436
NAS1-10192	760-72-01-05 N71-36675
NAS1-11019	760-74-01-03 N71-36415
NAS1-50024	760-75-01-00-21
NAS2-4515	N71-36416
NAS2-5168	
NAS2-5974	
NAS3-7605	
NAS3-7609	
NAS3-10482	
NAS8-4016	
NAS8-25700	
NAS9-9784	
NGR-39-009-111	
N71-37598	
NGR-47-003-015	
N71-36548	
HONR-4761 (00)	
N71-37924	
NSF GP-13982	
A71-43347	

1. Report No. NASA SP-7037 (13)		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle AERONAUTICAL ENGINEERING A Special Bibliography (Supplement 13)				5. Report Date January 1972	
				6. Performing Organization Code	
7. Author(s)				8. Performing Organization Report No.	
9. Performing Organization Name and Address National Aeronautics and Space Administration Washington, D. C. 20546				10. Work Unit No.	
				11. Contract or Grant No.	
12. Sponsoring Agency Name and Address				13. Type of Report and Period Covered	
				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract <p>This special bibliography lists 283 reports, articles, and other documents introduced into the NASA scientific and technical information system in December 1971. Emphasis is placed on engineering and theoretical aspects for design, construction, evaluation, testing, operation and performance of aircraft (including aircraft engines) and associated components, equipment and systems. Also included are entries on research and development in aeronautics and aerodynamics and research and ground support for aeronautical vehicles.</p>					
17. Key Words (Suggested by Author(s)) Aerodynamics Aeronautical Engineering Aeronautics Bibliographies				18. Distribution Statement Unclassified - Unlimited	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 93	
				22. Price* \$3.00 HC	

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC

NASA deposits its technical documents and bibliographic tools in eleven Federal Regional Technical Report Centers located in the organizations listed below. Each center is prepared to furnish the public such services as reference assistance, interlibrary loans, photocopy service, and assistance in obtaining copies of NASA documents for retention.

CALIFORNIA

University of California, Berkeley

COLORADO

University of Colorado, Boulder

DISTRICT OF COLUMBIA

Library of Congress

GEORGIA

Georgia Institute of Technology, Atlanta

ILLINOIS

The John Crerar Library, Chicago

MASSACHUSETTS

Massachusetts Institute of Technology, Cambridge

MISSOURI

Linda Hall Library, Kansas City

NEW YORK

Columbia University, New York

PENNSYLVANIA

Carnegie Library of Pittsburgh

TEXAS

Southern Methodist University, Dallas

WASHINGTON

University of Washington, Seattle

NASA publications (those indicated by an "*" following the accession number) are also received by the following public and free libraries:

CALIFORNIA

Los Angeles Public Library

San Diego Public Library

COLORADO

Denver Public Library

CONNECTICUT

Hartford Public Library

DELAWARE

Wilmington Institute Free Library, Wilmington

MARYLAND

Enoch Pratt Free Library, Baltimore

MASSACHUSETTS

Boston Public Library

MICHIGAN

Detroit Public Library

MINNESOTA

Minneapolis Public Library

James Jerome Hill Reference Library, St. Paul

MISSOURI

Kansas City Public Library

St. Louis Public Library

NEW JERSEY

Trenton Public Library

NEW YORK

Brooklyn Public Library

Buffalo and Erie County Public Library

Rochester Public Library

New York Public Library

OHIO

Akron Public Library

Cincinnati Public Library

Cleveland Public Library

Dayton Public Library

Toledo Public Library

OKLAHOMA

Oklahoma County Libraries, Oklahoma City

TENNESSEE

Cossitt-Goodwin Libraries, Memphis

TEXAS

Dallas Public Library

Fort Worth Public Library

WASHINGTON

Seattle Public Library

WISCONSIN

Milwaukee Public Library

An extensive collection of NASA and NASA-sponsored documents and aerospace publications available to the public for reference purposes is maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 750 Third Avenue, New York, New York, 10017

EUROPEAN

An extensive collection of NASA and NASA-sponsored publications is maintained by the National Lending Library for Science and Technology, Boston Spa, Yorkshire, England. By virtue of arrangements other than with NASA, the National Lending Library also has available many of the non-NASA publications cited in *STAR*. European requesters may purchase facsimile copy or microfiche of NASA and NASA-sponsored documents, those identified by both the symbols "*" and "#", from: ESRO/ELDO Space Documentation Service, European Space Research Organization, 114, av de Neuilly, 92-Neuilly-sur-Seine, France.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
WASHINGTON, D.C. 20546

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

FIRST CLASS MAIL

POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION



POSTMASTER: If Undeliverable / Section 159
Postal Manual / Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

— NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Washington, D.C. 20546